

Contents

1	Basic Test Results	2
2	AUTHORS	3
3	And.hdl	4
4	And16.hdl	5
5	DMux.hdl	6
6	DMux4Way.hdl	7
7	DMux8Way.hdl	8
8	Mux.hdl	9
9	Mux16.hdl	10
10	Mux4Way16.hdl	11
11	Mux8Way16.hdl	12
12	Not.hdl	13
13	Not16.hdl	14
14	Or.hdl	15
15	Or16.hdl	16
16	Or8Way.hdl	17
17	Xor.hdl	18

1 Basic Test Results

```
1 ***** TESTING FOLDER STRUCTURE START *****
2 Checking your submission for presence of invalid (non-ASCII) characters...
3 No invalid characters found.
4 Submission logins are: linorcohen
5 Is this OK?
6 ***** TESTING FOLDER STRUCTURE END *****
7
8 ***** PROJECT TEST START *****
9 Testing.
10 And16 passed test.
11 And passed test.
12 DMux4Way passed test.
13 DMux8Way passed test.
14 DMux passed test.
15 Mux16 passed test.
16 Mux4Way16 passed test.
17 Mux8Way16 passed test.
18 Mux passed test.
19 Not16 passed test.
20 Not passed test.
21 Or16 passed test.
22 Or8Way passed test.
23 Or passed test.
24 Xor passed test.
25 ***** PROJECT TEST END *****
26
27 Note: the tests you see above are all the presubmission tests
28 for this project. The tests might not check all the different
29 parts of the project or all corner cases, so write your own
30 tests and use them!
```

2 AUTHORS

1 linorcohen
2 Partner 1: Linor Cohen, linor.cohen@mail.huji.ac.il, 318861226
3 Remarks:

3 And.hdl

```
1 // This file is part of www.nand2tetrtris.org
2 // and the book "The Elements of Computing Systems"
3 // by Nisan and Schocken, MIT Press.
4 // File name: projects/01/And.hdl
5
6 /**
7  * And gate:
8  * out = 1 if (a == 1 and b == 1)
9  *      0 otherwise
10 */
11
12 CHIP And {
13     IN a, b;
14     OUT out;
15
16     PARTS:
17         Nand(a=a, b=b, out=aNandb);
18         Not(in=aNandb, out=out);
19 }
```

4 And16.hdl

```
1 // This file is part of www.nand2tetris.org
2 // and the book "The Elements of Computing Systems"
3 // by Nisan and Schocken, MIT Press.
4 // File name: projects/01/And16.hdl
5
6 /**
7  * 16-bit bitwise And:
8  * for i = 0..15: out[i] = (a[i] and b[i])
9  */
10
11 CHIP And16 {
12     IN a[16], b[16];
13     OUT out[16];
14
15     PARTS:
16         And(a=a[0], b=b[0], out=out[0]);
17         And(a=a[1], b=b[1], out=out[1]);
18         And(a=a[2], b=b[2], out=out[2]);
19         And(a=a[3], b=b[3], out=out[3]);
20         And(a=a[4], b=b[4], out=out[4]);
21         And(a=a[5], b=b[5], out=out[5]);
22         And(a=a[6], b=b[6], out=out[6]);
23         And(a=a[7], b=b[7], out=out[7]);
24         And(a=a[8], b=b[8], out=out[8]);
25         And(a=a[9], b=b[9], out=out[9]);
26         And(a=a[10], b=b[10], out=out[10]);
27         And(a=a[11], b=b[11], out=out[11]);
28         And(a=a[12], b=b[12], out=out[12]);
29         And(a=a[13], b=b[13], out=out[13]);
30         And(a=a[14], b=b[14], out=out[14]);
31         And(a=a[15], b=b[15], out=out[15]);
32 }
```

5 DMux.hdl

```
1 // This file is part of www.nand2tetrtris.org
2 // and the book "The Elements of Computing Systems"
3 // by Nisan and Schocken, MIT Press.
4 // File name: projects/01/DMux.hdl
5
6 /**
7  * Demultiplexor:
8  * {a, b} = {in, 0} if sel == 0
9  *         {0, in} if sel == 1
10 */
11
12 CHIP DMux {
13     IN in, sel;
14     OUT a, b;
15
16     PARTS:
17         Nand(a=sel, b=in, out=selNandin);
18         And(a=selNandin, b=in, out=a);
19         Not(in=selNandin, out=b);
20 }
```

6 DMux4Way.hdl

```
1 // This file is part of www.nand2tetrtris.org
2 // and the book "The Elements of Computing Systems"
3 // by Nisan and Schocken, MIT Press.
4 // File name: projects/01/DMux4Way.hdl
5
6 /**
7  * 4-way demultiplexor:
8  * {a, b, c, d} = {in, 0, 0, 0} if sel == 00
9  *                {0, in, 0, 0} if sel == 01
10 *                {0, 0, in, 0} if sel == 10
11 *                {0, 0, 0, in} if sel == 11
12 */
13
14 CHIP DMux4Way {
15     IN in, sel[2];
16     OUT a, b, c, d;
17
18     PARTS:
19     DMux(in=in, sel=sel[1], a=a1, b=b1);
20     DMux(in=a1, sel=sel[0], a=a, b=b);
21     DMux(in=b1, sel=sel[0], a=c, b=d);
22 }
```

7 DMux8Way.hdl

```
1 // This file is part of www.nand2tetris.org
2 // and the book "The Elements of Computing Systems"
3 // by Nisan and Schocken, MIT Press.
4 // File name: projects/01/DMux8Way.hdl
5
6 /**
7  * 8-way demultiplexor:
8  * {a, b, c, d, e, f, g, h} = {in, 0, 0, 0, 0, 0, 0, 0} if sel == 000
9  *                               {0, in, 0, 0, 0, 0, 0, 0} if sel == 001
10 *                               etc.
11 *                               {0, 0, 0, 0, 0, 0, 0, in} if sel == 111
12 */
13
14 CHIP DMux8Way {
15     IN in, sel[3];
16     OUT a, b, c, d, e, f, g, h;
17
18     PARTS:
19     DMux(in=in, sel=sel[2], a=a2, b=b2);
20     DMux(in=a2, sel=sel[1], a=a1, b=b1);
21     DMux(in=b2, sel=sel[1], a=c1, b=d1);
22     DMux(in=a1, sel=sel[0], a=a, b=b);
23     DMux(in=b1, sel=sel[0], a=c, b=d);
24     DMux(in=c1, sel=sel[0], a=e, b=f);
25     DMux(in=d1, sel=sel[0], a=g, b=h);
26 }
```


8 Mux.hdl

```
1 // This file is part of www.nand2tetris.org
2 // and the book "The Elements of Computing Systems"
3 // by Nisan and Schocken, MIT Press.
4 // File name: projects/01/Mux.hdl
5
6 /**
7  * Multiplexor:
8  * out = a if sel == 0
9  *      b otherwise
10 */
11
12 CHIP Mux {
13     IN a, b, sel;
14     OUT out;
15
16     PARTS:
17         Not(in=sel, out=Notsel);
18         Nand(a=a, b=Notsel, out=aNandNotsel);
19         Nand(a=sel, b=b, out=bNandsel);
20         Nand(a=aNandNotsel, b=bNandsel, out=out);
21 }
```

9 Mux16.hdl

```
1 // This file is part of www.nand2tetris.org
2 // and the book "The Elements of Computing Systems"
3 // by Nisan and Schocken, MIT Press.
4 // File name: projects/01/Mux16.hdl
5
6 /**
7  * 16-bit multiplexor:
8  * for i = 0..15 out[i] = a[i] if sel == 0
9  *                      b[i] if sel == 1
10 */
11
12 CHIP Mux16 {
13     IN a[16], b[16], sel;
14     OUT out[16];
15
16     PARTS:
17         Mux(a=a[0], b=b[0], sel=sel, out=out[0]);
18         Mux(a=a[1], b=b[1], sel=sel, out=out[1]);
19         Mux(a=a[2], b=b[2], sel=sel, out=out[2]);
20         Mux(a=a[3], b=b[3], sel=sel, out=out[3]);
21         Mux(a=a[4], b=b[4], sel=sel, out=out[4]);
22         Mux(a=a[5], b=b[5], sel=sel, out=out[5]);
23         Mux(a=a[6], b=b[6], sel=sel, out=out[6]);
24         Mux(a=a[7], b=b[7], sel=sel, out=out[7]);
25         Mux(a=a[8], b=b[8], sel=sel, out=out[8]);
26         Mux(a=a[9], b=b[9], sel=sel, out=out[9]);
27         Mux(a=a[10], b=b[10], sel=sel, out=out[10]);
28         Mux(a=a[11], b=b[11], sel=sel, out=out[11]);
29         Mux(a=a[12], b=b[12], sel=sel, out=out[12]);
30         Mux(a=a[13], b=b[13], sel=sel, out=out[13]);
31         Mux(a=a[14], b=b[14], sel=sel, out=out[14]);
32         Mux(a=a[15], b=b[15], sel=sel, out=out[15]);
33 }
```

10 Mux4Way16.hdl

```
1  // This file is part of www.nand2tetris.org
2  // and the book "The Elements of Computing Systems"
3  // by Nisan and Schocken, MIT Press.
4  // File name: projects/01/Mux4Way16.hdl
5
6  /**
7   * 4-way 16-bit multiplexor:
8   * out = a if sel == 00
9   *      b if sel == 01
10  *      c if sel == 10
11  *      d if sel == 11
12  */
13
14  CHIP Mux4Way16 {
15      IN a[16], b[16], c[16], d[16], sel[2];
16      OUT out[16];
17
18      PARTS:
19          Mux16(a=a, b=b, sel=sel[0], out=aMuxb);
20          Mux16(a=c, b=d, sel=sel[0], out=cMuxd);
21          Mux16(a=aMuxb, b=cMuxd, sel=sel[1], out=out);
22  }
```

11 Mux8Way16.hdl

```
1 // This file is part of www.nand2tetris.org
2 // and the book "The Elements of Computing Systems"
3 // by Nisan and Schocken, MIT Press.
4 // File name: projects/01/Mux8Way16.hdl
5
6 /**
7  * 8-way 16-bit multiplexor:
8  * out = a if sel == 000
9  *      b if sel == 001
10 *      etc.
11 *      h if sel == 111
12 */
13
14 CHIP Mux8Way16 {
15     IN a[16], b[16], c[16], d[16],
16         e[16], f[16], g[16], h[16],
17         sel[3];
18     OUT out[16];
19
20     PARTS:
21     Mux16(a=a, b=b, sel=sel[0], out=aMuxb);
22     Mux16(a=c, b=d, sel=sel[0], out=cMuxd);
23     Mux16(a=e, b=f, sel=sel[0], out=eMuxf);
24     Mux16(a=g, b=h, sel=sel[0], out=gMuxh);
25     Mux16(a=aMuxb, b=cMuxd, sel=sel[1], out=abcdMux);
26     Mux16(a=eMuxf, b=gMuxh, sel=sel[1], out=efghMux);
27     Mux16(a=abcdMux, b=efghMux, sel=sel[2], out=out);
28 }
```

12 Not.hdl

```
1 // This file is part of www.nand2tetris.org
2 // and the book "The Elements of Computing Systems"
3 // by Nisan and Schocken, MIT Press.
4 // File name: projects/01/Not.hdl
5
6 /**
7  * Not gate:
8  * out = not in
9  */
10
11 CHIP Not {
12     IN in;
13     OUT out;
14
15     PARTS:
16         Nand(a=in ,b=in ,out=out);
17 }
```

13 Not16.hdl

```
1 // This file is part of www.nand2tetris.org
2 // and the book "The Elements of Computing Systems"
3 // by Nisan and Schocken, MIT Press.
4 // File name: projects/01/Not16.hdl
5
6 /**
7  * 16-bit Not:
8  * for i=0..15: out[i] = not in[i]
9  */
10
11 CHIP Not16 {
12     IN in[16];
13     OUT out[16];
14
15     PARTS:
16         Not(in=in[0], out=out[0]);
17         Not(in=in[1], out=out[1]);
18         Not(in=in[2], out=out[2]);
19         Not(in=in[3], out=out[3]);
20         Not(in=in[4], out=out[4]);
21         Not(in=in[5], out=out[5]);
22         Not(in=in[6], out=out[6]);
23         Not(in=in[7], out=out[7]);
24         Not(in=in[8], out=out[8]);
25         Not(in=in[9], out=out[9]);
26         Not(in=in[10], out=out[10]);
27         Not(in=in[11], out=out[11]);
28         Not(in=in[12], out=out[12]);
29         Not(in=in[13], out=out[13]);
30         Not(in=in[14], out=out[14]);
31         Not(in=in[15], out=out[15]);
32 }
```

14 Or.hdl

```
1 // This file is part of www.nand2tetris.org
2 // and the book "The Elements of Computing Systems"
3 // by Nisan and Schocken, MIT Press.
4 // File name: projects/01/Or.hdl
5
6 /**
7  * Or gate:
8  * out = 1 if (a == 1 or b == 1)
9  *       0 otherwise
10 */
11
12 CHIP Or {
13     IN a, b;
14     OUT out;
15
16     PARTS:
17         Not(in=a, out=Nota);
18         Not(in=b, out=Notb);
19         Nand(a=Nota, b=Notb, out=out);
20 }
```

15 Or16.hdl

```
1 // This file is part of www.nand2tetris.org
2 // and the book "The Elements of Computing Systems"
3 // by Nisan and Schocken, MIT Press.
4 // File name: projects/01/Or16.hdl
5
6 /**
7  * 16-bit bitwise Or:
8  * for i = 0..15 out[i] = (a[i] or b[i])
9  */
10
11 CHIP Or16 {
12     IN a[16], b[16];
13     OUT out[16];
14
15     PARTS:
16         Or(a=a[0], b=b[0], out=out[0]);
17         Or(a=a[1], b=b[1], out=out[1]);
18         Or(a=a[2], b=b[2], out=out[2]);
19         Or(a=a[3], b=b[3], out=out[3]);
20         Or(a=a[4], b=b[4], out=out[4]);
21         Or(a=a[5], b=b[5], out=out[5]);
22         Or(a=a[6], b=b[6], out=out[6]);
23         Or(a=a[7], b=b[7], out=out[7]);
24         Or(a=a[8], b=b[8], out=out[8]);
25         Or(a=a[9], b=b[9], out=out[9]);
26         Or(a=a[10], b=b[10], out=out[10]);
27         Or(a=a[11], b=b[11], out=out[11]);
28         Or(a=a[12], b=b[12], out=out[12]);
29         Or(a=a[13], b=b[13], out=out[13]);
30         Or(a=a[14], b=b[14], out=out[14]);
31         Or(a=a[15], b=b[15], out=out[15]);
32 }
```


16 Or8Way.hdl

```
1  // This file is part of www.nand2tetris.org
2  // and the book "The Elements of Computing Systems"
3  // by Nisan and Schocken, MIT Press.
4  // File name: projects/01/Or8Way.hdl
5
6  /**
7   * 8-way Or:
8   * out = (in[0] or in[1] or ... or in[7])
9   */
10
11 CHIP Or8Way {
12     IN in[8];
13     OUT out;
14
15     PARTS:
16         Or(a=in[0], b=in[1], out=or1);
17         Or(a=or1, b=in[2], out=or2);
18         Or(a=or2, b=in[3], out=or3);
19         Or(a=or3, b=in[4], out=or4);
20         Or(a=or4, b=in[5], out=or5);
21         Or(a=or5, b=in[6], out=or6);
22         Or(a=or6, b=in[7], out=out);
23 }
```

17 Xor.hdl

```
1 // This file is part of www.nand2tetris.org
2 // and the book "The Elements of Computing Systems"
3 // by Nisan and Schocken, MIT Press.
4 // File name: projects/01/Xor.hdl
5
6 /**
7  * Exclusive-or gate:
8  * out = not (a == b)
9  */
10
11 CHIP Xor {
12     IN a, b;
13     OUT out;
14
15     PARTS:
16         Nand(a=a, b=b, out=aNandb);
17         Nand(a=a, b=aNandb, out=w1);
18         Nand(a=aNandb, b=b, out=w2);
19         Nand(a=w1, b=w2, out=out);
20 }
```