
PIC18F67J60-I/PT
SN754410NE
STP16C596
BL-M07A571
SN74S197D
AD8400
AD8561
SA5205A
Header 4X2
Header 5X2
Header 2
Header 4
Header 5
SW-PB
Cover
Title
Size
A2
Number
Revision
Date: 06.12.2009
File: E:\dim\Схема\PCB\Sheet1.SchDoc
Sheet of
Drawn By:


92 (mm)
57 (mm)
34.5 (mm)
+12V
P3
P2
Motors
INPUT_PWR
U53
U52
U51
L52
L51
U54
U1
U2
Ethernet
X1
C3
C2
C1
R43
R44
R45
R46
R47
R48
R49
R50
R51
R52
R53
R54
R55
R56
R57
R58
R59
R60
R61
R62
R63
R64
R65
R66
R67
R68
R69
R70
R71
R72
R73
R74
R75
R76
R77
R78
R79
R80
R81
R82

Bill of Materials

<Parameter Title not found>

Source Data From: PCB_Project1.PrjPCB
Project: PCB_Project1.PrjPCB
Variant: None

Creation Date: 06.12.2009 20:16:51
Print Date: 40153 40153,84512

Footprint	Comment	LibRef	Designator	Description	Quantity
EthernetCON	Component_1	Component_1	*1		1
CAPC3225N	Cap	Cap	C1, C52, C53, C58	Capacitor	4
CAPC2012L	Cap	Cap	C2, C3, C4, C6, C11, C12, C13, C55	Capacitor	8
CAPC4532L	Cap	Cap	C5, C7, C8, C9, C10	Capacitor	5
CAPC2512L	Cap	Cap	C20, C21	Capacitor	2
CAPC3225N	Cap Pol1	Cap Pol1	C51, C59	Polarized Capacitor (Radial)	2
CAPPR5-5x5	Cap Pol1	Cap Pol1	C100, C101	Polarized Capacitor (Radial)	2
Cover	Cover	Component_1	Cover		1
SOT95P240-3N	Diode	Diode	D1	Default Diode	1
SOT95P240-3N	AD1580	D Zener	D2	Zener Diode	1
KLD-0202	PWR2.5	PWR2.5	J1	Low Voltage Power Supply Connector	1
INDC2012L	Inductor	Inductor	L1, L51, L52	Inductor	3
HDR2X4	Header 4X2	Header 4X2	P1	Header, 4-Pin, Dual row	1
HDR1X4	Header 4	Header 4	P2	Header, 4-Pin	1
SMB_V-RJ45	SMB	SMB	P3	SMB Straight Connector	1
HDR1X5	Header 5	Header 5	P8	Header, 5-Pin	1
HDR1X2	Header 2	Header 2	P9, P10	Header, 2-Pin	2
HDR2X5	Header 5X2	Header 5X2	PD, PD1	Header, 5-Pin, Dual row	2
RESC1608L	Res3	Res3	R1, R2, R3, R4, R5, R6, R7, R8, R9, R1(R11, R12, R13, R14, R15, R16, R18, R2(R26, R27, R30, R31, R32, R33, R41, R4: R43, R44, R46	Resistor	29
RESC2012N	Res2	Res2	R17, R19, R21, R22, R51, R55, R57	Resistor	7
SPST-2	SW-PB	SW-PB	S1, S2, S3	Switch	3
TQFP-PT64_N	PIC18F67J60-I/PT	PIC18F67J60-I/PT	U1	High Performance, 1-Mbit Flash Microcontroller with Ethernet, 128K Flash, 64-Pin TQFP, Industrial Temperature Rar	1
NE016D014_N	SN754410NE	SN754410NE	U2	Quadruple Half-H Driver	1
	SN74S197D	SN74S197D	U51	100-MHz Presettable Decade or Binary Counter / Latch	1
SOIC127P600-8L	SA5205A	SA5205A	U52	Wide-band high-frequency amplifier	1
SOIC127P600-8L	AD8561	AD8561	U53	Ultrafast 7 ns Single Supply Comparator	1
SOIC127P600-8L	AD8400	AD8400	U54	Digital Potentiometers	1
DB024	STP16C596	STP16C596	U61, U62		2
LED matrix 7x5	BL-M07A571	BL-M07A571	U63, U64, U65, U66, U67		5
SOT223-4N	Volt Reg	Volt Reg	VR1	Voltage Regulator	1
SOT89N	Volt Reg	Volt Reg	VR2, VR3	Voltage Regulator	2
Quartz	XTAL	XTAL	Y1	Crystal Oscillator	1
Quartz	Z	XTAL	Y2	32768 kHz	1
					96

Approved **Notes**