

# ExercisesAuto

February 21, 2025

## 1 Applied : Auto dataset - Simple Linear Regression

- Simple Linear Regression utilizing Auto dataset

### 1.1 Import notebook functions

```
[1]: from notebookfuncs import *
```

### 1.2 Import standard libraries

```
[2]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from matplotlib.pyplot import subplots
```

### 1.3 New imports

```
[3]: import statsmodels.api as sm
```

### 1.4 Import statsmodel.objects

```
[4]: from statsmodels.stats.outliers_influence import variance_inflation_factor as V
↪ VIF
from statsmodels.stats.outliers_influence import summary_table
from statsmodels.stats.anova import anova_lm
```

### 1.5 Import ISLP objects

```
[5]: import ISLP
from ISLP import models
from ISLP import load_data
from ISLP.models import ModelSpec as MS, summarize, poly
```

```
[6]: Auto = load_data("Auto")
Auto.columns
```

```
[6]: Index(['mpg', 'cylinders', 'displacement', 'horsepower', 'weight',
          'acceleration', 'year', 'origin'],
          dtype='object')
```

```
[7]: Auto.shape
```

```
[7]: (392, 8)
```

```
[8]: Auto.describe()
```

```
[8]:
```

	mpg	cylinders	displacement	horsepower	weight \
count	392.000000	392.000000	392.000000	392.000000	392.000000
mean	23.445918	5.471939	194.411990	104.469388	2977.584184
std	7.805007	1.705783	104.644004	38.491160	849.402560
min	9.000000	3.000000	68.000000	46.000000	1613.000000
25%	17.000000	4.000000	105.000000	75.000000	2225.250000
50%	22.750000	4.000000	151.000000	93.500000	2803.500000
75%	29.000000	8.000000	275.750000	126.000000	3614.750000
max	46.600000	8.000000	455.000000	230.000000	5140.000000

	acceleration	year	origin
count	392.000000	392.000000	392.000000
mean	15.541327	75.979592	1.576531
std	2.758864	3.683737	0.805518
min	8.000000	70.000000	1.000000
25%	13.775000	73.000000	1.000000
50%	15.500000	76.000000	1.000000
75%	17.025000	79.000000	2.000000
max	24.800000	82.000000	3.000000

## 1.6 Convert cylinders and origin columns to categorical types

```
[9]: Auto["cylinders"] = Auto["cylinders"].astype("category")
      Auto["origin"] = Auto["origin"].astype("category")
      Auto.describe()
```

```
[9]:
```

	mpg	displacement	horsepower	weight	acceleration \
count	392.000000	392.000000	392.000000	392.000000	392.000000
mean	23.445918	194.411990	104.469388	2977.584184	15.541327
std	7.805007	104.644004	38.491160	849.402560	2.758864
min	9.000000	68.000000	46.000000	1613.000000	8.000000
25%	17.000000	105.000000	75.000000	2225.250000	13.775000
50%	22.750000	151.000000	93.500000	2803.500000	15.500000
75%	29.000000	275.750000	126.000000	3614.750000	17.025000
max	46.600000	455.000000	230.000000	5140.000000	24.800000

	year
count	392.000000
mean	75.979592
std	3.683737
min	70.000000
25%	73.000000
50%	76.000000
75%	79.000000
max	82.000000

```
count    392.000000
mean      75.979592
std        3.683737
min       70.000000
25%       73.000000
50%       76.000000
75%       79.000000
max       82.000000
```

**1.7 8) This question involves the use of Simple Linear Regression on the Auto dataset**

**1.7.1 (a) Use the `sm.OLS()` function to perform a simple linear regression with mpg as the response and horsepower as the predictor.**

**1.7.2 Use the `summarize()` function to print the results.**

**1.7.3 Comment on the output. For example:**

**i. Is there a relationship between the predictor and the response?**

**ii. How strong is the relationship between the predictor and the response?**

**iii. Is the relationship between the predictor and the response positive or negative?**

**iv. What is the predicted mpg associated with a horsepower of 98? What are the associated 95 % confidence and prediction intervals?**

```
[10]: y = Auto["mpg"]
      y.head()
```

```
[10]: name
      chevrolet chevelle malibu    18.0
      buick skylark 320            15.0
      plymouth satellite           18.0
      amc rebel sst                16.0
      ford torino                  17.0
      Name: mpg, dtype: float64
```

```
[11]: design = MS(["horsepower"])
      design = design.fit(Auto)
      X = design.transform(Auto)
```

```
[11]:                intercept  horsepower
name
chevrolet chevelle malibu      1.0         130
buick skylark 320              1.0         165
plymouth satellite             1.0         150
amc rebel sst                  1.0         150
ford torino                    1.0         140
```

```
...
ford mustang gl      1.0      86
vw pickup           1.0      52
dodge rampage       1.0      84
ford ranger         1.0      79
chevy s-10          1.0      82
```

[392 rows x 2 columns]

```
[12]: model = sm.OLS(y, X)
      results = model.fit()
      summarize(results)
```

```
[12]:      coef  std err      t  P>|t|
intercept  39.9359    0.717  55.660    0.0
horsepower -0.1578    0.006 -24.489    0.0
```

- There is evidence of a linear relationship between horsepower and the response mpg.

```
[13]: results.summary()
```

```
[13]:
```

<b>Dep. Variable:</b>	mpg	<b>R-squared:</b>	0.606
<b>Model:</b>	OLS	<b>Adj. R-squared:</b>	0.605
<b>Method:</b>	Least Squares	<b>F-statistic:</b>	599.7
<b>Date:</b>	Tue, 24 Sep 2024	<b>Prob (F-statistic):</b>	7.03e-81
<b>Time:</b>	08:55:19	<b>Log-Likelihood:</b>	-1178.7
<b>No. Observations:</b>	392	<b>AIC:</b>	2361.
<b>Df Residuals:</b>	390	<b>BIC:</b>	2369.
<b>Df Model:</b>	1		
<b>Covariance Type:</b>	nonrobust		

	coef	std err	t	P>  t	[0.025	0.975]
<b>intercept</b>	39.9359	0.717	55.660	0.000	38.525	41.347
<b>horsepower</b>	-0.1578	0.006	-24.489	0.000	-0.171	-0.145

<b>Omnibus:</b>	16.432	<b>Durbin-Watson:</b>	0.920
<b>Prob(Omnibus):</b>	0.000	<b>Jarque-Bera (JB):</b>	17.305
<b>Skew:</b>	0.492	<b>Prob(JB):</b>	0.000175
<b>Kurtosis:</b>	3.299	<b>Cond. No.</b>	322.

Notes:

[1] Standard Errors assume that the covariance matrix of the errors is correctly specified.

- The R2 value of 60.6% indicates that the regression of horsepower on mpg explains 60.6% of the variation in the model.
- The relationship between horsepower and mpg is negative, i.e., an increase in hp of 1 unit decreases the mileage by 0.1578 miles. An increase in the car's output in power is offset by a decrease in its economy.

```
[14]: design = MS(["horsepower"])
new_df = pd.DataFrame({"horsepower": [98]})
design = design.fit(new_df)
newX = design.transform(new_df)
```

```
[14]:      intercept  horsepower
0          1.0          98
```

```
[15]: new_predictions = results.get_prediction(newX)
mileage = new_predictions.predicted_mean[0]
mileage
```

```
[15]: 24.46707715251243
```

- The predicted mileage for a horsepower of 98 is 24.47 mpg.

```
[16]: new_predictions.conf_int(alpha=0.05)
```

```
[16]: array([[23.97307896, 24.96107534]])
```

- The 95% confidence interval is (23.97, 24.96)

```
[17]: new_predictions.conf_int(alpha=0.05, obs=True)
```


```
[17]: array([[14.80939607, 34.12475823]])
```

- The 95% prediction interval is (14.82, 34.13)

**1.7.4 (b) Plot the response and the predictor in a new set of axes ax.**

**1.7.5 Use the ax.axline() method or the abline() function defined in the lab to display the least squares regression line.**

```
[18]: ax = Auto.plot.scatter("horsepower", "mpg")
ax.axline(
    (ax.get_xlim()[0], results.params.iloc[0]),
    slope=results.params.iloc[1],
    color="r",
    linewidth=3,
)
```




- The least squares regression line is plotted above using `ax.axline()`. The plot displays some evidence of non-linearity in the relationship between horsepower and mpg.

**1.7.6 (c) Produce some of diagnostic plots of the least squares regression fit as described in the lab.**

**1.7.7 Comment on any problems you see with the fit.**


**Plot of fitted values versus residuals.**

```
[19]: _, ax = subplots(figsize=(8, 8))
      ax.scatter(results.fittedvalues, results.resid)
      ax.set_xlabel("Fitted values")
      ax.set_ylabel("Residuals")
      ax.axhline(0, c="k", ls="--")
```



We can also plot the residuals vs predictor plot where horsepower is the predictor.

```
[20]: _, ax = subplots(figsize=(8, 8))
      ax.scatter(Auto["horsepower"], results.resid)
      ax.set_xlabel("Horsepower")
      ax.set_ylabel("Residuals")
      ax.axhline(0, c="k", ls="--")
```



### Conclusions:

- There is evidence of non-linearity in the relationship between residuals and fitted values.
- There is evidence of heteroskedasticity i.e., non-constant variance in the residuals across the fitted values.

```
[21]: RSS = np.sum((y - results.fittedvalues) ** 2)
      RSS
```

```
[21]: 9385.915871932419
```

```
[22]: RSE = np.sqrt(RSS / (Auto.shape[0] - 2))
      RSE
```



```
[22]: 4.90575691954594
```

### 1.7.8 OLSResults.scale()

- Gives us a scale factor for the covariance matrix.
- The Default value is  $\text{ssr}/(n-p)$ . Note that the square root of scale is often called the standard error of the regression.
- [https://www.statsmodels.org/dev/generated/statsmodels.regression.linear\\_model.OLSResults.scale.html](https://www.statsmodels.org/dev/generated/statsmodels.regression.linear_model.OLSResults.scale.html)

```
[23]: np.sqrt(results.scale)
```

```
[23]: 4.90575691954594
```

```
[24]: mpg_mean = Auto["mpg"].mean()
```

```
[24]: 23.445918367346938
```

```
[25]: print("Percentage error in mpg estimation using model above is: ")
      np.round(RSE / mpg_mean * 100, decimals=2)
```

Percentage error in mpg estimation using model above is:


```
[25]: 20.92
```

### 1.7.9 Leverage statistics

```
[26]: infl = results.get_influence()
      _, ax = subplots(figsize=(8, 8))
      ax.scatter(np.arange(X.shape[0]), infl.hat_matrix_diag)
      ax.set_xlabel("Index")
      ax.set_ylabel("Leverage")
      high_leverage = np.argmax(infl.hat_matrix_diag)
      max_leverage = np.max(infl.hat_matrix_diag)
      print("Max leverage point:")
      print(high_leverage, np.round(max_leverage, decimals=2))
      ax.plot(high_leverage, max_leverage, "ro")
```

Max leverage point:

115 0.03



### Outlier identification using Standardized Residuals versus Fitted Values plot


```
[27]: _, ax = subplots(figsize=(8, 8))
ax.scatter(results.fittedvalues, results.resid_pearson)
ax.set_xlabel("Fitted values for mpg")
ax.set_ylabel("Standardized residuals")
ax.axhline(0, c="k", ls="--")
outliers_indexes = np.where(
    (results.resid_pearson > 3.0) | (results.resid_pearson < -3.0)
)[0]
for idx in range(len(outliers_indexes)):
    ax.plot(
        results.fittedvalues.iloc[outliers_indexes[idx]],
        results.resid_pearson[outliers_indexes[idx]],
        "ro",
```

```
)
print("Outlier rows: ")
print(Auto.iloc[outliers_indexes])
```

Outlier rows:

	mpg	cylinders	displacement	horsepower	weight	\
name						
mazda glc	46.6	4	86.0	65	2110	
honda civic 1500 gl	44.6	4	91.0	67	1850	

	acceleration	year	origin
name			
mazda glc	17.9	80	3
honda civic 1500 gl	13.8	80	3




Conclusions: + From the standardized residuals versus fitted values, there are two outliers present in the data. + These points can be investigated further whether to retain them in the dataset.

Note: - We could drop the outliers from the data and regress the model without these points. That is an exercise for you!


**We can also plot residuals versus order.**

```
[28]: _, ax = subplots(figsize=(14, 8))
      ax.scatter(np.arange(X.shape[0]), results.resid)
      ax.set_xlabel("Observation Order")
      ax.set_ylabel("Residuals")
      ax.axhline(0, c="k", ls="--")
```




Conclusions: - While there seems to be little evidence of negative or positive correlation over time, there is evidence of underestimation from observations 300 onwards. There also seems to be a time trend in the data from observation 300 or so where the expectation of the model is that mpg will be lower, but the actual values are much higher. This indicates that fuel mileage improved much more than expected in the later models from observation 300 onwards. This indicates that column year should be added to the model.

```
[29]: sm.qqplot(results.resid, line="s")
```



```
[30]: # Plot histogram of residuals  
plt.hist(results.resid, bins=10)
```



Conclusions: - From the above two plots for qq and histograms for residuals, we can deduce that the residuals are approximately normal.

References: <https://github.com/linusjf/LearnR/tree/development/Stats462>

```
[31]: allDone()
```

```
<IPython.lib.display.Audio object>
```