```
# https://stats.stackexchange.com/questions/120179/generating-data-with-a-given-sample-covar
def gen_exact(mean=None, sigma=None, size=None, rng=None):
 if (mean is None or sigma is None or size is None or rng is None):
   return None
 # Generate size cases
  # rng = np.random.RandomState(seed)
 X = rng.multivariate_normal(mean, sigma, size=size).T
 # Subtract the mean from each variable
 for n in range(X.shape[0]):
     X[n] = X[n] - X[n].mean()
 # Make each variable in X orthogonal to one another
 L_inv = np.linalg.cholesky(np.cov(X, bias = True))
 L_inv = np.linalg.inv(L_inv)
 X = np.dot(L_inv, X)
 # Rescale X to exactly match Sigma
 L = np.linalg.cholesky(sigma)
 X = np.dot(L, X)
 # Add the mean back into each variable
 for n in range(X.shape[0]):
     X[n] = X[n] + mean[n]
 # The covariance of the generated data should match Sigma
 cov = np.cov(X, bias = True)
 X = X.T
 return X
def gen_inexact(mean=None,sigma=None,size=None,rng=None):
  if (mean is None or sigma is None or size is None or rng is None):
   return None
 # Generate size cases
 # rng = np.random.RandomState(seed)
 X = rng.multivariate_normal(mean, sigma, size=size).T
 # Make each variable in X orthogonal to one another
 L_inv = np.linalg.cholesky(np.cov(X, bias = True))
```

L_inv = np.linalg.inv(L_inv)

```
X = np.dot(L_inv, X)

# Rescale X to exactly match Sigma
L = np.linalg.cholesky(sigma)
X = np.dot(L, X)

# The covariance of the generated data should match Sigma
cov = np.cov(X, bias = True)
X = X.T
return X
```