



Sriyaan Metals

Office: 204- Platinum Arcade, 2nd floor, JSS Road, Central plaza cinema road, Mumbai – 400004.

Mobile : +91 9819033982

Email ID : ssmetals09@gmail.com

**We Are Committed To Excellence
In Quality And Service**

- Accurate Dimension
- Stable Mechanical Property
- Perfect Surface
- Impeccable Production Technology



COMPANY PROFILE

We would like to introduce ourselves as one of India's leading manufacturer of Fittings & Flanges. (ISO certified). Our products are manufactured as per JIS/ISS / BSS / DIN / ASTM / ASME and customer's drawings and specifications. All our products are supplied with third party inspection Certificates.

We utilize high grade raw material and state of the art technology to produce Pipe fittings which are available to our clients with manufacturers test certificate as per EN 10204 / 3.1& 3.2 under third party inspection and with confirming to NACE MR-01-75.

We are an ISO "9001-2015" and IBR Approved manufacturer of Forged fittings, Pipe fittings, Butt weld pipe fittings, Socket weld fittings, Threaded Fittings & Various types of Pipe flanges. We have in house facilities for manufacturing of Fittings, Flanges & Branch connections, such as Cutting, Hot & Cold Forming, Pressing, Welding, Heat Treatment, Machining, pickling, Hydraulic Testing, Ball Passing and Passivation and anti rust coating for excellent protect & durable packaging.

Integrated piping solutions with worldwide fulfillment capability We manufacture fittings & flanges to meet your specifications. We will meet your engineering specs from DIN to ASTM A350 to JIS Standards . Western Steel Agency specializes in supplying specialty Fittings & flanges to the world's most demanding industries – Oil and Gas Exploration and Production, Oil Refining and Processing, Petrochemical, Chemical, Plumbing and HVAC.

Vision To continuously modernize, expand and technologically upgrade our products with a view to produce excellent and high quality goods in matching with the changing Needs of the customers



Chemical composition of stainless steel

Chemical Composition of Stainless Steel											Nearest Equivalent Specification		
AISI Grade	UNS NO.	EN	BS	C Max	Mn Max	P Max	S Max	Si Max	Cr	Ni	Mo	Cu	I.S.
Austenitic													
201	S20100	-	-	0.15	5.5/7.5	0.06	0.03	1	16.0/18.0	3.5/5.5	-	-	-
202	S20200	-	-	0.15	7.5/10	0.06	0.03	1	17.0/19.0	4.0/6.0	-	-	-
301	S30100	-	301S21	0.15	2.0max	0.045	0.040	1.0	16.0/18.0	6.0/8.0	-	-	10Cr17Ni7
302	S30200	-	-	0.15	2.0	0.045	0.030	1.0	17.0/19.0	8.0/10.0	-	-	07Cr18Ni9
303	S30300	-	303S31	0.15	2.0	0.045	0.15 min	1.0	17.0/19.0	8.0/10.0	-	-	15Cr18Ni9
304	S30400	1.4301	-	0.08	2.0	0.045	0.030	1.0	18.0/20.0	8.0/10.0	-	-	04Cr18Ni10
304L	S30403	1.4307	304S11	0.030	2.0	0.045	0.030	1.0	18.0/20.0	8.0/12.0	-	-	02Cr18Ni11
304LN	S30453	1.4306	304S61	0.030	2.0	0.045	0.030	0.75	18.0/20.0	8.0/11.0	-	-	-
304H	S30409	-	-	0.05	2.0	0.045	0.03	1	18.0/20.0	8.5/9.5	-	-	-
309	S30900	-	309S16	0.20	2.0max	0.045	0.030	1.0	22.0/24.0	12.0/15.0	-	-	20Cr24Ni12
309S	S30908	1.4833	-	0.08	2.0	0.045	0.030	1.0	22.0/24.0	12.0/15.0	-	-	-
310H	S31009	-	-	0.25	2.0	0.045	0.030	1.50	24.0/26.0	19.0/22.0	-	-	10Cr25Ni12
310S	S31008	1.4845	-	0.08	2.0	0.045	0.030	1.50	24.0/26.0	19.0/22.0	-	-	-
316	S31600	-	316S31	0.08	2.0	0.045	0.030	1.0	16.0/18.0	10.0/14.0	2.0/3.0	-	04Cr17Ni12Mo2
316L	S31603	1.4404	316S11	0.030	2.0	0.045	0.030	1.0	16.0/18.0	10.0/14.0	2.0/3.0	-	03Cr17Ni12Mo2
316LN	S31653	-	316S61	0.030	2.0	0.045	0.030	0.75	16.0/18.0	10.0/14.0	2.0/3.0	-	-
316Ti	S31635	1.4571	320S31	0.080	2.0	0.045	0.030	1.0	16.0/18.0	10.0/14.0	2.0/3.0	-	-
317	S31700	-	-	0.08	2.0	0.045	0.030	1.0	18.0/20.0	11.0/15.0	3.0/4.0	-	-
317L	S31703	-	317S12	0.030	2.0	0.045	0.030	1.0	18.0/20.0	11.0/15.0	3.0/4.0	-	-
317LN	S31753	-	-	0.03	2.0	0.045	0.03	1	18.0/20.0	11.0/15.0	3.0/4.0	-	-
321	S32100	1.4541	321S31	0.08	2.0	0.045	0.030	1.0	17.0/19.0	9.0/12.0	-	-	04Cr18Ni10Ti20
347	S34700	-	347S31	0.08	2.0	0.045	0.030	1.0	17.0/19.0	9.0/12.0	-	-	04Cr18Ni10Nb-40
904L	N08904	1.4539	-	0.02	2.0	0.045	0.035	1	19.0/23.0	23.0/28.0	4.0-5.0	-	-

Chemical Composition of Carbon Steel / Alloy Steel / Mild Steel

PIPE SPECIFICATION	C%	Mn%	P% (Max)	S% (Max)	Si% (Max)	Cr%	Ni%	Mo%
ASTM A 106 Gr. A	0.25 Max	0.27-0.93	0.035	0.035	0.10 Min	0.40 Max	0.40 Max	0.15 Max
ASTM A 106 Gr. B	0.30 Max	0.29-1.06	0.035	0.035	0.10 Min	0.40 Max	0.40 Max	0.15 Max
ASTM A 53 Gr. A	0.25 Max	0.95 Max	0.050	0.045	-	0.40 Max	0.40 Max	0.15 Max
ASTM A 53 Gr. B	0.30 Max	1.20 Max	0.050	0.045	-	0.40 Max	0.40 Max	0.15 Max
ASTM A 333 Gr. 1	0.30 Max	0.40-1.06	0.025	0.025	-	-	-	-
ASTM A 333 Gr. 6	0.30 Max	0.29-1.06	0.025	0.025	0.10 Min	-	-	0.44-0.65
API 5L Gr. A	0.22 Max	0.90 Max	0.030	0.030	-	-	-	-
API 5L Gr. B	0.22 Max	1.20 Max	0.030	0.030	-	-	-	-
ASTM A 335 Gr. P1	0.10-0.20	0.30-0.80	0.025	0.025	0.10-0.50	-	-	0.44-0.65
ASTM A 335 Gr. P2	0.10-0.20	0.30-0.61	0.025	0.025	0.10-0.30	0.50-0.81	-	0.44-0.65
ASTM A 335 Gr. P5	0.15 Max	0.30-0.60	0.025	0.025	0.50 Max	4.00-6.00	-	0.45-0.65
ASTM A 335 Gr. P9	0.15 Max	0.30-0.60	0.025	0.025	0.25-1.00	8.00-10.00	-	0.90-1.10
ASTM A 335 Gr. P11	0.05-0.15	0.30-0.60	0.025	0.025	0.50-1.00	1.00-1.50	-	0.44-0.65
ASTM A 335 Gr. P12	0.05-0.15	0.30-0.61	0.025	0.025	0.50 Max	0.80-1.25	-	0.44-0.65
ASTM A 335 Gr. P22	0.05-0.15	0.30-0.60	0.025	0.025	0.50 Max	1.90-2.60	-	0.87-1.13
IS 1239 Part I	-	-	0.050	0.050	-	-	-	-
IS 3589 Gr. Fe 380	0.16 Max	1.20 Max	0.040	0.040	-	-	-	-
IS 3589 Gr. Fe 410	0.20 Max	1.30 Max	0.040	0.040	-	-	-	-

Carbon steel pipe dimensions as per ASTM & WEIGHT / KG.PER MTR. (ANSI B36.10-36.19)

Nominal pipe size	OD mm	10	20	30	STD	40	60	XS	80	100	120	140	160	XXS	Nominal pipe size	FIGURES BASED ON AUSTENITIC STEEL			
																5S	10S	40S	80S
1/2	21,30	2.10 1.00			2.77 1.27	2.77 1.27		3.73 1.62	3.73 1.62				4.78 1.95	7.47 2.55	1/2	1.65 0.82	2.11 1.01	2.77 1.27	3.73 1.62
3/4	26,70	2.11 1.27			2.87 1.69	2.87 1.69		3.91 2.20	3.91 2.20				5.56 2.90	7.82 3.64	3/4	1.65 1.04	2.11 1.28	2.87 1.69	3.91 2.20
1	33,40	2.77 2.09			3.38 2.50	3.38 2.50		4.55 3.24	4.55 3.24				6.35 4.24	9.09 5.45	1	1.65 1.68	2.77 2.13	3.38 2.55	4.55 3.29
1 1/4	42,20	2.77 2.69			3.56 3.39	3.56 3.39		4.85 4.47	4.85 4.47				6.35 5.61	9.70 7.77	1 1/4	1.65 1.95	2.77 2.76	3.56 3.46	4.85 4.56
1 1/2	48,30	2.77 3.11			3.68 4.05	3.68 4.05		5.08 5.41	5.08 5.41				7.14 7.25	10.15 9.56	1 1/2	1.65 2.24	2.77 3.17	3.68 4.13	5.08 5.51
2	60,30	2.77 3.94			3.91 5.44	3.91 5.44		5.54 7.48	5.54 7.48				8.74 11.11	11.07 13.44	2	1.65 2.39	2.77 4.01	3.91 5.54	5.54 7.63
2 1/2	73,00	3.05 5.25			5.16 8.63	5.16 8.63		7.01 11.41	7.01 11.41				9.53 14.92	14.02 20.39	2 1/2	2.11 3.77	3.05 5.36	5.16 8.81	7.01 11.64
3	88,90	3.05 6.46			5.49 11.29	5.49 11.29		7.62 15.27	7.62 15.27				11.13 21.35	15.24 27.68	3	2.11 4.60	3.05 6.59	5.49 11.52	7.62 15.59
3 1/2	101,60	3.05 7.42			5.74 13.57	5.74 13.57		8.08 18.63	8.08 18.63				-	-	3 1/2	2.11 5.29	3.05 7.55	5.74 13.84	8.08 19.01
4	114,30	3.05 8.37			6.02 16.07	6.02 16.07		8.56 22.32	8.56 22.32		11.13 28.32		13.49 33.54	17.12 41.03	4	2.11 5.96	3.05 8.52	6.02 16.40	8.56 22.77
5	141,30	3.40 11.61			6.55 21.77	6.55 21.77		9.53 30.97	9.53 30.97		12.70 40.28		15.88 49.11	19.05 57.43	5	2.77 9.67	3.40 11.82	6.55 22.20	9.53 31.59
6	168,30	3.40 13.81			7.11 28.26	7.11 28.26		10.97 42.56	10.97 42.56		14.27 54.20		18.26 67.56	21.95 79.22	6	2.77 11.55	3.40 14.13	7.11 28.83	10.97 43.42
8	219,10	3.76 20.01	6.35 33.31	7.04 36.81	8.18 42.55	8.18 42.55	10.30 53.10	12.70 64.64	12.70 64.64	15.09 75.92	18.26 90.44	20.62 100.92	23.01 111.27	22.23 107.92	8	2.77 15.09	3.76 20.37	8.18 43.39	12.70 65.95
10	273,10	4.19 27.29	6.35 41.77	7.80 51.03	9.27 60.31	9.27 60.31	12.70 81.50	12.70 81.55	15.09 96.01	18.26 114.75	21.44 133.06	25.40 155.15	28.58 172.33	25.40 155.15	10	3.40 23.08	4.19 27.79	9.27 61.52	12.70 83.19
12	323,90	4.57 36.00	6.35 49.73	8.38 65.20	9.53 73.88	9.53 79.73	10.31 109.00	14.30 97.46	12.70 132.08	17.48 159.91	21.44 186.97	25.40 208.14	28.58 238.76	33.32 186.97	12	3.96 31.89	4.57 35.99	9.53 75.32	12.70 99.43
14	355,60	6.35 54.69	7.92 67.90	9.53 81.33	9.53 81.33	11.13 94.55	15.10 126.40	12.70 107.39	19.05 158.10	23.83 194.96	27.79 224.65	31.75 253.56	35.71 281.70		14	3.96 35.06	4.78 41.36		
16	406,40	6.35 62.64	7.92 77.83	9.53 93.27	9.53 93.27	12.70 123.30	16.70 160.00	12.70 123.30	21.44 203.53	26.19 245.56	30.96 286.64	36.53 333.19	40.49 365.35		16	4.19 41.56	4.78 47.74		
18	457,00	6.35 70.57	7.92 87.71	11.13 122.38	9.53 105.16	14.27 155.80	19.00 206.00	12.70 139.15	23.83 254.55	29.36 309.62	34.93 363.56	39.67 408.26	45.24 459.37		18	4.19 46.71	4.78 53.31		
20	508,00	6.35 78.55	9.53 117.15	12.70 155.12	9.53 117.15	15.09 183.42	20.60 248.50	12.70 155.12	26.19 311.17	32.54 381.53	38.10 441.49	44.45 508.11	50.01 564.81		20	4.78 59.32	5.54 68.65		
22	559,00	6.35 86.54	9.53 129.13	12.70 171.09	9.53 129.13	-	22.20 294.00	12.70 171.09	28.58 373.83	34.93 451.42	41.28 527.02	47.63 600.63	53.98 672.26		22	4.78 65.33	5.54 75.62		
24	610,00	6.35 94.53	9.53 141.12	14.27 209.64	9.53 141.12	17.48 255.41	24.60 355.00	12.70 187.06	30.96 442.08	38.89 547.71	46.02 640.03	52.37 720.15	59.54 808.22		24	5.54 82.58	6.35 94.53		
26	660,00	7.92 127.36	12.70 202.72	-	9.53 152.87	-		12.70 202.72							26				
28	711,00	7.92 137.32	12.70 218.69	15.88 271.21	9.53 164.85	-		12.70 218.69							28				
30	762,00	7.92 147.28	12.70 234.67	15.88 292.18	9.53 176.84	-		12.70 234.67							30	6.35 118.34	7.92 147.29		
32	813,00	7.92 157.24	12.70 250.64	15.88 312.15	9.53 188.82	17.48 342.91		12.70 250.64							32				
34	864,00	7.92 167.20	12.70 266.61	15.88 332.12	9.53 200.31	17.48 364.90		12.70 266.61							34				
36	914,00	7.92 176.96	12.70 282.27	15.88 351.70	9.53 212.56	19.05 420.42		12.70 282.27							36				
38	965,00				9.53 224.54			12.70 298.24							38				
40	1016,00				9.53 236.53			12.70 314.22							40				
42	1067,00				9.53 248.52			12.70 330.19							42				

APPLICATION INDUSTRY



**REFINERY, PETROCHEMICAL
& CHEMICAL**



CEMENT



POWER & STEEL



FERTILIZERS & SUGAR



OIL & GAS INDUSTRIES



PAPER & PULP



**ENGINEERING &
PROJECTS**



PHARMACEUTICAL



**AUTOMOBILE
INDUSTRIES**



**FOOD & BEVERAGE
INDUSTRIES**



TEXTILES INDUSTRIES



OTHERS