



## Git sem conflitos

#linuxdevbr Por ANA RUTE | 03/08/2019 @ana\_rute





## Git sem conflitos

Ou como não chorar quando der conflito

#linuxdevbr Por ANA RUTE | 03/08/2019 @ana\_rute





### \$ whoami




Ana Rute Mendes Desenvolvedora na Collabora


Outreachy @ Mozilla







### Git stash







### Dicas de commit

COMMENT	DATE
CREATED MAIN LOOP & TIMING CONTROL	14 HOURS AGO
ENABLED CONFIG FILE PARSING	9 HOURS AGO
MISC BUGFIXES	5 HOURS AGO
CODE ADDITIONS/EDITS	4 HOURS AGO
O MORE CODE	4 HOURS AGO
O HERE HAVE CODE	4 HOURS AGO
AAAAAAAAA	3 HOURS AGO
ADKFJSLKDFJSDKLFJ	3 HOURS AGO
MY HANDS ARE TYPING WORDS	2 HOURS AGO
HAAAAAAAAANDS	2 HOURS AGO

AS A PROJECT DRAGS ON, MY GIT COMMIT MESSAGES GET LESS AND LESS INFORMATIVE.



## 1. Quanto antes melhor e sempre que possível



## 2. Evite usar git add.

Ao invés disso use git add -u ou adicione os arquivos manualmente.

Se mexeu em muita coisa sem commitar aos poucos, utilize git add -p

Dica: github.com/github/gitignore





## 3. Não faça de git commit -m um hábito

Use o corpo da mensagem do commit para explicar o PORQUÊ daquela mudança.

Seu eu do futuro agradece.



# 4. Use git commit --amend para modificar o último commit

Seja para adicionar um arquivo, alterar o autor ou só mudar a mensagem de commit.





### Boas práticas de commit

## VERBO IMPERATIVO + O QUE FOI FEITO (Max 50 caracteres)

git-gui: allow Ctrl+T to toggle multiple paths  dscho authored and gitster committed on Jan 9	
git-gui: fix exception when trying to stage with empty file list  dscho authored and gitster committed on Jan 9	
git-gui: avoid exception upon Ctrl+T in an empty list  as dscho authored and gitster committed on Jan 9	



## Apagador de incêndio #1

git reflog



```
791ea95 (HEAD -> master, origin/master, origin/HEAD) HEAD@{0}: checkout: moving
from c6d697f2fdea1a9df5ca93fa7fcd99811f8c3e2f to master
c6d697f HEAD@{1}: checkout: moving from master to c6d697f
791ea95 (HEAD -> master, origin/master, origin/HEAD) HEAD@{2}: rebase -i (finish
): returning to refs/heads/master
791ea95 (HEAD -> master, origin/master, origin/HEAD) HEAD@{3}: rebase -i (fixup)
: update index
94d8215 HEAD@{4}: rebase -i (fixup): # This is a combination of 3 commits.
e3173b2 HEAD@{5}: rebase -i (fixup): # This is a combination of 2 commits.
359656f HEAD@{6}: rebase -i (start): checkout HEAD~9
c6d697f HEAD@{7}: rebase -i (finish): returning to refs/heads/master
c6d697f HEAD@{8}: rebase -i (start): checkout refs/remotes/origin/master
c6d697f HEAD@{9}: clone: from git@github.com:anarute/anarute.github.io.git
```





### Navegando entre commits

git checkout





## Copiando um commit entre branches

git cherry-pick





## Limpando o histórico local

```
git reset --soft
git reset --hard
```





## Modificando o passado

git rebase -i

Abrindo a caixa de pandora



### git diff

```
diff --git a/src/companies/src/containers/App/components/AppMenu.jsx b/src/companies/src/
containers/App/components/AppMenu.jsx
index 5cc45f3..ecff196 100644
--- a/src/companies/src/containers/App/components/AppMenu.jsx
+++ b/src/companies/src/containers/App/components/AppMenu.jsx
@@ -6,7 +6,7 @@ import { withRouter } from 'react-router-dom';
import UserTypes from '../../constants/User/UserTypes';
-import Navbar from
+import NavbarResponsive from
'../../../commons/components/src/components/Navbar/NavbarResponsive';
```





### Adicionei pro staging o que não deveria

(com `git add .` por exemplo...)



### Desisti de uma mudança

```
On branch master
Changes not staged for commit:
    (use "git add <file>..." to update what will be committed)
    (use "git checkout -- <file>..." to discard changes in working directory)
    modified: hello

no changes added to commit (use "git add" and/or "git commit -a")
```




#### Deu conflito


```
On branch feature/GUPY-1609
Your branch is up-to-date with 'origin/feature/GUPY-1609'.
You have unmerged paths.
  (fix conflicts and run "git commit")
  (use "git merge --abort" to abort the merge)
Changes to be committed:
        new file: env test
        modified: .vscode/settings.json
        modified: package-lock.json
Unmerged paths:
 (use "git add <file>..." to mark resolution)
gisterActions.jsx
```



### Git + VS Code



### Git Lens



### Git e terminal

```
~/git/snippets(master) » rm LICENSE
~/git/snippets(master*) »
```

```
cd testproject
~/testproject / master / gco detached-head-state -q
~/testproject / fdffaf6 / touch dirty-working-directory
~/testproject / fdffaf6± / cd
~ ssh milly
```

→ scraperdashboard git:(fix-validation) x time
shell 1.82s user 0.81s system 0% cpu 19:41.05 total
children 17.49s user 4.30s system 1% cpu 19:41.05 total
→ scraperdashboard git:(fix-validation) x

#### Aliases

Alias	Command
g	git
ga	git add
gaa	git addall
gapa	git addpatch
gua	git addupdate
gb	git branch
gba	git branch -a



## Obrigada! Dúvidas?

```
#linuxdevbr
Por ANA RUTE | 03/08/2019

@ana_rute
```