

MitoChime: A Machine Learning Pipeline for Detecting PCR-Induced Chimeras in Mitochondrial Illumina Reads

Duran, Lin, Pailden

University of the Philippines Visayas

December 14, 2025

Outline

- 1 Introduction
- 2 Problem Statement & Proposed Solution
- 3 Objectives
- 4 Scope and Limitations
- 5 Methodology

Next Generation Sequencing (NGS)




*Source: University of the Philippines
Visayas, 2022*

Illumina Seq Workflow

Step 1. Library Preparation

① Library preparation



Source: *Microbe Notes*, 2024




Source: *Philippine Genome Center Visayas*, 2025

Illumina Seq Workflow

Step 2. Library Bridge Amplification (PCR)

② DNA library bridge amplification




Source: *Microbe Notes*, 2024



Source: *Philippine Genome Center Visayas*, 2025


Illumina Seq Workflow

Step 3. Sequencing and Alignment



Example of a short-read:


#00500123:45:HSTWLBXX:1:11101:12345:1000 T:A:0:ATCG
GATTTCACCTCCATGGTACCGTAATCGGTAGGTATCTATCGGTACCGTATG
+
AAAAFFFFF33333333333333333333333333333333333333



Example of an assembled sequence:


```
>assembled_mitochondrial_genome
GATCAGAGGCTCTATCAACCTATTAAACCATCAGGGAGCTCTCCATGCA
TTGGTATTTTTCGCTGGGGGGTATGCACGCGATGACATTCGAGACGCTG
AGCCCTCTTAAACAAACAGGAGAAACCTGATCATGATGACATTTGGCTG
TAGGGTCAGGTAGAGGAGACGCTGTAAGCTCAGTAGGACTTGCTCTTGT
GGGCTATTTCTCGCAGGACATCTCTCAACCTGAGCCCTAGTGTCTATGGA
ACACTGAAGCTCAGCAGCTAGCAGCTTACCGTAGACCTTAGCGTAGTATG
TCTCGTAGAGGCTCTCTTAGTCAGTTAGTAGTACCCCTAAGGCTCTACCT
```

PCR-Chimera Formation



Source: Omelina et al., 2024


The Mitochondrial Genome



Source: UZ Brussel., 2020

Disrupts Genome Assembly


③ DNA library sequencing



Example of a short-read:

@HIS00123:45:H5TWLBCXX:1:11101:12345:1000 1:N:0:ATCG
GATTGACTCCATGGTACCGTAATGGCTAGGTATCTATGGGTACCGTATG
+
AAAAFFFFF111111111111111111111111111111111111

④ Alignment and data analysis



Example of an assembled sequence:

```
>assembled_mitochondrial_genome
GATCAGAGGCTATACCCATTATACCACTACGGGAGCTCTCCATGCA
TTGGTATTTTTCCTCGGGGGTATGCACCGCATGACATTGCGAGACCTG
AGCCCTCTTAAACACAAACGAGGAAACCTGATCATGATGACCTTTTGCTC
TAGGGTCAGGTAGAGGAGACCTGGTAGCTCAGTAGGACTTGCTCTGTG
GGGCTATTCTCGCAGGCACTACTCTCAACCTGAGCCCTAGTCTCATGGA
ACACTGAAGCTAGCAGCTAGCAGCTCTACCGTAGACCTTAGGCTATAGC
TCTCGTAGCTCGCTTCTAGTCAGTTAGTAGTACCTGATCCCTACTACTC
```

Existing Approaches

Table 2.1: Comparison of Chimera Detection Approaches and Tools

Method / Tool	Core Approach	Key Limitations
Reference-based Detection	Compares each query sequence against curated databases of verified, non-chimeric sequences; evaluates segment similarity to identify mosaic patterns.	Accuracy depends on database completeness; performs poorly for novel taxa or missing parents; limited sensitivity for low-divergence chimeras.
De novo Detection	Identifies chimeras using only internal dataset structure; leverages abundance hierarchy and compositional similarity to infer whether low-abundance sequences can be reconstructed from abundant parents.	Assumes true sequences are more abundant; fails when amplification bias distorts abundances; struggles when parental sequences are similarly abundant or highly similar.
UCHIME	Alignment-based model that partitions the query into segments, identifies parent candidates, and computes a chimera score via a three-way alignment; supports reference and de novo modes.	Reduced accuracy for very closely related parents ($<0.8\%$ divergence); sensitive to incomplete databases; de novo mode fails if parents are absent or not sufficiently more abundant.
UCHIME2	Updated UCHIME with improved benchmarking (CHSIMA) and multiple sensitivity/specificity presets; better handles incomplete references and dataset variability.	"Fake models" limit theoretical accuracy; genuine variants may mimic chimeras; not recommended as a standalone step in OTU or denoising pipelines due to increased false positives/negatives.
CATCh	First ensemble ML model for 16S chimera detection; integrates outputs of UCHIME, ChimeraSlayer, DECIPHER, Pintail, and Perseus using an SVM to boost overall prediction accuracy.	Performance constrained by underlying tools; ML model cannot capture features not present in component algorithms; may misclassify in highly novel or low-coverage datasets.
ChimPipe	Pipeline for detecting biological chimeras in RNA-seq using discordant paired-end reads and split-read alignments; identifies isoforms and breakpoint coordinates.	Requires high-quality genome and annotation; tailored to RNA-seq rather than amplicons; computationally intensive; limited to organisms with available reference genomes.

Problem Statement & Proposed Solution

- **Problem Statement:** Chimeric sequencing reads can disrupt mitochondrial genome assembly, but current assembly pipelines assume artifact-free input and existing chimera detection tools are not designed specifically for organellar, particularly mitochondrial datasets, leaving assemblies vulnerable to undetected artifacts.
- **Proposed Solution:** A machine-learning pipeline designed to detect PCR-induced chimeric reads using both alignment-based and sequence-derived features to improve the quality and reliability of downstream mitochondrial genome assemblies.

General Objective

- Develop and evaluate a machine-learning pipeline (MitoChime) to detect PCR-induced chimeric reads in *S. lemur* mitochondrial sequencing data to improve downstream assembly quality.

Specific Objectives

- 1 Construct simulated *Sardinella lemuru* Illumina paired-end datasets containing both clean and PCR-induced chimeric reads.
- 2 Extract alignment-based and sequence-based features such as k-mer composition, microhomology, and split-alignment counts from both clean and chimeric reads
- 3 Train, validate, and compare supervised machine learning models for classifying reads as clean or chimeric.
- 4 Determine feature importance and identify indicators of PCR-induced chimerism.
- 5 Integrate the optimized classifier into a modular and interpretable pipeline deployable on standard computing environments at PGC Visayas.

Scope of the Study

- Focuses on PCR-induced chimeric reads in *Sardinella lemuru* mitochondrial sequencing data to:
 - to limit interspecific variation in mitochondrial genome size, GC content, and repetitive regions so that differences in read patterns can be attributed more directly to PCR-induced chimerism
 - to align the analysis with relevant *S. lemuru* sequencing projects at PGC Visayas
 - to take advantage of the availability of *S. lemuru* mitochondrial assemblies and raw datasets in public repositories such as the National Center for Biotechnology Information (NCBI), which facilitates reference selection and benchmarking
 - to develop a tool that directly supports local studies on *S. lemuru* population structure and fisheries management produce tools applicable to local population and fisheries studies

Scope of the Study

- Uses wgsim-based simulations and selected empirical mitochondrial datasets
- Analysis targets low-dimensional alignment and sequence features (k-mers, GC content, clipping, split alignments) to maintain interpretability and computational accessibility
- Long-read platforms and other taxa are not included

Key Exclusions

- Naturally occurring chimeras
- NUMTs
- Large-scale nuclear genome rearrangements
- High-dimensional deep learning embeddings

Other Limitations

- No simulations with variable sequencing error rates
- No testing of alternative parameter settings (k-mer length, microhomology windows)
- Reliance on supervised machine learning may limit detection of novel/unknown chimeric patterns




Figure: Process Diagram of the Special Project

The *S. lemuru* mitochondrial reference genome (NCBI: NC_039553.1) was downloaded in FASTA format and used as the basis for generating simulated reads.

Data Preprocessing

- A Python script was used to generate the reads.
- Clean reads were produced with wgsim from the reference genome with error rate set to 5%.
- A chimeric reference was created by creating a custom script to combine non-adjacent segments with microhomology
- Chimeric reads were simulated with wgsim.
- All reads were mapped with minimap2 to extract alignment information.
- SAM/BAM files were converted, sorted, and indexed with samtools.

- Final dataset: 40k reads, roughly balanced between clean and chimeric (19,984 clean reads and 20,000 chimeric).
- Some of the clean reads failed to align due to the set error rate.

Data Preprocessing

```
NC_039553.1_3_540_8:0:0_6:0:0_ef2      163      NC_039553.1      3      60      150M
TGGTGTAGCTTAAACAAAGCATAACACTGAAGATGTTACGATGGGCCGTGATAAGCCCCACACGCACTGAAAGGTTT
.....
AS:i:220      nn:i:0      tp:A:P      cm:i:8      s1:i:164      s2:i:0      de:f:0.0533
NC_039553.1_4_430_13:0:0_11:0:0_243d      163      NC_039553.1      4      60      150M
GGTGTAGCTTAAACAAAGCATAACACTGCAGATGATCCGCTGGGCCGTGATAAGCCGCAGCAGGAGTGAAAGTTTTG
.....
AS:i:170      nn:i:0      tp:A:P      cm:i:9      s1:i:135      s2:i:0      de:f:0.0867
```

Figure: SAM File of Clean Reads

Data Preprocessing

```
era_1_A9831-10051_B14983-15061_MH0_105028_105471_0:0:0_0:0:0_e2e 2129 NC_039553.1
ATCACCCACTTGACAAGCCCCACCGCCTGTACAATTGCCGTTACAGCTCTAGCACTCA I
ms:i:116 AS:i:116 nn:i:0 tp:A:P cm:i:10 s1:i:55 s2:i:0 de:f:0 SA:Z
era_1_A9831-10051_B14983-15061_MH0_105008_105480_0:0:0_0:0:0_e5a 2193 NC_039553.1
ATCACCCACTTGACAAGCCCCACCGCCTGTACAATTGCCGTTACAGCTCTAGCACTCAAGATTGGCC
I
cm:i:11 s1:i:57 s2:i:0 de:f:0 SA:Z:NC_039553.1,98,-,87M63S,60,0; NM:i:0 ms:i
rl:i:0
```

Figure: SAM File of Chimeric Reads

Feature Extraction Pipeline

- BAM files were processed with a Python script (`extract_features.py`) to build a TSV feature matrix.
- Used Pysam for parsing alignments and NumPy for computation.

Feature Extraction Pipeline

- Focused on three features linked to PCR-induced chimeras:
 - ① **Supplementary Alignment (SA)**: Detects split alignments; counts and metrics extracted from SA tags
 - ② **K-mer Composition Difference**: Breakpoints inferred; left/right segments compared using cosine and JS metrics.
 - ③ **Microhomology**: Overlap at junction quantified (length + GC content) within a defined window.
- Pipeline design and outputs to be validated by experts.

Feature Extraction Pipeline

read_id	label	read_len	mean_base	ref_name	ref_start	strand	mapq	cigar	has_sa	sa_count	num_seg	sa_diff_cor
NC_03955	0	150	13	NC_03955	3	0	60	150M	0	0	1	0
NC_03955	0	150	13	NC_03955	4	0	60	150M	0	0	1	0
NC_03955	0	150	13	NC_03955	5	0	60	150M	0	0	1	0
NC_03955	0	150	13	NC_03955	6	0	60	150M	0	0	1	0
NC_03955	0	150	13	NC_03955	9	0	60	150M	0	0	1	0

Figure: TSV Dataset showing Clean Reads

Feature Extraction Pipeline

read_id	label	read_len	mean_b	ref_name	ref_start	strand	mapq	cigar	has_sa	sa_count	num_seg	sa_diff
chimera_1	1	150	40	NC_03955	40	1	60	150M	0	0	1	0
chimera_1	1	150	40	NC_03955	53	0	60	150M	0	0	1	0
chimera_1	1	150	40	NC_03955	65	0	60	150M	0	0	1	0
chimera_1	1	150	40	NC_03955	65	0	60	150M	0	0	1	0
chimera_1	1	150	40	NC_03955	67	0	60	150M	0	0	1	0
chimera_1	1	150	40	NC_03955	67	1	60	118M32S	1	1	2	0
chimera_1	1	150	40	NC_03955	69	1	60	150M	0	0	1	0
chimera_1	1	150	40	NC_03955	76	0	60	109M41S	1	1	2	0

Figure: TSV Dataset showing Chimeric Reads

Dataset construction and split

- Simulated feature tables:
 - Clean reads (label 0)
 - PCR-induced chimeras (label 1)
- `build_datasets.py`:
 - Concatenate tables
 - Shuffle rows (avoid file-order artefacts)
- 80/20 **stratified** train-test split
- Test set held out and used **only once** at the end

Validation strategy

- Layer 1: 80/20 stratified train–test split
- Layer 2: 5-fold stratified cross-validation on training set
 - Train on 4 folds, validate on 1
 - Rotate so each fold is validation once
- Layer 3: Final evaluation on held-out test set
- Hyperparameter tuning:
 - RandomizedSearchCV inside CV for top models
- Goal: stable estimates and **unbiased** test performance

Model zoo and preprocessing pipeline

- **Baseline:** dummy majority-class classifier
- **Linear models:** logistic regression, calibrated linear SVM
- **Tree ensembles:**
 - Random Forest, Extra Trees
 - Gradient Boosting, XGBoost, LightGBM, CatBoost
- **Others:** bagging trees, k-NN, Gaussian NB, shallow MLP
- Common scikit-learn pipeline:
 - Median imputation (numeric missing values)
 - Standardisation (zero mean, unit variance)
- Ensures a **fair comparison** across models

Effect of hyperparameter tuning





Figure: Test F1: baseline vs tuned.

Figure: Test ROC-AUC: baseline vs tuned.

- Tuning done with RandomizedSearchCV on training set
- Small but consistent gains ($\Delta F1$, $\Delta AUC \approx 0.001-0.01$)
- Top-ranked models remain the same (CatBoost, Gradient Boosting, LightGBM)

ROC and precision–recall curves




Figure: ROC (left) and PR (right) curves for CatBoost, Gradient Boosting, Random Forest, and logistic regression.

- Ensembles: ROC–AUC ≈ 0.84 ; logreg: ≈ 0.82
- Average precision ≈ 0.88 for ensembles
- Precision > 0.9 up to recall ≈ 0.5 – 0.6

Confusion matrix: CatBoost (test set)






Figure: Confusion matrix heatmap for CatBoost.

- Clean reads (*negative class*):
 - Specificity ≈ 0.95 ($TN = 3782 / 3997$)
 - False positive rate ≈ 0.05 ($FP = 215 / 3997$)
- Chimeric reads (*positive class*):
 - Precision ≈ 0.92 ($TP = 2631 / (2631 + 215)$)
 - Recall ≈ 0.66 ($TP = 2631 / 4000$)
- Behaviour at default threshold:
 - **Conservative chimera filter:** low FP, higher FN
 - Misses $\sim 34\%$ of chimeras ($FN = 1369 / 4000$)

Downstream impact of residual chimeras (GetOrganelle)



- **Clean:** 1 contig (16,613 bp)
- **Mixed 50%:** 1 contig (16,593 bp)
- **Chimera-only:** 11 contigs ($\sim 39.7\%$ mapped)
- **Implication:** missed chimeras can degrade assembly completeness/contiguity.

Figure: Clean, 50% mixed, and chimera-only assemblies.

Top features for CatBoost




Figure: Permutation importance ($\Delta F1$) for CatBoost.

- Strongest predictive signals:
 - kmer_js_divergence (within-read composition shift)
 - total_clipped_bases (junction-like clipping)
 - kmer_cosine_diff (windowed k-mer change)
- Also informative:
 - Left/right soft-clipping
 - Mapping quality (MAPQ)
 - SA count (supplementary alignments)
- Consistent with PCR chimera breakpoints and split mappings

Feature family importance




Figure: Aggregated permutation importance by feature family (CatBoost).

- Aggregated importance:
 - **Clipping** features dominate
 - **K-mer jump** features are also strong
- Smaller contributions:
 - SA structure
 - Micro-homology
 - Other alignment context
- Similar ranking observed for Gradient Boosting and Random Forest

Summary of findings

- Tree-based ensembles (CatBoost, Gradient Boosting, LightGBM) outperform linear baselines.
- Best performance on held-out reads:
 - $F1 \approx 0.77$
 - $ROC-AUC \approx 0.84$
- Most predictive signals match chimera junction patterns:
 - within-read k-mer composition shifts (*k-mer jump*)
 - extensive soft-clipping / clipped bases
- At the default threshold, CatBoost is **conservative**:
 - specificity ≈ 0.95 (keeps clean reads)
 - recall ≈ 0.66 (misses some chimeras)

Next steps

- **Error analysis:** characterize FP vs FN cases (focus on false negatives).
- **Calibration:** adjust threshold / use cost-sensitive objective to increase recall while controlling FP.
- **Biological validation:** compare assemblies before vs after filtering (contig count, length, coverage).
- **Exploratory extension:** sequence models (CNN / Transformer / RNN) for subtle breakpoint patterns.

Thank you!