# FIRST LINE OF TITLE
# SECOND LINE OF TITLE

THIS IS A TEMPORARY TITLE PAGE
It will be replaced for the final print by a version
provided by the service academique.

Thèse n. 1234 2011
présenté le 12 Mars 2011
à la Faculté des Sciences de Base
laboratoire SuperScience
programme doctoral en SuperScience
École Polytechnique Fédérale de Lausanne

ÉCOLE POLYTECHNIQUE
FÉDÉRALE DE LAUSANNE

pour l'obtention du grade de Docteur ès Sciences
par

Paolino Paperino

acceptée sur proposition du jury:

Prof Name Surname, président du jury
Prof Name Surname, directeur de thèse
Prof Name Surname, rapporteur
Prof Name Surname, rapporteur
Prof Name Surname, rapporteur

Lausanne, EPFL, 2011

# Contents

# List of Figures

# List of Tables

# Torsion Part I

# Connection Part II

# 6 Bench for HPC

## 6.1 Introduction

In this section aims at providing basic but reliable guidlines to produce fast and mannagable code for our algorithms

[AMR02]

## 6.2 Languages

- Csharp - Julia - C++ - Intel MKL - OpenBLAS

## 6.3 From syntax to processor

A short story about how a code is translated to get machin instructions

## 6.4 Benchmark

## Bibliography

[AMR02] Ralph Abraham, Jerrold E. Marsde, and Tudor Ratiu. *Manifolds, Tensor Analysis, and Applications (Ralph Abraham, Jerrold E. Marsden and Tudor Ratiu)*. 2002.




Figure 6.1 – Each operator is evaluated on a vector of Float64 of size $n = 10^6$ for about 10s. Results are given relatively to MKL performance (MKL $= 1$).