A1

Pico 2 / panel USB-C cable

U1

SN74LVC245AN

ACCESSORY SPI / 3V3 SIGNALS / NO POWER

U4

SN74LVC245AN

CORE J4 / SIGNALS ONLY

U5

SN74LVC245AN

U2

SN74LS06N / I2C sink only

U3

MAX232N / 5V RS232

U6

SN74AHCT125N / LED + serial 5V

J1

6-pin DIN I2C harness

J2

DE9 DCE harness

J3

J4

J5

5V ONLY / CENTRE +

F1

2A fast / input

Q1

SUP53P06-20-E3 / reverse polarity

J6

CORE BERG 5V / 12V NC

J7

LED STRIP 5V / 0.6A MAX

J8

AUDIO LOGIC / FUTURE AMP

D1

1N5819 / VSYS feed only

C1

1uF 50V nonpolar

C2

1uF 50V nonpolar

C3

1uF 50V nonpolar

C4

1uF 50V nonpolar

C5

100nF 50V

C6

100nF 50V

C7

100nF 50V

C8

100nF 50V

C9

100nF 50V

C10

100nF 50V

C11

100nF 50V

C12

100nF 16V

C13

1000uF 10V LED bulk

RN1

5 x 4k7 I2C pullups

RN2

3 x 14 LS06 boot pulldown

R1

10k

R2

10k

R3

10k

R4

330

R5

10k

R6

10k

5V regulated centre-positive barrel only. Q1 protects reverse polarity, NOT overvoltage.
USB-C: Adafruit4056 panel extension to Pico USB socket: VBUS NOT tied to V5.
Core J4 pins2 and7 NC; Core power uses separate 5V Berg cable;12V position NC.
Accessory is custom3V3 SPI only, not UEXT/RS232/5V bus. Active Next adapter pending.
Pin-map study: passive symbols; ERC is not electrical validation. Routing, ESD, host power-off and firmware pending. 2A input fuse, 0.6A maximum LED allocation.

NOT FOR FABRICATION / 5V barrel input / NO MAINS / NOT 12V

Sheet: /
File: cyber-external-dock-r1.kicad_sch

Title: RODDY EXTERNAL DOCK / LOW VOLTAGE INTERFACE

Size: A1	Date:	Rev: R1 POWER REVISION / L
KiCad E.D.A. 10.0.6		Id: 1/1