MICHIGAN STATE COMPUTATIONAL MATH, SCIENCE AND ENGINEERING DEPARTMENT 080 4889C7E8 7A020000 488<u>B1</u>541 08000048 89D64889 C7E<u>86</u>802 0000488D 355B0400 00488B05 20080000 4889C7E8 88020000 BE100000 004889C7 E8690200 00488B15 Hå«Ëz...Hä.A...Hå:Hå«Ëh...Hç5[...Hä. ...Hå«Ëà...æ...Hå«Ëi...Hä 6880 4889С7E8 7A020000 48881541 08000048 89D64889 С7E86802 0000488D 355B0400 00488B05 20080000 4889С7E8 88020000 ВЕ100000 00488В15 на«EZ...на.я..па+па«E1...па»...па+па«E1...па»...па+па«E3...е].—нç53...на."...на«E3...е].—нç53...на."...на«E3...е].—нç53...на."...на«E3...е].—нс53...на."...на«E3...е].—нс53...на."...на«E3...е].—нс53...на."...на«E3...е].—нс53...на."...на«E3...е].—нс53...на."...на«E3...е].—нс53...на."...на«E3...е].—нс53...на."...на«E3...е].—нс53...на."...на«E3...е].—нс53...на."...на«E3...е].—нс53...на."...на«E3...е].—нс53...на."...на«E3...е].—нс53...на."...на«E3...е].—нс53...на."...на«E3...е].—нс53...на."...на«E3...е]...е]. на«E3...е].—нс53...на."...на«E3...е].—на«E3...е]. 5400 07000048 8B05F606 00004889 C7E86C01 0000C9C3 554889E5 BEFFFF00 00BF0100 0000E8A5 FFFFFFD C3554889 E5B80080 FFFF5DC3 554889E5 B8FF7F00 005DC355 ...Ha.'...Ha«Ë1....√UHàάæ''...σ...Ë•''']√UHàÂ∏.Ã'']√UHàÂ∏.Ã'']√UHàÂ∏.Ã''

MICHIGAN STATE

Outline

- what are threads and processes
- how to make a thread
- how to synchronize threads
- how to communicate between threads.

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE COMPUTATIONAL MATH, SCIENCE AND ENGINEERING DEPARTMENT 33 3 000000EF F8010000 DE7H0048 8D553304 0000488B 05E30700 004889C7 E84B0200 00D86D00 DB3C2448 89C7E813 02000048 8B15CE07 ...Hå-Hå«Ë3...Ë"...€]-Hç53...Hå."...Hå«Ë4...em,∈«\$Hå«Ë1...Hä.€...Hä.€...Hä.€...Hä.€...Hå«Ë1...E¥...€], Hç53...Hä."...Hå«Ë4...em,∈«\$Hå«Ë1...Hä.€...Hä. 6400 07000048 8B05F606 00004889 C7E86C01 0000C9C3 554889E5 BEFFFF00 00BF0100 0000E8A5 FFFFF5D C3554889 E5B80080 FFFF5DC3 554889E5 B8FF7F00 005DC355 ...Ha.'...Ha.«Ë....√UHàÁ@`'...ø....Ё•```]√UHàÁ∏.Ã``]√UHàÁ∏.Ã``]√UHàÁ∏.Ã``

MICHIGAN STATE

What's a process?

The class definition of a process is a program *in execution*. It has

- a virtual address space
- hardware context (registers, stack, file handles, etc.)
- O.S. info about priority, other resources being used

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE

Processes

- Reality: each CPU can only run one program at a time
- Fiction to user: many people getting short (~10-100 ms) time slices
 - pseudo-parallelism → multiprogramming
 - modeled as sequential processes
 - context switch

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE UNIVERSITY

Context Switch?

Processes get a fairshare of the CPU. Need to context switch, move one process off and another on the CPU

 What's involved in doing such a switch (do you imagine)

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE UNIVERSITY

Time and latency

https://eli.thegreenplace.net/2018/mea suring-context-switching-and-memoryoverheads-for-linux-threads/

Maybe 2 us to switch (4000 clock ticks)

What's the latency here?

CMSE 822, FS21, W.F. Punch


MICHIGAN STATE COMPUTATIONAL MATH, SCIENCE AND ENGINEERING DEPARTMENT 5400 07000048 8B05F606 00004889 C7E86C01 0000C9C3 554889E5 BEFFFF00 00BF0100 0000E8A5 FFFFFFD C3554889 E5B80080 FFFF5DC3 554889E5 B8FF7F00 005DC355 ...Ha.'...Ha«Ë1....√UHàάæ''...σ...Ë•''']√UHàÂ∏.Ã'']√UHàÂ∏.Ã'']√UHàÂ∏.Ã''

MICHIGAN STATE UNIVERSITY

Threads

- process: address space + single thread of control
- sometimes want multiple threads of control (flow) in same address space
- quasi-parallel
- threads separate resource grouping & execution
- thread: program counter, registers, stack
- also called lightweight processes
- multithreading: avoid blocking when waiting for resources
 - multiple services running in parallel
- state: running, blocked, ready, terminated

CMSE 822, FS21, W.F. Punch



MICHIGAN STATE UNIVERSITY

Why threads?

- Parallel execution
- Shared resources → faster communication without serialization
- faster to suspend if some are I/Obound → overlap computation and I/O
- easy porting to multiple CPUs

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE COMPUTATIONAL MATH, SCIENCE AND ENGINEERING DEPARTMENT Thread variants POSIX (pthreads) Java threads Windows threads CMSE 822, FS21, W.F. Punch

MICHIGAN STATE UNIVERSITY

Process vs. Thread (1)


- Process: unit of allocation
 - Resources, privileges, etc
- Thread: unit of execution
 - PC, SP, registers
- Each process has one or more threads
- Each thread belong to one process

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE UNIVERSITY

Process vs. Thread (2)

- Processes
 - Inter-process communication is expensive: need to context switch
 - Secure: one process cannot corrupt another process



MICHIGAN STATE UNIVERSITY

Process vs. Thread (3)

- Threads
 - Inter-thread communication cheap: can use process memory and may not need to context switch
 - Not secure: a thread can write the memory used by another thread

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE

Benefits of Threads

- Less time to create a new thread than a process (<u>maybe</u>, OS dependent)
- Less time to terminate a thread than a process (ditto)
- Switching between threads takes less time that switching processes (yes!)
- Threads can communicate with each other via shared memory
 - without invoking the kernel

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE

Threads

- Several actions that affect all of the threads in a process
 - The OS must manage these at the process level.
- Examples:
 - Suspending a process involves suspending all threads of the process
 - Termination of a process, terminates all threads within the process

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE

Activities similar to Processes

- Threads have execution states and may synchronize with one another.
 - Similar to processes
- We look at these two aspects of thread functionality in turn.
 - Startup/execution
 - Synchronization

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE

Concurrency vs. Parallel Processing

Concurrency means that multiple tasks are being processed at the same time. Not necessarily executing simultaneously

Parallel Processing means that multiple tasks are running at the same time (are executing on the CPU)

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE UNIVERSITY

Why concurrent?

It is convenient to assign elements of execution to a thread even if that thread is not presently running.

Web browser has multiple threads, one associated with each tab (for example). Maintains a state of execution!

CMSE 822, FS21, W.F. Punch

C	OMPUTATIONAL MATH, SCIENCE AND ENGINEERING DEPARTMENT	MICHIGAN STATE UNIVERSITY
	00044818 15479800 00488165 0000000 45800064 8076127 0000048 8006488 07785005 00048810 5570000 00488105 0000000 45800064 8076127 0000048 8076127 0000004 80500064 80500000 00000000 44800078 104510 1050000 448105005 00000048 80500500 000004850 00000000 44800078 104510 1050000 448105005 00000004 80500050 0000004850 00000000 44800078 104510 1050000 4481050050 00000048 000000000 0000000000 44800078 104510 1050000 4481050050 0000000000000000 4481050050 0000000000000000000000000000000	ā.5 Há+Há«Ē\ Hç5y Hā
	5 BF190000 01000000 75190000 01000000 85190000 01000000 4A190000 01000000 3F190000 01000000 65190000 01000000 55190000 01000000 34190000 01000000 5u	J?eU4
	29190000 01000000 941A0000 01000000 9F1A0000 01000000 A81A0000 01000000 B21A0000 01000000 BC1A0000 01000000 C61A0000 01000000 D01A0000 01000000)î	
	00000000 00000000 00000000 00000000 0000	
	- $-$	

MICHIGAN STATE

two models in C++11

There are really two models in C++11:

- thread model
- async task model

The former is more standardized, the latter more "interesting" from a task view.

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE

built atop a thread implementation

C++11 attempts to be more generic as it provides a model upon which different architectures and be utilized:

- pthreads for Unix
- ConcRT (concurrency runtime) windows

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE

thread

#include<thread>

thread(callable object)

thread constructor <u>copies</u> the callable object to the local thread space and <u>starts</u> that separate thread by invoking the callable object

CMSE 822, FS21, W.F. Punch

```
1.1
#include<iostream>
using std::cout; using std::endl;
#include<thread>
using std::thread;
void a fun(){
  cout << "Hello World"<<endl;</pre>
int main(){
  thread thrd(a fun);
                            argument is a
  thrd.join();
                            callable function
                 declare the
                 thread obj
 either join
 or detach
```

MICHIGAN STATE

compiling

On linux:

g++ -pthread file_to_compile.cpp

underlying implementation being used to do the C++ threading model

CMSE 822, FS21, W.F. Punch

```
1.2
```

```
#include<iostream>
using std::cout; using std::endl;
#include<thread>
                                 start thread
using std::thread;
                                 on lambda
int main(){
  thread thrd(
     []() {cout << "Hello World" << endl; }</pre>
  );
  thrd.join();
```

```
1.3
#include<iostream>
using std::cout; using std::endl;
#include<thread>
using std::thread;
#include<string>
using std::string;
class MyClass{
private:
  string my mesg ;
                                           constructor via
 public:
                                           init list
  MyClass(string s) : my mesg (s){};
  void operator()(){
    cout << my mesg << endl;</pre>
                                        op() overload makes
};
                                        and instance callable
int main(){
  MyClass mc("Hello World");
                                     invoke the
  thread thrd(mc)
  thrd.join();
                                     instance
```

MICHIGAN STATE

What you cannot do

- As shown, you cannot return a value from a thread
 - you can change a reference passed in
 - we'll see other ways, but not this way
- You cannot ever copy a thread
 - if you pass one around, it has to be by reference or by a move.

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE

join vs detach

The thread starts <u>immediately</u> and <u>independently</u> of the main thread.

The question is how they sync:

- join, caller waits at the join call for the thread to end
- detach, caller ignores the thread and each proceeds independently
 - often called a daemon

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE

when to call

You only have to call join/detach before the thread object/var is destroyed:

- you can join/detach long after the thread has finished
- if you detach, the thread may run long after the thread object is detached and after the main ends

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE

call once and done

If you have detached a thread, you can no longer communicate with it.

but you can still sync with it (more later)
 If you have joined a thread, you cannot join it again

.joinable() is a boolean that indicates whether you can join a thread

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE

when does a thread end

- if the associated thread var is destroyed (goes out of scope)
 - at that point the destructor calls terminate, ending the thread.
- if the thread throws an exception
 - thread ends

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE

what happens with exceptions

If the thread throws an exception and it is not handled, then the process halts.

If the main throws and exception before the thread is joined, the thread is destroyed and the thread terminated

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE

exceptions are really tricky

We will see down the line that handling exceptions can be tricky.

The rule is basically "If something can go wrong it will" with concurrency.

We need to be extra careful.

CMSE 822, FS21, W.F. Punch

MICHIGAN STATE UNIVERSITY

beware detach

- if possible, only work with local/copied values. This avoids a thread trying to access destroyed values in another context
- if using globals, make sure they stay in scope until the thread ends
 - we'll see how to do this later

CMSE 822, FS21, W.F. Punch