

COMPUTER SCIENCE DEPARTMENT MICHIGAN STATE UNIVERSITY

Random numbers

a quick overview of random numbers

Random numbers

COMPUTER SCIENCE DEPARTMENT MICHIGAN STATE UNIVERSITY

What the heck does random mean?

From the Wik:

"Randomness means lack of pattern or predictability in events. Randomness suggests a non-order or non-coherence in a sequence of symbols or steps, such that there is no intelligible pattern or combination."

Random numbers

COMPUTER SCIENCE DEPARTMENT MICHIGAN STATE UNIVERSITY

really random events

Physical systems:

- radioactive decay
- thermal noise (activity of electrons when no voltage applied)
- photoelectric effect (release of photons from a photoelectric source)

These are unpredictable

Random numbers

COMPUTER SCIENCE DEPARTMENT MICHIGAN STATE UNIVERSITY

random algorithm and sequence

Random number generators generate random numbers using an **algorithm**

By definition, an algorithm is predictable (that's what an algorithm is)

So how can a random number generator be really random?

Random numbers

it's the sequence

Remember:

"Randomness means lack of pattern..."

What is **random** in random number generators is the sequence

You cannot (through statistics or other means) predict the next number in a sequence based on the existing sequence.

Random numbers

10, 21, 78, 51, 58, 29, 14, 71, 71, 95

What comes next (range of 10-100)?

It's random. You cannot predict the next number (if the generator is any good).

Random numbers

the seed

Every random number generator starts with a seed, a starting value

Weirdly, if you start the generator with the same seed you get the same sequence!

The algorithm generates the same sequence starting from the same seed.

Random numbers

Same sequence from same seed

You may say to yourself, "Same sequence from the same seed, how is that random?"

Remember, randomness in this sense is the predictability of the next number given only the sequence.

Also, same sequence from same seed is useful for testing!!!

Random numbers

only need to know 4

There are 16 random engines, 21 distributions. Remember 5 (2 engine, 3 distributions):

- default_random_engine
- mt19937_64
- uniform_int_distribution<>
- uniform_real_distribution<>
- normal_distribution<>

Random numbers

well, maybe one more

The better, more useful, engine is the Mersenne twister which has a horrible name: mt19937_64

The default_random_engine does exist but it is the default chosen by the implementors. You don't know which one it is (in fact, this engine had some problems in earlier g++ implementations).

Random numbers

The basics

dre is an instance of a random engine, a source of randomness

it takes a seed arg (not required)

```
#include<random>
```

```
std::mt19937_64 dre(seed)
```

distribution range inclusive

```
std::uniform_int_distribution<long> dist(10,100)
```

```
long my_long = dist(dre)
```

dist is a distribution

distribution always passed an engine as an argument!

Random numbers

random_device

Entropy

Most modern computers (though perhaps not smaller devices such as cell phones) have various physical devices that generate "randomness":

- key stroke timings
- mouse movement
- video refresh
- all kinds of hardware stuff

Random numbers

Based on entropy in your device, if you have it, you can generate a random number:

- not recommended for a lot of random numbers, entropy might be limited
- good as a seed
 - better than the current time, which was often used

Random numbers

random_device

```
#include<random>
using std::random_device;

random_device rd;
cout << rd.entropy() << endl;
cout << rd.min() << endl;
cout << rd.max() << endl;
cout << rd() << endl;
```

Random numbers

rd.entropy()

returns 0 if in fact the random_device is not gathering info from hardware but some other random number generator.

At present, doesn't work on any implementation despite the fact that random_device does indeed work!

Random numbers

```

entropy source
for seed
random seed
from entropy
#include<random>
std::random_device rd;
std::mt19937_64 dre( rd() )
std::uniform_float_distribution<>
                        dist(0,1)
double my_double= dist(dre)

```

<> means **default**,

- long for int_dist
- double for float_dist

again, distribution passes as an arg an engine to generate a random number

Random numbers

COMPUTER SCIENCE DEPARTMENT MICHIGAN STATE UNIVERSITY

Pass engine by reference (never const)

You always pass a random engine by reference, **never** copy and **never** by const:

- Reference because if copied it will reset the sequence to the default seed (you get the same seq. every time)
- Never const because generating a number changes the engine each time.

