


ICS 624 Spring 2013

Data Mining Overview (1)


Asst. Prof. Lipyeow Lim
Information & Computer Science Department
University of Hawaii at Manoa

Classification Problem




- **Model construction**: describing a set of predetermined classes
 - Each tuple/sample in **training set** is assumed to belong to a predefined class, as determined by the **class label attribute**
- **Model usage**: for classifying future or unknown objects
 - **Estimate accuracy** of the model using test set with ground truth
 - Accuracy rate is the percentage of test set samples that are correctly classified by the model
 - Test set is independent of training set, otherwise **over-fitting**
 - If the accuracy is acceptable, use the model to **classify data** tuples whose class labels are not known
- If class labels are **continuous** => **“Prediction Problem”**

Process (1): Model Construction



Process (2): Using the Model in Prediction



Supervised vs. Unsupervised Learning


- Supervised learning (classification)
 - Supervision: The training data (observations, measurements, etc.) are accompanied by labels indicating the class of the observations
 - New data is classified based on the training set
- Unsupervised learning (clustering)
 - The class labels of training data is unknown
 - Given a set of measurements, observations, etc. with the aim of establishing the existence of classes or clusters in the data

Decision Tree Induction: Training Dataset

This follows an example of Quinlan's ID3 (Playing Tennis)

age	income	student	credit_rating	buys_computer
<=30	high	no	fair	no
<=30	high	no	excellent	no
31...40	high	no	fair	yes
>40	medium	no	fair	yes
>40	low	yes	fair	yes
>40	low	yes	excellent	no
31...40	low	yes	excellent	yes
<=30	medium	no	fair	no
<=30	low	yes	fair	yes
>40	medium	yes	fair	yes
<=30	medium	yes	excellent	yes
31...40	medium	no	excellent	yes
31...40	high	yes	fair	yes
>40	medium	no	excellent	no

Output: A Decision Tree for “*buys_computer*”



Algorithm for Decision Tree Induction

- Basic algorithm (a greedy algorithm)
 - Tree is constructed in a **top-down recursive divide-and-conquer manner**
 - At start, all the training examples are at the root
 - Attributes are categorical (if continuous-valued, they are discretized in advance)
 - Examples are partitioned recursively based on selected attributes
 - Test attributes are selected on the basis of a heuristic or statistical measure (e.g., **information gain**)
- Conditions for stopping partitioning
 - All samples for a given node belong to the same class
 - There are no remaining attributes for further partitioning – **majority voting** is employed for classifying the leaf
 - There are no samples left

Overfitting and Tree Pruning

- Overfitting: An induced tree may overfit the training data
 - Too many branches, some may reflect anomalies due to noise or outliers
 - Poor accuracy for unseen samples
- Two approaches to avoid overfitting
 - Prepruning: Halt tree construction early—do not split a node if this would result in the goodness measure falling below a threshold
 - Difficult to choose an appropriate threshold
 - Postpruning: Remove branches from a “fully grown” tree—get a sequence of progressively pruned trees
 - Use a set of data different from the training data to decide which is the “best pruned tree”

Accuracy Measures

Pred. \ Truth	C_1	C_2
C_1	True positive	False negative
C_2	False positive	True negative

- Accuracy of a classifier M , $\text{acc}(M)$: percentage of test set tuples that are correctly classified by the model M
 - Error rate (misclassification rate) of $M = 1 - \text{acc}(M)$
 - Given m classes, $CM_{i,j}$, an entry in a **confusion matrix**, indicates # of tuples in class i that are labeled by the classifier as class j
- Alternative accuracy measures (e.g., for cancer diagnosis)
 - sensitivity = $\text{t-pos} / \text{pos}$ /* true positive recognition rate */
 - specificity = $\text{t-neg} / \text{neg}$ /* true negative recognition rate */
 - precision = $\text{t-pos} / (\text{t-pos} + \text{f-pos})$
 - accuracy = $\text{sensitivity} * \text{pos} / (\text{pos} + \text{neg}) + \text{specificity} * \text{neg} / (\text{pos} + \text{neg})$
 - This model can also be used for cost-benefit analysis

Evaluating the Accuracy (I)


- **Holdout method**
 - Given data is randomly partitioned into two independent sets
 - Training set (e.g., 2/3) for model construction
 - Test set (e.g., 1/3) for accuracy estimation
 - Random sampling: a variation of holdout
 - Repeat holdout k times, accuracy = avg. of the accuracies obtained
- **Cross-validation** (k -fold, where $k = 10$ is most popular)
 - Randomly partition the data into k *mutually exclusive* subsets, each approximately equal size
 - At i -th iteration, use D_i as test set and others as training set
 - Leave-one-out: k folds where $k = \#$ of tuples, for small sized data
 - Stratified cross-validation: folds are stratified so that class dist. in each fold is approx. the same as that in the initial data

Evaluating the Accuracy (II)

- **Bootstrap**
 - Works well with small data sets
 - Samples the given training tuples uniformly *with replacement*
 - i.e., each time a tuple is selected, it is equally likely to be selected again and re-added to the training set
- Several bootstrap methods, and a common one is **.632 bootstrap**
 - Suppose we are given a data set of d tuples. The data set is sampled d times, with replacement, resulting in a training set of d samples. The data tuples that did not make it into the training set end up forming the test set. About 63.2% of the original data will end up in the bootstrap, and the remaining 36.8% will form the test set (since $(1 - 1/d)^d \approx e^{-1} = 0.368$)
 - Repeat the sampling procedure k times, overall accuracy of the model:

$$acc(M) = \sum_{i=1}^k (0.632 \times acc(M_i)_{test_set} + 0.368 \times acc(M_i)_{train_set})$$

Ensemble Methods: Increasing the Accuracy



- Ensemble methods
 - Use a combination of models to increase accuracy
 - Combine a series of k learned models, M_1, M_2, \dots, M_k , with the aim of creating an improved model M^*
- Popular ensemble methods
 - **Bagging**: averaging the prediction over a collection of classifiers
 - **Boosting**: weighted vote with a collection of classifiers
 - Ensemble: combining a set of heterogeneous classifiers

Bagging: Bootstrap Aggregation

- Analogy: Diagnosis based on multiple doctors' majority vote
- Training
 - Given a set D of d tuples, at each iteration i , a training set D_i of d tuples is sampled with replacement from D (i.e., bootstrap)
 - A classifier model M_i is learned for each training set D_i
- Classification: classify an unknown sample X
 - Each classifier M_i returns its class prediction
 - The bagged classifier M^* counts the votes and assigns the class with the most votes to X
- Prediction: can be applied to the prediction of continuous values by taking the average value of each prediction for a given test tuple
- Accuracy
 - Often significant better than a single classifier derived from D
 - For noise data: not considerably worse, more robust
 - Proved improved accuracy in prediction

Boosting

- Analogy: Consult several doctors, based on a combination of weighted diagnoses—weight assigned based on the previous diagnosis accuracy
- How boosting works?
 - Weights are assigned to each training tuple
 - A series of k classifiers is iteratively learned
 - After a classifier M_i is learned, the weights are updated to allow the subsequent classifier, M_{i+1} , to pay more attention to the training tuples that were misclassified by M_i
 - The final M^* combines the votes of each individual classifier, where the weight of each classifier's vote is a function of its accuracy
- The boosting algorithm can be extended for the prediction of continuous values
- Comparing with bagging: boosting tends to achieve greater accuracy, but it also risks overfitting the model to misclassified data

Adaboost (Freund and Schapire, 1997)

- Given a set of d class-labeled tuples, $(\mathbf{X}_1, y_1), \dots, (\mathbf{X}_d, y_d)$
- Initially, all the weights of tuples are set the same ($1/d$)
- Generate k classifiers in k rounds. At round i ,
 - Tuples from D are sampled (with replacement) to form a training set D_i of the same size
 - Each tuple's chance of being selected is based on its weight
 - A classification model M_i is derived from D_i
 - Its error rate is calculated using D_i as a test set
 - If a tuple is misclassified, its weight is increased, o.w. it is decreased
- Error rate: $err(\mathbf{X}_j)$ is the misclassification error of tuple \mathbf{X}_j . Classifier M_i error rate is the sum of the weights of the misclassified tuples:

$$error(M_i) = \sum_j^d w_j \times err(\mathbf{X}_j)$$

- The weight of classifier M_i 's vote is

$$\log \frac{1 - error(M_i)}{error(M_i)}$$

Random Decision Forests

T.K.Ho. Random Decision Forests. ICDAR 1995.

X_1	X_2	X_3	X_4	X_5	Y
...	

- **Idea:** Construct a forest of decision trees by
 - Randomly choosing a subset of features
 - Building a decision tree using the subset of features
 - Combine the class labels from the forest using a discriminant function (see paper for details).
- **Claims:**
 - Increasing the size of the subset of features increases the accuracy
 - Increasing the size of the forest increases accuracy
 - Accuracy doesn't seem to be limited cf. other techniques

One-Class Classification

K. Hempstalk, E. Frank, and I. Witten. One-class classification by combining density and class probability estimation. In Proc. of ECML'08, pages 505–519, 2008

- **Problem:** Training data does not contain examples with negative labels (“2nd class”)
- **Idea 1:** Artificially generate negative examples
 - A uniformly random example may be far away from the decision boundary
 - Use a “reference distribution” $P(X|A)$ close to target class
- **Idea 2:** View the problem as density estimation – decision boundary is a threshold
 - Use Bayes’ Thm to correct for the reference distribution
 - $P(X|T) = P(X|A) * [1 - P(T)] P(T|X) / \{ P(T) [1 - P(T|X)] \}$
 - Use traditional classifiers to estimate $P(\text{Target}|X)$
 - Tune the decision threshold to get desired accuracy