Separating Viewer Motion from 3D Model Registration for Video See-Through Navigation

Ranyang Li, Nan Wei, Zhipeng Lin, Wufeng Liu, Chao Fan, and Junjun Pan

***Abstract*—Registering a 3D navigation model onto a live video see-through stream fails when the camera rotates rapidly, even when the physical target moves smoothly. Because the observed model-to-camera pose T_{cm} composes the world-to-camera transformation T_{cw} with the model-to-world transformation T_{wm}, temporal filtering on T_{cm} misinterprets camera rotation as 3D target motion, while rendering with the exposure-time pose leaves an uncompensated pixel shift across the pipeline delay τ. Pure 2D rotational image warps (Asynchronous TimeWarp) also break down at close working distances where camera translation and independent target motion induce depth parallax. We present a viewer-decoupled 3D registration method built on an inertial-guided static-anchor network (*EgoAnchorNet*) and a two-stage temporal architecture. At frame exposure midpoint t_e, EgoAnchorNet subtracts the IMU-predicted rotational flow so stationary background pixels collapse to a translational epipolar field, separating static scene anchors (91.1% IoU) from moving targets (88.9% IoU) and driving cascaded differentiable Gauss–Newton solvers for both $T_{cw}(t_e)$ and $T_{wm}(t_e)$. At display completion $t_d = t_e + \tau$, the scene-referenced model pose $T_{wm}(t_e)$ is held fixed while only the viewer pose T_{cw} is propagated across τ via the rigidly mounted IMU. In a three-condition counterfactual ablation across nine classical and learned methods (SIFT, ORB, KLT, LoFTR, RAFT, ATW, VGGT, Reloc3r, and Pi3), removing viewer ego-motion cuts fast-turn ($[2.0, 10.0)$ rad/s) target-region rotation error by 43.4%–77.8% and AR overlay drift from 42.1 px (52.4 px under 2D ATW) to 10.2 px. In direct head-to-head evaluation under simultaneous camera and target motion, EgoAnchorNet achieves 0.08° median camera rotation error and 1.31° target rotation error at 68.2 ms per pair, outperforming VGGT (1.82°, 165 ms), Pi3 (2.01°, 95 ms), and Reloc3r (2.24°, 118 ms), while reducing high-rate 3D model Average Distance (ADD) error to 1.79–2.19 mm.**

***Index Terms*—Video see-through augmented reality, 3D model registration, static-anchor motion disentanglement, viewer motion compensation, camera-IMU fusion, angular-velocity stratification.**

I. Introduction

VIDEO see-through augmented reality (AR) navigation overlays a pre-reconstructed 3D model—such as a computed tomography (CT) organ mesh or a computer-aided design (CAD) target—directly onto live video frames captured by a 4K camera or a stereo endoscope [11]–[13]. Unlike optical see-through head-mounted displays (HMDs), the display is the video frame itself, and both the handheld or robot-mounted camera and the physical target move in 3D space while surrounding background structures remain stationary. Whenever the camera rotates rapidly, the rendered 3D overlay detaches from the physical target.

This failure stems from how registration pipelines represent and update the composite model-to-camera transformation

$$T_{cm}(t) = T_{cw}(t)\, T_{wm}(t) \in \mathrm{SE}(3), \tag{1}$$

where $T_{cw}(t)$ maps world coordinates into the camera frame and $T_{wm}(t)$ places the 3D model in the scene. Treating $T_{cm}(t)$ as a single state variable creates three compounding errors under viewer motion. First, in the image plane, camera rotation $\boldsymbol{\omega}$ sweeps every pixel by approximately $f\|\boldsymbol{\omega}\|\Delta t$ regardless of depth z, masking the boundary between stationary background regions ($\mathcal{M}_{\text{stat}}$) and the independently moving target ($\mathcal{M}_{\text{obj}}$). Second, in 3D pose estimation, any correspondence or optical-flow solver that does not strictly isolate $\mathcal{M}_{\text{stat}}$ leaks target motion into the camera ego-motion estimate $T_{cw}(t)$, while temporal smoothing on the composite pose $T_{cm}(t)$ projects camera acceleration onto the 3D model trajectory. Third, over the pipeline latency $\tau = t_d - t_e$ between exposure midpoint t_e and display write t_d, rendering with $T_{cm}(t_e)$ leaves an uncompensated rotational swim $f\|\boldsymbol{\omega}\|\tau$, whereas 2D post-rendering warps such as Asynchronous TimeWarp (ATW) [5], [6], [14] fail at close working distances ($z \approx 150$ mm) where camera translation and target displacement violate the zero-parallax homography assumption.

To determine whether high-rate registration failure is driven by target dynamics or by viewer ego-motion, we first conduct a three-condition counterfactual ablation in which both ground-truth camera trajectory $T_{wc}(t)$ and independent target trajectory $T_{wm}(t)$ are controlled (Fig. 1): Condition 1 retains both camera and target 6DoF motion; Condition 2 removes viewer ego-motion while preserving the exact 3D target trajectory $T_{wm}(t)$; and Condition 3 freezes the target in world space while replaying the exact camera trajectory $T_{wc}(t)$ (or extrapolates the coupled pose T_{cm}). Across nine classical and learned baselines—SIFT [4], ORB [10], Lucas–Kanade (KLT) [7], LoFTR [9], RAFT [8], 2D ATW [5], VGGT [3], Reloc3r [2], and Pi3 [1]—Condition 1 and Condition 3 degrade together in the $[2.0, 10.0)$ rad/s bin, whereas removing viewer ego-motion

This work was supported in part by the National Natural Science Foundation of China under Grant 62402163; in part by the Open Project Program of the State Key Laboratory of Virtual Reality Technology and Systems under Grant VRLAB2023C03; in part by the High-Level Talents Fund of Henan University of Technology under Grants 2022BS076 and 2022BS075; and in part by the Cultivation Project of the Tuoxin Team at Henan University of Technology under Grant 2024TXTD18. *(Corresponding authors: Ranyang Li; Junjun Pan.)*

Ranyang Li, Wufeng Liu, and Chao Fan are with the School of Artificial Intelligence and Big Data, Henan University of Technology, Zhengzhou 450001, China (e-mail: lry@haut.edu.cn).

Nan Wei is with Henan Provincial People's Hospital, Zhengzhou University, Zhengzhou 450003, China.

Zhipeng Lin and Junjun Pan are with the State Key Laboratory of Virtual Reality Technology and Systems, Beihang University, Beijing 100191, China (e-mail: linzhi_p@outlook.com; pan_junjun@buaa.edu.cn).




Fig. 1. Three-condition counterfactual ablation under simultaneous camera and target motion (1280 × 720, shared aggressive 6DoF camera trajectory, 10 pairs per angular-velocity bin). **(a)** Uncompensated AR overlay (Condition 1: camera and target both moving at 3.40 rad/s); the 3D navigation prism (red) shifts by 39.3 px from the ground-truth target mesh (green). **(b)** Camera ego-motion removed (Condition 2), leaving only the target's single-frame motion (13.6 px, cyan). **(c)** Corner displacement field (39.3 px → 13.6 px, −65%). **(d)** Median rotation error in the 360 × 210 target region of interest (ROI) for Pi3 [1], Reloc3r [2], VGGT [3], SIFT [4], and EgoAnchorNet (Ours). **(e)** AR registration error across Condition 1 (ego + target), Condition 3 (ego only, target fixed), 2D Asynchronous TimeWarp (ATW) [5], [6], EgoAnchorNet Stage-I, and Condition 2 (Stage-II ego removed). **(f)** Pyramidal Lucas–Kanade [7] and dense RAFT [8] survival on the target. **(g)** Detector-free LoFTR [9] matches, SIFT keypoints, and ORB [10] matches on the target.

in Condition 2 restores dense matches (+77.0%–94.3%) and tracking survival (89.2%–99.0%), cuts target-ROI rotation error by 43.4%–77.8%, and reduces AR overlay shift from 42.1 px (52.4 px under 2D ATW) to 10.2 px.

We resolve both the spatial and temporal coupling between viewer and target motion through an inertial-guided static-anchor network (*EgoAnchorNet*) and a two-stage registration architecture. At the exposure midpoint t_e, EgoAnchorNet uses the preintegrated rotation increment ΔR_{imu} from a rigidly mounted IMU to subtract depth-independent rotational optical flow, reducing stationary background flow to a pure translational epipolar field that separates $\mathcal{M}_{\text{stat}}$ from $\mathcal{M}_{\text{obj}}$. Cascaded differentiable Gauss–Newton solvers then estimate $T_{cw}(t_e)$ strictly on $\mathcal{M}_{\text{stat}}$ and $T_{wm}(t_e)$ on the camera-subtracted residual flow of $\mathcal{M}_{\text{obj}}$. Temporal filtering acts on the scene-referenced pose $T_{wm}(t_e) = T_{cw}(t_e)^{-1} T_{cm}(t_e)$, and at display time $t_d = t_e + \tau$, only the viewer pose T_{cw} is propagated across τ via the IMU. Our contributions are threefold:

1) **Inertial De-Rotated Static-Anchor Disentanglement and Cascaded Dual-$\mathrm{SE}(3)$ Solver (*EgoAnchorNet*):** We introduce an inertial de-rotation operator that removes rotational flow before motion segmentation, isolating stationary scene anchors (99.1% IoU) from moving targets (88.9% IoU) and driving cascaded differentiable Gauss–Newton solvers that jointly recover metric

camera ego-motion (0.08° median rotation error) and 3D target motion (1.31° median rotation error).

2) **Two-Stage Viewer-Decoupled Registration and Display-Time Compensation Architecture:** We decouple exposure-time scene-coordinate filtering on $T_{wm}(t_e)$ from display-time IMU propagation on $T_{cw}(t_d)$, preventing viewer acceleration from corrupting the 3D model state while eliminating depth-invariant rotational swim over τ.
3) **Counterfactual Dual-Motion Benchmark and Angular-Velocity-Stratified Verification:** We build a hybrid benchmark pairing 6DoF dual-motion ground truth with real endoscopic textures from SCARED [15], evaluate nine classical/learned baselines and four network ablations across four angular-velocity bins, and verify 1.79–2.19 mm 3D model ADD accuracy across 4K+IMU and stereo+IMU setups.

II. Related Work

We group prior work by the failure modes that occur when a 3D model is registered to a live video stream under viewer motion, and list open-source implementations in Table I.

A. Display Latency and View Reprojection in AR and Graphics

Post-rendering reprojection updates a rendered image to match viewer motion between rendering and display. Lincoln et al. [14] reduced motion-to-photon latency on an optical see-through HMD to 80 μs using low-persistence modulation and 2D post-render warps at $50^\circ/\text{s}$ head turns. For video see-through HMDs, Ishihara et al. [13] combined eye-camera parallax warping with latency compensation (50–62.5 ms uncompensated delay), and Wang et al. [16] compensated geometric and radiometric delay in projector-camera systems (ViComp).

In recent ACM SIGGRAPH and XR runtime systems, Lu and Rowe [5] introduced QUASAR (SIGGRAPH 2025), which streams pixel-aligned quad geometry rather than 2D frames so a client can reproject views under 6DoF motion with motion parallax and disocclusion handling, releasing open-source baselines for Asynchronous TimeWarp (ATW, $H = KR_{\text{new}}^{-1}R_{\text{old}}K^{-1}$), MeshWarp, and QuadStream. Gao et al. [6] developed XRgo and OpenWarp (integrated into ILLIXR) for 6DoF mesh and raymarching reprojection, while Yang et al. [17] (Mob-FGSR, SIGGRAPH 2024) used motion-vector frame extrapolation to hide rendering latency on mobile GPUs.

Two properties prevent these display-warping methods from solving video see-through 3D model registration: (i) rotational 2D warps (ATW) assume zero translation or infinite depth, which fails at close working distances ($z \approx 150$ mm) where camera translation and independent target motion produce large parallax (52.4 px ATW error in Fig. 1(e)); and (ii) all of them assume the virtual object's 3D pose in the scene is already known, so they do not prevent an upstream pose filter on T_{cm} from absorbing viewer rotation.

TABLE I
Open-Source Repositories for Latency Reprojection, Dynamic Motion Decoupling, and Correspondence Estimation.

System	Venue	Scope	GitHub Repository
ViComp [16]	TVCG 24	Proj.-cam warp	`cyxwang/ViComp`
OpenWarp [6]	MMSys 25	6DoF XR warp	`Zee2/openwarp`
QUASAR [5]	SIGGRAPH 25	Quad / ATW warp	`quasar-gfx/QUASAR`
PAD3R [18]	SIGGRAPH Asia 25	Offline 4D recon.	`pad3r/pad3r-public`
Shape of Motion [19]	ICCV 25	Offline 4D tracks	`vye16/shape-of-motion`
MegaSaM [20]	CVPR 25	Dynamic video BA	`mega-sam/mega-sam`
BA-Track [21]	ICCV 25	Decoupled 3D BA	`wrchen530/batrack`
VGGT [3]	CVPR 25	Feed-forward 3D	`facebookresearch/vggt`
Reloc3r [2]	CVPR 25	Pairwise pose	`ffrivera0/reloc3r`
Pi3 [1]	arXiv 25	Equivariant pose	`yyfz/Pi3`
LoFTR [9]	CVPR 21	Dense matcher	`zju3dv/LoFTR`
RAFT [8]	ECCV 20	Recurrent flow	`princeton-vl/RAFT`
OpenVINS [22]	ICRA 20	Stereo-IMU VIO	`rpng/open_vins`
XR-Check [23]	ISMAR 25	XR tracking bench.	`Duke-I3T-Lab/XR_Tracking_Evaluation`

B. Decoupling Camera Ego-Motion from Dynamic Objects

Separating camera-induced pixel motion from independent object motion has been studied in recent SIGGRAPH and computer vision pipelines. At SIGGRAPH Asia 2025, Liao et al. [18] proposed PAD3R, which reconstructs deformable 3D objects from casual monocular videos by pairing a DINOv2 camera pose estimator with CoTracker3 2D correspondences. Wang et al. [19] (Shape of Motion) and Li et al. [20] (MegaSaM) recover camera trajectories in dynamic videos by masking or down-weighting moving foreground regions during differentiable bundle adjustment. Chen et al. [21] (BA-Track) decompose observed 3D point tracks into a camera-induced component and a dynamic-object component so epipolar bundle adjustment can retain both static and moving points.

For online correspondence and pose estimation, detector-free transformer matchers such as LoFTR [9] and recurrent optical-flow networks such as RAFT [8] replace hand-crafted descriptors (SIFT [4], ORB [10]) and local Lucas–Kanade tracking [7]. Feed-forward 3D foundation models—including DUSt3R [24], VGGT [3], Reloc3r [2], and Pi3 [1]—regress relative poses directly from image pairs, while visual-inertial odometry (VIO) systems such as OpenVINS [22], Basalt [25], ORB-SLAM3 [26], and collaborative mobile AR SLAM [27] fuse camera tracks with IMU preintegration.

However, three gaps remain when applying these methods to live 3D model registration:

1) Offline 4D optimization pipelines (PAD3R [18], Shape of Motion [19], MegaSaM [20], BA-Track [21]) require multi-pass global optimization over full video sequences rather than causal frame-by-frame execution within a 33–70 ms budget.
2) When a moving target occupies the navigation ROI, feed-forward pose networks (VGGT [3], Pi3 [1], Reloc3r [2]) and dense matchers/trackers (LoFTR [9], RAFT [8]) suffer from viewer-induced blur and perspective foreshortening (Fig. 1 and Table II).
3) Lightweight single-pose flow solvers (such as baseline coupled EgoLite) assign non-zero weight to deforming or moving regions and solve only for camera ego-motion, leaving the moving target's 3D trajectory unestimated and allowing target motion to bias camera translation.

C. 3D Model Registration in Endoscopic and Camera Navigation

In surgical and industrial navigation, a prior 3D model (CT/MRI mesh or CAD model) is aligned to live video [11], [12]. Continuous bronchoscopy and laparoscopy registration systems [11], [12] report that fast scope rotation causes blur and overlay swim, forcing operators to pan slowly or restricting overlays to static keyframes. Public endoscopic datasets such as SCARED [15] and EndoSLAM [28] lack synchronized camera-mounted IMU streams paired with controlled angular-velocity tiers and independent target motion ground truth; furthermore, poses in ray-cast synthetic sets are often derived from 2D–3D registration itself, making them circular for causal evaluation. Recent ISMAR benchmarks on spatial tracking [23], [29], 3D reconstruction alignment (MR-Compare [30]), and perceptual registration ambiguity [31] confirm that session-averaged trajectory metrics conceal high-velocity failures and that registration offsets beyond task tolerance cause users to select the wrong target. We therefore evaluate both 3D millimetre error and 2D pixel shift directly against IMU angular velocity.

III. Methodology

A. Coordinate Frames, Notation, and Preliminaries

We define four right-handed 3D coordinate frames: the stationary world (scene) frame $\mathcal{F}_w$, the moving camera frame $\mathcal{F}_c$ (with $+X$ right, $+Y$ down, and $+Z$ along the optical axis), the rigidly mounted IMU frame $\mathcal{F}_i$, and the local coordinate frame $\mathcal{F}_m$ of the 3D navigation model. A rigid transformation $T_{ab} = (R_{ab}, \mathbf{p}_{ab}) \in \mathrm{SE}(3)$ with rotation $R_{ab} \in \mathrm{SO}(3)$ and translation $\mathbf{p}_{ab} \in \mathbb{R}^3$ maps a homogeneous point $\mathbf{X}_b \in \mathbb{R}^3$ from $\mathcal{F}_b$ to $\mathcal{F}_a$ via $\mathbf{X}_a = R_{ab}\mathbf{X}_b + \mathbf{p}_{ab}$. Specifically, $T_{cw}(t) = T_{wc}(t)^{-1}$ denotes the world-to-camera pose, $T_{wm}(t)$ denotes the model-to-world pose, $T_{cm}(t) = T_{cw}(t)T_{wm}(t)$ denotes the composite model-to-camera pose, and $R_{ci} \in \mathrm{SO}(3)$ is the calibrated camera-from-IMU extrinsic rotation.

For a twist vector $\boldsymbol{\xi} = [\boldsymbol{\rho}^\top, \boldsymbol{\theta}^\top]^\top \in \mathbb{R}^6$ with translational component $\boldsymbol{\rho} \in \mathbb{R}^3$ and rotational component $\boldsymbol{\theta} \in \mathbb{R}^3$, the hat operator $[\cdot]_\times : \mathbb{R}^3 \to \mathfrak{so}(3)$ produces the skew-symmetric matrix $[\boldsymbol{\theta}]_\times$, and $\exp_{\mathrm{SE}(3)}(\boldsymbol{\xi}^\wedge)$ and $\log_{\mathrm{SE}(3)}(T)$ denote the matrix exponential and logarithm between $\mathfrak{se}(3)$ and $\mathrm{SE}(3)$. Given camera intrinsics $K \in \mathbb{R}^{3\times3}$ with focal lengths (f_x, f_y) and principal point (c_x, c_y), the perspective projection of a 3D point $\mathbf{X}_c = [X, Y, Z]^\top \in \mathcal{F}_c$ onto pixel coordinates $\mathbf{u} = [u, v]^\top \in \mathbb{R}^2$ is $\mathbf{u} = \Pi(K\mathbf{X}_c)$, where $\Pi([x, y, z]^\top) = [x/z, y/z]^\top$.

B. Image-Plane Drift over the Pipeline Delay

Let $\mathbf{X}_m \in \mathcal{F}_m$ be a vertex on the 3D model. Over the pipeline delay $\tau = t_d - t_e$ between frame exposure midpoint t_e and completed overlay write t_d, the camera moves by the left increment

$$\Delta T_c(t_e, t_d) = T_{cw}(t_d)\, T_{cw}(t_e)^{-1} = \exp_{\mathrm{SE}(3)}\left(\begin{bmatrix}\boldsymbol{\rho}\\ \boldsymbol{\theta}\end{bmatrix}^\wedge\right), \quad (2)$$

with rotation vector $\boldsymbol{\theta} \approx \boldsymbol{\omega}\,\tau$ induced by camera angular velocity $\boldsymbol{\omega} \in \mathbb{R}^3$ and translation $\boldsymbol{\rho} \approx \mathbf{v}\,\tau$ induced by linear velocity $\mathbf{v} \in \mathbb{R}^3$. For mean focal length $f = \frac{1}{2}(f_x + f_y)$ and target depth z, rendering at t_d with the exposure-time pose $T_{cm}(t_e)$ produces a first-order pixel shift

$$\Delta u_{\text{drift}}(\tau) \approx \underbrace{f\,\|\boldsymbol{\omega}\|\,\tau}_{\text{viewer rotation}} + \underbrace{\frac{f\,\|\mathbf{v}\|\,\tau}{z}}_{\text{viewer translation}} + \underbrace{\Delta u_{\text{target}}(\tau)}_{\text{target motion}}. \quad (3)$$

At $f = 1095$ px (1280×720) and $\tau = 60$ ms, a 2.6 rad/s camera turn yields 171 px of rotational shift regardless of depth z, exceeding the target's own single-frame displacement $\Delta u_{\text{target}}(\tau)$.

C. EgoAnchorNet: Inertial-Guided Static-Anchor Dual-$\mathrm{SE}(3)$ Solver

In a scene partitioned into stationary background pixels $\mathcal{M}_{\text{stat}}$ ($\mathbf{X}_w(t_{e,k}) = \mathbf{X}_w(t_{e,k-1})$) and independently moving target pixels $\mathcal{M}_{\text{obj}}$ ($\mathbf{X}_w(t_{e,k}) = R_B\mathbf{X}_w(t_{e,k-1}) + \mathbf{p}_B$), a 3D point $\mathbf{X}_{c,k-1} = Z(\mathbf{u})\,K^{-1}\tilde{\mathbf{u}}$ (where $\tilde{\mathbf{u}} = [u, v, 1]^\top$ and $Z(\mathbf{u}) > 0$ is metric depth) transforms between frames $t_{e,k-1}$ and $t_{e,k}$ as

$$\mathbf{X}_{c,k}(\mathbf{u}) = \begin{cases} \Delta R_{\text{cam}}\,\mathbf{X}_{c,k-1}(\mathbf{u}) + \Delta\mathbf{t}_{\text{cam}}, & \mathbf{u} \in \mathcal{M}_{\text{stat}},\\ \Delta R_{\text{obj}}\,\mathbf{X}_{c,k-1}(\mathbf{u}) + \Delta\mathbf{t}_{\text{obj}}, & \mathbf{u} \in \mathcal{M}_{\text{obj}}, \end{cases} \quad (4)$$

where $(\Delta R_{\text{cam}}, \Delta\mathbf{t}_{\text{cam}}) \in \mathrm{SE}(3)$ is the camera relative motion and $(\Delta R_{\text{obj}}, \Delta\mathbf{t}_{\text{obj}}) \in \mathrm{SE}(3)$ is the composite target-in-camera relative motion.

1) Inertial De-Rotation and Translational Epipolar Reduction: From a single image pair, raw optical flow $\mathbf{f}_{\text{obs}}(\mathbf{u}) = \Pi(K\mathbf{X}_{c,k}(\mathbf{u})) - \mathbf{u}$ is dominated by camera rotation ΔR_{cam}, which sweeps all pixels across the image plane regardless of whether they belong to $\mathcal{M}_{\text{stat}}$ or $\mathcal{M}_{\text{obj}}$ (Fig. 4(a)). Using the preintegrated IMU rotation increment $\Delta R_{\text{imu}} = \exp_{\mathrm{SO}(3)}([R_{ci}\boldsymbol{\omega}_i\Delta t]_\times)$, we compute the pure rotational flow

$$\mathbf{f}_{\text{rot}}(\mathbf{u}; \Delta R_{\text{imu}}) = \Pi\big(K\,\Delta R_{\text{imu}}\,K^{-1}\tilde{\mathbf{u}}\big) - \mathbf{u}, \quad (5)$$

and subtract it from $\mathbf{f}_{\text{obs}}(\mathbf{u})$ to form the de-rotated flow field

$$\mathbf{f}_{\text{rot-free}}(\mathbf{u}) = \mathbf{f}_{\text{obs}}(\mathbf{u}) - \mathbf{f}_{\text{rot}}(\mathbf{u}; \Delta R_{\text{imu}}). \quad (6)$$

Proposition 1 (Translational Epipolar Reduction on Static Anchors): Assume calibrated IMU-to-camera rotation $\Delta R_{\text{imu}} = \Delta R_{\text{cam}}$. For any stationary anchor pixel $\mathbf{u} \in \mathcal{M}_{\text{stat}}$ with rotated depth $Z'(\mathbf{u}) = \mathbf{e}_3^\top(\Delta R_{\text{cam}}\mathbf{X}_{c,k-1}(\mathbf{u}) + \Delta\mathbf{t}_{\text{cam}})$, the de-rotated flow $\mathbf{f}_{\text{rot-free}}(\mathbf{u})$ is independent of camera rotation on rays where $Z(\mathbf{u}) \gg |\Delta t_z|$ and satisfies the exact radial focus-of-expansion constraint

$$\mathbf{f}_{\text{rot-free}}(\mathbf{u}) = \frac{1}{Z'(\mathbf{u})}\begin{bmatrix} f_x & 0 & u_{\text{rot}} - c_x\\ 0 & f_y & v_{\text{rot}} - c_y\end{bmatrix}\begin{bmatrix}\Delta t_{\text{cam},x}\\ \Delta t_{\text{cam},y}\\ -\Delta t_{\text{cam},z}\end{bmatrix}, \quad (7)$$

where $\mathbf{u}_{\text{rot}} = [u_{\text{rot}}, v_{\text{rot}}]^\top = \Pi(K\Delta R_{\text{cam}}K^{-1}\tilde{\mathbf{u}})$. Conversely, for any moving target pixel $\mathbf{u} \in \mathcal{M}_{\text{obj}}$ with non-zero world motion $(R_B, \mathbf{p}_B) \neq (I_3, \mathbf{0})$, $\mathbf{f}_{\text{rot-free}}(\mathbf{u})$ deviates from Eq. (7) by the target-induced flow residual $\Delta\mathbf{f}_{\text{obj}}(\mathbf{u}) \neq \mathbf{0}$.




Fig. 2. Two-stage viewer-decoupled registration architecture. At the exposure midpoint t_e (Stage I), the measured composite pose $T_{cm}(t_e)$ is mapped to scene coordinates via $T_{cw}(t_e)^{-1}$ so filtering acts on $T_{wm}(t_e)$ without absorbing camera angular velocity $\boldsymbol{\omega}$. At display completion $t_d = t_e + \tau$ (Stage II), only the viewer pose T_{cw} is propagated across the measured pipeline delay τ using the rigidly mounted IMU.

Proof: For $\mathbf{u} \in \mathcal{M}_{\text{stat}}$, let $\mathbf{X}_{\text{rot}} = \Delta R_{\text{cam}} \mathbf{X}_{c,k-1}(\mathbf{u}) = Z(\mathbf{u}) \Delta R_{\text{cam}} K^{-1} \tilde{\mathbf{u}} = [X_r, Y_r, Z_r]^\top$. By projective scale invariance, $\Pi(K\mathbf{X}_{\text{rot}}) = \Pi(K \Delta R_{\text{cam}} K^{-1} \tilde{\mathbf{u}}) = \mathbf{u}_{\text{rot}}$, so $X_r/Z_r = (u_{\text{rot}} - c_x)/f_x$ and $Y_r/Z_r = (v_{\text{rot}} - c_y)/f_y$. Substituting $\mathbf{X}_{c,k}(\mathbf{u}) = \mathbf{X}_{\text{rot}} + \Delta \mathbf{t}_{\text{cam}}$ with $Z'(\mathbf{u}) = Z_r + \Delta t_{\text{cam},z}$ into $\mathbf{f}_{\text{rot-free}}(\mathbf{u}) = \Pi(K\mathbf{X}_{c,k}(\mathbf{u})) - \mathbf{u}_{\text{rot}}$ yields

$$f_{\text{rot-free},u}(\mathbf{u}) = \frac{f_x(X_r + \Delta t_{\text{cam},x})}{Z_r + \Delta t_{\text{cam},z}} - (u_{\text{rot}} - c_x) = \frac{f_x \Delta t_{\text{cam},x} - (u_{\text{rot}} - c_x)\Delta t_{\text{cam},z}}{Z'(\mathbf{u})}, \tag{8}$$

and identically for $f_{\text{rot-free},v}(\mathbf{u})$, which gives Eq. (7). Thus all rays $\mathbf{u} \in \mathcal{M}_{\text{stat}}$ point away from (or toward) the single translational epipole $\mathbf{e}_{\text{cam}} = \Pi(K\Delta\mathbf{t}_{\text{cam}})$. For $\mathbf{u} \in \mathcal{M}_{\text{obj}}$, $\Delta R_{\text{obj}} = R_{c,k}^\top R_B R_{c,k-1} \neq \Delta R_{\text{cam}}$ or $\Delta \mathbf{t}_{\text{obj}} \neq \Delta \mathbf{t}_{\text{cam}}$, violating Eq. (7). ■

Guided by Proposition 1, we feed image features $(F_0, F_{1\leftarrow 0}, |F_0 - F_{1\leftarrow 0}|)$, observed flow $\mathbf{f}_{\text{obs}}$, and de-rotated flow features $(\mathbf{f}_{\text{rot-free}}, \|\mathbf{f}_{\text{rot-free}}\|)$ on a $1/8$-resolution grid (32×40) into a dilated residual decoder to predict: (i) static-anchor probability $p_{\text{stat}}(\mathbf{u}) \in [0,1]$ and moving-target probability $p_{\text{obj}}(\mathbf{u}) = 1 - p_{\text{stat}}(\mathbf{u})$; (ii) branch-specific flow log-variances $(\log \sigma_c^2(\mathbf{u}), \log \sigma_o^2(\mathbf{u}))$; and (iii) metric depth $Z(\mathbf{u}) = Z_{\text{nom}} \exp(r(\mathbf{u}))$ in millimetres ($Z_{\text{nom}} = 150$ mm).

*2) Cascaded Dual-*SE(3) *Differentiable Gauss–Newton Solvers:* Unlike baseline EgoLite—which blends moving regions into the camera solver via a positive weight share and solves only a single camera pose—EgoAnchorNet enforces strict zero-contamination gating between two cascaded Gauss–Newton solvers:

1) *Camera Ego-Motion Solver on Static Anchors:* Using weights $w_{\text{stat}}(\mathbf{u}) = p_{\text{stat}}(\mathbf{u})^2 \exp(-\log \sigma_c^2(\mathbf{u}))$ that vanish on $\mathcal{M}_{\text{obj}}$, we minimize the Huber-reweighted (ρ_H) static flow objective coupled with the IMU rotational prior ($\lambda_{\text{imu}} = 400$):

$$\min_{\Delta R_{\text{cam}}, \Delta \mathbf{t}_{\text{cam}}} \sum_{\mathbf{u}} w_{\text{stat}}(\mathbf{u})\, \rho_H\Big(\big\|\mathbf{f}_{\text{obs}}(\mathbf{u}) - \mathbf{f}_{\text{cam}}(\mathbf{u})\big\|^2\Big) + \lambda_{\text{imu}} \big\| \log_{\text{SO}(3)}\big(\Delta R_{\text{imu}}\, \Delta R_{\text{cam}}^\top\big)\big\|^2. \tag{9}$$

2) *Target 3D Motion Solver on Isolated Residual Flow:* Evaluating $\mathbf{f}_{\text{cam}}(\mathbf{u}; Z, \Delta R_{\text{cam}}, \Delta \mathbf{t}_{\text{cam}})$ across the full grid and subtracting it from $\mathbf{f}_{\text{obs}}$ isolates the target's non-zero motion field $\mathbf{f}_{\text{iso}}(\mathbf{u}) = \mathbf{f}_{\text{obs}}(\mathbf{u}) - \mathbf{f}_{\text{cam}}(\mathbf{u})$ (Fig. 4(d)). A second differentiable Gauss–Newton solver weighted by $w_{\text{obj}}(\mathbf{u}) = p_{\text{obj}}(\mathbf{u})^2 \exp(-\log \sigma_o^2(\mathbf{u}))$ then solves for the target's 3D relative transformation $(\Delta R_{\text{obj}}, \Delta \mathbf{t}_{\text{obj}})$:

$$\min_{\Delta R_{\text{obj}}, \Delta \mathbf{t}_{\text{obj}}} \sum_{\mathbf{u}} w_{\text{obj}}(\mathbf{u})\, \rho_H\Big(\big\|\mathbf{f}_{\text{obs}}(\mathbf{u}) - \mathbf{f}_{\text{obj}}(\mathbf{u})\big\|^2\Big). \tag{10}$$

A closed-loop refinement module then concatenates the post-solve residuals $\mathbf{r}_c = \mathbf{f}_{\text{obs}} - \mathbf{f}_{\text{cam}}$ and $\mathbf{r}_o = \mathbf{f}_{\text{obs}} - \mathbf{f}_{\text{obj}}$ with the decoder features to update $(p_{\text{stat}}, \log \sigma_c^2, \log \sigma_o^2)$ and run two additional Gauss–Newton iterations for both branches.

D. Two-Stage Scene-Fixed Filtering and Display Update

Given exposure-midpoint measurements, filtering $\tilde{T}_{cm}$ directly feeds the coupled innovation

$$\boldsymbol{\xi}_{cm,k} = \log_{\text{SE}(3)}\Big(\tilde{T}_{cm,k-1}^{-1}\, \tilde{T}_{cm,k}\Big) = \log_{\text{SE}(3)}\Big(T_{wm,k-1}^{-1}\, (T_{cw,k-1}^{-1} T_{cw,k})\, T_{wm,k}\Big), \tag{11}$$

which mixes camera motion $T_{cw,k-1}^{-1} T_{cw,k}$ into the model update.

In Stage I (Fig. 2), we remove the exposure-time viewer pose $T_{cw}(t_{e,k})$ before smoothing:

$$\tilde{T}_{wm}(t_{e,k}) = T_{cw}(t_{e,k})^{-1}\, \tilde{T}_{cm}(t_{e,k}), \tag{12}$$

and update the scene-referenced model pose $\bar{T}_{wm}(t_{e,k})$ on SE(3):

$$\bar{T}_{wm}(t_{e,k}) = \bar{T}_{wm}(t_{e,k-1}) \cdot \exp_{\text{SE}(3)}\Big(\mathcal{G}\big(\log_{\text{SE}(3)}(\bar{T}_{wm,k-1}^{-1} \tilde{T}_{wm,k})\big)\Big), \tag{13}$$

where $\mathcal{G}(\cdot)$ is the filter gain operator.

In Stage II, at display time $t_d = t_e + \tau$, $\bar{T}_{wm}(t_{e,k})$ is held fixed in the scene while only the viewer pose is propagated

over $[t_e, t_d]$ using IMU angular velocity $\boldsymbol{\omega}_i(t)$ and calibrated camera-to-IMU rotation R_{ci}:

$$\hat{T}_{cw}(t_d) = \mathcal{P}\big(T_{cw}(t_e),\, \{R_{ci}\boldsymbol{\omega}_i(t)\}_{t\in[t_e,t_d]},\, \tau\big)\,, \tag{14}$$

and the display overlay pose is composed as

$$\hat{T}_{cm}(t_d) = \hat{T}_{cw}(t_d)\,\bar{T}_{wm}(t_e). \tag{15}$$

For high-resolution rolling-shutter CMOS sensors (such as our 3840×2160 4K camera with active line readout time $\tau_{\text{read}} = 15.0$ ms), scanline $y \in [0, H-1]$ is exposed at timestamp

$$t_e(y) = t_e + \tau_{\text{read}}\left(\frac{y}{H} - \frac{1}{2}\right). \tag{16}$$

Applying a single frame-midpoint rotation across all scanlines leaves a residual inter-band rolling-shutter skew of magnitude up to $\frac{1}{2}f\|\boldsymbol{\omega}\|\tau_{\text{read}}$ between the top and bottom image bands during rapid turns. Replacing t_e in Eq. (14) with the row-specific timestamp $t_e(y)$ integrates the 200 Hz gyroscope over $[t_e(y), t_d]$ per scanline band, eliminating intra-frame rolling-shutter skew at display time.

IV. Experimental Setup and Hybrid Dataset

A. Hardware Platforms and Hybrid R2S Dual-Motion Corpus

We evaluate two physical camera-IMU configurations and a hybrid dual-motion benchmark:

1) **Device A (4K Rolling-Shutter Camera + IMU):** A monocular 4K CMOS camera (3840×2160, calibrated intrinsics $f_x = 3799.19$ px, $f_y = 3796.09$ px, $c_x = 1844.58$ px, $c_y = 1082.58$ px, reprojection RMS 0.775 px across 120 views; downsampled to 1280×720, 512×288, and 320×256 for network inference) rigidly paired with a 200 Hz 6-axis USB IMU (USB stream delay $\tau_{\text{usb}} = 150.0$ ms) and a 187 Hz Bluetooth target-reference IMU. The camera-to-IMU rotation R_{ci} is calibrated via rigid hand-eye alignment:

$$R_{ci} = \begin{bmatrix} 0.007668 & -0.946526 & -0.322536 \\ -0.003137 & 0.322521 & -0.946557 \\ 0.999966 & 0.008270 & -0.000496 \end{bmatrix}.$$

2) **Device B (Calibrated Stereo Endoscope + IMU):** A dual-channel stereo endoscopic camera rig (1280×720 per eye, 30 fps, left intrinsics $f_x = 1095.34$ px, $f_y = 1097.58$ px, $c_x = 691.36$ px, $c_y = 383.36$ px, RMS 0.243 px; right intrinsics $f_x = 1070.21$ px, $f_y = 1061.31$ px, $c_x = 636.32$ px, $c_y = 331.94$ px, RMS 0.284 px) rigidly bound to the 200 Hz USB IMU. Because the two UVC camera streams lack a hardware trigger, cross-correlating image-plane target trajectories reveals a sub-frame right-camera lag of $\Delta k = -0.518$ frames (correlation 0.9111). Jointly fitting the stereo extrinsics $p_{C1} = R_{C1,C0}p_{C0} + \mathbf{t}_{C1,C0}$ over 41 quasi-static pairs (≤ 4.0 px inter-frame motion) with sub-frame lag interpolation yields a measured metric baseline of $\|\mathbf{t}_{C1,C0}\| = \mathbf{46.30}$ mm ($\mathbf{t}_{C1,C0} = [-46.09, +3.73, -2.45]^\top$ mm, vs. 46.50 mm nominal CAD housing) and an inter-tube optical rotation vector of $\mathbf{r}_{C1,C0} = [-2.07^\circ, -0.49^\circ, +10.18^\circ]^\top$ with a median stereo reprojection RMS of 0.290 px (overall fit RMS 0.575 px).

3) **Hybrid Dual-Motion + Static-Anchor Corpus:** To train and evaluate EgoAnchorNet with exact pixel-level stationarity labels and independent 6DoF poses for both camera and target, we generate $1{,}125$ dual-motion pairs (865 training across 24 sequences, 260 validation across 8 sequences, plus 40 held-out test pairs across 4 angular-velocity bins). Half of the sequences texture the stationary background surface with real porcine abdominal cavity keyframes from SCARED [15] (datasets 5–7), while the target object executes independent 6DoF spline trajectories ($\pm$20–32 mm translation, 14°–24° rotation, 95th-percentile speed 79.1 mm/s) and the camera executes aggressive 6DoF trajectories (±40 mm translation, 10°–24° rotation) without tracking the target. Each pair provides exact 32×40 metric depth maps, binary static-anchor masks $\mathcal{M}_{\text{stat}}$, noisy 200 Hz IMU preintegrated rotations ΔR_{imu}, and ground-truth $(\Delta R_{\text{cam}}, \Delta\mathbf{t}_{\text{cam}})$ and $(\Delta R_{\text{obj}}, \Delta\mathbf{t}_{\text{obj}})$.

B. Timing, Hardware, and Angular-Velocity Bins

Experiments run on an NVIDIA RTX 5090 Laptop GPU (24 GB VRAM) with distributed verification on RTX 3080 (16 GB) and GTX 1070 (8 GB) nodes. EgoAnchorNet is trained for 8 epochs using AdamW (lr $= 3\times10^{-4}$, cosine schedule, batch size 8, 290 s wall-clock training time). Pipeline delay τ is timed on one clock from exposure midpoint t_e to overlay completion t_d, covering both single-frame intervals ($\Delta t = 33.3$ ms at 30 fps) and full pipeline latency ($\tau = 60.0$ ms, pose estimation included). Frames and pairs are partitioned into four IMU angular-velocity bins:

$$\mathcal{B}_1 = [0.0, 0.5), \quad \mathcal{B}_2 = [0.5, 1.0),$$
$$\mathcal{B}_3 = [1.0, 2.0), \quad \mathcal{B}_4 = [2.0, 10.0) \text{ rad/s}.$$

To ensure statistical rigor across skewed and heavy-tailed error distributions, we report both non-parametric **Median [Interquartile Range, IQR]** and parametric **Mean $\pm$ Standard Deviation (SD)**.

V. Results

A. Full-Frame Background Dominance vs. Target ROI

At 150 mm depth in a 1280×720 view, the target board occupies a median of 5.69% (maximum 14.96%) of the image area, while 94% of the pixels lie on the static background. When Pi3 [1] and Reloc3r [2] are run on the full frame, they fit the static background and return mean camera rotation errors of 0.68°–0.85° regardless of target motion. Cropping to the 360×210 target ROI exposes the coupled relative motion between camera and target (Table II, Task 1).

B. Head-to-Head Comparison with Classical and SOTA Methods

Table II, Fig. 1, and Fig. 3 compare Condition 1, Condition 2, Condition 3, and our proposed EgoAnchorNet across all nine baselines:

TABLE II
UNIFIED HEAD-TO-HEAD BENCHMARK AND THREE-CONDITION COUNTERFACTUAL ABLATION ACROSS CLASSICAL, SOTA LEARNED, AND PROPOSED METHODS STRATIFIED BY CAMERA ANGULAR VELOCITY (1280×720, 10 PAIRS PER BIN, $N = 40$ TOTAL; VALUES REPORTED AS **MEDIAN [IQR]** / MEAN $\pm$ SD).

Task / Metric	Method	Condition / Setting	$\mathcal{B}_1 : [0.0, 0.5)$	$\mathcal{B}_2 : [0.5, 1.0)$	$\mathcal{B}_3 : [1.0, 2.0)$	$\mathcal{B}_4 : [2.0, 10.0)$	**All Bins** ($N = 40$)	Time
1. Pose Error (°)	SIFT [4] + Essential	Cond. 1: Ego + Target	3.00 [7.50] / 21.4±49.5	1.40 [1.67] / 3.93±5.63	3.76 [19.5] / 16.0±22.7	7.69 [7.40] / 40.6±69.0	3.13 [8.49] / 20.5±46.0	42 ms
	Reloc3r [2] (CVPR'25)	Cond. 1: Ego + Target	2.24 [1.27] / 2.61±1.74	1.65 [1.84] / 1.33±0.98	1.91 [1.19] / 2.08±1.33	3.78 [2.10] / 4.22±1.55	2.24 [1.56] / 2.56±1.78	118 ms
	Pi3 [1] (2025)	Cond. 1: Ego + Target	1.98 [1.02] / 2.43±2.10	1.56 [1.02] / 1.39±0.87	2.51 [1.67] / 2.11±0.84	2.62 [1.48] / 2.89±1.03	2.01 [1.59] / 2.21±1.43	95 ms
	VGGT [3] (CVPR'25)	Cond. 1: Ego + Target	2.51 [1.38] / 2.32±1.41	1.60 [1.28] / 2.32±2.05	1.80 [1.07] / 1.91±0.66	1.94 [2.43] / 2.59±1.26	1.82 [1.32] / 2.29±1.46	165 ms
	VGGT [3] (CVPR'25)	Cond. 3: Ego Only	1.12 [0.82] / 1.26±1.27	1.42 [3.10] / 2.17±1.62	2.50 [1.64] / 2.84±1.69	3.20 [2.18] / 15.5±36.2	1.88 [2.64] / 5.44±19.1	165 ms
	Coupled EgoLite	Cond. 1: Ego + Target	1.46 [0.87] / 1.61±0.72	1.23 [0.45] / 1.22±0.38	1.36 [0.52] / 1.35±0.46	1.48 [0.34] / 1.46±0.41	1.40 [0.52] / 1.41±0.53	54 ms
	SIFT [4] + Essential	Cond. 2: Ego Removed	1.45 [3.61] / 20.8±53.1	3.80 [4.31] / 21.2±53.0	3.03 [2.95] / 3.54±1.81	1.71 [1.48] / 1.79±0.98	2.11 [3.90] / 11.8±38.6	—
	VGGT [3] (CVPR'25)	Cond. 2: Ego Removed	1.60 [0.96] / 1.67±0.76	1.37 [0.86] / 1.16±0.59	1.29 [0.36] / 1.30±0.68	1.81 [0.99] / 1.57±0.71	1.40 [0.92] / 1.43±0.72	—
	Reloc3r [2] (CVPR'25)	Cond. 2: Ego Removed	1.53 [1.06] / 1.27±0.69	1.23 [0.90] / 1.10±0.58	1.46 [1.55] / 1.18±0.82	1.28 [1.43] / 1.06±0.79	1.38 [1.10] / 1.15±0.73	—
	Pi3 [1] (2025)	Cond. 2: Ego Removed	2.11 [0.54] / 1.75±0.92	1.65 [1.89] / 1.33±0.97	1.87 [1.70] / 1.29±0.91	0.96 [1.44] / 0.92±0.75	1.71 [2.11] / 1.32±0.94	—
	EgoAnchorNet (Ours, Target)	**Cond. 1: Ego + Target**	**1.58 [0.78] / 1.61±0.67**	**1.23 [0.88] / 1.06±0.58**	**1.26 [0.19] / 1.19±0.54**	**1.33 [0.64] / 1.22±0.50**	**1.31 [0.63] / 1.27±0.61**	**68 ms**
	EgoAnchorNet (Ours, Camera)	**Cond. 1: Ego + Target**	**0.09 [0.08] / 0.09±0.06**	**0.07 [0.04] / 0.07±0.03**	**0.07 [0.04] / 0.07±0.04**	**0.12 [0.07] / 0.12±0.06**	**0.08 [0.07] / 0.09±0.05**	**68 ms**
2. AR Shift (px)	Uncompensated Overlay	Cond. 1: Ego + Target	32.1 [33.2] / 32.1±19.9	26.1 [16.4] / 22.6±10.1	33.8 [7.51] / 33.3±9.85	42.1 [6.40] / 42.5±5.82	33.6 [16.5] / 32.6±14.4	—
	2D ATW Warp [5], [6]	Cond. 1: Rot. Homog.	30.7 [28.1] / 32.6±17.0	22.9 [11.8] / 26.6±14.2	31.6 [18.4] / 29.9±21.6	52.4 [37.2] / 54.6±24.1	32.2 [27.1] / 35.9±22.5	< 1 ms
	Coupled EgoLite	Cond. 1: Ego + Target	10.3 [7.73] / 14.0±10.9	12.8 [8.49] / 12.7±5.72	8.77 [6.28] / 9.83±4.77	15.0 [3.99] / 15.5±6.33	12.0 [8.30] / 13.0±7.61	54 ms
	EgoAnchorNet Stage-I (Ours)	**Cond. 1: Ego + Target**	**10.6 [7.71] / 13.2±10.3**	**9.52 [6.29] / 11.4±4.35**	**6.74 [6.93] / 8.38±4.50**	**11.8 [12.9] / 16.4±14.4**	**9.79 [8.99] / 12.3±9.83**	**68 ms**
	Two-Stage Viewer-Decoupled	**Cond. 2: Ego Removed**	**13.9 [9.51] / 10.9±5.87**	**6.58 [3.06] / 7.10±3.20**	**5.11 [3.68] / 6.68±3.90**	**10.2 [3.30] / 9.38±3.18**	**7.48 [7.65] / 8.52±4.53**	**< 1 ms**
3. 3D ADD (mm)	Coupled EgoLite	Cond. 1: Ego + Target	3.93 [3.93] / 3.68±2.12	2.86 [1.26] / 3.32±2.20	2.37 [3.35] / 3.40±2.40	3.70 [4.03] / 4.34±2.19	2.90 [3.91] / 3.68±2.26	54 ms
	EgoAnchorNet (Ours)	**Cond. 1: Ego + Target**	**2.22 [1.58] / 2.51±1.35**	**2.08 [0.97] / 2.11±0.95**	**1.70 [0.75] / 1.64±0.55**	**1.79 [1.49] / 2.60±2.27**	**1.89 [1.10] / 2.21±1.48**	**68 ms**
4. Tracking (%)	KLT [7] Survival (%)	Cond. 1: Ego + Target	76.6 [18.3] / 78.0±14.6	76.4 [27.6] / 79.6±16.5	60.8 [14.8] / 64.0±18.2	25.6 [38.3] / 34.1±21.3	68.2 [27.2] / 63.9±25.5	6 ms
	RAFT [8] Survival (%)	Cond. 1: Ego + Target	62.4 [43.3] / 62.4±23.8	69.7 [34.5] / 65.8±23.0	50.9 [42.5] / 55.7±27.3	57.7 [45.3] / 54.0±26.6	60.1 [45.1] / 59.4±25.7	28 ms
	EgoAnchorNet Inliers (%)	**Cond. 1: Ego + Target**	**96.6 [11.6] / 94.0±6.76**	**94.2 [8.29] / 93.4±7.96**	**85.0 [22.4] / 83.7±13.8**	**68.7 [38.7] / 70.3±22.3**	**91.8 [22.3] / 85.4±17.1**	**68 ms**
	RAFT [8] Survival (%)	Cond. 2: Ego Removed	64.3 [54.8] / 69.2±26.4	98.7 [15.7] / 93.0±8.10	97.6 [11.4] / 93.1±9.07	89.2 [9.07] / 91.9±5.19	95.0 [15.7] / 86.8±17.9	—
	KLT [7] Survival (%)	Cond. 2: Ego Removed	99.4 [13.4] / 93.1±10.2	99.8 [0.43] / 97.5±4.80	99.8 [2.96] / 95.9±6.77	99.0 [2.05] / 98.2±2.41	99.6 [2.47] / 96.2±6.96	—
5. Features / Match	LoFTR [9] Matches	Cond. 1: Ego + Target	453 [84.3] / 477±157	446 [88.5] / 446±142	354 [119] / 405±114	325 [115] / 306±99	394 [132] / 408±144	48 ms
	LoFTR [9] Matches	Cond. 2: Ego Removed	**557 [145] / 618±159**	**696 [54.8] / 686±59**	**632 [242] / 664±151**	**632 [99.8] / 630±119**	**635 [153] / 649±130**	—
	SIFT [4] Keypoints	Cond. 1: Ego + Target	641 [485] / 639±238	302 [113] / 291±82	253 [93.0] / 241±73	249 [67.3] / 231±47	290 [134] / 351±215	35 ms
	SIFT [4] Keypoints	Cond. 2: Ego Removed	**614 [255] / 672±174**	**481 [57.3] / 484±38**	**530 [117] / 572±132**	**464 [79.8] / 481±53**	**521 [92.5] / 552±138**	—
	ORB [10] Matches	Cond. 1: Ego + Target	382 [109] / 388±99	435 [74.3] / 423±47	412 [61.3] / 406±34	287 [59.5] / 300±58	385 [97.3] / 379±80	12 ms
	ORB [10] Matches	Cond. 2: Ego Removed	**498 [40.8] / 499±30**	**551 [54.5] / 546±41**	**553 [65.0] / 539±49**	**508 [49.3] / 506±57**	**528 [68.8] / 523±49**	—

1) **Pose Estimation Accuracy and Latency Trade-Off (Fig. 3(a), (c), (d)):** Under simultaneous camera and target motion (Condition 1), raising camera angular velocity from $\mathcal{B}_1$ ($[0.0, 0.5)$ rad/s) to $\mathcal{B}_4$ ($[2.0, 10.0)$ rad/s) drives median target-ROI rotation error to $7.69°$ (mean $40.6° \pm 69.0°$) for SIFT [4], $3.78°$ ($4.22° \pm 1.55°$) for Reloc3r [2], $2.62°$ ($2.89° \pm 1.03°$) for Pi3 [1], and $1.94°$ ($2.59° \pm 1.26°$, and $3.20°$ under Condition 3) for VGGT [3]. Operating directly on the uncompensated dual-motion stream (Condition 1), **EgoAnchorNet** achieves a fast-bin target rotation error of **$1.33°$ [IQR $0.64°$]** (mean $1.22° \pm 0.50°$; all-bin median **$1.31°$**) and a camera ego-motion rotation error of **$0.12°$ [IQR $0.07°$]** (all-bin median **$0.08°$**). At 68.2 ms median GPU inference time per pair, EgoAnchorNet is both more accurate and faster than Pi3 ($2.01°$, 95 ms), Reloc3r ($2.24°$, 118 ms), and VGGT-1B ($1.82°$, 165 ms).
2) **AR Overlay Registration vs. 2D ATW Warp (Fig. 3(b)):** In Condition 1, uncompensated one-frame overlay shift across all 88 inner target corners reaches a median of 42.1 px (mean 42.5 ± 5.82 px) in $\mathcal{B}_4$. Applying a 2D rotational homography warp (ATW [5], [6], $H = KR_1^T R_0 K^{-1}$) increases fast-bin error to 52.4 px (mean 54.6 ± 24.1 px) because close-range camera translation (± 40 mm at $z = 150$ mm) and target motion violate the zero-parallax assumption. EgoAnchorNet Stage-I reduces the all-bin median reprojection error from 33.6 px to 9.79 px (11.8 px in $\mathcal{B}_4$), and Stage-II viewer-only compensation further lowers it to 7.48 px across all bins (10.2 px in $\mathcal{B}_4$, a -75.8% reduction). On 3D metric accuracy across the 40 pairs, EgoAnchorNet cuts median 3D model ADD error from 3.70 mm (Coupled EgoLite) to **1.79 mm** in $\mathcal{B}_4$ (1.89 mm across all bins).
3) **Target Tracking and Dense Optical Flow:** In $\mathcal{B}_4$, pyramidal Lucas–Kanade [7] survival drops to 25.6% (mean $34.1\% \pm 21.3\%$) and dense RAFT [8] cycle-consistency survival drops to 57.7% ($54.0\% \pm 26.6\%$). EgoAnchorNet maintains an all-bin median flow inlier rate of 91.8% (68.7% in $\mathcal{B}_4$), while removing viewer ego-motion in Condition 2 restores RAFT and KLT survival to 89.2% and 99.0%.
4) **Feature Extraction and Transformer Matching:** In $\mathcal{B}_4$ under Condition 1, detector-free LoFTR [9] matches in the target ROI fall from 453 to 325, SIFT keypoints fall from 641 to 249, and ORB matches fall to 287. Removing camera ego-motion (Condition 2) restores 632 LoFTR matches ($+94.3\%$), 464 SIFT keypoints ($+86.1\%$), and 508 ORB matches ($+77.0\%$).

C. EgoAnchorNet Component Ablation on 260 Validation Pairs

Fig. 4 and Table III evaluate EgoAnchorNet on the 260 validation pairs of the hybrid dual-motion corpus:

1) **Static-Anchor vs. Moving-Target Disentanglement:** Across all four angular-velocity bins, EgoAnchorNet segments stationary background anchors $\mathcal{M}_{\text{stat}}$ with 98.99%–99.18% IoU and the independently moving target $\mathcal{M}_{\text{obj}}$ with 86.92%–90.10% IoU. On the 4.19 rad/s sample in Fig. 4(a)–(d), subtracting the solved 3D camera flow $\mathbf{f}_{\text{cam}}$ suppresses background flow and isolates the target's own motion field $\|\mathbf{f}_{\text{obs}} - \mathbf{f}_{\text{cam}}\|$.
2) **Camera Ego-Motion Precision:** In the fastest bin ($[2.0, 10.0)$ rad/s, $n = 106$), Coupled EgoLite (which




Fig. 3. Head-to-head comparison of EgoAnchorNet and Two-Stage Viewer-Decoupled Registration against classical and SOTA baselines on the 40-pair dual-motion test benchmark. **(a)** Target-ROI rotation error (Median $\pm$ 0.5 IQR) across the four angular-velocity bins. **(b)** 1280×720 AR reprojection error (px, Median $\pm$ 0.5 IQR) comparing 2D ATW Warp [5], [6], Uncompensated Overlay, Coupled EgoLite, EgoAnchorNet Stage-I, and Two-Stage Viewer-Decoupled Registration. **(c)** Empirical cumulative distribution function (ECDF) of rotation error across all $N = 40$ pairs. **(d)** Fast-bin ($[2.0, 10.0)$ rad/s) rotation error vs. per-pair GPU inference latency (ms) on an NVIDIA RTX 5090.

TABLE III
EGOANCHORNET COMPONENT ABLATION ON THE HYBRID DUAL-MOTION VALIDATION CORPUS (260 PAIRS ACROSS FOUR ANGULAR-VELOCITY BINS: $n = 10$ IN $\mathcal{B}_1$, $n = 38$ IN $\mathcal{B}_2$, $n = 106$ IN $\mathcal{B}_3$, $n = 106$ IN $\mathcal{B}_4$; MEDIANS REPORTED).

Metric	Model Variant	$[0.0, 0.5)$ rad/s	$[0.5, 1.0)$ rad/s	$[1.0, 2.0)$ rad/s	$[2.0, 10.0)$ rad/s	Fast-Bin Gain
Camera Trans. Error (mm)	Coupled EgoLite (No Anchor Gate, Single SE(3))	**0.74**	2.49	2.95	3.67	Baseline
	EgoAnchorNet w/o IMU De-Rotation Prior	0.89	1.80	2.20	3.30	−10.1%
	EgoAnchorNet w/o Closed-Loop Refinement	0.79	1.96	2.62	3.49	−4.9%
	EgoAnchorNet Full (Ours)	0.96	**1.75**	**2.10**	**2.18**	−40.6%
Target 3D Trans. Error (mm)	Coupled EgoLite (No Anchor Gate, Single SE(3))	**0.81**	3.18	3.62	4.25	Baseline
	EgoAnchorNet w/o IMU De-Rotation Prior	0.87	2.72	3.18	3.60	−15.3%
	EgoAnchorNet w/o Closed-Loop Refinement	**0.81**	3.45	3.66	4.10	−3.5%
	EgoAnchorNet Full (Ours)	0.88	**2.50**	**3.06**	**2.94**	−30.8%
3D Model ADD Error (mm)	Coupled EgoLite (No Anchor Gate, Single SE(3))	**0.71**	2.36	2.47	3.45	Baseline
	EgoAnchorNet w/o IMU De-Rotation Prior	0.78	**1.69**	1.90	2.73	−20.9%
	EgoAnchorNet w/o Closed-Loop Refinement	0.72	2.61	2.39	3.01	−12.8%
	EgoAnchorNet Full (Ours)	0.78	1.80	**1.70**	**1.90**	−44.9%
AR Screen Reprojection (px)	Coupled EgoLite (No Anchor Gate, Single SE(3))	4.83	10.12	11.75	14.40	Baseline
	EgoAnchorNet w/o IMU De-Rotation Prior	4.71	11.16	10.81	15.87	+10.2%
	EgoAnchorNet w/o Closed-Loop Refinement	5.13	**9.47**	11.31	11.05	−23.3%
	EgoAnchorNet Full (Ours)	**4.66**	10.69	**9.50**	**9.97**	−30.8%
Region Segmentation IoU (%)	Static-Anchor Region $\mathcal{M}_{\text{stat}}$ IoU (%)	98.99	99.01	99.18	99.08	—
	Independently Moving Target $\mathcal{M}_{\text{obj}}$ IoU (%)	86.92	89.72	90.10	88.89	—

lacks static-anchor gating and IMU de-rotation) suffers 0.21° rotation error and 3.67 mm camera translation




Fig. 4. EgoAnchorNet qualitative static-anchor disentanglement and quantitative ablation across 260 validation pairs. **(a)** Input frame at 4.19 rad/s overlaid with total observed flow $\mathbf{f}_{obs}$. **(b)** Predicted static-anchor probability p_{stat} (green: stationary background anchor; red: moving target). **(c)** Ground-truth static-anchor mask (98.5% IoU). **(d)** Isolated target motion magnitude $\|\mathbf{f}_{obs} - \mathbf{f}_{cam}\|$ after subtracting solved 3D camera ego-motion flow; background motion is suppressed. **(e)–(h)** Median camera translation error (mm), target 3D translation error (mm), 3D model ADD error (mm), and screen reprojection error (px at 1280×720) across four angular-velocity bins for Coupled EgoLite, EgoAnchorNet w/o IMU de-rotation, EgoAnchorNet w/o closed-loop refinement, and EgoAnchorNet (full).

error because moving target pixels bias the camera Gauss–Newton update. EgoAnchorNet reduces fast-bin camera rotation error to 0.08° and camera translation error to 2.18 mm (-40.6%).

3) **Target 3D Motion and End-to-End Registration:** Solving the second Gauss–Newton update on the camera-subtracted residual flow reduces fast-bin target 3D translation error from 4.25 mm (Coupled EgoLite) to 2.94 mm (-30.8%), 3D model ADD error from 3.45 mm to 1.90 mm (-44.9%), and 1280×720 screen reprojection error from 14.40 px to 9.97 px (-30.8%). Removing either the IMU de-rotation prior (2.73 mm ADD, 15.87 px) or the closed-loop dual residual refinement (3.01 mm ADD, 11.05 px) degrades high-rate registration accuracy.

D. Stage-II Latency Compensation, Calibrated Stereo Triangulation, and 4K Rolling-Shutter Warp

Table IV tests our Stage-II display update on a 40 mm 3D navigation target along an orbit-plus-fast-yaw trajectory ($\tau = 60$ ms, 89 frames, 30 fps, $\sigma_{px} = 1.2$ px). Rendering with the exposure-time pose $T_{cm}(t_e)$ increases 3D model ADD from 4.86 mm at < 0.8 rad/s to 14.94 mm at ≥ 1.6 rad/s.

TABLE IV
3D MODEL REGISTRATION ERROR (ADD IN MM AND SCREEN REPROJECTION IN PX) AT $\tau = 60$ MS PIPELINE DELAY (89 FRAMES, 30 FPS, $\sigma_{PX} = 1.2$ PX).

Strategy	$[0, 0.8)$ $(n = 63)$	$[0.8, 1.6)$ $(n = 11)$	$[1.6, 10)$ $(n = 15)$	**Reproj. (px)**
Delayed $T_{cm}(t_e)$	4.86 mm	11.34 mm	14.94 mm	3.63
Coupled T_{cm} Extrap.	7.76 mm	7.82 mm	5.46 mm	**1.51**
Viewer-Decoupled	**2.03 mm**	**2.07 mm**	**2.19 mm**	1.55

Extrapolating the composite pose T_{cm} lowers 2D reprojection error to 1.51 px but corrupts 3D model position across all bins (7.76 mm slow, 5.46 mm fast). Decoupling viewer motion keeps 3D ADD at 2.03–2.19 mm across all bins with 1.55 px reprojection error.

Table V (Part A) and Fig. 5(a) verify metric 3D stereo triangulation on the dual-channel endoscope (`calib_intrinsics_20260922_123120`). Because the right optical tube exhibits a 10.18° relative roll ($\mathbf{r}_{C1,C0} = [-2.07^\circ, -0.49^\circ, +10.18^\circ]^\top$) and a -0.518-frame USB stream offset, triangulating the 88-corner target under the nominal parallel CAD baseline ($b = 46.50$ mm,




Fig. 5. Calibrated stereo 3D triangulation, 4K rolling-shutter row-timed IMU warp, and real 4K+IMU consecutive-frame evaluation. **(a)** Metric 3D grid shape RMSE (mm) and stereo-vs-monocular PnP 3D ADD discrepancy (mm) across 41 stereo pairs under nominal CAD baseline (46.50 mm, $R = I$), unfiltered asynchronous stereo fit (55.86 mm), measured extrinsics without lag compensation (46.30 mm), and measured extrinsics with sub-frame lag compensation ($\Delta k = -0.518$ frames). **(b)** 4K (3840×2160, $\tau_{\text{read}} = 15.0$ ms, $\tau = 30.0$ ms) top, middle, and bottom band registration shift (px) across IMU angular-velocity bins comparing Frame-Level IMU Warp vs. Row-Timed IMU Warp (Eq. (16)). **(c)** Consecutive-frame rotation error of Reloc3r [2], Pi3 [1], and EgoAnchorNet (Camera) across the four gyro bins.

TABLE V
CALIBRATED STEREO METRIC TRIANGULATION (41 PAIRS) AND 4K (3840×2160) ROLLING-SHUTTER ROW-TIMED VS. FRAME-LEVEL IMU WARP (260 PAIRS; MEDIANS REPORTED).

Part A: Stereo Extrinsic Calibration & Metric 3D Triangulation					
Stereo Configuration	**Base. (mm)**	**RMS (px)**	**Epi. Dyn. (px)**	**Shape (mm)**	**ADD (mm)**
Nominal CAD ($R = I$)	46.50	49.29	79.77	2.088	5.999
Unfiltered Async (m25)	55.86	9.55	10.64	0.956	7.051
Measured ($\Delta k = 0$)	46.30	0.293	2.573	0.090	0.356
Measured + Lag ($\Delta k = -0.518$)	**46.30**	**0.290**	**1.472**	**0.087**	**0.355**
Part B: 4K Rolling-Shutter Band Shift (px) & Inter-Band Skew ($\tau_{\text{read}} = 15$ ms)					
Stage-II Mode (Bin)	**Top Band**	**Mid Band**	**Bot Band**	**All Med [IQR]**	**Band Skew**
Uncompensated ($\mathcal{B}_1$)	54.42	52.90	55.96	53.30 [30.64]	8.46
Frame-Level IMU ($\mathcal{B}_1$)	40.77	37.55	33.00	38.01 [15.82]	6.51
Row-Timed IMU ($\mathcal{B}_1$)	**38.81**	**37.53**	**35.41**	**37.80 [15.54]**	**5.62**
Uncompensated ($\mathcal{B}_4$)	330.37	275.27	224.26	275.47 [108.1]	107.12
Frame-Level IMU ($\mathcal{B}_4$)	57.95	34.29	53.49	47.01 [17.58]	43.25
Row-Timed IMU ($\mathcal{B}_4$)	**35.37**	**34.00**	**33.59**	**34.60 [23.37]**	**5.08**

$R = I$) yields 49.29 px reprojection RMS, 9.51% scale error, 2.088 mm 3D grid shape RMSE, and 5.999 mm stereo-vs-PnP 3D ADD discrepancy. Fitting moving frames without lag filtering (`synced_m25`) biases the baseline to 55.86 mm (7.051 mm ADD). Using our quasi-static calibrated extrinsics ($b = 46.30$ mm) with sub-frame lag compensation reduces stereo reprojection RMS to 0.290 px, cuts dynamic epipolar error by 42.8% (from 2.573 to 1.472 px), recovers the 3.000 mm grid scale within 0.18%, and lowers 3D shape RMSE to 0.087 mm and stereo-vs-PnP 3D ADD to 0.355 mm.

Table V (Part B) and Fig. 5(b) compare Frame-Level vs. Row-Timed Stage-II IMU compensation on the 3840×2160 4K rolling-shutter sensor ($\tau_{\text{read}} = 15.0$ ms, $\tau = 30.0$ ms). In the fast bin $\mathcal{B}_4$ ($[2.0, 10.0)$ rad/s, $n = 106$), uncompensated rendering exhibits 275.47 px median shift and 107.12 px inter-band skew between the top (330.37 px) and bottom (224.26 px) scanline bands. Frame-level IMU compensation aligns the middle band (34.29 px) but leaves the top (57.95 px) and bottom (53.49 px) bands skewed by 43.25 px. Row-timed IMU integration (Eq. (16)) brings the top (35.37 px), middle (34.00 px), and bottom (33.59 px) bands into tight agreement, collapsing fast-bin inter-band skew by 88.3% to 5.08 px (34.60 px overall 4K shift, equivalent to 9.98 px at 1280×720) while preserving slow-turn accuracy in $\mathcal{B}_1$ (37.80 px vs. 38.01 px).

Fig. 5(c) evaluates consecutive 30 fps frames from three real 4K camera + 200 Hz IMU sessions (`gtraj_20261002_002134`, `003129`, and `024309`, 48 pairs, 12 per gyro bin), where consecutive-frame rotation error in $[2.0, 10.0)$ rad/s rises from 0.434° to 0.971° for Pi3 and from 0.466° to 0.627° for Reloc3r, whereas EgoAnchorNet maintains 0.05°–0.12° camera rotation error.

VI. LIMITATIONS

1) *No optical see-through HMD:* All experiments render overlays onto 4K or stereo video frames; optical combiner calibration and eye-tracked pupil swim are outside our scope.
2) *Non-rigid soft-tissue deformation:* While we calibrate the metric 46.30 mm stereo baseline and compensate 4K rolling-shutter row readout skew, our Stage-I solver models locally rigid target increments $\Delta T_{\text{obj}} \in \text{SE}(3)$; high-amplitude physiological peristalsis, respiratory insufflation, and electrocautery smoke in live wet-lab surgery require coupling our static-anchor disentanglement with a low-rank deformable surface warp field.

VII. CONCLUSION

Under simultaneous camera and target motion, viewer ego-motion drives feature loss, tracking failure, target-ROI pose error, and latency-induced overlay drift. By using IMU-guided de-rotation to isolate stationary scene anchors, solving camera ego-motion and target 3D motion in cascaded Gauss–Newton

stages under calibrated 46.30 mm stereo geometry, and propagating only the viewer pose with row-timed IMU readout compensation at display time, our method keeps 3D model ADD at 1.79–2.19 mm, reduces 4K rolling-shutter inter-band skew by 88.3%, and removes 75.8% of high-rate AR overlay shift.

Data and Code Availability

The evaluation protocol, three-condition counterfactual benchmark summaries, figure generation scripts, and LaTeX manuscript sources are publicly available at https://github.com/liranyang123456-commits/Viewer-Decoupled-3D-Registration, with the dual-motion simulator and real 4K+IMU capture tools hosted at https://github.com/liranyang123456-commits/EGO_Mo.

References

[1] Y. Wang, J. Zhou, H. Zhu, W. Chang, Y. Zhou, Z. Li, J. Chen, J. Pang, C. Shen, and T. He, "Pi3: Permutation-equivariant visual geometry learning," *arXiv preprint arXiv:2507.13347*, 2025.

[2] S. Dong, S. Wang, S. Liu, L. Cai, Q. Fan, J. Kannala, and Y. Yang, "Reloc3r: Large-scale training of relative camera pose regression for generalizable, fast, and accurate visual localization," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025.

[3] J. Wang, M. Chen, N. Karaev, A. Vedaldi, C. Rupprecht, and D. Novotny, "VGGT: Visual geometry grounded transformer," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025.

[4] D. G. Lowe, "Distinctive image features from scale-invariant keypoints," *International Journal of Computer Vision*, vol. 60, no. 2, pp. 91–110, 2004.

[5] E. Lu and A. Rowe, "QUASAR: Quad-based adaptive streaming and rendering," *ACM Transactions on Graphics*, vol. 44, no. 4, pp. 1–16, 2025.

[6] S. Gao, W. Sentosa, M. Huzaifa, and S. V. Adve, "XRgo: Design and evaluation of rendering offload for low-power extended reality devices," in *Proceedings of the ACM Multimedia Systems Conference (MMSys)*, 2025, pp. 89–100.

[7] B. D. Lucas and T. Kanade, "An iterative image registration technique with an application to stereo vision," in *Proceedings of the International Joint Conference on Artificial Intelligence (IJCAI)*, 1981, pp. 674–679.

[8] Z. Teed and J. Deng, "RAFT: Recurrent all-pairs field transforms for optical flow," in *Proceedings of the European Conference on Computer Vision (ECCV)*, 2020, pp. 402–419.

[9] J. Sun, Z. Shen, Y. Wang, H. Bao, and X. Zhou, "LoFTR: Detector-free local feature matching with transformers," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021, pp. 8922–8931.

[10] E. Rublee, V. Rabaud, K. Konolige, and G. Bradski, "ORB: An efficient alternative to SIFT or SURF," in *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, 2011, pp. 2564–2571.

[11] W. E. Higgins, L. Rai, and S. A. Merritt, "3d continuous-video-to-CT registration for guided bronchoscopy," *IEEE Transactions on Medical Imaging*, vol. 32, no. 8, pp. 1418–1431, 2013.

[12] S. Bernhardt, S. A. Nicolau, L. Soler, and C. Doignon, "The status of augmented reality in laparoscopic surgery as of 2016," *Medical Image Analysis*, vol. 37, pp. 66–90, 2017.

[13] T. Ishihara, Y. Itoh, and G. Klinker, "Integrating both parallax and latency compensation into video see-through head-mounted display," *IEEE Transactions on Visualization and Computer Graphics*, vol. 29, no. 5, pp. 2409–2419, 2023.

[14] P. Lincoln, A. Blate, M. Singh, T. Whitted, A. State, A. Lastra, and H. Fuchs, "From motion to photons in 80 microseconds: Towards minimal latency for virtual and augmented reality," *IEEE Transactions on Visualization and Computer Graphics*, vol. 22, no. 4, pp. 1367–1376, 2016.

[15] M. Allan, J. Mcleod, C. Wang, J.-C. Rosenthal *et al.*, "Stereo correspondence and reconstruction of endoscopic data challenge," *arXiv preprint arXiv:2101.01133*, 2021.

[16] C.-Y. Wang, A. State, and H. Fuchs, "ViComp: Video compensation for projector-camera systems," *IEEE Transactions on Visualization and Computer Graphics*, vol. 30, no. 5, pp. 2150–2160, 2024.

[17] S. Yang, Q. Zhu, J. Zhuge, Q. Qiu, C. Li, Y. Yan *et al.*, "Mob-FGSR: Frame generation and super resolution for mobile real-time rendering," in *ACM SIGGRAPH Conference Papers*, 2024, pp. 1–11.

[18] T.-H. Liao, H. Liu, Y. Xu, S. Ge, G. Yang, and J.-B. Huang, "PAD3R: Pose-aware dynamic 3D reconstruction from casual videos," in *ACM SIGGRAPH Asia Conference Papers*, 2025.

[19] Q. Wang, V. Ye, H. Gao, J. Austin, Z. Li, and A. Kanazawa, "Shape of motion: 4D reconstruction from a single video," in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025.

[20] Z. Li, R. Tucker, F. Cole, Q. Wang, L. Jin, V. Ye, A. Kanazawa, A. Holynski, and N. Snavely, "MegaSaM: Accurate, fast, and robust structure and motion from casual dynamic videos," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025.

[21] W. Chen, G. Zhang, F. Wimbauer, R. Wang, N. Araslanov, A. Vedaldi, and D. Cremers, "Back on track: Bundle adjustment for dynamic scene reconstruction," in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025.

[22] P. Geneva, K. Eckenhoff, W. Lee, Y. Yang, and G. Huang, "OpenVINS: A research platform for visual-inertial estimation," in *Proceedings of the IEEE International Conference on Robotics and Automation (ICRA)*, 2020, pp. 4666–4672.

[23] T. Hu, T. Du, Z. Qu, and M. Gorlatova, "XR reality check: What commercial devices deliver for spatial tracking," in *Proceedings of the IEEE International Symposium on Mixed and Augmented Reality (ISMAR)*, 2025, pp. 932–942.

[24] S. Wang, V. Leroy, Y. Cabon, B. Chidlovskii, and J. Revaud, "DUSt3R: Geometric 3d vision made easy," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024, pp. 20 697–20 709.

[25] V. Usenko, N. Demmel, D. Schubert, J. Stückler, and D. Cremers, "Visual-inertial mapping with non-linear factor recovery," *IEEE Robotics and Automation Letters*, vol. 5, no. 2, pp. 422–429, 2020.

[26] C. Campos, R. Elvira, J. J. G. Rodríguez, J. M. M. Montiel, and J. D. Tardós, "ORB-SLAM3: An accurate open-source library for visual, visual-inertial, and multimap SLAM," *IEEE Transactions on Robotics*, vol. 37, no. 6, pp. 1874–1890, 2021.

[27] X. Pan, G. Huang, Z. Zhang, J. Li, H. Bao, and G. Zhang, "Robust collaborative visual-inertial SLAM for mobile augmented reality," *IEEE Transactions on Visualization and Computer Graphics*, vol. 30, no. 11, pp. 7245–7255, 2024.

[28] K. B. Ozyoruk, G. I. Gokceler, T. L. Bobrow, G. Coskun, K. Incetan, Y. Almalioglu, F. Mahmood, E. Curto, L. Perdigoto, M. Oliveira *et al.*, "EndoSLAM dataset and an unsupervised monocular visual odometry and depth estimation approach for endoscopic videos," *Medical Image Analysis*, vol. 71, p. 102058, 2021.

[29] B. Lima, B. Georgevich, T. Vieira, E. Neto, R. Júnior, and A. Vangasse, "How accurate is the HoloLens 2? a robotic ground-truth and sensor occlusion evaluation," in *Proceedings of the IEEE International Symposium on Mixed and Augmented Reality (ISMAR)*, 2025.

[30] C. Zhu, E. Kruijff, P. Zhang, and S. Julier, "MR-Compare: A mixed-reality framework for spatially grounded visual comparison of 3D gaussian splatting and mesh reconstructions with the physical environment," in *Proceedings of the IEEE International Symposium on Mixed and Augmented Reality (ISMAR)*, 2026.

[31] Z. Lu, K. Shapiro, E. Kruijff, A. Steed, and S. Julier, "When registration error becomes ambiguous: Behavioural effects of static misalignment in augmented reality," in *Proceedings of the IEEE International Symposium on Mixed and Augmented Reality (ISMAR)*, 2026.

Ranyang Li is with the School of Artificial Intelligence and Big Data, Henan University of Technology, Zhengzhou, China. His research interests include mixed reality spatial registration, visual-inertial navigation, and medical image computing.

Nan Wei is with Henan Provincial People's Hospital, Zhengzhou University, Zhengzhou, China. Her research interests include image-guided intervention and clinical navigation systems.

Zhipeng Lin is with the State Key Laboratory of Virtual Reality Technology and Systems, Beihang University, Beijing, China. His research interests include augmented reality, computer graphics, and surgical simulation.

Wufeng Liu is with the School of Artificial Intelligence and Big Data, Henan University of Technology, Zhengzhou, China. His research interests include computer vision and 3D scene reconstruction.

Chao Fan is with the School of Artificial Intelligence and Big Data, Henan University of Technology, Zhengzhou, China. His research interests include intelligent sensing and multi-sensor fusion.

Junjun Pan is a Professor with the State Key Laboratory of Virtual Reality Technology and Systems, Beihang University, Beijing, China. His research interests include virtual reality, augmented reality, computer graphics, and medical simulation.