

Seminar Report

Applying Semi-Supervised Locally Linear Embedding

Department of Statistics
Ludwig-Maximilians-Universität München



By Lisa Wimmer
Under the supervision of Jann Goschenhofer, Ph.D.
Munich, month dayth, 2021

Abstract

Storyline

- Goal: present SS-LLE as a local, graph-based manifold learning method incorporating prior knowledge
- Step 0: define basic mathematical concepts required to understand argumentation (plus notation)
- Step 1: introduce idea of **isometry** (most basic: MDS)
- Step 2: introduce idea of **graph-based** models
 - Achieve non-linearity
 - Common structure: build graph \rightarrow derive matrix as quadratic form over graph function \rightarrow derive embedding from eigenvalue problem
 - Most basic: ISOMAP (global, dense, convex)
- Step 3: introduce idea of **locality**
 - Relax global to local isometry
 - Find sparse rather than dense matrices
 - **Laplacian eigenmaps** as concept in which the others can be generalized
 - Define weighting scheme for neighborhood
 - Use Laplacian to derive matrix
 - Solve sparse eigenvalue problem
- Step 4: introduce **local linearity**
 - **LLE**
 - Obtain weights via linear reconstructions
 - Can be shown to approximate graph Laplacian (Belkin & Niyogi (2006))
 - **Hessian LLE**
 - Replace Laplacian by Hessian
- Step 5: introduce **prior knowledge**
 - **SS-LLE**
 - Improve results by pre-specifying some manifold coordinates

Contents

1	Introduction	1
2	Mathematical Framework	2
2.1	Basic Topological Concepts	2
2.2	Spectral Decomposition	2
3	Local Graph-Based Manifold Learning	2
3.1	Concept of Isometry	2
3.2	Graph-Based Models	3
3.2.1	Neighborhoods	3
3.2.2	Basics of Spectral Graph Theory	3
3.2.3	General Structure of Graph-Based Models	3
3.2.4	ISOMAP	3
3.3	Laplacian Eigenmaps	3
3.4	Locally Linear Embedding (LLE)	3
3.5	Hessian Locally Linear Embedding (HLLE)	3
4	Semi-Supervised Locally Linear Embedding (SS-LLE)	4
4.1	Employment of Prior Information	4
4.2	SS-LLE Algorithm	4
4.3	Strengths and Drawbacks of SS-LLE	4
5	Experiment Results	4
5.1	Data	4
5.2	Experimental Design	4
5.3	Results and Discussion	4
6	Conclusion	4
A	Appendix	V
B	Electronic Appendix	VI

List of Figures

List of Tables

1 Introduction

Machine learning problems increasingly employ data of high dimensionality. While a large amount of samples is beneficial to learning, high-dimensional feature spaces, such as in speech recognition or gene processing, pose serious obstacles to the performance and convergence of most algorithms (Cayton, 2005).

Three aspects strike as particularly problematic: computational operations, interpretation of results, and geometrical idiosyncrasies. Computational cost must be considered but is becoming less of an issue with the evolution of technology (Leist et al., 2009). By contrast, the demand for explainable results (for reasons of, say, safety or ethics) is rather intensified by the advance of complex methods. Alas, interpretation in more than a few dimensions is virtually inaccessible to humans (Doshi-Velez and Kim, 2017). The geometric aspect is often addressed as *curse of dimensionality*, a term subsuming various phenomena of high-dimensional spaces. It is generally not straightforward to infer properties of objects in complex spaces as geometric intuition developed in two or three dimensions can be misleading. Crucially, the exponential increase of spatial volume induces sparsity. Consequences of this behavior are, among others, a sharp incline in the number of points required to sample the feature space and a loss in meaningfulness of distances. Many learners, however, rely on these concepts¹ and see their functionality deteriorate (Verleysen and Francois, 2005).

These challenges make the case for *dimensionality reduction*, that is, the endeavor of compressing problem dimensionality to a manageable size. Far from undue simplification, dimensionality reduction relies on the idea that the latent data-generating process is indeed of much lower dimension than is observed. More formally, the data are assumed to lie on a d -dimensional *manifold* embedded in the D -dimensional observation space, with $d \ll D$. The goal is thus to uncover the structure of this manifold in an unsupervised manner (Cayton, 2005).

Various approaches have been proposed to learn points' manifold coordinates so they can be mapped to the corresponding d -dimensional Euclidean space². A taxonomy can for example be found in van der Maaten et al. (2009). Many methods rely on spectral techniques, trying to find a matrix representation of the data whose principal eigenvectors are used to span a d -dimensional subspace. Among these spectral methods some are confined to learning linear embeddings (such as *principal component analysis (PCA)* or *multi-dimensional scaling (MDS)*). Since linearity is a strong assumption that will not hold for general manifolds, non-linear techniques are more widely applicable. They can be further divided along the scope of the structure they attempt to preserve: full spectral methods (for instance, *ISOMAP*) retain a global notion of distance, whereas sparse approaches focus on local properties. Locality allows sparse methods to better capture non-convex structures where global isometry is not appropriate (van der Maaten et al., 2009).

¹For instance, consider support vector machines and k -nearest neighbors, both of which rely on distances, or tuning, which requires extensive sampling of the hyperparameter space.

²The most intuitive example of this is probably the representation of the Earth, which is a two-dimensional manifold enclosed in three-dimensional space, on two-dimensional maps.

One such technique is *locally linear embedding (LLE)*, proposed by Roweis and Saul (2000). It is based on the idea that points on the manifold lie within locally linear neighborhoods reflecting intrinsic geometric properties. Consequently, weights of linear reconstruction from neighboring points in the D -dimensional original space should be the same as for the d -dimensional manifold coordinates. LLE thus maps vicinity structures, characterized by neighborhood graphs, to the d -dimensional subspace and finds the coordinates that preserve them best. This requires solving the least-squares problem of minimizing reconstruction error and then the sparse eigenvalue problem of minimizing embedding cost. Convexity of the latter guarantees globality of any local optimum.

LLE uses no prior information. As Yang et al. (2006) argue, however, prior knowledge can improve performance by anchoring the unsupervised task to some known coordinates. The results presented in their work indicate considerable success of *semi-supervised locally linear embedding (SS-LLE)*.

It is the aim of this report to (1) reproduce these results, thereby creating an open-source implementation, and (2) to apply SS-LLE to further manifold learning tasks. The rest of the report is organized as follows: chapter 2 provides a mathematical framework where fundamental concepts are briefly introduced; chapter 3 explains the idea of local graph-based manifold learning; chapter 4 presents SS-LLE in detail; chapter 5 discusses the results of the conducted experiments; and chapter 6 draws final conclusions.

2 Mathematical Framework

2.1 Basic Topological Concepts

- Topology
- Topological space
- Topological manifold
- Riemannian manifold
- Curve/geodesic
- Tangent space

2.2 Spectral Decomposition

- Eigenvalues/eigenvectors
- Spectral decomposition

3 Local Graph-Based Manifold Learning

3.1 Concept of Isometry

- Notion of distance

- Preserving distances in manifold learning
- MDS (very brief)

3.2 Graph-Based Models

3.2.1 Neighborhoods

- k -/ ϵ -neighborhoods and neighborhood graphs
- Linear reconstruction and reconstruction error

3.2.2 Basics of Spectral Graph Theory

- Degree and adjacency matrices
- Laplacian operators

3.2.3 General Structure of Graph-Based Models

- Neighborhood graph
- Weight matrix
- Eigenwert problem

3.2.4 ISOMAP

- (One of the) earliest, simplest variant(s)
- MDS with geodesics

3.3 Laplacian Eigenmaps

- Notion of locality
- Laplacian eigenmaps

3.4 Locally Linear Embedding (LLE)

- Notion of local linearity
- Approximation of graph Laplacian

3.5 Hessian Locally Linear Embedding (HLLE)

- Hessian instead of Laplacian (eigenmaps)
- Hessian instead of LS fit (LLE)

4 Semi-Supervised Locally Linear Embedding (SS-LLE)

4.1 Employment of Prior Information

- Why use labels in the first place?
- How will that help?
- How do we even find prior points?
- Exact vs inexact knowledge

4.2 SS-LLE Algorithm

- What is different wrt standard LLE?

4.3 Strengths and Drawbacks of SS-LLE

Potential shortcoming: what if manifold is not well-sampled? Not a problem with synthetic data, but IRL. But probably problematic with all manifold approaches

Also: generalization to new points (w/o recomputing everything) neighborhood-preserving propositions

5 Experiment Results

5.1 Data

5.2 Experimental Design

- Implementation details
- Hyperparameters
- Evaluation criteria

5.3 Results and Discussion

6 Conclusion

Lorem ipsum

A Appendix

Lorem ipsum

B Electronic Appendix

Data, code and figures are provided in electronic form.

References

- Cayton, L. (2005). Algorithms for manifold learning, *Technical Report CS2008-0923*, University of California, San Diego (UCSD).
- Doshi-Velez, F. and Kim, B. (2017). Towards a rigorous science of interpretable machine learning, *arXiv: Machine Learning*.
- Leist, A., Playne, D. P. and Hawick, K. A. (2009). Exploiting graphical processing units for data-parallel scientific applications, *Concurrency and Computation. Practice and Experience* **21**(18): 2400–2437.
- Roweis, S. T. and Saul, L. K. (2000). Nonlinear dimensionality reduction by locally linear embedding, *Science* **290**(5500): 2323–2326.
- van der Maaten, L., Postma, E. and van den Herik, J. (2009). Dimensionality reduction: A comparative review, *Technical Report TiCC TR 2009-005*, Tilburg University.
- Verleysen, M. and Francois, D. (2005). The curse of dimensionality in data mining and time series prediction, in J. Cabestany, A. Prieto and F. Sandoval (eds), *Computational Intelligence and Bioinspired Systems*, Springer.
- Yang, X., Fu, H., Zha, H. and Barlow, J. (2006). Semi-supervised nonlinear dimensionality reduction, *Proceedings of the 23rd International Conference on Machine Learning*, Pittsburgh, PA, USA.

Declaration of Authorship

I hereby declare that the report submitted is my own unaided work. All direct or indirect sources used are acknowledged as references. I am aware that the Thesis in digital form can be examined for the use of unauthorized aid and in order to determine whether the report as a whole or parts incorporated in it may be deemed as plagiarism. For the comparison of my work with existing sources I agree that it shall be entered in a database where it shall also remain after examination, to enable comparison with future Theses submitted. Further rights of reproduction and usage, however, are not granted here. This paper was not previously presented to another examination board and has not been published.