Modern Models, Historical isiXhosa: A Held-Out Study of Language-Modelling Fit

Kaylin Aspoas (3163666) and **Lisa Pitsi (2590083)**
University of the Witwatersrand, 1 Jan Smuts Ave, Braamfontein, Johannesburg, 2000, South Africa

Abstract

Language coverage does not establish coverage of a language's historical varieties. We evaluate five frozen pretrained models on nineteenth-century isiXhosa newspapers and a modern NCHLT comparison corpus. Final evaluation uses 300 sentences per corpus from disjoint newspaper issues and modern documents, with character-length stratification. XLM-R, Afro-XLMR and InkubaLM assign worse character-normalised scores to historical text, with median gaps of 0.796, 0.815 and 0.627 and source-group bootstrap intervals excluding zero. mBERT and AfriBERTa show no clear directional difference. Validation reproduces the same pattern. These findings indicate a historical-modern corpus mismatch for three models; they do not demonstrate semantic failure or isolate temporal change from register, orthography and transcription differences.

Introduction

The IsiXhosa Intellectual Traditions Digital Archive preserves writing that is central to studying African intellectual history (Schoots et al., 2023). Making this material digitally accessible, however, does not establish that present-day NLP systems process it adequately. We ask: do selected modern pretrained models assign worse language-modelling scores to isiXhosa newspaper text from 1870-1894 than to a modern comparison corpus? We hypothesise a positive historical-modern scoring gap in models with documented isiXhosa training coverage.

Historical English research finds benefits from historically specific pretraining (Manjavacas & Fonteyn, 2022), motivating evaluation across periods rather than assuming transfer. African-language adaptation likewise improves selected downstream benchmarks (Alabi et al., 2022), while AfriBERTa demonstrates the value of targeted multilingual pretraining (Ogueji et al., 2021). These studies motivate our experiment but do not establish historical isiXhosa performance. We use pseudo-log-likelihood (PLL) for masked models (Salazar et al., 2020) and causal log-likelihood for InkubaLM. The experiment measures distributional fit, not semantic understanding or whether a model identifies the text as a foreign dialect.

Methods

The historical input comprises the supplied isiXhosa text blocks from Imvo Zabantsundu and Isigidimi sama-Xosa. The tracker covers 3,608 pages; a 100-isiXhosa-word minimum retains 3,592. Automated normalisation, segmentation and filtering yield 327,265 sentences from 3,574 pages. Sentences require at least three whitespace words and 25 characters, with at most 80 words. A proposed 90% page-level isiXhosa word-share filter was rejected: the diagnostic showed it would additionally exclude 895 substantial pages, although their English blocks were already separated. Figure 2 shows the diagnostic thresholds. The spike at 3,000 reflects display clipping, not an exact page word count. Modern comparison text is the NCHLT clean isiXhosa corpus (Puttkammer et al., 2014), associated with text-resource development for South African languages (Eiselen & Puttkammer, 2014). After automated filtering, duplicate removal and a 200-sentence document cap, 41,188 sentences remain. Government-domain provenance (Puttkammer et al., 2014) makes this a register-mismatched comparator. We performed no manual correction or modernisation because we lacked isiXhosa proficiency. Automated processing is distinct from manual linguistic verification. After exploratory scoring, we created source-disjoint development, validation and test partitions. All pages of a historical issue share a partition; modern grouping uses original document identifiers. Previously evaluated sources are assigned to development. Normalised exact duplicates and exact cross-corpus overlaps are removed. The resulting pools contain 263,748 historical and 41,188 modern sentences. Validation and test each contain 300 sentences per corpus, sampled equally across five character-length bins defined from development historical text (seed 20261031). Validation covers 100 historical issues and 114 modern documents; test covers 101 and 112. Models remain frozen: the development partition is not used for training or hyperparameter optimisation. The checkpoints are bert-base-multilingual-cased, castorini/afriberta_large, FacebookAI/xlm-roberta-large, Davlan/afro-xlmr-large and lelapa/InkubaLM-0.4B. XLM-R uses multilingual web pretraining (Conneau et al., 2020); the Afro-XLMR and InkubaLM documentation explicitly includes isiXhosa (Alabi et al., 2022) (Tonja et al., 2024). mBERT and AfriBERTa serve as comparison baselines, without isiXhosa in their documented language lists (Ogueji et al., 2021) (Devlin et al., 2018). For each sentence, we divide total negative log score by its character count. Masked models score each non-special subword while other tokens remain visible; the causal model uses shifted next-token loss. The primary statistic is the historical minus modern median within each model. We report 95% percentile intervals from 2,000 source-group bootstrap draws, Cliff's delta, and approximate centred-bootstrap p-values with Holm correction across the five models.

Results

The held-out test reproduces validation (Table 1; Figures 1 and 3). All three positive-gap model intervals exclude zero; approximate Holm-adjusted bootstrap p-values are 0.0025. Both baseline intervals include zero. Test mean lengths are closely aligned: 111.41 historical versus 111.47 modern characters (medians 91 and 100). Figure 4 documents the




Figure 1: Final held-out score distributions for 300 historical and 300 modern isiXhosa sentences. Lower character-normalised negative (pseudo) log scores indicate better fit within each model. XLM-R, Afro-XLMR and InkubaLM show higher historical medians, while mBERT and AfriBERTa show substantial overlap between corpora. Panels use different scales; absolute scores should not be used to rank models. Outlier markers are omitted.

original exploratory comparison. [1]

Table 1: Historical minus modern median negative (pseudo) log score per character. Positive gaps indicate worse historical fit within a model. Test: 300 sentences per corpus. Intervals resample source groups; delta is a descriptive sentence-order effect. Absolute scores and gap magnitudes are not a common performance ranking across masked and causal objectives.

Model	Validation gap	Test gap (95% CI)	Cliff's delta
mBERT	-0.039	-0.056 [-0.128, 0.024]	-0.093
AfriBERTa	-0.060	-0.026 [-0.067, 0.020]	-0.047
XLM-R	0.857	0.796 [0.696, 0.872]	0.669
Afro-XLMR	0.842	0.815 [0.725, 0.885]	0.837
InkubaLM	0.629	0.627 [0.578, 0.682]	0.825

Discussion

The stable direction across validation and test supports a corpus-level historical disadvantage for XLM-R, Afro-XLMR and InkubaLM under the chosen objectives. It does not show that these models cannot represent archival isiXhosa meaningfully. Nor does the baseline pattern establish historical robustness: a small difference can arise when neither corpus is well modelled. The small AfriBERTa reverse difference from the initial exploration is not clearly reproduced in either held-out partition. Language inclusion alone therefore should not be treated as sufficient evidence of historical coverage, and these five checkpoints do not identify a causal effect of pretraining language composition. Earlier exploratory comparisons found higher character-normalised negative log scores, indicating poorer fit, for Imvo than Isigidimi in all five models. This is a newspaper contrast, not evidence that progressively older language is harder: publication period, content and text quality overlap. Similarly, NCHLT government text and historical newspapers differ in register and topic. Orthographic conventions, residual errors, unknown pretraining overlap and imperfect automated sentence boundaries could contribute to the main gap. Character normalisation reduces dependence on token counts but does not eliminate tokenizer effects. Standard subword PLL can inflate scores when other pieces of the target word remain visible (Kauf & Ivanova, 2023). The retained objective constrains interpretation. AfriBERTa also shows metric sensitivity: its secondary per-token test gap is 0.223 [0.045, 0.361], unlike its near-zero primary per-character gap. An exploratory synthetic-noise check on 100 modern sentences found that nominal corruption of 1%, 2% and 5% of letters produced score shifts equivalent to approximately 18-24%, 38-46% and 79-87% of the original mean per-token gaps in the three positive-gap models. These are sensitivity comparisons under a generic corruption mechanism, not measured percentages of historical degradation caused by OCR. They use the exploratory sample and a different summary statistic from Table 1. Actual residual transcription error and its score effect remain unmeasured without scan-verified reference passages. For responsible deployment, archival coverage warrants direct evaluation rather than inference from a language label. Poorer modelling fit could affect archival retrieval, classification or other access tools, but no downstream harm was measured here. Researchers, heritage institutions and isiXhosa-speaking communities could be affected if such systems privilege contemporary forms. Conversely, aggressively removing unusual forms or modernising spelling without expertise risks discarding historical evidence. Appropriate next steps are speaker- and historian-informed evaluation, register-matched modern comparisons, and verified transcription audits. Historical-domain adaptation is a research direction suggested by prior work, not an intervention tested in this project.

Conclusion

Three evaluated models assign consistently worse language-modelling scores to the sampled nineteenth-century isiXhosa corpus than to modern NCHLT text, including on a source-disjoint final test. The result supports a historical-modern corpus mismatch while leaving its linguistic and technical causes unresolved. It motivates historically informed evaluation; it does not establish semantic failure, dialect classification or measured downstream exclusion.

Contribution Statement

Kaylin Aspoas (3163666) led the construction and cleaning of the historical corpus, implemented the language-model evaluation pipeline and conducted robustness, and produced the project's visualisations. Lisa Pitsi (2590083) led the research framing and Responsible NLP motivation for the project, developed the modern comparison corpus from NCHLT resources, and performed the statistical comparison between historical and modern corpora. Both authors jointly interpreted the results, discussed their implications, and collaborated on writing, editing, and refining the final report and extended abstract.

[1] Code and results: https://github.com/lisabeeaan/NLP-Project2

References

Alabi, J. O., Adelani, D. I., Mosbach, M., & Klakow, D. (2022, October). Adapting pre-trained language models to African languages via multilingual adaptive fine-tuning. In N. Calzolari et al. (Eds.), *Proceedings of the 29th international conference on computational linguistics* (pp. 4336–4349). Gyeongju, Republic of Korea: International Committee on Computational Linguistics. Retrieved from https://aclanthology.org/2022.coling-1.382/

Conneau, A., Khandelwal, K., Goyal, N., Chaudhary, V., Wenzek, G., Guzmán, F., ... Stoyanov, V. (2020, July). Unsupervised cross-lingual representation learning at scale. In D. Jurafsky, J. Chai, N. Schluter, & J. Tetreault (Eds.), *Proceedings of the 58th annual meeting of the Association for Computational Linguistics* (pp. 8440–8451). Online: Association for Computational Linguistics. Retrieved from https://aclanthology.org/2020.acl-main.747/ doi: 10.18653/v1/2020.acl-main.747

Devlin, J., Chang, M.-W., Lee, K., & Toutanova, K. (2018). Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*.

Eiselen, R., & Puttkammer, M. (2014, May). Developing text resources for ten South African languages. In N. Calzolari et al. (Eds.), *Proceedings of the ninth international conference on language resources and evaluation (LREC'14)* (pp. 3698–3703). Reykjavik, Iceland: European Language Resources Association (ELRA). Retrieved from https://aclanthology.org/L14-1106/

Kauf, C., & Ivanova, A. A. (2023, July). A better way to do masked language model scoring. In A. Rogers, J. Boyd-Graber, & N. Okazaki (Eds.), *Proceedings of the 61st annual meeting of the Association for Computational Linguistics (volume 2: Short papers)* (pp. 925–935). Toronto, Canada: Association for Computational Linguistics. Retrieved from https://aclanthology.org/2023.acl-short.80/ doi: 10.18653/v1/2023.acl-short.80

Manjavacas, E., & Fonteyn, L. (2022, June). Adapting vs. Pretraining Language Models for Historical Languages. *Journal of Data Mining and Digital Humanities*, *NLP4DH*. Retrieved from https://inria.hal.science/hal-03592137 doi: 10.46298/jdmdh.9152

Ogueji, K., Zhu, Y., & Lin, J. (2021, November). Small data? no problem! exploring the viability of pretrained multilingual language models for low-resourced languages. In D. Ataman, A. Birch, A. Conneau, O. Firat, S. Ruder, & G. G. Sahin (Eds.), *Proceedings of the 1st workshop on multilingual representation learning* (pp. 116–126). Punta Cana, Dominican Republic: Association for Computational Linguistics. Retrieved from https://aclanthology.org/2021.mrl-1.11/ doi: 10.18653/v1/2021.mrl-1.11

Puttkammer, M., Schlemmer, M., Pienaar, W., & Bekker, R. (2014). *NCHLT isiXhosa text corpora.* Retrieved from https://hdl.handle.net/20.500.12185/314 (SADiLaR Language Resource Repository, License: Creative Commons Attribution 2.5 South Africa License: http://creativecommons.org/licenses/by/2.5/za/legalcode)

Salazar, J., Liang, D., Nguyen, T. Q., & Kirchhoff, K. (2020, July). Masked language model scoring. In D. Jurafsky, J. Chai, N. Schluter, & J. Tetreault (Eds.), *Proceedings of the 58th annual meeting of the Association for Computational Linguistics* (pp. 2699–2712). Online: Association for Computational Linguistics. Retrieved from https://aclanthology.org/2020.acl-main.240/ doi: 10.18653/v1/2020.acl-main.240

Schoots, J., Ngwendu, A., De Wet, J., & Muftic, S. (2023, May). IsiXhosa intellectual traditions digital archive: Digitizing isiXhosa texts from 1870-1914. In R. Mabuya, D. Mthobela, M. Setaka, & M. Van Zaanen (Eds.), *Proceedings of the fourth workshop on resources for African indigenous languages (RAIL 2023)* (pp. 54–64). Dubrovnik, Croatia: Association for Computational Linguistics. Retrieved from https://aclanthology.org/2023.rail-1.7/ doi: 10.18653/v1/2023.rail-1.7

Tonja, A. L., Dossou, B. F., Ojo, J., Rajab, J., Thior, F., Wairagala, E. P., ... others (2024). Inkubalm: A small language model for low-resource african languages. *arXiv preprint arXiv:2408.17024*.

Supplementary Figures




Figure 2: The left panel shows that most pages have a high isiXhosa word share, while a substantial minority contain more English elsewhere on the page. Its red 90% line is a rejected diagnostic cutoff, not the active filter. The right red line marks the retained 100-isiXhosa-word minimum. Values above 3,000 are clipped for display, so the final spike does not mean those pages contain exactly 3,000 words.




Figure 3: Validation shows the same directional pattern as the final test: a historical disadvantage for XLM-R, Afro-XLMR and InkubaLM and substantial overlap for the two baselines. Agreement across separate source groups supports the stability of the main corpus comparison. It does not isolate temporal language change from other corpus differences.




Figure 4: The original sample already shows worse historical scores for XLM-R, Afro-XLMR and InkubaLM, with close baseline medians. For the four masked models, higher mean PLL per token is better, so a lower historical box indicates poorer fit. InkubaLM uses perplexity, where lower is better, so its higher historical box indicates poorer fit. These are exploratory results on the original sample, not the final character-normalised held-out results.

Wits University Faculty of Science
Postgraduate Student AI Declaration

I understand that the use of generative AI tools (such as ChatGPT or similar) without explicitly declaring such use constitutes a form of plagiarism and is classified by Wits University as academic misconduct.

I declare that in the course of conducting the research towards my degree or in the preparation of this **research report** (select one by marking with an **X**):

☐ I did not make use of generative AI tools

☒ I did make use of generative AI tools for the following (tick all that apply):

- ☐ Idea Generation (research problem/design, hypothesis)
- ☒ Sourcing Related Work (summarising, identifying sources)
- ☐ Methods and Experiment Design (experiment setup, model tuning)
- ☒ Data Analysis (presentation, coding, interpretation)
- ☐ Theoretical Development (theorem proving, conceptual analysis)
- ☒ Code Development (generating algorithms, writing scripts)
- ☒ Presentation (rendering graphics, formatting)
- ☒ Editing (grammar, readability)
- ☐ Writing (text generation, document structuring)
- ☒ Citation Formatting (structuring, organising)

If other uses were involved, please specify below:

Generative AI tool used (list all)	**Used for?**
Claude (Anthropic)	Parts of the code; summarising related work; editing the report. The ideas and interpretation of results are our own; We understand and take full responsibility for all code and writing submitted.

If generative AI tools were used as an integral part of the experimental design or in the direct execution of my research, I confirm that details of this use are clearly outlined in the relevant experimental/methodology chapters of my thesis/dissertation/research report.

Student number: 3163666 and 2590083

Candidate signature: _____

Date: 1 November 2026

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The abstract and Introduction state the research question and hypothesis (a positive historical-modern scoring gap in models with documented isiXhosa coverage). The abstract reports the median gaps with source-group bootstrap intervals as in Table 1, and states the same limits as the Discussion: the results show a corpus mismatch for three models, not semantic failure, and do not separate temporal change from register, orthography and transcription differences.

   Guidelines:

   - The answer NA means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A No or NA answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: The Discussion covers the register and topic mismatch between NCHLT government text and historical newspapers, orthographic conventions, residual transcription error, unknown pretraining overlap, imperfect automated sentence boundaries, tokenizer effects that character normalisation does not remove, PLL inflation for subword models, AfriBERTa's sensitivity to the choice of metric, the newspaper (Imvo versus Isigidimi) confound, and that no manual verification was possible without isiXhosa proficiency.

   Guidelines:

   - The answer NA means that the paper has no limitation while the answer No means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
   - The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
   - If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
   - While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory Assumptions and Proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

   Answer: [NA]

Justification: The paper makes no theoretical claims; all results are empirical.

Guidelines:

- The answer NA means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental Result Reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: [Yes]

   Justification: The Methods section gives the sources, filtering thresholds, de-duplication, the per-document cap, the source-disjoint development, validation and test partitions, the character-length stratified sampling and its seed (20261031), the exact model checkpoints, the scoring procedure (pseudo-log-likelihood per subword for masked models, shifted next-token loss for InkubaLM, normalised per character) and the statistics (2,000 source-group bootstrap draws, Cliff's delta, Holm correction). The submitted code and `README.txt` reproduce every step.

   Guidelines:

   - The answer NA means that the paper does not include experiments.
   - If the paper includes experiments, a No answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
   - If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
   - Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
   - While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
     (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
     (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
     (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
     (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [Yes]

Justification: The full code is submitted and is also at https://github.com/lisabeeaan/NLP-Project2, with requirements.txt and a README giving the commands to build the corpora, prepare the held-out partitions (seed 20261031) and reproduce every score and statistic; the frozen split manifests, protocol and samples are archived with checksums. The models are public Hugging Face checkpoints and the NCHLT corpus is publicly available from SADiLaR; the historical newspaper text is the isiXhosa Intellectual Traditions data supplied for the course (Schoots et al., 2023).

Guidelines:

- The answer NA means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (https://nips.cc/public/guides/CodeSubmissionPolicy) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so "No" is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (https://nips.cc/public/guides/CodeSubmissionPolicy) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental Setting/Details**

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer, etc.) necessary to understand the results?

Answer: [Yes]

Justification: No model is trained or fine-tuned: all five checkpoints are frozen and the development partition is not used for training or hyperparameter optimisation. The Methods section gives the partitions, sample sizes (300 sentences per corpus for validation and test), length bins, sampling seed, scoring objective per model and the statistical procedure.

Guidelines:

- The answer NA means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment Statistical Significance**

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [Yes]

Justification: Table 1 reports 95% percentile intervals from 2,000 bootstrap draws that resample source groups (newspaper issues and modern documents), so the intervals reflect source-level rather than sentence-level variation; the Results also give Cliff's delta and approximate centred-bootstrap p-values with Holm correction across the five models.

Guidelines:

- The answer NA means that the paper does not include experiments.
- The authors should answer "Yes" if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.

- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g. negative error rates).
- If error bars are reported in tables or plots, The authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments Compute Resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [Yes]

   Justification: All experiments were conducted on the University of the Witwatersrand MS Cluster using the bigbatch partitions. Model scoring used an NVIDIA GeForce RTX 3090 GPU with 24 GB of GPU memory. The inspected machine had an Intel Core i9-10940X processor with 14 physical cores and 28 logical CPUs; these describe the host hardware rather than the CPU allocation requested for each job. All five model checkpoints were evaluated without training or fine-tuning. Masked-model scoring required one forward pass per scored subword. Total GPU-hours and peak memory consumption were not systematically recorded, so we do not report a verified aggregate compute estimate.

   Guidelines:

   - The answer NA means that the paper does not include experiments.
   - The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
   - The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
   - The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code Of Ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes]

   Justification: The work uses published nineteenth-century newspapers from a public digital archive and a public modern corpus, collects no new data, involves no human subjects and releases no model. The Discussion addresses the cultural stakes for isiXhosa-speaking communities and cautions against modernising historical text without expertise.

   Guidelines:

   - The answer NA means that the authors have not reviewed the NeurIPS Code of Ethics.
   - If the authors answer No, they should explain the special circumstances that require a deviation from the Code of Ethics.
   - The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader Impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [Yes]

Justification: The Discussion notes that poorer modelling fit could affect archival retrieval, classification or other access tools built on these models, so researchers, heritage institutions and isiXhosa-speaking communities could be disadvantaged if such systems privilege contemporary forms; that removing unusual forms or modernising spelling without expertise risks discarding historical evidence; and that no downstream harm was measured. It recommends direct evaluation of archival coverage with speaker- and historian-informed evaluation.

Guidelines:

- The answer NA means that there is no societal impact of the work performed.
- If the authors answer NA or No, they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pretrained language models, image generators, or scraped datasets)?

Answer: [NA]

Justification: No model or new dataset with a risk of misuse is released.

Guidelines:

- The answer NA means that the paper poses no such risks.
- Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
- Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [Yes]

Justification: The historical newspapers are the isiXhosa Intellectual Traditions data (Schoots et al., 2023), used as supplied for the course and cited; the NCHLT isiXhosa Text Corpora are used under their Creative Commons Attribution 2.5 South Africa licence (SADiLaR, `https://hdl.handle.net/20.500.12185/314`) and cited. The model checkpoints are used under the licences on their Hugging Face model cards: Apache 2.0 (mBERT), MIT (AfriBERTa, XLM-R, Afro-XLMR) and CC BY-NC 4.0 (InkubaLM), whose non-commercial terms cover this academic evaluation.

Guidelines:

- The answer NA means that the paper does not use existing assets.
- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New Assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: [Yes]

    Justification: The only new asset is our code, submitted with `README.txt` documenting how to install the requirements and reproduce each step; no new dataset or model is released.

    Guidelines:

    - The answer NA means that the paper does not release new assets.
    - Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
    - The paper should discuss whether and how consent was obtained from people whose asset is used.
    - At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and Research with Human Subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: [NA]

    Justification: The paper involves no crowdsourcing or research with human subjects.

    Guidelines:

    - The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.
    - Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
    - According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional Review Board (IRB) Approvals or Equivalent for Research with Human Subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [NA]

    Justification: The paper involves no crowdsourcing or research with human subjects.

    Guidelines:

- The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.
- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.