```python
// ────────────────────────────────────────
// Python Basics - Übung 1 - Bodner Lisa
// ────────────────────────────────────────
import random //random for different outcomes each time
if __name__ == ,__main__':
    dataset = random.sample(range(1, 11), 10)
    datapoint = random.randint(0, 11)

    // ─── if/elif/else: ───
    if datapoint == 0:
        print(f"datapoint is at min value: {datapoint}")
    elif datapoint in range(1, 9):
        print(f"datapoint is somewhere in between {datapoint}")
    else:
        print(f"datapoint is at max value: {datapoint}")

    // ─── for/while loops w break and pass ───
    i = 1
    for num in dataset:
        print(f"{i}. random value: {num}")
        i+=1

    // prints random numbers until a 4 shows up
    n = random.randint(1, 10)
    while n != 4:
        print(f" {n} is still not 4")
        n = random.randint(1, 10)
```

```
// prints random numbers until a 5 shows up, max 10
for i in range(1, 11):
    n = random.randint(1, 11)
    if n == 5:
        break
    print(f"{i}. time its not 5 but {n} :'")

// prints only the sevens of the ten generated numbers
for i in range(1, 11):
    n = random.randint(1, 11)
    if n != 7:
        pass
    else:
        print(f"{i}. number is 7")

// ——— exception handling ———
try:
    for i in range(1,12):
       print(f"{i}. datapoint: {dataset[i]}")
except IndexError:
    print("out of bounds :(„)
finally:
    print(“process done“)
```