

# Package ‘handcodeR’

May 10, 2026

**Type** Package

**Title** Text Annotation App

**Version** 0.2.1

**Description** Shiny-App that allows to annotate vectors of texts to predefined categories by hand. Features a modern UI with unlimited classification variables.

**License** MIT + file LICENSE

**URL** <https://github.com/liserman/handcodeR>

**BugReports** <https://github.com/liserman/handcodeR/issues>

**Depends** R (>= 4.0)

**Imports** shiny (>= 1.7.0), shinyWidgets (>= 0.7.6), bslib (>= 0.5.0), shinyjs (>= 2.1.0)

**Suggests** testthat (>= 3.0.0)

**Encoding** UTF-8

**Config/testthat/edition** 3

**Config/roxygen2/version** 8.0.0

**RoxygenNote** 7.3.3

**NeedsCompilation** no

**Author** Lukas Isermann [aut, cre] (ORCID:  
<<https://orcid.org/0000-0002-7195-9302>>),  
Dennis Klingenspoehr [aut] (ORCID:  
<<https://orcid.org/0009-0000-7876-5634>>)

**Maintainer** Lukas Isermann <[lukas.isermann@uni-mannheim.de](mailto:lukas.isermann@uni-mannheim.de)>

## Contents

|                             |   |
|-----------------------------|---|
| handcodeR-package . . . . . | 2 |
| handcode . . . . .          | 2 |
| handcode_binary . . . . .   | 4 |

|              |          |
|--------------|----------|
| <b>Index</b> | <b>6</b> |
|--------------|----------|

---

|                   |                                       |
|-------------------|---------------------------------------|
| handcodeR-package | <i>handcodeR: Text Annotation App</i> |
|-------------------|---------------------------------------|

---

### Description

Shiny-based application for hand-coding text data into predefined categories. Supports categorial multi-class annotation, binary two-choice annotation, paired-text comparison workflows, and recovery via autosave and quicksave.

### Main functions

- [handcode](#): categorial multi-class annotation
- [handcode\\_binary](#): binary / two-choice annotation

### Author(s)

**Maintainer:** Lukas Isermann <lukas.isermann@uni-mannheim.de> ([ORCID](#))

Authors:

- Dennis Klingenspohr <dennis.klingenspohr@gmail.com> ([ORCID](#))

### See Also

Useful links:

- <https://github.com/liserman/handcodeR>
- Report bugs at <https://github.com/liserman/handcodeR/issues>

---

|          |                                   |
|----------|-----------------------------------|
| handcode | <i>Categorial Text Annotation</i> |
|----------|-----------------------------------|

---

### Description

Launch a Shiny app for hand-coding texts into one or more categorial classification variables. Each variable is defined by name and its set of allowed categories passed via . . .

### Usage

```
handcode(
  data,
  ...,
  start = "first_empty",
  randomize = FALSE,
  context = FALSE,
  missing = c("Not applicable"),
```

```

    pre = NULL,
    post = NULL,
    comparison = NULL,
    pre_comparison = NULL,
    post_comparison = NULL,
    autosave = FALSE,
    add_notes = FALSE,
    enable_numeric = FALSE
  )

```

## Arguments

|                              |                                                                                                                                                      |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>data</code>            | A character vector of texts, or a data frame with a <code>texts</code> column (and optionally pre-existing classification columns to resume coding). |
| <code>...</code>             | Named character vectors defining classification variables. Each name becomes a variable, each vector its category levels.                            |
| <code>start</code>           | Either <code>"first_empty"</code> (default) or an integer index indicating which row to start coding at.                                             |
| <code>randomize</code>       | Logical. If TRUE, randomize text order. Default FALSE.                                                                                               |
| <code>context</code>         | Logical. If TRUE, show preceding/following texts as context. Default FALSE.                                                                          |
| <code>missing</code>         | Character vector of labels for missing/not-applicable values. Default <code>c("Not applicable")</code> .                                             |
| <code>pre</code>             | Optional character vector of texts to prepend as context (one per row).                                                                              |
| <code>post</code>            | Optional character vector of texts to append as context (one per row).                                                                               |
| <code>comparison</code>      | Optional character vector for paired-text comparison workflows.                                                                                      |
| <code>pre_comparison</code>  | Optional context-before vector for the comparison text.                                                                                              |
| <code>post_comparison</code> | Optional context-after vector for the comparison text.                                                                                               |
| <code>autosave</code>        | Logical. If TRUE, periodically save progress to disk after the user confirms a save location. Requires an interactive session. Default FALSE.        |
| <code>add_notes</code>       | Logical. If TRUE, show a free-text notes input in the UI. Default FALSE.                                                                             |
| <code>enable_numeric</code>  | Logical. If TRUE, enable numeric keyboard shortcuts for category selection. Default FALSE.                                                           |

## Value

A data frame containing the original texts plus one column per classification variable. Returns `invisible(NULL)` if the user cancels the autosave or recovery setup.

## See Also

[handcode\\_binary](#) for two-choice annotation.

## Examples

```
## Not run:
texts <- c("I love this product", "Worst purchase ever", "It's okay")
result <- handcode(
  texts,
  sentiment = c("positive", "neutral", "negative")
)

## End(Not run)
```

---

handcode\_binary

*Binary Text Annotation*

---

## Description

Launch a Shiny app for hand-coding texts into two-choice (left/right) classification variables. Each variable is defined by name and a length-2 character vector via `...`, where the first entry is the left choice and the second is the right choice.

## Usage

```
handcode_binary(
  data,
  ...,
  start = "first_empty",
  randomize = FALSE,
  context = FALSE,
  missing = c("Not applicable"),
  pre = NULL,
  post = NULL,
  comparison = NULL,
  pre_comparison = NULL,
  post_comparison = NULL,
  autosave = FALSE,
  add_notes = FALSE,
  enable_numeric = FALSE,
  multifactorial = TRUE,
  quickcode = FALSE,
  colors = list()
)
```

## Arguments

|      |                                                                                                                                                      |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| data | A character vector of texts, or a data frame with a <code>texts</code> column (and optionally pre-existing classification columns to resume coding). |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------|

|                 |                                                                                                                                                                                                                      |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ...             | Named length-2 character vectors defining binary classification variables. The first element labels the left choice, the second labels the right choice.                                                             |
| start           | Either "first_empty" (default) or an integer index indicating which row to start coding at.                                                                                                                          |
| randomize       | Logical. If TRUE, randomize text order. Default FALSE.                                                                                                                                                               |
| context         | Logical. If TRUE, show preceding/following texts as context. Default FALSE.                                                                                                                                          |
| missing         | Character vector of labels for missing/not-applicable values. Default c("Not applicable").                                                                                                                           |
| pre             | Optional character vector of texts to prepend as context (one per row).                                                                                                                                              |
| post            | Optional character vector of texts to append as context (one per row).                                                                                                                                               |
| comparison      | Optional character vector for paired-text comparison workflows.                                                                                                                                                      |
| pre_comparison  | Optional context-before vector for the comparison text.                                                                                                                                                              |
| post_comparison | Optional context-after vector for the comparison text.                                                                                                                                                               |
| autosave        | Logical. If TRUE, periodically save progress to disk after the user confirms a save location. Requires an interactive session. Default FALSE.                                                                        |
| add_notes       | Logical. If TRUE, show a free-text notes input in the UI. Default FALSE.                                                                                                                                             |
| enable_numeric  | Logical. If TRUE, enable numeric keyboard shortcuts for category selection. Mutually exclusive with quickcode = TRUE. Default FALSE.                                                                                 |
| multifactorial  | Logical. If TRUE (default), allow multiple classification variables. If FALSE, exactly one variable is permitted.                                                                                                    |
| quickcode       | Logical. If TRUE, enable single-key quickcoding mode for one classification variable. Mutually exclusive with enable_numeric = TRUE and multifactorial = FALSE, and limited to a single ... variable. Default FALSE. |
| colors          | Named list with left and right hex color strings used for the binary buttons. Defaults to list(left = "#10b981", right = "#dc2626").                                                                                 |

### Value

A data frame containing the original texts plus one column per binary classification variable. Returns invisible(NULL) if the user cancels the autosave or recovery setup.

### See Also

[handcode](#) for multi-class categorical annotation.

### Examples

```
## Not run:
texts <- c("I love this product", "Worst purchase ever", "It's okay")
result <- handcode_binary(
  texts,
  sentiment = c("positive", "negative")
)

## End(Not run)
```

# Index

## \* **internal**

handcodeR-package, [2](#)

handcode, [2](#), [2](#), [5](#)

handcode\_binary, [2](#), [3](#), [4](#)

handcodeR (handcodeR-package), [2](#)

handcodeR-package, [2](#)