Real-Time Video Generation With MiniMax H3

8× RTX PRO 5000 · vLLM-Omni

Shunyang Li | Public technical brief | October 2026



Agenda

01 Toward Real-Time H3 Generation
02 vLLM-Omni and ComfyUI Applications




01 · Real-Time H3 Generation




Real-Time Ref2VA Raises the Systems Bar

A 124-frame clip at 24 FPS is real time only when end-to-end latency stays below 5.167 s (RTF < 1)



Generative Backbone · Full Parameters (B)

RTF = latency ÷ media duration; the 124-frame deadline is 5.167 s. H3 has the largest dense backbone in this peer set; Wan2.2 has 27B total and 14B active parameters



Model Capability · Native 768P · 33B Dense

32B encoder → 33B dense Omni Transformer → visual/audio VAE. Fifty blocks × 50 steps keep compute and memory pressure high; about 13B AdaLN parameters can be cached

Sources: MiniMax H3, Wan2.2, LTX-2.5 and HunyuanVideo-1.5 official releases · author 960×544 Ref2VA workload

SM120 Brings FP4 Compute; PCIe Limits Scale

All discrete SM120 cards pair fifth-generation Tensor Cores with GDDR7 and PCIe Gen5; none provides GPU-to-GPU NVLink

SKU	Compute	Memory	GPU I/O / Fabric
RTX PRO 5000 ×8 Blackwell	SM120 · 110 SMs 5th-gen Tensor · FP4	72 GB GDDR7 ECC 48 GB variant	PCIe Gen5 ×16 Planned: NIC → RDMA*
RTX PRO 6000 WS / Server	SM120 · 188 SMs 5th-gen Tensor · FP4	96 GB GDDR7 ECC	PCIe Gen5 ×16 No GPU NVLink
GeForce RTX 5090	SM120 · 170 SMs 5th-gen Tensor · FP4	32 GB GDDR7	PCIe Gen5 ×16 No NVLink
DGX Spark · GB10	SM121 · 48 SMs 5th-gen Tensor · FP4	128 GB unified LPDDR5X	NVLink-C2C in SoC 200 Gb/s ConnectX-7

* Planned system path; GPUDirect RDMA requires a compatible NIC and PCIe topology · Sources: NVIDIA product specs, CUDA GPU table, GPUDirect RDMA guide

Latency Breakdown

NCCL occupies 49.2% of the average GPU timeline

Stage	Average GPU Time*	Share
Mean GPU timeline*	250.0 s	100.0%
NCCL communication	123.0 s	49.2%
↳ DiT collectives	116.1 s	46.4%
↳ Encoder, VAE, and other collectives	7.0 s	2.8%
Tensor compute	84.5 s	33.8%
↳ Attention	45.3 s	18.1%
↳ GEMM / MLP	39.2 s	15.7%
AdaLN weight staging + device layout	38.5 s	15.4%
Encoder, VAE, and other GPU work	4.0 s	1.6%

- Of the 38.5 s average, 36.9 s is AdaLN projection weight staging from CPU; layout is 1.5 s
- This run uses the default runtime cache, not a complete precomputed schedule sidecar

Base Ref2VA · 960×544 · 124f @ 24 FPS · 50 steps · BF16 · 8× RTX PRO 5000 · default AdaLN offload · local NCCL / RDMA off · *sum across 8 GPU timelines ÷ 8

How Denoising Works

H3 follows a learned velocity field from noise toward clean video and audio latents

State and direction

- x(t) is the current latent; the DiT predicts a data-ward velocity

Solver update


- Euler advances x(t) by a small interval along that velocity
- The next DiT call needs the new latent, so conventional steps run in sequence

Network function evaluation (NFE)

- One NFE is one complete DiT forward

Base H3

- 50 NFE × 50 main blocks = 2,500 main-block passes



Classical Flow-Matching Sampling

A chain of dependent solver updates turns noise into clean latents

Sources: MiniMax H3 Base configuration · NVIDIA FastGen-PDD sampling background (arXiv:2607.26004) · author abstraction

Few-Step Distillation

PDD predicts four denoising intervals per DiT call: 50 calls → 8

Learn from the 50-step teacher

- Base H3 supplies the direction for each short denoising interval

Predict four moves at once


- One student call predicts four consecutive directions from the same noisy latent

Take the step, then ask again

- Combine those directions, update the latent, and repeat

What changes for H3

- 50 → 8 DiT calls; repeated block work falls from 2,500 to 400 (−84%)



N = fine intervals · L = intervals predicted in parallel

Paper example: N = 12, L = 4 · H3 PDD8: N = 32, L = 4

Sources: NVIDIA FastGen-PDD, Fig. 2 (arXiv:2607.26004) · Alibaba-PAI MiniMax-H3 Ref2VA Acc-8Step @ 335001f

Sparse Attention

VSA scans globally, then spends fine attention only where it matters

Why dense attention hurts

- 34,373 tokens create 1.181B candidate pairs per head and block

Look broadly, then zoom in


- Coarse attention scans all cubes; Top-K picks where fine attention should work

Bring both views together

- A learned gate mixes global context with selected fine detail

What stays dense

- USP8 still exchanges full-length Q/K/V/O between GPUs



(a) VSA Architecture

$$O = O_c \odot G_c + O_f \odot G_f$$

Global coarse context + selected fine detail · FastH3 adaptation: G_f = 1

Source: Video Sparse Attention, arXiv:2505.13389, Fig. 1 · current H3 Ulysses communication path audited from source

Quantization

QAD trains the deployed NVFP4 path against a frozen BF16 teacher

Why PTQ is not enough

- Four-bit rounding can move the model away from its BF16 output

Same sample, two paths


- The teacher stays frozen; the student sees deployment quantization noise

Only the student learns

- Distillation + STE update the student; the teacher disappears at inference

Mixed precision by design

- High-throughput linears use NVFP4; sensitive surrounding math stays BF16



Teacher Guides; NVFP4 Student Learns

Concept: L_QAD = D(y_BF16, y_NVFP4) · the teacher disappears at inference

Sources: NVIDIA Model Optimizer QAD workflow, NVIDIA Technical Blog, Fig. 5 (2025) · FastH3 Omni NVFP4-QAD rev 0087718

Communication

USP8 turns every attention block into four synchronized all-to-all exchanges

Scope	Tensor / Execution	A2A Rounds	Minimum Off-Rank Payload*	Rate at 5.167 s*
One DiT Block	Q / K / V forward + O reverse	4	1.728 GB	61.7 MB/rank/A2A
Base50	50 steps × 50 blocks = 2,500	10,000	4.319 TB	836.0 GB/s
PDD8	8 steps × 50 blocks = 400	1,600	691.1 GB	133.8 GB/s
Boundary	Current VSA / Sage keeps dense BF16 exchange	—	Logical bytes	Not achieved bandwidth

Source-derived @ vLLM-Omni H3 rev 63487a7f · logical one-way off-rank payload lower bound; not measured PCIe/NIC traffic or achieved bandwidth

CUDA Graph

Replay trims launch gaps; fixed head bands expose overlap

All heads + Graph

- Cuts launch overhead, but attention still waits for the full exchange

Head bands + Graph

- Starts attention as each fixed band arrives and pipelines later bands

Measured compute-only

- All-head −0.39% · four bands −2.30%; banding pays off through overlap

Capture boundary

- Graph: unpack → attention → pack; RDMA and readiness events stay outside



Same Graph Benefit · Different Overlap

Measured compute-only: all-head −0.39% · four bands −2.30% · banding pays off through overlap

CUDA Graph Reuse

New video shapes need a new profile; a fixed live stream can replay the same graphs again and again

Question	LLM Decode	H3 Video	Serving Policy
Shape key	Batch bucket q_len = 1	H/W/T · reference slots head band	Cache a small set of hot profiles
Replay window	Many token steps and requests	Across blocks + steps PDD8: 400 · Base50: 2,500*	Reuse persistent slots across continuation windows
VSA Top-K	—	Count fixed per profile indices and values change	Content changes replay the same Graph
New geometry	Select another batch bucket	Bucket hit or eager path	Capture only after the profile becomes hot
Buffer addresses	Static or pooled decode buffers	Registered QKV/O staging buffers	Use a persistent buffer pool

*Per band/profile GraphExec when configuration matches · (1,2,3,1) uses four GraphExecs · Sources: CUDA Programming Guide; current H3 prototype audit

USP

Each GPU swaps a token shard for seven full-sequence heads

Start with token shards

- Eight GPUs split 56,960 tokens; each rank keeps 7,120 tokens and all 56 heads

Swap the sharding axis


- Q/K/V/G all-to-all changes [S/8, 56] into [S, 7]

Do the expensive part locally

- Each GPU sees the full sequence for its own seven heads

Switch back for the block

- The O all-to-all restores token shards for projection, residual, and MLP



Same Tensor, Different Ownership

7,120 × 56 → 56,960 × 7 → 7,120 × 56 · repeated in every attention block

Adapted from DeepSpeed-Ulysses (Jacobs et al., 2023) · current H3 path: DP1 / TP1 / USP8 / Ring1 · measured 362-frame profile

USP Communication

The exchange is balanced in bytes; the host paths are not

Four PCIe islands

- Each island holds two GPUs and two nearest 400-Gb/s CX-8 ports

Three kinds of peer path

- From one rank: 1 PXB, 2 NODE, and 4 SYS peers

Most peers cross sockets

- Four of seven off-rank peers use the SYS path

Why the baseline is uneven

- IB is disabled, so local NCCL follows these host paths



Eight GPUs · Four PCIe Islands

The math is balanced. The roads are not.

Sources: MiniMaxH3Pipeline and denoise-loop code audit · retained nvidia-smi topo -m · 8 nearest 400-Gb/s CX-8 ports

RDMA

The nearest-NIC path moves the same payload in less than half the measured communication + layout time

Route	Logical Off-Rank Volume	Rank-Max / Block	Effective BW / Rank	Serialized PDD8*
NCCL local	446.6 MB / rank / block 1.429 TB / all ranks / PDD8 request	24.87 ms	17.95 GB/s	9.95 s
Nearest-NIC GDR	446.6 MB / rank / block 1.429 TB / all ranks / PDD8 request	10.86 ms	41.14 GB/s	4.34 s
RDMA delta	Same five-slot bytes	−56.4%	2.29×	−5.61 s
Measured scope	Communication + path-required layout	Exact vs independent all_gather	No attention or GEMM	No overlap *serial × 400; not E2E

Measured 2026-10-25 · 5 warmups + 8 trials × 4 calls · rank-max then mean · *serialized block mean × 400; not end-to-end

RDMA Validation


The four-GPU transport path is byte-exact; the full eight-GPU H3 run still needs a clean machine

Q/K first
- V waits for an explicit CUDA event

Graph replay
- Fixed-address unpack remains exact after the input changes

Tiled O return
- Whole and row-chunk returns match byte for byte

Eight-GPU acceptance gate
- Full attention + W_O, end-to-end latency, memory, and Nsight overlap



Four-GPU Real RDMA · 96 of 96 Rank Cases Exact

24 configs × 4 ranks · 8-GPU H3 candidate pending

Measured evidence: real-rdma-four-gpu-20261024-v2 · 2026-10-24 · candidate correctness precheck; latency and overlap not measured

Real-Time Demonstrated; Attribution Pending

Only Base50 uses the locked 960×544, 124-frame request; each optimized result uses a different workload

Status	Workload	System	Result / Limit
Measured baseline	960×544 · 124f · 5.167 s	Base50 · BF16 · USP8 · NCCL	247.956 s · RTF 47.992
15 s study	960×544 · 362f · 15.083 s	PDD8 · QAD · VSA · RDMA	14.974 s mean · RTF 0.993
10 s study	960×544 · 243f · 10.125 s	4-step Turbo · MXFP8 · Sage · RDMA	6.958 s · RTF 0.687
Portrait study	576×1024 · 119 new frames · 4.958 s	4-step MXFP8 · Sage · FP4 VAE · RDMA	4.459 s median · RTF 0.899
Required matched test	Lock image, audio, prompt, seed, shape, and request mode	PDD8 → VSA → QAD/Sage → RDMA	At least 3 runs per stage


Sources: [A] Base50 r4 · [B] QAD 15 s cohort · [C] paired 10 s study · [D] portrait production · compare only within a row; timing and memory methods differ

02 · ComfyUI Apps With vLLM-Omni




vLLM-Omni Brings Multi-GPU H3 to ComfyUI

Open PR #9194 adds character replacement, continuation-aware references, and chainable LoRA controls



Official vLLM-Omni Architecture

ComfyUI authors the workflow; vLLM-Omni runs scheduling, model execution, and multi-GPU deployment



ComfyUI Workflow · PR #9194

The workflow supports single- and multi-character replacement, source-derived duration, long-video continuation, and LoRA controls

Sources: vLLM-Omni v0.26 public deck, slide 22 · vLLM-Omni PR #9194 (open)

