Real-Time Video Generation With MiniMax H3

8× RTX PRO 5000 · vLLM-Omni

Shunyang Li | Public technical brief | October 2026



Agenda

01 Toward Real-Time H3 Generation
02 vLLM-Omni and ComfyUI Applications




01 · Real-Time H3 Generation




Real-Time Ref2VA Raises the Systems Bar

A 124-frame clip at 24 FPS is real time only when end-to-end latency stays below 5.167 s (RTF < 1)



Generative Backbone · Full Parameters (B)

RTF = latency ÷ media duration; the 124-frame deadline is 5.167 s. H3 has the largest dense backbone in this peer set; Wan2.2 has 27B total and 14B active parameters



Model Capability · Native 768P · 33B Dense

32B encoder → 33B dense Omni Transformer → visual/audio VAE. Fifty blocks × 50 steps keep compute and memory pressure high; about 13B AdaLN parameters can be cached

Sources: MiniMax H3, Wan2.2, LTX-2.5 and HunyuanVideo-1.5 official releases · author 960×544 Ref2VA workload

SM120 Brings FP4 Compute; PCIe Limits Scale

All discrete SM120 cards pair fifth-generation Tensor Cores with GDDR7 and PCIe Gen5; none provides GPU-to-GPU NVLink

SKU	Compute	Memory	GPU I/O / Fabric
RTX PRO 5000 ×8 Blackwell	SM120 · 110 SMs 5th-gen Tensor · FP4	72 GB GDDR7 ECC 48 GB variant	PCIe Gen5 ×16 Planned: NIC → RDMA*
RTX PRO 6000 WS / Server	SM120 · 188 SMs 5th-gen Tensor · FP4	96 GB GDDR7 ECC	PCIe Gen5 ×16 No GPU NVLink
GeForce RTX 5090	SM120 · 170 SMs 5th-gen Tensor · FP4	32 GB GDDR7	PCIe Gen5 ×16 No NVLink
DGX Spark · GB10	SM121 · 48 SMs 5th-gen Tensor · FP4	128 GB unified LPDDR5X	NVLink-C2C in SoC 200 Gb/s ConnectX-7

* Planned system path; GPUDirect RDMA requires a compatible NIC and PCIe topology · Sources: NVIDIA product specs, CUDA GPU table, GPUDirect RDMA guide

Latency Breakdown

NCCL occupies 49.2% of the average GPU timeline

Stage	Average GPU Time*	Share
Mean GPU timeline*	250.0 s	100.0%
NCCL communication	123.0 s	49.2%
↳ DiT collectives	116.1 s	46.4%
↳ Encoder, VAE, and other collectives	7.0 s	2.8%
Tensor compute	84.5 s	33.8%
↳ Attention	45.3 s	18.1%
↳ GEMM / MLP	39.2 s	15.7%
AdaLN weight staging + device layout	38.5 s	15.4%
Encoder, VAE, and other GPU work	4.0 s	1.6%

- Of the 38.5 s average, 36.9 s is AdaLN projection weight staging from CPU; layout is 1.5 s
- This run uses the default runtime cache, not a complete precomputed schedule sidecar

Base Ref2VA · 960×544 · 124f @ 24 FPS · 50 steps · BF16 · 8× RTX PRO 5000 · default AdaLN offload · local NCCL / RDMA off · *sum across 8 GPU timelines ÷ 8

How Denoising Works

H3 follows a learned velocity field from noise toward clean video and audio latents

State and direction

- x(t) is the current latent; the DiT predicts a data-ward velocity

Solver update


- Euler advances x(t) by a small interval along that velocity
- The next DiT call needs the new latent, so conventional steps run in sequence

Network function evaluation (NFE)

- One NFE is one complete DiT forward

Base H3

- 50 NFE × 50 main blocks = 2,500 main-block passes



Classical Flow-Matching Sampling


A chain of dependent solver updates turns noise into clean latents

Sources: MiniMax H3 Base configuration · NVIDIA FastGen-PDD sampling background (arXiv:2607.26004) · author abstraction

Few-Step Distillation

PDD predicts four denoising intervals per DiT call: 50 calls → 8

- Base H3 calls the full DiT 50 times. Each call predicts one short interval, updates the latent, and provides the starting point for the next call
- PDD uses Base H3 as the teacher and trains a student on groups of four adjacent denoising intervals
- One student call predicts four consecutive directions from the same noisy latent
- The solver combines those directions, advances the latent, and invokes the student again
- The released H3 schedule covers 32 fine intervals in eight student calls
- **50 → 8 DiT calls; 2,500 → 400 repeated block passes (−84%)**



N = fine intervals · L = intervals predicted in parallel

Paper example: N = 12, L = 4 · H3 PDD8: N = 32, L = 4

Sources: NVIDIA FastGen-PDD, Fig. 2 (arXiv:2607.26004) · Alibaba-PAI MiniMax-H3 Ref2VA Acc-8Step @ 335001f

Sparse Attention

VSA scans globally, then spends fine attention only where it matters

Why dense attention hurts

- 34,373 tokens create 1.181B candidate pairs per head and block

Look broadly, then zoom in


- Coarse attention scans all cubes; Top-K picks where fine attention should work

Bring both views together

- A learned gate mixes global context with selected fine detail

What stays dense

- USP8 still exchanges full-length Q/K/V/O between GPUs



(a) VSA Architecture

$$O = O_c \odot G_c + O_f \odot G_f$$

Global coarse context + selected fine detail · FastH3 adaptation: G_f = 1

Source: Video Sparse Attention, arXiv:2505.13389, Fig. 1 · current H3 Ulysses communication path audited from source

Quantization: Three-Way Video Comparison

BF16 reference · BF16 weights quantized without QAD · Published NVFP4 QAD checkpoint

BF16 Reference	Online NVFP4	QAD NVFP4
		
Original BF16 weights	BF16 weights → NVFP4	Published QAD checkpoint
Request E2E: 48.12 s*	**Request E2E: 32.37 s***	**Request E2E: 28.40 s***
LPIPS ↓ 0.0000 | SSIM ↑ 1.0000	LPIPS ↓ 0.2892 | SSIM ↑ 0.5882	LPIPS ↓ 0.2502 | SSIM ↑ 0.6438


1344 × 768 · 124 frames @ 24 FPS · 8 steps · Seed 1234

*Single requests; warmup / encoder / HSDP differ. Metrics: all frames vs. BF16.

Matched request · cuDNN BF16 attention + original VAE · checkpoint comparison, including encoder precision

FastH3 Omni: Quantization-Aware Distillation

Train the quantized student against a frozen teacher on the eight-forward sampling ladder



Eight forward evaluations

Few-step distillation reduces the number of DiT calls

Real quantized linears

The student forward executes NVFP4 GEMM from the first training step

Quality recovery

Weights learn to absorb quantization error before deployment

Source: FastVideo PR #1989 · public OmniRef recipe @ ea3275d · implementation analysis, not a reproduced training result

QAD: What Runs in Four Bits

Execution precision and parameter updates are separate choices

Module	Student forward	Update
Q / K / V / O	NVFP4 W4A4	Train
FFN projections	NVFP4 W4A4	Train
VSA gate	NVFP4 W4A4	Frozen
Norms	Original path	Frozen
Input / output / time*	FP32	Frozen
Fine attention	FP4 emulator	Backprop

*Designated boundary modules

NVFP4 linear forward

```
w = weight.to(torch.bfloat16)
w_sf = 2688.0 / w.abs().amax().float()
w4, ws = nvfp4_quantize(w, w_sf, ...)
x4, xs = nvfp4_quantize(x, x_sf, ...)
alpha = 1.0 / (w_sf * x_sf)
out = mm_fp4(x4, w4.T,
             xs, ws.T, alpha, ...)
```

FP32 masters + STE backward
Per-16 E4M3 scales
FFN global activation scales calibrated

Source: OmniRef YAML + nvfp4_qad.py + omniref_pdd.py @ ea3275d · 50 DiT blocks · no skipped blocks

QAD: Recover Video and Audio

Match denoised outputs and local activations while keeping VSA gate weights frozen

1 Denoised output

Match student x0 to teacher x0

Normalize each sampling step and modality by its initial PTQ error

Video and audio carry equal weight

2 Layer reconstruction

Give each student unit the teacher's input

Correct attention and FFN error locally, with per-block backward

Video : audio : conditioning
1 : 1 : 0.25

3 Student rollout

Train on the student's own trajectory

After step 20, use student rollout on 25% of rows

Reduce exposure to teacher-only states

Day-0 deployment: preserve packed weights, independent projection scales and TP scale layout

Source: pdd_qad.py + pdd_qad_recon.py + OmniRef YAML @ ea3275d · public recipe, not our training benchmark

Ulysses

Every DiT block reshards Q, K, and V across eight GPUs, then restores O

Scope	Execution	A2A Rounds	Minimum Off-Rank Payload*	Aggregate Rate for RTF 1*
One A2A	Q, K, V, or O	1	0.432 GB	—
One DiT Block	Q / K / V forward + O reverse	4	1.728 GB	—
Base50	50 steps × 50 blocks = 2,500	10,000	4.319 TB	836.0 GB/s
PDD8	8 steps × 50 blocks = 400	1,600	691.1 GB	133.8 GB/s

Source-derived @ vLLM-Omni H3 rev 63487a7f · logical one-way off-rank payload lower bound; not measured PCIe/NIC traffic or achieved bandwidth

CUDA Graph

Reuse vLLM’s graph lifecycle around H3’s request-stable compute island

Reuse vLLM’s lifecycle

- Dispatch, capture, cache, replay, and eager fallback stay in the existing framework

Capture only stable H3 work


- Fixed buffers replay unpack QKV → VSA → pack O

Leave communication at the boundary

- RDMA, readiness events, reverse gather, and dynamic scheduling remain eager

Measured on one fixed profile

- 8-GPU head pipeline: 13.250 s → 11.994 s (−9.48%)



vLLM Executor Runtime · Detail View

Direct crops of the official planning and dispatch nodes

CUDA Graph Reuse

Video shapes vary across requests, so replay is keyed by a qualified profile

One request repeats the same geometry

- 50 blocks × 8 steps provide 400 replay opportunities per head band; tensor values may change

Match the complete profile


- Packed length S, sparse budget Kmax, reference layout, head band, and backend

On a hit, copy and replay

- Copy current values into stable buffers, then launch the cached graph

On a miss, run eager

- Serve immediately, qualify recurring profiles, then capture; report hit rate, cold cost, and graph memory



vLLM CUDAGraphWrapper · Detail View

H3 extends the dispatch key; the wrapper still owns replay and fallback

Ulysses

Each GPU swaps a token shard for seven full-sequence heads

Start with token shards

- Eight GPUs split 56,960 tokens; each rank keeps 7,120 tokens and all 56 heads

Swap the sharding axis


- Q/K/V/G all-to-all changes [S/8, 56] into [S, 7]

Do the expensive part locally

- Each GPU sees the full sequence for its own seven heads

Switch back for the block

- The O all-to-all restores token shards for projection, residual, and MLP




Sequence shards → head shards → sequence shards

Original website illustration: P = 4
Measured H3 configuration at left: P = 8

Source: retained scaling website · Ulysses illustration P=4 · H3 profile at left P=8

Eight-GPU Topology

Two CPU sockets · four ConnectX-8 cards · two GPUs per PCIe subtree



One-way link capacities · network ports support simultaneous TX and RX

Sources: local PCIe / port audit · NVIDIA ConnectX-8 · xGMI installed link configuration unavailable

Local NCCL to RDMA

Matched eight-GPU Q/K/V/O exchanges · FI RDMA is 2.33–2.47× faster across three sequence lengths

Local NCCL: one P2P peer, six SHM peers


- Cross-subtree payload uses host memory
- Two GPUs share one 63.0 GB/s uplink
- $2 \times B \times 6/7 \leq 63.0 \rightarrow B \leq 36.8$ GB/s

Cross-NUMA also shares xGMI

- $4 \times B \times 4/7 \leq C \rightarrow B \leq 7C/16$
- Local-path ceiling: min(36.8, 7C/16)

FI RDMA: one nearest 400G port per GPU

- Bypasses host buffers and CPU-facing uplinks
- $B \leq \min(63.0, 128/2, 50) = 50$ GB/s



B: off-rank TX per GPU · C: usable xGMI bandwidth
Necessary link bounds; SHM and software add costs

2.33–2.47× measured communication speedup
Includes layout, allocation and scheduling

Original vLLM-Omni Ulysses

Q/K/V: pack head shards → NCCL all-to-all → restore sequence layout

```
# comm.py:44–62 · original Q/K/V branch
input_t = (
    input.reshape(bs, shard_seqlen,
                  seq_world_size, shard_hc, hs)
    .transpose(0, 2).contiguous()
)
output = torch.empty_like(input_t)
dist.all_to_all_single(output, input_t, group=group)
output = output.reshape(seqlen, bs, shard_hc, hs)
output = (output.transpose(0, 1).contiguous()
          .reshape(bs, seqlen, shard_hc, hs))
```

Four exchanges per dense block

- Q / K / V: scatter heads
- O: scatter sequence

NCCL selects the route

- P2P / SHM / NET depend on topology and configuration

At batch = 1

- Q/K/V output transpose is a view; contiguous() does not always copy

ulysses.py:538–547 → SeqAllToAll4D.forward → all_to_all_4D → PyTorch NCCL
O reverses the exchange at ulysses.py:721 · pinned source: 63487a7f22db

Source: Base50 checkout 63487a7f22db · comm.py:44–62 · line wrapping adjusted; guards omitted · Apache-2.0

RDMA Validation

Four-GPU transport is byte-exact;
eight-GPU H3 validation is still pending

Q/K first

- V waits for an explicit CUDA event

Graph replay


- Fixed-address unpack remains exact after the input changes

Tiled O return

- Whole and row-chunk returns match byte for byte

Eight-GPU acceptance gate

- Full attention + W_O, end-to-end latency, memory, and Nsight overlap



Four-GPU Real RDMA · 96 of 96 Rank Cases Exact

24 configs × 4 ranks · 8-GPU H3 candidate pending

Measured evidence: real-rdma-four-gpu-20261024-v2 · 2026-10-24 · candidate correctness precheck; latency and overlap not measured

Ulysses Communication: Conclusion

Use GPU-affine FI RDMA for the tested eight-GPU configuration

Measured benefit

2.33–2.47× faster Q/K/V/O exchanges

17.0–18.3 → 39.9–42.7 GB/s/GPU

Three sequence lengths; exact output checks

Topology explains the opportunity

Local NCCL: one P2P peer, six SHM peers

FI RDMA: one nearest 400G port per GPU

Payload bypasses shared CPU uplinks and host buffers

Scope of the measured gain

Comparison includes transport, layout, allocation and scheduling

PCIe versus xGMI saturation is not isolated

CPU remote reads do not establish GPU-path capacity

Next optimization

Produce directly into registered RDMA buffers

Validate overlap and full H3 end-to-end impact

Controlled local-NCCL comparison · communication speedup only · full-model benefit requires matched E2E validation

Real-Time Demonstrated; Attribution Pending

Only Base50 uses the locked 960×544, 124-frame request; each optimized result uses a different workload

Status	Workload	System	Result / Limit
Measured baseline	960×544 · 124f · 5.167 s	Base50 · BF16 · USP8 · NCCL	247.956 s · RTF 47.992
15 s study	960×544 · 362f · 15.083 s	PDD8 · QAD · VSA · RDMA	14.974 s mean · RTF 0.993
10 s study	960×544 · 243f · 10.125 s	4-step Turbo · MXFP8 · Sage · RDMA	6.958 s · RTF 0.687
Portrait study	576×1024 · 119 new frames · 4.958 s	4-step MXFP8 · Sage · FP4 VAE · RDMA	4.459 s median · RTF 0.899
Required matched test	Lock image, audio, prompt, seed, shape, and request mode	PDD8 → VSA → QAD/Sage → RDMA	At least 3 runs per stage


Sources: [A] Base50 r4 · [B] QAD 15 s cohort · [C] paired 10 s study · [D] portrait production · compare only within a row; timing and memory methods differ

02 · ComfyUI Apps With vLLM-Omni




vLLM-Omni Brings Multi-GPU H3 to ComfyUI

Open PR #9194 adds character replacement, continuation-aware references, and chainable LoRA controls



Official vLLM-Omni Architecture

ComfyUI authors the workflow; vLLM-Omni runs scheduling, model execution, and multi-GPU deployment



ComfyUI Workflow · PR #9194

The workflow supports single- and multi-character replacement, source-derived duration, long-video continuation, and LoRA controls

Sources: vLLM-Omni v0.26 public deck, slide 22 · vLLM-Omni PR #9194 (open)

