


```
In [1]: # A bit of setup
import numpy as np
import matplotlib.pyplot as plt

%matplotlib inline
plt.rcParams['figure.figsize'] = (10.0, 8.0) # set default size of plots
plt.rcParams['image.interpolation'] = 'nearest'
plt.rcParams['image.cmap'] = 'gray'

# for auto-reloading extenrnal modules
# see http://stackoverflow.com/questions/1907993/autoreload-of-modules-in-ipython
%load_ext autoreload
%autoreload 2
```

```
In [323]: np.random.seed(0)
N = 100 # number of points per class
D = 2 # dimensionality
K = 3 # number of classes
X = np.zeros((N*K,D))
y = np.zeros(N*K, dtype='uint8')
for j in xrange(K):
    ix = range(N*j,N*(j+1))
    r = np.linspace(0.0,1,N) # radius
    t = np.linspace(j*4,(j+1)*4,N) + np.random.randn(N)*0.2 # theta
    X[ix] = np.c_[r*np.sin(t), r*np.cos(t)]
    y[ix] = j
fig = plt.figure()
plt.scatter(X[:, 0], X[:, 1], c=y, s=40, cmap=plt.cm.Spectral)
plt.xlim([-1,1])
plt.ylim([-1,1])
#fig.savefig('spiral_raw.png')
```



In [329]:

#Train a Linear Classifier

```

# initialize parameters randomly
W = 0.01 * np.random.randn(D,K)
b = np.zeros((1,K))

# some hyperparameters
step_size = 1e-0
reg = 1e-3 # regularization strength

# gradient descent loop
num_examples = X.shape[0]
for i in xrange(200):

    # evaluate class scores, [N x K]
    scores = np.dot(X, W) + b

    # compute the class probabilities
    exp_scores = np.exp(scores)
    probs = exp_scores / np.sum(exp_scores, axis=1, keepdims=True) # [N x
K]

    # compute the loss: average cross-entropy loss and regularization
    corect_logprobs = -np.log(probs[range(num_examples),y])
    data_loss = np.sum(corect_logprobs)/num_examples
    reg_loss = 0.5*reg*np.sum(W*W)
    loss = data_loss + reg_loss
    if i % 10 == 0:
        print "iteration %d: loss %f" % (i, loss)

    # compute the gradient on scores
    dscores = probs
    dscores[range(num_examples),y] -= 1
    dscores /= num_examples

    # backpropate the gradient to the parameters (W,b)
    dW = np.dot(X.T, dscores)
    db = np.sum(dscores, axis=0, keepdims=True)

    dW += reg*W # regularization gradient

    # perform a parameter update
    W += -step_size * dW
    b += -step_size * db

```

```


iteration 0: loss 1.096956
iteration 10: loss 0.917265
iteration 20: loss 0.851503
iteration 30: loss 0.822336
iteration 40: loss 0.807586
iteration 50: loss 0.799448
iteration 60: loss 0.794681
iteration 70: loss 0.791764
iteration 80: loss 0.789920
iteration 90: loss 0.788726
iteration 100: loss 0.787938
iteration 110: loss 0.787409
iteration 120: loss 0.787049
iteration 130: loss 0.786803
iteration 140: loss 0.786633
iteration 150: loss 0.786514
iteration 160: loss 0.786431
iteration 170: loss 0.786373
iteration 180: loss 0.786331
iteration 190: loss 0.786302

```

```
In [330]: # evaluate training set accuracy
scores = np.dot(X, W) + b
predicted_class = np.argmax(scores, axis=1)
print 'training accuracy: %.2f' % (np.mean(predicted_class == y))
```

training accuracy: 0.49

```
In [331]: # plot the resulting classifier
h = 0.02
x_min, x_max = X[:, 0].min() - 1, X[:, 0].max() + 1
y_min, y_max = X[:, 1].min() - 1, X[:, 1].max() + 1
xx, yy = np.meshgrid(np.arange(x_min, x_max, h),
                     np.arange(y_min, y_max, h))
Z = np.dot(np.c_[xx.ravel(), yy.ravel()], W) + b
Z = np.argmax(Z, axis=1)
Z = Z.reshape(xx.shape)
fig = plt.figure()
plt.contourf(xx, yy, Z, cmap=plt.cm.Spectral, alpha=0.8)
plt.scatter(X[:, 0], X[:, 1], c=y, s=40, cmap=plt.cm.Spectral)
plt.xlim(xx.min(), xx.max())
plt.ylim(yy.min(), yy.max())
#fig.savefig('spiral_linear.png')
```



```

# initialize parameters randomly
h = 100 # size of hidden layer
W = 0.01 * np.random.randn(D,h)
b = np.zeros((1,h))
W2 = 0.01 * np.random.randn(h,K)
b2 = np.zeros((1,K))

# some hyperparameters
step_size = 1e-0
reg = 1e-3 # regularization strength

# gradient descent loop
num_examples = X.shape[0]
for i in xrange(10000):

    # evaluate class scores, [N x K]
    hidden_layer = np.maximum(0, np.dot(X, W) + b) # note, ReLU activation
    scores = np.dot(hidden_layer, W2) + b2

    # compute the class probabilities
    exp_scores = np.exp(scores)
    probs = exp_scores / np.sum(exp_scores, axis=1, keepdims=True) # [N x
K]

    # compute the loss: average cross-entropy loss and regularization
    corect_logprobs = -np.log(probs[range(num_examples),y])
    data_loss = np.sum(corect_logprobs)/num_examples
    reg_loss = 0.5*reg*np.sum(W*W) + 0.5*reg*np.sum(W2*W2)
    loss = data_loss + reg_loss
    if i % 1000 == 0:
        print "iteration %d: loss %f" % (i, loss)

    # compute the gradient on scores
    dscores = probs
    dscores[range(num_examples),y] -= 1
    dscores /= num_examples

    # backpropate the gradient to the parameters
    # first backprop into parameters W2 and b2
    dW2 = np.dot(hidden_layer.T, dscores)
    db2 = np.sum(dscores, axis=0, keepdims=True)
    # next backprop into hidden layer
    dhidden = np.dot(dscores, W2.T)
    # backprop the ReLU non-linearity
    dhidden[hidden_layer <= 0] = 0
    # finally into W,b
    dW = np.dot(X.T, dhidden)
    db = np.sum(dhidden, axis=0, keepdims=True)

    # add regularization gradient contribution
    dW2 += reg * W2
    dW += reg * W

    # perform a parameter update
    W += -step_size * dW
    b += -step_size * db
    W2 += -step_size * dW2
    b2 += -step_size * db2

```

```

iteration 0: loss 1.098744
iteration 1000: loss 0.294946
iteration 2000: loss 0.259301
iteration 3000: loss 0.248310
iteration 4000: loss 0.246170
iteration 5000: loss 0.245649
iteration 6000: loss 0.245491
iteration 7000: loss 0.245400
iteration 8000: loss 0.245335
iteration 9000: loss 0.245292

```

```

In [333]: # evaluate training set accuracy
hidden_layer = np.maximum(0, np.dot(X, W) + b)
scores = np.dot(hidden_layer, W2) + b2
predicted_class = np.argmax(scores, axis=1)
print 'training accuracy: %.2f' % (np.mean(predicted_class == y))


```

training accuracy: 0.98

```

In [336]: # plot the resulting classifier
h = 0.02
x_min, x_max = X[:, 0].min() - 1, X[:, 0].max() + 1
y_min, y_max = X[:, 1].min() - 1, X[:, 1].max() + 1
xx, yy = np.meshgrid(np.arange(x_min, x_max, h),
                     np.arange(y_min, y_max, h))
Z = np.dot(np.maximum(0, np.dot(np.c_[xx.ravel(), yy.ravel()], W) + b), W
2) + b2
Z = np.argmax(Z, axis=1)
Z = Z.reshape(xx.shape)
fig = plt.figure()
plt.contourf(xx, yy, Z, cmap=plt.cm.Spectral, alpha=0.8)
plt.scatter(X[:, 0], X[:, 1], c=y, s=40, cmap=plt.cm.Spectral)
plt.xlim(xx.min(), xx.max())
plt.ylim(yy.min(), yy.max())
#fig.savefig('spiral_net.png')

```



Notebook In [ ]: [https://cs.stanford.edu/people/karpathy/cs231files/minimal\\_n...](https://cs.stanford.edu/people/karpathy/cs231files/minimal_n...)