A SURVEY-BASED ANALYSIS OF NTFS AND FAT32 FILE SYSTEM PERFORMANCE

Dr. K.Deepa

Department of Information Technology

Sri Ramakrishna Engineering College, India

deepa.senthil@srec.ac.in

Orc Id: 0000-0003-2964-0741

Dhanshika R

Department of Information Technology

Sri Ramakrishna Engineering College, India

dhanshika..2405011@srec.ac.in

Dharshini S

Department of Information Technology

Sri Ramakrishna Engineering College, India

dharshini.2405016@srec.ac.in

Lithigaa GJ

Department of Information Technology

Sri Ramakrishna Engineering College, India

lithigaa.2405051@srec.ac.in

ABSTRACT:

File systems underpin data organization and management in operating systems, with FAT32 and NTFS serving as prominent options in Windows ecosystems. This paper conducts a detailed analysis of FAT32 and NTFS, evaluating their core architectures, allocation strategies, and performance metrics. Key aspects include cluster management, fragmentation mitigation, space allocation via bitmaps, journaling for recovery, and ACL-based security in NTFS versus FAT32's basic File Allocation Table (FAT). Through structural examination and performance benchmarking, the study reveals NTFS's superior handling of large-scale storage, enhanced fault tolerance, and granular permissions, positioning it as ideal for enterprise and high-reliability scenarios. FAT32, however, excels in cross- —NTFS, FAT32, Master File Table, cluster allocation, fragmentation, bitmap management, journaling, ACL security, performance.

INDEX TERMS:

NTFS, FAT32, File Systems, Master File Table (MFT), Cluster Allocation, Fragmentation, Bitmap Allocation, Journaling, Access Control Lists (ACL), Storage Performance, Fault Tolerance, Data Security.

I. INTRODUCTION

Background and Motivation

A file system is a logical framework used by operating systems to manage the storage, organization, and retrieval of data on storage devices, defining how files are named, stored, and accessed while maintaining information such as file locations, permissions, and allocation. Early systems used simple file systems due to limited resources, with the File Allocation Table (FAT) family becoming widely adopted. FAT32, an extension of FAT16, improved storage capacity by organizing data into clusters and using a table to track file locations, making it suitable for removable storage and cross-platform use. However, as computing evolved with larger storage, multi-user environments, and higher security needs, FAT32's limitations— such as lack of security, scalability, and reliability—became evident. To address these issues, Microsoft introduced the New Technology File System (NTFS), which offers advanced features like a centralized Master File Table (MFT) for metadata management, efficient space allocation, enhanced security through access control, and fault tolerance through journaling. This transition highlights the evolution of file systems toward improved scalability, reliability, and security in modern computing environments.

Problem Statement

Traditional file systems like FAT32 are popular because they are simple and work across different platforms. However, they have several limitations that make them less effective in today's computing environments. These limitations include poor security features, no fault tolerance, inefficient storage use, and limited scalability for large storage volumes. As data- heavy applications grow, along with multi-user systems and the need for reliable data management, these issues have become more serious. To tackle these problems, more advanced file systems like NTFS have been created. They include features such as organized metadata management, access control, efficient space allocation, and journaling for fault tolerance. Still, we need to carefully evaluate how well these features fix the shortcomings of traditional file systems. This study will analyze FAT32 and NTFS based on their structure, performance, reliability, and security. The goal is to see how suitable each is for modern computing needs.

II. LITERATURE REVIEW

A. Studies on FAT32 File System

Several researchers have examined the structure and operation of the FAT32 file system because it is commonly used in removable storage devices like USB drives and memory cards. FAT32 divides storage into three main parts: the reserved area, the file allocation table (FAT) region, and the data region. Files are stored in clusters, and metadata such as file name, creation time, and attributes are recorded in directory entries. Lee et al. studied how FAT32 file systems allocate space and proposed a method to reconstruct the creation times of deleted files. Their work showed that directory entries for deleted files remain accessible until new files overwrite them. This allows for data recovery, making it valuable in digital forensic applications. Further research on FAT32 allocation strategies suggests that the file system often uses a next-available allocation method. In this approach, the search for free clusters starts from the most recently allocated cluster rather than the beginning of the storage device. While this method speeds up allocation, it can lead to fragmentation as storage fills up. Overall, these studies show that FAT32 is simple and compatible with many platforms, but it has drawbacks related to fragmentation and limited metadata handling.

B. Studies on NTFS File System

NTFS is a newer file system created to address the limitations of FAT-based systems. Researchers have looked into the allocation methods of NTFS to better understand its efficiency and reliability. NTFS employs an indexed allocation method where metadata is stored in the Master File Table (MFT), which improves how storage is organized and how files are accessed. Karresand et al. examined the allocation behavior of NTFS in Windows operating systems and found that the system generally uses a best-fit allocation strategy. This method selects the most appropriate free space available, reducing wasted space and enhancing disk usage. Their study also showed that small files can be directly stored within metadata structures, leading to quicker disk access and better system performance. These features make NTFS a better choice for large storage systems than FAT32. Overall, NTFS is seen as more reliable and efficient due to its better storage management and improved control over fragmentation.

C. Studies on FAT32 and NTFS

The studies on FAT32 and NTFS reveal differences in storage efficiency, reliability, and performance. FAT32 uses a simpler linked allocation technique, making it suitable for small storage devices and portable systems. However, its limitations in file size support and metadata management reduce its efficiency in modern computing environments. In contrast, NTFS offers better performance with indexed allocation and improved metadata structures. Studies indicate that NTFS allocation patterns vary based on file-writing methods, like block writing or stream writing, and aim to reduce fragmentation during storage operations. Additionally, FAT32 allocation behavior can change when files are deleted and new files are added. These changes affect cluster usage and overall storage performance over time. These findings suggest that while FAT32 is still useful for compatibility, NTFS provides enhanced performance and reliability in modern computing systems.

D. Research Gap

While many studies have looked into FAT32 and NTFS file systems separately, there is little research that directly analyze their performance under the same system conditions. Most existing studies focus on allocation methods and recovery techniques rather than assessing real-time performance metrics like read/write speed, storage utilization, and system efficiency. Moreover, many experiments take place in controlled settings that may not accurately reflect real-world usage scenarios involving large amounts of data and ongoing storage operations. Thus, there is a need for a detailed analysis of FAT32 and NTFS file systems to assess their performance characteristics and determine their suitability for various storage environments.

E. Performance and Storage Efficiency Evaluation

Performance and storage efficiency can be considered among those elements that contribute greatly to the evaluation of file system operation. Numerous researchers have evaluated the performance attributes of FAT32 and NTFS file systems with regards to their storage efficiency, performance under fragmentation, and allocation speed. Being characterized by a simpler allocation approach, FAT32 allows for better allocation speed. However, this file system experiences significant performance losses caused by high fragmentation levels when storage usage increases.

The research into FAT32 allocation practices indicates that cluster allocation depends on file creation and deletion procedures, which affect the efficiency of storage usage. Linked allocation is one of the major drawbacks in the functioning of the file system since it prevents the efficient handling of large volumes of information by this system. On the contrary, NTFS is distinguished by better storage efficiency because of indexed allocation and proper metadata storage. In addition, the use of NTFS allows taking advantage of additional system properties including improved metadata management and allocation.

Objectives of the Proposed System

The main aim of the proposed system is to analyze FAT32 and NTFS file systems to assess their effectiveness in modern computing environments. This study focuses on examining the differences between the two file systems, including how they manage metadata and allocate storage. It also looks into fragmentation behavior and its effect on system performance. Additionally, the study evaluates the features of NTFS, such as the Master File Table (MFT), bitmap-based space management, and journaling for fault tolerance. It further analyzes the security methods offered by NTFS through Access Control Lists (ACLs) compared to the limited security features of FAT32. Lastly, it intends to analyze overall performance, reliability, and efficiency to determine the best file system for various applications, including portable storage devices and large-scale enterprise settings.

Related Work

Several studies have examined the design and performance characteristics of different file systems to understand their impact on storage efficiency and system reliability. Early research on FAT-based file systems primarily focused on their simplicity and compatibility across multiple operating systems. Because FAT32 uses a straightforward file allocation table structure, it has been widely adopted in removable storage devices and embedded systems. However, researchers have also highlighted limitations such as inefficient disk space utilization, increased fragmentation, and the absence of built-in security and recovery mechanisms.

With the development of advanced operating systems, researchers began to analyze more sophisticated file systems such as NTFS. Previous work has shown that NTFS improves data management through the use of structured metadata storage and advanced allocation techniques. The Master File Table (MFT) used in NTFS allows efficient organization of file metadata, enabling better indexing and retrieval of stored information. Studies have also emphasized the importance of bitmap-based space allocation in NTFS, which helps track free and used disk clusters more efficiently compared to the traditional allocation table approach used in FAT32.

Another area of research has focused on system reliability and fault tolerance. Journaling mechanisms implemented in NTFS have been widely studied for their role in maintaining file system consistency during unexpected system interruptions. These mechanisms record file system changes before they are permanently written to disk, allowing faster recovery and reducing the risk of data corruption.

Security has also been a significant research topic in file system design. Earlier file systems such as FAT32 provide minimal security support, while NTFS incorporates Access Control Lists (ACLs) that allow administrators to define detailed permission structures for files and directories. Several studies have demonstrated that such security features make NTFS more suitable for multi-user and enterprise environments.

Although prior research has investigated the individual characteristics of these file systems, a comprehensive evaluation of their architectural features and performance-related mechanisms remains valuable. This work contributes to the existing literature by examining NTFS and FAT32 through a structured comparison of metadata management, fragmentation behavior, storage allocation techniques, journaling capability, and security features.

The current study provide a detailed pattern of FAT32 and NTFS file systems to improve understanding of their structural and functional differences. It examines key aspects like cluster allocation, fragmentation behavior, metadata management, and space allocation methods to assess storage efficiency. The study also emphasizes important features in NTFS, such as the Master File Table (MFT), journaling for fault tolerance, and Access Control Lists (ACLs) for security. These features show how NTFS overcomes the limitations of FAT32. Additionally, it includes experimental observations to evaluate performance differences in real-world scenarios. Overall, this study offers clear insights into the strengths and weaknesses of both file systems and identifies their suitability for various uses, from portable storage to enterprise-level systems.

Analysis of NTFS and FAT32

A file system determines how data is stored, organized, and retrieved from storage devices. FAT32 and NTFS are two important file systems used in Microsoft Windows environments, each designed with different architectural goals and operational capabilities. FAT32 focuses on simplicity and compatibility, whereas NTFS is designed to support modern computing requirements such as large storage volumes, improved reliability, and advanced security mechanisms. This section presents a detailed comparison of the structural and functional characteristics of NTFS and FAT32.

A. Metadata Organization and Master File Table (MFT)

Metadata refers to the information that describes the attributes and structure of files stored within a file system. In NTFS, metadata is managed using a centralized database structure known as the Master File Table (MFT). The MFT contains a record for every file and directory stored on the disk. Each record typically stores file attributes such as file name, file size, timestamps (creation, modification, and access time), security descriptors, and the physical location of file data on the disk.

The use of the MFT provides several advantages. Since metadata is organized in a structured database format, NTFS can quickly locate file information and maintain consistency across the file system. Additionally, small files can sometimes be stored directly within the MFT record itself, which reduces disk access time and improves performance. The MFT also supports multiple attributes for each file, enabling advanced features such as compression, encryption, and indexing.

In contrast, FAT32 uses a simpler metadata approach. Instead of maintaining a centralized metadata database, FAT32 stores file information in directory entries while the File Allocation Table keeps track of the clusters associated with each file. Each entry in the FAT indicates the next cluster in the chain that belongs to a file. Although this structure is easy to implement and understand, it becomes inefficient when handling large numbers of files or large storage volumes because the system must traverse cluster chains to determine file locations.

B. Disk Cluster Allocation and Storage Management

Both NTFS and FAT32 store file data in units called clusters, which consist of one or more disk sectors. The cluster size determines the minimum amount of disk space allocated to a file. In FAT32, cluster allocation is managed through the File Allocation Table. When a file is created, the system searches for free clusters and links them together using entries in the table. Each cluster entry points to the next cluster belonging to the file, forming a chain.

While this approach simplifies storage management, it can lead to inefficiencies, especially when files are frequently modified. Searching through the FAT to locate free clusters may also become slower as disk size increases. Furthermore, FAT32 can experience internal fragmentation because even small files occupy an entire cluster.

NTFS manages disk space more efficiently by storing allocation details in the Master File Table (MFT) and using advanced methods to place data in contiguous clusters. This reduces fragmentation and improves overall storage performance.




Fig 1:FAT32 cluster allocation

C. Fragmentation Behavior

Fragmentation occurs when file data becomes scattered across non-contiguous disk locations. This phenomenon typically happens when files are repeatedly created, modified, or deleted. FAT32 is particularly prone to fragmentation because it allocates clusters sequentially without advanced optimization techniques. As files grow in size, additional clusters may be allocated in different disk locations, causing the file to become fragmented.

Fragmentation negatively affects performance because the disk head must move to multiple locations to read a single file. Over time, this results in slower data access and increased disk activity. As a result, systems using FAT32 often require periodic disk defragmentation utilities to reorganize file data.

NTFS reduces fragmentation through more intelligent allocation algorithms and improved metadata management. The file system attempts to allocate contiguous clusters during file creation and expansion. Additionally, the structured nature of the MFT allows the system to track file extents more efficiently, minimizing the likelihood of excessive fragmentation.Security is a major difference between NTFS and FAT32.

D. Access Control List (ACL) and Security Management

FAT32 does not provide built-in mechanisms for controlling access to files and directories. In this file system, any user or process that can access the storage device typically has unrestricted access to the stored files. This limitation makes FAT32 unsuitable for multi-user environments where data security and controlled access are required.

NTFS addresses this limitation by implementing Access Control Lists (ACLs). An ACL is a security structure that defines the permissions associated with a file or directory. Each ACL contains entries specifying which users or system groups are allowed to perform actions such as reading, writing, modifying, or executing files.

These permissions are enforced by the operating system and enable administrators to control how data is accessed and shared within a system. NTFS also supports additional security features such as file encryption and auditing, further enhancing data protection in enterprise and multi- user environments.

FAT32 doesn't have any protective controls, but NTFS does have a better way to protect information. It makes sure that interactions with stored content are both intentional and accountable by letting administrators give specific people or groups different privileges. This structured approach not only makes things more private, but it also makes the computing environment more disciplined and reliable, especially when people need to share access. It also supports advanced capabilities that help maintain data integrity over time. Such design considerations make it well-suited for modern systems requiring reliability and organized access management.




Fig 2: NTFS Access Control List (ACL) permissions

E. Bitmap-Based Space Management

NTFS uses a bitmap data structure to track the allocation status of disk clusters. In this bitmap, each bit represents a cluster on the disk, indicating whether that cluster is free or currently in use. This approach allows the system to quickly identify available storage space and allocate clusters efficiently when new files are created.

The bitmap structure also improves the speed of storage management operations because the system can directly check cluster availability without scanning the entire disk. This contributes to improved performance, especially in large storage systems.

FAT32 does not include a dedicated bitmap structure for tracking free space. Instead, it determines cluster availability by examining entries in the File Allocation Table. As the size of the storage device increases, scanning the FAT to locate free clusters becomes less efficient compared to the bitmap-based approach used by NTFS.

F. Journaling and Fault Tolerance

Reliability and data integrity are critical aspects of modern file systems. NTFS includes a journaling mechanism that records changes to file system metadata before those changes are permanently written to disk. This process is implemented through a transaction log that tracks pending operations.

In the event of a system crash or unexpected power failure, the journal allows the operating system to restore the file system to a consistent state by replaying or discarding incomplete operations. This significantly reduces the risk of file system corruption and minimizes the time required for system recovery.

FAT32 does not provide journaling capabilities. When a system failure occurs, there is a greater risk that file system structures such as the allocation table may become inconsistent or corrupted. Recovery often requires the use of disk repair utilities to scan the file system and attempt to reconstruct damaged structures.

G. Scalability and Performance Consideration

NTFS is designed to support modern storage requirements, including large disk volumes, high-capacity storage devices, and complex file structures. Its advanced metadata management, efficient allocation strategies, and built-in reliability features contribute to improved performance and scalability.

FAT32, while simple and widely compatible, has several limitations in terms of scalability. It supports smaller maximum file sizes and lacks many of the advanced features necessary for modern enterprise environments. However, its simplicity and compatibility make it suitable for removable media and devices that require interoperability across different operating systems.

Overall, the architectural design of NTFS provides significant advantages in terms of performance, security, and reliability, while FAT32 remains useful in scenarios where simplicity and cross-platform compatibility are the primary requirements

VI . EXPERIMENTAL ANALYSIS

To evaluate the practical performance differences between NTFS and FAT32, a series of experimental observations were conducted using storage devices formatted with both file systems. The experiments focused on measuring key performance aspects such as file creation time, data transfer speed, storage allocation efficiency, and system recovery behavior. These experiments help illustrate how the structural differences between the two file systems influence real-world storage performance.

A. Experimental Setup

The experimental analysis was carried out on a standard computer system running a Windows-based operating system. Two separate partitions of equal size were created on the same storage device to ensure consistent testing conditions. One partition was formatted using the FAT32 file system, while the other was formatted using the NTFS file system.

Multiple datasets consisting of small, medium, and large files were prepared to evaluate different file storage scenarios. The testing process included copying files to the storage partitions, deleting files, modifying file contents, and measuring the time required for each operation. Disk monitoring tools were used to observe cluster allocation behavior, fragmentation levels, and

storage utilization patterns.

B. File Creation and Write Performance

During the testing process, it was observed that FAT32 demonstrated slightly faster file creation times for small files due to its simpler allocation structure. The absence of complex metadata management allows the file system to perform basic file operations quickly. However, as the size and number of files increased, the performance difference between the two file systems decreased.

NTFS introduced additional overhead during file creation because it records metadata within the Master File Table and updates various internal structures. Despite this overhead, NTFS provided more consistent performance when handling large numbers of files due to its efficient metadata indexing and storage management.




Fig 3: NTFS File Access Time using PowerShell

C. File Creation and Write Performance

During the testing process, it was observed that FAT32 demonstrated slightly faster file creation times for small files due to its simpler allocation structure. The absence of complex metadata management allows the file system to perform basic file operations quickly. However, as the size and number of files increased, the performance difference between the two file systems decreased.

NTFS introduced additional overhead during file creation because it records metadata within the Master File Table and updates various internal structures. Despite this overhead, NTFS provided more consistent performance when handling large numbers of files due to its efficient metadata indexing.




Fig 4: FAT32 Access Time using PowerShell

D. Fragmentation Analysis

Fragmentation tests were conducted by repeatedly creating, modifying, and deleting files on both file systems. The results showed that FAT32 experienced higher levels of fragmentation as disk usage increased. Fragmented files required additional disk access operations, which reduced overall performance.

NTFS showed better resistance to fragmentation because of its allocation algorithms and organized metadata management. NTFS can still become fragmented, but over time the file system usually keeps files better organized. This makes the system work better and less often needs maintenance. Also, its design makes it easier to handle files, which makes it better for modern computing environments where data is used a lot and all the time.




Fig 5: NTFS Fragmentation Analysis (Pre)




Fig 6: NTFS Fragmentation Analysis (Post)




Fig 7: FAT32 Fragmentation Analysis (Pre)




Fig 8: FAT32 Fragmentation Analysis (Post)

D. System Recovery and Reliability

Another important experimental factor was the behavior of each file system during unexpected system interruptions. When simulated power interruptions were introduced during file operations, NTFS was able to recover more quickly due to its journaling mechanism. The transaction log allowed the file system to restore consistency by completing or discarding incomplete operations.

FAT32 lacked such recovery mechanisms. As a result, system interruptions occasionally caused inconsistencies within the file allocation table, requiring manual repair using disk checking utilities.

E. Summary of Experimental Findings

The experimental results confirm that NTFS provides improved reliability, better management of large storage volumes, and enhanced data protection through journaling and security features. FAT32, while offering faster performance for simple operations and maintaining strong compatibility across devices, demonstrates limitations in terms of fragmentation control, storage scalability, and system recovery capabilities.

These observations highlight the trade-off between simplicity and advanced functionality. NTFS is better suited for modern computing environments that require reliability, security, and large storage capacity, while FAT32 remains useful for portable devices and systems requiring broad compatibility.

V. RESULTS AND DISCUSSION

The evaluation of NTFS and FAT32 reveals significant differences in their architecture, performance characteristics, and operational capabilities. The analysis of major parameters such as metadata management, storage allocation, fragmentation behavior, security mechanisms, bitmap management, and journaling functionality highlights how each file system addresses data management requirements.

From the analysis of metadata organization, it is observed that NTFS provides a more structured and efficient mechanism through the use of the Master File Table (MFT). The centralized storage of file metadata enables faster file access and improved indexing. FAT32, on the other hand, relies on directory entries and the file allocation table to maintain file location information. While this design simplifies implementation, it becomes less efficient when managing large volumes of files or large storage capacities.

In terms of storage allocation, FAT32 uses the File Allocation Table to link clusters associated with a file. Although this method is simple and easy to implement, it requires continuous scanning of the allocation table to identify free clusters. This process becomes increasingly inefficient as disk size grows. NTFS improves this process through advanced allocation methods combined with bitmap-based space tracking. The bitmap structure enables the file system to quickly identify free clusters and allocate storage space more efficiently.

The study of fragmentation behavior indicates that FAT32 is more prone to file fragmentation due to its sequential cluster allocation strategy. As files grow or are modified, their data may become scattered across different disk locations, resulting in increased disk head movement and slower data access times. NTFS reduces fragmentation through improved allocation algorithms and metadata management, which help maintain more contiguous storage patterns.

Security analysis further demonstrates the advantages of NTFS. FAT32 lacks built-in mechanisms for managing file permissions, making it unsuitable for environments that require controlled access to data

NTFS addresses this limitation by implementing Access Control Lists (ACLs), which allow administrators to define detailed permissions for files and directories. This capability is essential for multi-user systems and enterprise-level

computing environments.

Reliability and fault tolerance are also critical aspects of file system design. NTFS incorporates a journaling mechanism that records file system changes before they are permanently written to disk. This transaction logging process enables faster recovery and helps maintain file system consistency during unexpected system failures. In contrast, FAT32 does not support journaling, which increases the likelihood of data corruption in the event of system crashes or power interruptions.

Overall, the results of this analysis indicate that NTFS provides superior performance, scalability, security, and reliability than FAT32. However, FAT32 continues to remain relevant in specific scenarios such as removable storage devices and embedded systems, where simplicity and cross-platform compatibility are more important than advanced file system features.

CONCLUSION

In conclusion, this study presents a comprehensive analysis between FAT32 and NTFS file systems, highlighting their structural design, performance characteristics, and practical applicability. The analysis clearly demonstrates that NTFS offers significant advantages in terms of metadata management, storage efficiency, security, and fault tolerance. Features such as the Master File Table (MFT), bitmap-based allocation, journaling, and Access Control Lists (ACLs) make NTFS highly suitable for modern computing environments that require reliability, scalability, and secure data handling.

On the other hand, FAT32, with its simple architecture and minimal overhead, remains relevant in scenarios where compatibility and ease of use are primary concerns. It is particularly useful for removable storage devices and systems that require interoperability across multiple platforms. However, its limitations in file size support, lack of security features, and vulnerability to fragmentation and data corruption reduce its effectiveness in large-scale and high-performance environments.

Overall, the study concludes that while FAT32 continues to serve basic and portable storage needs, NTFS is the preferred choice for contemporary systems due to its advanced capabilities and robust performance. The selection of an appropriate file system ultimately depends on the specific requirements of the application, balancing factors such as compatibility, performance, security, and reliability.

REFERENCE

[1] Raksha Rane and Asmit Singh, “Demystifying File Systems: A Comprehensive Exploration of Data Organization,” International Journal of Computer Science and Information Technology, 2024.

[2] Li Qiyang, Zhang Quanxin, Tan Yu-an, Li Yuanzhang, and Zheng Jun, “Research on Allocator Strategy of FAT32 File System Based on Linux & Windows,” International Journal of Computer Applications, 2016.

[3] Microsoft Corporation, “NTFS Technical Reference Guide,” Microsoft Developer Documentation, 2019.

[4] Andrew S. Tanenbaum and Herbert Bos,“Modern Operating Systems,” 4th Edition, Pearson Education, 2015.

[5] William Stallings, “Operating Systems: Internals and Design Principles,” 9th Edition, Pearson Education, 2018.

[6] Liu Naiqi, Wang Zhongshan, Hao Yujie, and Qin Ke,“Computer Forensics Research and Implementation Based on NTFS File System,” International Conference on Computer Science and Software Engineering, 2008.

[7] W. Y. Lee,“Extraction of Creation-Time for Recovered Files on Windows FAT32 File System,” Applied Sciences, vol. 9, no. 24, pp. 1–17, 2019.

[8] M. P. Mehta, “Formalising File systems in the ACL2 Theorem Prover: An Application to FAT32,” arXiv Computer Science Archive, pp. 1–20, 2018.

[9] M. Karresand et al., “Disk Cluster Allocation Behavior in Windows NTFS,” Digital Investigation Journal,pp.S3–S11,2019.

[10] W. Lee and J. Lee, “File Allocation Characteristics in Windows FAT32 Systems,” International Journal of Computer.Applications,2018.

[11] A. Sharma and R. Kumar,“Analysis of File System Allocation and Storage Management,”IEEE International Conference on Computing Technologies, 2017.

[12] S. Patel and D. Shah,“Performance Evaluation of Modern File Systems in Storage Devices,”IEEE International Conference on Data Engineering, 2016.

[13] H. Kim et al.,“File System Fragmentation and Storage Optimization Techniques,”IEEE Storage Systems,Journal,2018.

[14] L. Chen et al.,“Efficient Disk Storage Management Using Advanced File Systems,”IEEE Transactions on Computers,2020.

[15] D. Wang and Y. Liu,“Storage Efficiency Analysis of FAT-Based File Systems,”IEEE International Conference on Big Data Storage Systems, 2021.