

SPECIFICATION

Current Rating:1A Max.
Withstand Voltage:100V AC For 1 Minute
Contact Resistance:30 Milliohms Max.
Insulation Resistance:100 Megaohms Min.
Total Mating Force:3.57 Kgf Max.
Total Umating Force:1.0 Kgf Min.
Temperature Range:-30°C~+80°C
Housing:LCP+G.F.(UL94V-0)
△ Contact:Phosphor Bronze
11071:Gold Flash Over All,Over Nickel
11073:Gold Plated 30u" On Contact Area,Gold Flash On Other Area,Over Nickel

Shell:Brass,Tin Plated
RoHS Compliant

Recommended P.C.B. Layout

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

11071

SCALE NONE

APPROVED BY

EMILY

CHECKED BY

HZF

DRAWING BY


CYP

REV.

A1

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE

X. ±0.50 X. ±.3"
.X ±0.15 .X ±.1"
.XX ±0.10 .XX ±.1"
.XXX ±0.05 .XXX ±0.5"

UNIT
mm

NO. REV.

REVISIONS

CHK

DATE

