

Warranty Instructions

I. Warranty & Usage Instructions for Three-Layer and Multi-Layer Solid Wood Composite Flooring

1. Warranty Period (Limited Structural Warranty: 10 Years)

The manufacturer warrants to the buyer that, if the flooring is used under normal residential and commercial conditions, the milling and layering of the flooring will be free from manufacturing defects throughout the product's 10-year life cycle.

2. Surface Wear Warranty (Based on Coating Type & Usage Category):

Residential Use: Under normal living conditions and with appropriate cleaning and maintenance according to the applicable coating type, the manufacturer warrants that the flooring surface will not wear through to the raw wood in any single area within 3-5 years from the date of purchase; and will not wear through in more than 20% of the installed area within 5-10 years.

Light Commercial Use: Under light commercial area conditions and with appropriate maintenance for the applicable coating, the manufacturer warrants that the flooring surface will not wear through to the raw wood in any single area within 2-3 years from the date of purchase. (Light commercial area is defined as commercial spaces in public areas with light to moderate traffic, excluding areas with frequent food or liquid spills.)

II. Warranty Coverage

1. Structural Issues: Structural damage to the flooring caused by defects in the production process or raw materials, such as delamination, separation, or breakage. Examples include cracking at the glued joints between layers in multi-layer solid wood composite flooring, or separation of the surface layer, core layer, and backing layer in three-layer solid wood composite flooring.

2. Finish Issues: Severe wear, discoloration, peeling, or flaking of the finish under normal use, affecting appearance and usability. Examples include significant finish damage due to daily foot traffic friction or noticeable large patches of finish peeling off.

3. Dimensional Stability Issues: Significant warping, cupping, buckling, or denting deformation of the flooring under normal indoor environmental conditions, rendering it unusable. For example, flooring exhibiting noticeable bending or buckling without cause under normal indoor humidity and temperature (excluding installation issues).

(Continuation of Dimensional Stability Issues Example): environments (excluding installation issues).

III. Non-Warranty Coverage

1. **Human Damage:** Damage caused by human factors such as impact from heavy objects, scratches from sharp items, unauthorized disassembly/modification, or intentional vandalism. Examples include scratches and breakage caused by forcefully scraping sharp metal objects on the floor, or structural damage resulting from self-disassembly.
2. **Improper Use:** Damage resulting from failure to follow daily cleaning and maintenance instructions as per this manual, prolonged placement of high-temperature objects on the floor, or prolonged exposure to large amounts of standing water. Examples include placing a hot pot directly on the floor or allowing bathroom water to leak and soak the floor for an extended period.
3. **Force Majeure:** Damage caused by force majeure events such as natural disasters (e.g., floods, earthquakes, fires), war, or government actions.
4. **Non-Authorized Purchase:** Products purchased through unauthorized dealers or channels are not covered by this warranty.

IV. Warranty Claim Process

1. **Identify the Problem:** If the user discovers a problem during use that may fall under warranty coverage, immediately stop any actions that could cause further damage to the flooring and preserve the scene.
2. **Contact After-Sales Service:** Please promptly call our after-sales service hotline [Specific Phone Number] or contact us via email [Email Address]. Provide proof of purchase (e.g., invoice, order screenshot), product batch number (found on packaging or the back of the flooring), a description of the problem, and clear photos of the scene.
3. **After-Sales Response:** The distributor's after-sales team will contact you within 3 working days of receiving your feedback to confirm the issue details and arrange for a professional technician to conduct an on-site inspection (you may need to wait for a period depending on the actual situation).
4. **Problem Assessment:** Upon arrival, the technician will assess the flooring issue to determine if it falls under warranty coverage. If covered, a repair or replacement plan will be developed and confirmed with you.
5. **Repair or Replacement:** Once the plan is confirmed, we will arrange repairs or replacements as soon as possible, minimizing downtime and impact on your life while ensuring quality. After completion, we will conduct a quality inspection of the repaired/replaced flooring to ensure the issue is properly resolved.

V. Usage Instructions

(A) Daily Use

1. **Moving People & Items:** After installation, it is recommended to wait 24 hours before normal foot traffic begins, allowing the flooring to fully settle and bond with the subfloor. When moving furniture or heavy objects, always lift them; dragging them across the floor surface is strictly prohibited to prevent scratching the finish. For frequently moved furniture, attach felt pads to the bottom to reduce friction.
2. **Maintain Air Circulation:** Ensure indoor air circulation by installing a fresh air system or opening windows regularly to maintain suitable indoor temperature and humidity. Avoid keeping doors and windows closed for long periods, as stagnant air can affect the floor's lifespan. Ventilate regularly even if the space is unoccupied temporarily.
3. **Water & Moisture Protection:** Solid wood composite flooring is susceptible to water damage. Prevent water splashes during daily use, especially at junctions with bathrooms, kitchens, and balconies – ensure waterproofing measures are adequate. If a small amount of water spills, wipe it up immediately with a dry cloth. In case of large-scale water exposure, contact professionals promptly to prevent warping or delamination. Always turn off water taps before traveling or leaving the home unoccupied for extended periods.
4. **Avoid Direct Sunlight:** Prolonged direct sunlight can cause fading and cracking. Install curtains, blinds, or other shading devices to regulate indoor light. Avoid direct sunlight on the floor during intense summer sun.
5. **Temperature & Humidity Control:** Avoid localized, prolonged heat exposure. Do not place high-power heaters, irons, or other high-temperature objects directly on the floor. When used over underfloor heating, strictly follow the heating system's instructions for slow heating/cooling cycles. The surface temperature of the flooring is recommended not to exceed 26° C (79° F).
6. **Humidity Control:**
Maintain indoor humidity between 40% - 65%. During dry seasons, use a humidifier to increase air humidity; during humid seasons, use an air conditioner's dehumidify function or a dehumidifier to reduce humidity.

VI. Cleaning & Maintenance

1. **Cleaning Agents (Polyurethane Finish):** For floors finished with polyurethane, regularly clean using Dulux Hardwood Floor Cleaner or Basic Coatings Squeegee Commercial Floor Cleaner. Never use liquid wax, oils, oil soaps, or petroleum-based cleaners.

Cleaning Agents (UV Oil & Hardwax Oil Finishes): For floors finished with UV-cured oil and hardwax oil.

2. **Regular Cleaning (UV Oil & Hardwax Oil):** Immediately after installation and for regular cleaning, mop using WOCA Soap Natural or WOCA Soap White (check floor item specification for Natural or White). These are concentrates mixed with water. They not only clean but also nourish and enhance protection/sealing by leaving a thin layer of coconut and soy fats. Frequent use of WOCA Soap (up to once a week) will extend the time between re-oiling and help prevent stains and water marks.

Remember: Frequent use of WOCA Soap is the most important key to maintaining UV-oiled and hardwax oil-coated floors.

3. **Cleaning Method:** Use a sponge mop (not microfiber). Use a second bucket of rinse water to remove dirt from the mop before re-dipping it in the cleaning solution. Change the water in the rinse bucket frequently.
4. **Spot Cleaning:** For convenient spot cleaning, use WOCA Soap&Spray Natural or Soap&Spray White (check floor item specification for Natural or White). These products are pre-diluted and ready to use.
5. **Stubborn Stains:** For tougher stains, use WOCA Spot Remover. If mopping or wiping doesn't remove the stain, try gently rubbing with a 3M 4100 Super Fine White Pad.
6. **Refreshing Finish:** Depending on traffic (twice to four times per year), use WOCA Oil Refresher Natural or WOCA Oil Refresher White (check floor item specification for Natural or White). This introduces a small amount of oil to refresh the surface and extend the time before re-oiling is necessary. If water doesn't bead on the floor or the floor looks worn, refreshing is needed more frequently. If the surface becomes hazy, you may be using the Refresher too often; reduce frequency and use Soap instead.
7. **Minor Scratches:** Light scratches are best repaired by hand-rubbing WOCA Master Floor Oil Natural or WOCA Master Floor Oil White, or applying Master Color Oil to the affected area using a soft cloth. If necessary, first clean the area to be repaired with WOCA Wood Cleaner. Ensure the area is dry before applying oil.
8. **Daily Cleaning:** For daily cleaning, use a clean, soft cloth or a well-wrung mop to wipe the floor and remove dust and stains. For stubborn stains, use a diluted neutral cleaner applied gently with a soft cloth, then rinse with clean water and dry thoroughly. Never use acidic, alkaline, or organic solvents (e.g., gasoline, alcohol) as they can damage the finish.
9. **Regular Vacuuming:** Vacuum the floor at least once a week, especially between floor joints, to prevent the accumulation of dust, sand, and other fine particles that can wear down the surface during daily use.
10. **Maintenance:** It is recommended to maintain the floor 2 to 4 times per year using professional floor care products like WOCA. This enhances surface shine and increases the wear resistance and gloss of the floor finish.

VII. Damage Repair:

1. **Clean Surface:** Start by cleaning dust and debris from the damaged area and its surroundings using a clean, soft cloth or broom. Ensure the repair area is clean and dry. If stains are present, gently wipe with a neutral cleaner, then rinse with clean water and dry thoroughly.
2. **Assess Damage:** If the damage is minor scratches or wear, proceed with direct repair. For deeper dents, cracks, or large areas of finish loss, more complex repair methods or professional assistance may be required.
3. **Minor Scratch Repair:** For light scratches, use a wood touch-up pen, crayon, or

repair marker matching the floor color to fill the scratch. Then, gently buff the area with a soft cloth to blend it with the surrounding finish. Alternatively, apply professional floor repair oil to the scratch and gently buff with a soft cloth, allowing the oil to penetrate and repair the scratch while nourishing the wood.

4. Deeper Scratch/Small Area Repair: For deeper scratches, lightly sand the damaged area and its surroundings with fine sandpaper to create a smooth, level surface (sand an area slightly larger than the damage). Then, based on the floor's color, select an appropriate aerosol touch-up paint. In a well-ventilated area, apply 2 to 3 even coats to the damaged area, allowing a few minutes between coats. Once the paint is dry, lightly sand again with fine sandpaper to smooth the surface. Finally, apply floor wax for protection.

5. Large Area Finish Damage Repair: For large areas of finish damage, refinishing may be necessary. First, sand the entire affected area down to the bare wood using sandpaper. Apply a primer and let it dry. Then, apply 2 to 3 coats of finish paint, lightly sanding between coats once dry. Finally, apply wax for maintenance.

6. Important Notes: When repairing solid wood composite flooring finishes, ensure you select high-quality, compatible repair materials and strictly follow the product instructions. If unsure about the repair outcome, it is recommended to hire a professional flooring repair technician.