

SPC Rigid Core Flooring — Commercial & Residential Grade

- Core structure: virgin PVC + CaCO₃ limestone rigid core (flooring) / composite core (panels)
- Total thickness: 4.0–8.0 mm (flooring) · panel thickness per line specification
- Wear layer (flooring): 0.3 / 0.5 / 0.7 mm (12 / 20 / 28 mil)
- Reaction to fire: Class Bfl-s1 (EN 13501-1) / B1 (GB 8624) — where applicable
- Formaldehyde emission: E0 / ND (EN 717-1, FloorScore scope)
- Dimensional stability: ≤ 0.10% (EN 434 / ASTM F2199)
- Locking system (flooring): Uniclic / Valinge click
- Slip resistance: R10 (DIN 51130) — flooring
- Heavy metals & phthalates: REACH / CPSIA pass (no harmful plasticizers)
- Warranty: 25-year residential / 10–15-year commercial (flooring)

Verification & status

STATUS: PENDING — final accredited certificate expected Q1 2027

Last verified: [FILL] | Issuing body: [FILL] | This is a scope document, not an issued certificate.

All values above are representative for the product line. Final specification, test reports and certificates are confirmed per SKU and purchase order. Buyers may request interim test data via sales@yenyong.com.