

Simulation of M/M/2/2+5 Queueing System

Jiaqi Yan, Ping Liu
CS555 Project
supervised by Edward Chlebus

November 22, 2015

Abstract

In this project, we simulate and analyze the M/M/2/2+5 queueing system. To generate generate packet arriving time and processing time, we use Python's built-in *random* module, which is validated carefully. Then we apply the **Welch graphical procedure** to eliminate the warm-up period in the simulation. With the stationary region, we then analyze the system's properties such as blocking probability and mean number of packet in the system. The 90% confidence interval for these properties are also given.

Contents

1	Discrete Event Simulation	3
2	Random Generator	3
2.1	Validation	3
3	Eliminate Warm-up Period	4
4	System Properties at Stationary State	4
4.1	Blocking Probability	4
4.2	Mean Spending Time	4
4.3	Mean Number of Packet	4




Figure 1: Histogram of Uniform Random Values Generated by Numpy

1 Discrete Event Simulation

We designed and implemented our own simple simulator for M/M/2/2+5 queueing system. The simulation workflow is shown in Algorithm 1.

2 Random Generator

2.1 Validation

In M/M/2/2+5 queueing system, the number of packet arriving in a fixed interval follows **Poisson Distribution** and the service time for each packet follows **Exponential Distribution**. These input data is generated by *Numpy's random* module. Before running the simulator, it is important to test the wellness of this random generator.

We evaluate Numpy's random generator in two ways. First we generate random values follows uniform distribution and then plot their histogram. As shown in Figure 1, the number of random values falling into each interval is close to each other. This means that the generated values are very close to uniformly distributed. Besides, we compare the normalized histogram to the 'best fit' curve of both uniform distribution and normal distribution in Figure 1 and 2. From both figures we can say that the random generator generated random values of user-specified distribution.

To generate different random value sequences, we feed the random generator a seed, which is the integral value of system current time. That is the number of




Figure 2: Comparison to Best Fit Curve for Normal Distribution

seconds since **Unix Epoch**. We generated two sequences of 1000000 numbers each and use **t-test** to test statistically are they significantly different from each other.

3 Eliminate Warm-up Period

4 System Properties at Stationary State

4.1 Blocking Probability

4.2 Mean Spending Time

4.3 Mean Number of Packet

Algorithm 1 Core of Discrete Event Simulation

```
1: function SIMULATION_CORE(arrive_time_seq, serve_time_seq)
2:   let arrive_time_seq denote the arriving time of each packet
3:   let serve_time_seq denote the service time of each packet
4:   let N denote the number of total packets
5:   while pkt_served + pkt_dropped < N do
6:     if pkt_seen < N then                                ▷ Insert new arrival event to event list
7:       ts ← arrive_time_seq[pkt_seen]
8:       Create new arrival event evt with time stamp ts and id pkt_seen
9:       Insert evt to event_list
10:    end if
11:    Sort event_list based on events' time stamp
12:    Pop up the next event evtx we need to handle in event_list
13:    clock ← evtx.time_stamp
14:    if evtx is departure event then
15:      if queue buffer is empty then
16:        Set the status of the server evtx is leaving to idle
17:      else
18:        – – waiting
19:      end if
20:      ++ pkt_served
21:      evtx.exit_time ← clock
22:      spending_time ← evtx.exit_time – evtx.enter_time
23:      Record the spending time of packet of event evtx
24:    end if
25:    if evtx is arrival event then
26:      if queue buffer is full then
27:        ++ pkt_dropped
28:      else
29:        if There is available server then
30:          id ← evtx.pkt_id
31:          ts ← clock + serve_time_seq[id]
32:          Choose an available server s
33:          Mark s as busy
34:        else
35:          (ts, s) ← SCHEDULE_DEPARTURE( )
36:          ++ waiting
37:        end if
38:        Create new departure event evt with time stamp ts
39:        evt.enter_time ← clock
40:        evt.depart_srv ← s
41:        Insert evt to event_list
42:      end if
43:    end if
44:  end while
45: end function
```
