

**Quick Links for Python**[Recent Articles](#)[MCQ / Quizzes](#)[Practice Problems](#)**Basics**[Introduction](#)[New Generation Language](#)[Keywords, Set 1 Set 2](#)[Explore More...](#)**Variables**[Variables, Expressions & Functions](#)[Global and Local Variables](#)[Type Conversion](#)[Explore More...](#)**Operators**[Increment and Decrement Operator](#)[Teranry Operator & Divison Operator](#)[Logical and Bitwise Not Operators on Boolean](#)[Any & ALL](#)

Operator Functions Set 1 & Set 2
Data Types
Introduction
Arrays Set 1, Set 2
String Methods Set 1, Set 2, Set 3
String Template Class & String Formatting using %
List Methods Set 1, Set 2, Set 3
Tuples & Sets
Dictionary Methods Set 1, Set 2
ChainMap
Explore More...
Control Flow
Loops and Control Statements
Counters & Accessing Counters
Iterators & Iterator Functions Set 1, Set 2
Generators
Explore More...
Functions
Function Decorators
Returning Multiple Values
Yield instead of Return
Python Closures & Coroutine
Explore More...
Modules
Introduction



Numeric Functions & Logarithmic and Power functions	
Calender Functions Set 1, Set 2	
Complex Numbers Introduction & Important functions	
Explore More...	
Object Oriented Concepts	
Class, Object and Members	
Data Hiding and Object Printing	
Inheritance, Subclass and super	
Class method vs static method & Class or Static Variables	
Explore More...	
Exception Handling	
Exception Handling	
User-Defined Exceptions	
Built-in Exceptions	
Libraries and Functions	
Timeit	
Numpy Set 1, Set 2	
Get and Post	
import module & reload module	
Collection Modules Deque, Namedtuple & Heap	
Explore More...	
Machine Learning with Python	
Classifying data using Support Vector Machines(SVMs) in Python	



K means Clustering
How to get synonyms/antonyms from NLTK WordNet in Python?
Explore More...
Misc
Sql using Python & MongoDB and Python
Json formatting & Python Virtual environment
Metaprogramming with Metaclasses in Python
Python Input Methods for Competitive Programming
Explore More...
Applications and Projects
Creating a proxy webserver Set 1, Set 2
Send Message to FB friend
Twitter Sentiment Analysis & Whatsapp using Python
Desktop Notifier & Junk File Organizer
Explore More...

getpass() and getuser() in Python (Password without echo)

getpass() prompts the user for a password without echoing. The getpass module provides a secure way to handle the password prompts where programs interact with the users via the terminal.

This module provides two functions :

1. getpass()

```
getpass.getpass(prompt='Password: ', stream=None)
```



The `getpass()` function is used to prompt to users using the string prompt and reads the input from the user as Password. The input read defaults to "Password: " is returned to the caller as a string.

Let's walk through some examples to understand its implementation.

Example 1 : No Prompt provided by the caller

```
# A simple Python program to demonstrate
# getpass.getpass() to read password
import getpass

try:
    p = getpass.getpass()
except Exception as error:
    print('ERROR', error)
else:
    print('Password entered:', p)
```

[Run on IDE](#)

Here, no prompt is provided by the caller. So, it is set to the default prompt "Password".

Output :

```
$ python3 getpass_example1.py

Password:
('Password entered:', 'aditi')
```

Example 2 : Security Question

There are certain programs that ask for security questions rather than asking for passwords for better security. Here, the prompt can be changed to any value.

```
# A simple Python program to demonstrate
# getpass.getpass() to read security question
import getpass

p = getpass.getpass(prompt='Your favorite flower? ')

if p.lower() == 'rose':
    print('Welcome..!!!')
else:
    print('The answer entered by you is incorrect..!!!')
```

[Run on IDE](#)

Output :

```
$ python3 getpass_example2.py

Your favorite flower?
Welcome..!!!

$ python3 getpass_example2.py
```



```
Your favorite flower?  
The answer entered by you is incorrect..!!!
```

2. `getuser()`

`getpass.getuser()`

The `getuser()` function displays the login name of the user. This function checks the environment variables `LOGNAME`, `USER`, `LNAME` and `USERNAME`, in order, and returns the value of the first non-empty string.

Example 3 :

```
# Python program to demonstrate working of  
# getpass.getuser()  
import getpass  
  
user = getpass.getuser()  
  
while True:  
    pwd = getpass.getpass("User Name : %s" % user)  
  
    if pwd == 'abcd':  
        print "Welcome!!!"  
        break  
    else:  
        print "The password you entered is incorrect."
```

[Run on IDE](#)

Output :

```
$ python3 getpass_example3.py  
  
User Name : bot  
Welcome!!!  
  
$ python3 getpass_example3.py  
  
User Name : bot  
The password you entered is incorrect.
```

This article is contributed by **Aditi Gupta**. If you like GeeksforGeeks and would like to contribute, you can also write an article using contribute.geeksforgeeks.org or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



GATE CS Corner Company Wise Coding Practice

Python

Recommended Posts:

Reading and Generating QR codes in Python using QRtools

fnmatch – Unix filename pattern matching in Python

Python Virtual Environment | Introduction

Bisect Algorithm Functions in Python

Timeit in Python with Examples

(Login to Rate and Mark)

2.5

Average Difficulty : **2.5/5.0**
Based on **2** vote(s)



Add to TODO List



Mark as DONE

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments

Share this post!

@geeksforgeeks, Some rights reserved

Contact Us!

About Us!

Careers!

Privacy Policy

