

K2 Hello World

Start K2

- Copy the contents of the CD onto your local disk.
- From the CD/USB –
 - `cd binary`
 - `java -jar org.sakaiproject.kernel.app-0.1-SNAPSHOT.jar -f -`

Browse to the Console

- <http://localhost:8080>
- navigate to the console
- login as admin/admin

Launchpad

o framework that uses a Java Content Repository, such as Apache Jackrabbit. It uses either scripts or Java servlets, selected based on simple name conventions. The embedded Apache Felix OSGi framework and console provide a dynamic environment where components can be loaded, unloaded and reconfigured at runtime.

onfiguration, providing an embedded JCR content repository and web site for documentation and examples. The Launchpad makes it easy to get started with Sling.

Apache Felix Web Management Console Bundles



Bundle information: 86 bundles in total - all 86 bundles active.

<div> <div></div> <div>Browse...</div> <div>- Start</div> <div>- Start Level 20</div> <div>Install or Update</div> <div>Refresh Packages</div> </div>					
Id	Name	Version	Symbolic Name	Status	Actions
22	activemq-core	5.2.0	org.apache.activemq.activemq-core	Active	
51	Apache Commons IO Bundle	1.4	org.apache.commons.io	Active	
82	Apache Felix Bundle Repository	1.4.0	org.apache.felix.bundlerepository	Active	
32	Apache Felix Configuration Admin Service	1.0.10	org.apache.felix.configadmin	Active	
35	Apache Felix Declarative Services	1.0.8	org.apache.felix.scr	Active	
33	Apache Felix EventAdmin	1.0.0	org.apache.felix.eventadmin	Active	
34	Apache Felix Metatype Service	1.0.3.SNAPSHOT	org.apache.felix.org.apache.felix.metatype	Active	
83	Apache Felix Web Management Console	1.2.10	org.apache.felix.webconsole	Active	
3	Apache Sling API	2.0.5.SNAPSHOT	org.apache.sling.api	Active	
4	Apache Sling Bundle Repository	2.0.4-incubator	org.apache.sling.bundlerepository.impl	Active	

Requests

Bundle Resource Provider	Bundles	Components	Configuration	Configuration Status	Deployment Packages	Event Admin	Licenses	Log Service
MIME Types	OSGi Repository	Recent requests	Script Engines	System Information	Threads			

Recent Requests ([Clear](#))

[Request 0 \(latest\)](#) [Request 1](#) [Request 2](#) [Request 3](#) [Request 4](#) [Request 5](#) [Request 6](#) [Request 7](#) [Request 8](#) [Request 9](#) [Request 10](#) **[Request 11](#)** [Request 12](#) [Request 13](#) [Request 14](#) [Request 15](#) [Request 16](#) [Request 17](#) [Request 18](#) [Request 19](#)

Request 11 - RequestProgressTracker Info

```
0 (2009-07-07 11:38:56) Starting Request Processing
0 (2009-07-07 11:38:56) Method=POST, PathInfo=/test/nodepath/node1246981136
0 (2009-07-07 11:38:56) Starting ResourceResolution
3 (2009-07-07 11:38:56) URI=/test/nodepath/node1246981136 resolves to Resource=NonExistingResource, path=/test/nodepath/node1246981136, elapsed = 3ms
3 (2009-07-07 11:38:56) Resource Path Info: SlingRequestPathInfo: path='/test/nodepath/node1246981136', selectorString='null', extension='null', suffix='null'
3 (2009-07-07 11:38:56) Starting ServletResolution
3 (2009-07-07 11:38:56) Starting resolverServlet(NonExistingResource, path=/test/nodepath/node1246981136)
4 (2009-07-07 11:38:56) Using Servlet org.apache.sling.servlets.post.impl.SlingPostServlet, elapsed = 1ms
4 (2009-07-07 11:38:56) URI=/test/nodepath/node1246981136 handled by Servlet org.apache.sling.servlets.post.impl.SlingPostServlet, elapsed = 1ms
4 (2009-07-07 11:38:56) Applying request filters
4 (2009-07-07 11:38:56) Calling filter: org.apache.sling.engine.impl.debug.RequestProgressTrackerLogFilter
4 (2009-07-07 11:38:56) Starting org.apache.sling.servlets.post.impl.SlingPostServlet#0
9 (2009-07-07 11:38:56) org.apache.sling.servlets.post.impl.SlingPostServlet#0, elapsed = 5ms
9 (2009-07-07 11:38:56) Request Processing ends, elapsed = 9ms
```

more Requests




Recent Requests (Clear)

[Request 0 \(latest\)](#) [Request 1](#) [Request 2](#) [Request 3](#) [Request 4](#) [Request 5](#) [Request 6](#) [Request 7](#) [Request 8](#) [Request 9](#) **[Request 10](#)** [Request 11](#) [Request 12](#) [Request 13](#) [Request 14](#) [Request 15](#) [Request 16](#) [Request 17](#) [Request 18](#) [Request 19](#)


Request 10 - RequestProgressTracker Info

```
0 (2009-07-07 11:38:56) Starting Request Processing
0 (2009-07-07 11:38:56) Method=GET, PathInfo=/test/nodepath/node1246981136.json
0 (2009-07-07 11:38:56) Starting ResourceResolution
1 (2009-07-07 11:38:56) URI=/test/nodepath/node1246981136.json resolves to Resource=JcrNodeResource, type=nt:unstructured, path=/test/nodepath/node1246981136, el
1 (2009-07-07 11:38:56) Resource Path Info: SlingRequestPathInfo: path='/test/nodepath/node1246981136', selectorString='null', extension='json', suffix='null'
1 (2009-07-07 11:38:56) Starting ServletResolution
1 (2009-07-07 11:38:56) Starting resolverServlet(JcrNodeResource, type=nt:unstructured, path=/test/nodepath/node1246981136)
1 (2009-07-07 11:38:56) Using Servlet org.apache.sling.servlets.get.DefaultGetServlet, elapsed = 0ms
1 (2009-07-07 11:38:56) URI=/test/nodepath/node1246981136.json handled by Servlet=org.apache.sling.servlets.get.DefaultGetServlet, elapsed = 0ms
1 (2009-07-07 11:38:56) Applying request filters
1 (2009-07-07 11:38:56) Calling filter: org.apache.sling.engine.impl.debug.RequestProgressTrackerLogFilter
1 (2009-07-07 11:38:56) Starting org.apache.sling.servlets.get.DefaultGetServlet#0
1 (2009-07-07 11:38:56) Using org.apache.sling.servlets.get.impl.helpers.JsonRendererServlet to render for extension=json
2 (2009-07-07 11:38:56) org.apache.sling.servlets.get.DefaultGetServlet#0, elapsed = 1ms
2 (2009-07-07 11:38:56) Request Processing ends, elapsed = 2ms
```


Mount K2 Filesystem



Standard Apps



```
ace.html.esp
1  <%
2    var privilegesInfo = new Packages.org.apache.sling.jcr.jackrabbit.accessmanager.PrivilegesInfo();
3    if (!privilegesInfo.canReadAccessControl(currentNode)) {
4      //no rights to view the access control of the node, so just return a 404 status
5      response.sendError(404);
6    } else {
7      var principalId = request.getParameter("pid");
8      var isUser = false;
9      var isValidPrincipal = false;
10     if (principalId != null && principalId != "") {
11       var userManager = Packages.org.apache.sling.jcr.base.util.AccessControlUtil.getUserManager(currentNode.s
ession);
12       if (userManager != null) {
13         var authorizable = userManager.getAuthorizable(principalId);
14         if (authorizable != null) {
15           isUser = !authorizable.isGroup();
16           isValidPrincipal = true;
17         } else {
18           //no user/group matches the supplied principal id
19         }
20       }
21     }
22   }
23   <%>
24   <!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">
25   <html xml:lang="en" lang="en"
26     xmlns="http://www.w3.org/1999/xhtml"
27   >
28   <head>
29     <meta http-equiv="content-type" content="text/html; charset=utf-8" />
30     <title>Access Control Entry : <%=currentNode.name%></title>
31
32     <style TYPE="text/css">
33     <!--
34       ul.error-msg {
35         list-style-position: inside;
36         list-style-type: none;
37       }
38     -->
```


Hello World

- Create a Node
 - `curl -Fsling:resourceType=sakai/hello http://admin:admin@localhost:8080/helloworld`
- Browse to the Node http://admin:admin@localhost:8080/helloworld.json

Bind a Servlet

- `mkdir -p /apps/sakai/hello`
- `vi /apps/sakai/hello/html.jsp`
- Browse to <http://localhost:8080/helloworld>
-

Do something more

- Get the current resource
- <http://cwiki.apache.org/SLING/scripting-variables.html>
- currentNode == the Current JCR node eg /helloworld
- edit /apps/sakai/hello/html.jsp