

Approximating Combinatorial Contracts with Arbitrary Costs

Xiaotie Deng^{1,2*} Hanyu Li^{2†} Chenghua Liu^{3‡}

¹Department of Computer Science, City University of Hong Kong

²CFCS, School of Computer Science, Peking University

³Institute of Software, Chinese Academy of Sciences

Abstract

We study single-agent combinatorial contracts under linear payments. Under a reward share $\alpha \in [0, 1]$, an agent chooses a subset S of n hidden actions, generating reward $f(S)$ at cost $c(S)$, to maximize $\alpha f(S) - c(S)$, while the principal receives $(1 - \alpha)f(S)$. For nonnegative additive rewards and monotone supermodular costs, Dütting et al. (SODA 2026) proved an exponential supply-query lower bound for exact optimization and left open whether a representation-independent approximation is possible. We resolve this question in a stronger form, removing all structural assumptions on the cost function: for nonnegative additive rewards, arbitrary normalized nonnegative set costs, and every $\varepsilon \in (0, 1)$, we give a deterministic $(1 - \varepsilon)$ -approximation using $O(n \log(n + 1)/\varepsilon)$ supply queries, with query complexity independent of numerical bit lengths and breakpoint separation. More generally, the same guarantee and asymptotic query complexity hold for normalized monotone subadditive rewards and arbitrary normalized nonnegative costs under exact best-response and value-query access. The key idea is a cost-independent, reward-side scale certificate. The algorithm tries all singleton rewards as candidate anchors; one of them brackets the optimal retained share within a factor n^2 . Geometric search and monotonicity of the induced response reward then yield the approximation without enumerating best-response breakpoints.

1 Introduction

Contract design governs how one party incentivizes another to act on its behalf. A central difficulty is *hidden action*: the principal observes the outcome of a delegated task, but not the costly actions taken by the agent to produce it. The principal must therefore base payment on the observable outcome while anticipating how the payment changes the agent’s behavior. This classical economic problem has recently become a subject of growing interest in theoretical computer science and algorithmic game theory [7].

Many delegated tasks involve several actions that may be taken together, rather than a single choice between effort and no effort. The combinatorial-action model introduced by Dütting, Ezra, Feldman, and Kesselheim [3] captures this setting. A project has n available actions,

*csdeng@cityu.edu.hk

†lhydave@pku.edu.cn

‡liuch.russell@gmail.com

indexed by $[n] = \{1, \dots, n\}$, and the agent may take any subset $S \subseteq [n]$. The set function $f(S)$ is the principal's expected gross reward when S is taken, while $c(S)$ is the agent's cost. In the standard binary-outcome interpretation, the project either succeeds or fails and, after normalizing the reward from success to one, $f(S)$ is its success probability. The set functions allow actions to be substitutes or complements. They also create a computational challenge: there are 2^n possible action sets.

Because the principal cannot observe S , payment cannot depend directly on the chosen actions. A linear contract is specified by a share $\alpha \in [0, 1]$: the agent receives an α fraction of the generated reward. Facing this contract, the agent chooses a *best response*

$$S_\alpha \in \arg \max_{S \subseteq [n]} \{\alpha f(S) - c(S)\}.$$

Thus the response S_α is simply the action set that maximizes the agent's expected payment minus cost. Ties are resolved in the principal's favor, as formalized in Section 3. Anticipating the response, the principal receives

$$P(\alpha) = (1 - \alpha)f(S_\alpha)$$

and seeks a contract maximizing this quantity. We denote the optimal principal utility by $\text{OPT} = P^* = \max_{\alpha \in [0, 1]} P(\alpha)$.

An explicit description of a general set function may itself contain exponentially many numbers. We therefore work with oracle access. A value query evaluates $f(S)$ or $c(S)$, while a best-response query returns S_α for a specified contract. For additive rewards, let v_i be the reward of action i , so $f(S) = \sum_{i \in S} v_i$. Best responses can then be implemented by a standard supply query to the cost function [6]: given an item-price vector p , it returns a set maximizing

$$\sum_{i \in S} p_i - c(S).$$

Setting $p_i = \alpha v_i$ yields S_α . Supply access thus lets the algorithm observe the economically relevant response without requiring an explicit representation of the cost function.

As α varies, the agent's response changes only at *breakpoints*. General procedures can enumerate them with oracle access in time polynomial in their number [2, 5]. That number can nevertheless be exponential [3], and the relevant breakpoints can be arbitrarily close [6]. Exact optimization asks for the best breakpoint. Approximation poses a different question: can the principal obtain nearly optimal utility without identifying the exact response change that attains the optimum? We call an FPTAS *representation independent* if, for every $\varepsilon \in (0, 1)$, it makes a number of oracle calls polynomial in n and $1/\varepsilon$, independent of numerical bit lengths, scales, and breakpoint separation. This is an exact-real query model: oracle inputs and answers are exact real numbers, and complexity counts oracle calls rather than bit operations.

Dütting, Feldman, Gal-Tzur, and Rubinstein [6] studied the query and communication complexity of this problem across several combinations of submodular and supermodular rewards and costs. Most relevant here, they consider additive rewards and monotone supermodular costs. Additivity means that every action has an independent reward v_i , whereas supermodularity means that marginal costs increase as more actions are taken. They prove that any algorithm computing the exact optimal contract in this setting requires $2^{\Omega(n)}$ supply queries.

Their tightness discussion leaves a sharp approximation question. A weakly polynomial FPTAS, whose complexity depends on the numerical bit lengths, was known [3]. Removing

this dependence, the representation-independent FPTAS for additive costs in [4] extends to monotone subadditive costs [6, Appendix B]. The latter work explicitly left open whether instances with supermodular costs, even with additive rewards, admit any representation-independent approximation, even under best-response access.

The known approximation method [4, 6] has an appealingly simple form: compute welfare, guess one action from the optimal response, and search a geometric grid of contracts. Its scale certificate, however, is a singleton *cost*, and the argument relating that cost to the cost of the entire response relies on additive or subadditive costs. Supermodular costs reverse the relevant inequality, while arbitrary costs provide no such comparison. This is the precise obstruction behind the open problem.

We show that the exponential barrier is specific to exact optimization. For the class in the lower bound of [6], exact optimization requires $2^{\Omega(n)}$ supply queries, whereas a $(1 - \varepsilon)$ -approximation requires only $O(n \log(n + 1)/\varepsilon)$ such queries. In fact, the approximation does not need supermodularity, monotonicity, or any other structure on the cost function.

Theorem 1 (Supply-oracle resolution). *Let $f(S) = \sum_{i \in S} v_i$ be additive with $v_i \geq 0$, and let $c(\emptyset) = 0$ and $c(S) \geq 0$ for every $S \subseteq [n]$. For every $\varepsilon \in (0, 1)$, a deterministic algorithm returns a contract with principal utility at least $(1 - \varepsilon) \text{OPT}$ using*

$$O\left(\frac{n \log(n + 1)}{\varepsilon}\right)$$

standard supply queries to c , $O(n)$ reward-value queries, and one cost-value query. The bound is independent of numerical values and breakpoint separation.

This theorem directly resolves the open problem in [6]. Its proof reveals that the relevant structure lies on the reward side. A set function is normalized if it is zero on the empty set. Recall that f is subadditive if $f(S \cup T) \leq f(S) + f(T)$ for every $S, T \subseteq [n]$. The supply-oracle result is a special case of the following statement.

Theorem 2 (General reward theorem). *Let $f : 2^{[n]} \rightarrow \mathbb{R}_{\geq 0}$ be normalized, monotone, and subadditive, and let $c(\emptyset) = 0$ and $c(S) \geq 0$ for every $S \subseteq [n]$. For every $\varepsilon \in (0, 1)$, there is a deterministic algorithm that returns a contract whose principal utility is at least $(1 - \varepsilon) \text{OPT}$. It uses*

$$O\left(\frac{n \log(n + 1)}{\varepsilon}\right)$$

exact best-response and value queries. More precisely, these are reward-value queries; one additional cost-value query is used to evaluate welfare. The bound is independent of numerical values and breakpoint separations.

Additivity is needed only to implement a best-response query as a standard supply query to the cost function. Combining Theorem 1 with the exact lower bound gives the following separation.

Corollary 3 (Exact–approximate separation). *In the exact-real supply-oracle model, combinatorial contracts with additive rewards and monotone supermodular costs exhibit an exponential separation between exact and approximate query complexity: exact optimization requires $2^{\Omega(n)}$ supply queries in the worst case, whereas a $(1 - \varepsilon)$ -approximation uses $O(n \log(n + 1)/\varepsilon)$ supply queries.*

Our proof retains the simple welfare–guess–search template, but changes what fixes the scale. Instead of using a singleton cost, we anchor the search by a singleton *reward*. This makes the argument independent of the cost structure.

In the nontrivial case $\text{OPT} > 0$, let α^* be an optimal contract, let S^* be its induced response, and let $\delta^* = 1 - \alpha^*$ be the principal’s optimal retained share. Our analysis combines two structural observations. First, a welfare–profit comparison relates the maximum welfare, or total surplus, to the principal’s optimal utility:

$$\text{OPT} \leq W \leq n \text{OPT}, \quad W = \max_{S \subseteq [n]} \{f(S) - c(S)\}.$$

Second, if j^* is a largest-singleton-reward action in S^* , monotonicity and subadditivity give

$$f(\{j^*\}) \leq f(S^*) \leq n f(\{j^*\}).$$

Since $\text{OPT} = \delta^* f(S^*)$, the two observations yield

$$\frac{W}{n^2 f(\{j^*\})} \leq \delta^* \leq \min \left\{ 1, \frac{W}{f(\{j^*\})} \right\}. \quad (1)$$

The algorithm tries each of the n singleton rewards as the unknown $f(\{j^*\})$. One guess therefore produces a multiplicative interval of width at most n^2 containing δ^* . A geometric grid covers that interval with $O(\log(n+1)/\varepsilon)$ contracts. Monotonicity of the reward induced by the agent’s response then shows that one grid point gives a $(1 - \varepsilon)$ -approximation. In contrast to exact optimization, the algorithm never enumerates response breakpoints, searches over the numerical range of costs or rewards, or separates cases according to the cost class. The lower bound hides the identity of the best breakpoint; the approximation needs only its multiplicative scale.

As follow-up to this open-problem resolution, we clarify why approximation escapes the exact lower bound and where this advantage ends. On the equal-revenue family, ordinary approximation needs only the multiplicative scale of the optimal breakpoint, whereas relative error $\gamma_n = \Theta(2^{-n})$ forces identification of its hidden identity and restores exponential query complexity. Separately, we show robustness to additive best-response error τ , with guarantee $(1 - \varepsilon) \text{OPT} - 3\tau/\varepsilon$, and establish tightness of the scale certificate.

This paper is organized as follows. Section 2 reviews related work, Section 3 fixes the oracle model, and Section 4 develops the reward-anchored scale certificate and the resulting FPTAS. Section 5 presents the follow-up results on robustness, high-accuracy query complexity, and tightness; their proofs appear in the appendices. Section 6 concludes with a discussion of the remaining boundary.

2 Related work

The original work on the combinatorial-action model [3] gave an exact algorithm for gross-substitutes rewards, proved NP-hardness for submodular rewards, and gave a weakly polynomial FPTAS for general monotone rewards and costs with best-response access. Ezra, Feldman, and Schlesinger [8] strengthened the computational hardness: with submodular rewards and additive costs, no polynomial-time value-query algorithm obtains a constant-factor approximation unless $\text{P} = \text{NP}$. Complementing these hardness results, breakpoint-enumeration algorithms run in

time polynomial in the number of breakpoints and give exact tractability for supermodular rewards and submodular costs [2, 5].

Dütting, Ezra, Feldman, and Kesselheim [4] subsequently gave a representation-independent FPTAS for general monotone rewards and additive costs; its welfare–profit comparison, welfare query, item guess, and geometric search motivate part of our analysis. Dütting, Feldman, Gal-Tzur, and Rubinstein [6] observed that this approach extends to monotone subadditive costs and established the exact supply-query lower bound for supermodular costs. Our result retains the representation-independent query bound while removing every structural assumption on the cost function.

Recent work studies exact optimization for special reward and cost classes [10], demand-type representations [1], and inapproximability for budgeted variants [9]. None of these results gives the subadditive-reward, arbitrary-cost oracle guarantee proved here.

3 Model, objective, and oracle access

There are n hidden actions, and the agent may take any set $S \subseteq [n]$. Taking S creates expected gross reward $f(S)$ for the principal and cost $c(S)$ for the agent. The principal cannot pay for the unobserved actions directly; it can only specify how the observable reward will be divided.

Contract, response, and objective. The principal first chooses a linear contract $\alpha \in [0, 1]$, promising the agent an α share of the generated reward. The agent’s utility from S is therefore $\alpha f(S) - c(S)$, so the contract induces the best response

$$S_\alpha \in \arg \max_{S \subseteq [n]} \{\alpha f(S) - c(S)\}.$$

Ties are broken toward larger $f(S)$, as preferred by the principal. The principal keeps the remaining share $1 - \alpha$; its utility and optimum are

$$P(\alpha) = (1 - \alpha)f(S_\alpha), \quad P^* = \text{OPT} = \max_{\alpha \in [0, 1]} P(\alpha).$$

Given an accuracy parameter $\varepsilon \in (0, 1)$, our algorithm must return a contract $\hat{\alpha}$ with $P(\hat{\alpha}) \geq (1 - \varepsilon)P^*$. The output is the contract parameter; the agent subsequently selects $S_{\hat{\alpha}}$.

For our main result, the reward $f : 2^{[n]} \rightarrow \mathbb{R}_{\geq 0}$ is normalized, monotone, and subadditive: $f(\emptyset) = 0$, adding actions cannot decrease reward, and $f(S \cup T) \leq f(S) + f(T)$. The cost $c : 2^{[n]} \rightarrow \mathbb{R}_{\geq 0}$ is arbitrary except that $c(\emptyset) = 0$. The maximum total surplus is

$$W = \max_{S \subseteq [n]} \{f(S) - c(S)\}$$

and serves only as a scale benchmark; the principal’s objective remains $P(\alpha)$. Since the agent maximizes $f(S) - c(S)$ at $\alpha = 1$, one best-response query computes W .

Because f and c may have exponential-size descriptions, the algorithm uses exact queries: a best-response query at α returns S_α , while value queries return $f(S)$ or $c(S)$. Complexity counts oracle calls, not numerical bit lengths.

For additive rewards, write $f(S) = \sum_{i \in S} v_i$, where $v_i = f(\{i\})$. A best-response query at $\alpha > 0$ is the standard supply query to c at prices $p_i = \alpha v_i$:

$$S \in \arg \max_T \left\{ \sum_{i \in T} p_i - c(T) \right\},$$

The standard larger-cost tie-breaking agrees with principal-favoring tie-breaking because tied sets satisfy $c(S) - c(T) = \alpha(f(S) - f(T))$.

4 Reward-anchored geometric search

The algorithm searches for the scale of the principal’s optimal retained share. A contract whose retained share lies just below the optimal one is approximately optimal because the reward of a best response grows with the agent’s share. The main difficulty is to locate this scale without numerical or structural assumptions on costs. We first formalize the approximation target, then derive a cost-independent welfare benchmark and a reward-side scale certificate, and finally turn the certificate into a geometric search.

4.1 From approximation to scale localization

It is useful to parameterize a contract by

$$\delta = 1 - \alpha,$$

the fraction of generated reward retained by the principal. Fix an optimal contract–response pair (α^*, S^*) and write $\delta^* = 1 - \alpha^*$, so that $P^* = \delta^* f(S^*)$.

The starting point of the known search framework is response-reward monotonicity.

Lemma 4 (Response-reward monotonicity [3, 4, 6]). *If $0 \leq \alpha \leq \alpha' \leq 1$, then $f(S_\alpha) \leq f(S_{\alpha'})$.*

The response sets themselves need not be nested. The intuition is that a larger agent share places greater weight on generated reward, so the reward of a utility-maximizing response cannot decrease. Formally, the statement follows immediately by comparing the two best-response inequalities; we use it as a standard fact from the earlier framework.

This monotonicity identifies exactly what the search must find. If a query uses a retained share satisfying

$$(1 - \varepsilon)\delta^* \leq \delta \leq \delta^*, \tag{2}$$

then its agent share $\alpha = 1 - \delta$ is at least α^* . Hence $f(S_\alpha) \geq f(S^*)$, and its principal utility satisfies

$$P(\alpha) = \delta f(S_\alpha) \geq (1 - \varepsilon)\delta^* f(S^*) = (1 - \varepsilon)P^*.$$

Thus approximation reduces to locating the multiplicative scale of the unknown δ^* ; the identity of the exact optimal breakpoint is not needed.

A uniform additive grid is insufficient because δ^* has no inverse-polynomial lower bound. A geometric grid avoids dependence on numerical magnitudes, provided it starts from a polynomial-width multiplicative interval containing δ^* . Indeed, if $b/R \leq \delta^* \leq b$ for $R = \text{poly}(n)$, then the points $b(1 - \varepsilon)^k$ contain one satisfying (2) after $O(\log R/\varepsilon)$ steps. This is the geometric-search step used in prior work [4, 6]; here we invoke it rather than reprove it as a separate abstract lemma.

Earlier algorithms obtain the starting interval by guessing the cost of an action in S^* . Additive or subadditive costs then relate that singleton cost to $c(S^*)$ [4, 6]. With arbitrary set costs, singleton costs provide no information about the cost of the whole response. Our task is therefore to construct an enumerable anchor for δ^* using rewards instead.

4.2 The reward-anchored scale certificate

Recall that

$$W = \max_{S \subseteq [n]} \{f(S) - c(S)\}.$$

Equivalently, W is the agent's maximum utility at $\alpha = 1$. The lower comparison $P^* \leq W$ is immediate: the agent can always choose the empty set, so an induced response has nonnegative agent utility, and its welfare is at least the principal's utility. The substantive direction is the following upper bound. Its proof views the agent's maximum utility as an upper envelope of lines. As the offered share increases, we charge welfare growth when a new action first appears on that envelope. At most n actions can appear for the first time, and each charge is bounded by the principal's optimal utility.

Lemma 5. *For normalized monotone subadditive rewards and arbitrary normalized nonnegative costs,*

$$P^* \leq W \leq nP^*.$$

Proof. Let (α^*, S^*) be optimal. Since the empty set is available, $c(S^*) \leq \alpha^* f(S^*)$, and hence

$$P^* = (1 - \alpha^*)f(S^*) \leq f(S^*) - c(S^*) \leq W.$$

If $W = 0$, the claim is immediate. Assume henceforth that $W > 0$. Let $g(\alpha)$ denote the agent's maximum utility under contract α . As a function of the offered share, it is the convex, piecewise-linear upper envelope

$$g(\alpha) = \max_S \{\alpha f(S) - c(S)\}.$$

Because $\emptyset$ is available and costs are nonnegative, $g(0) = 0$; also $g(1) = W$. Let

$$0 = a_0 < a_1 < \dots < a_k < a_{k+1} = 1$$

be the endpoints of its positive-length linear pieces, and let S_t be an active response on $[a_t, a_{t+1})$. Choose the representatives at endpoints consistently with principal-favoring tie-breaking. The slopes $f(S_t)$ are nondecreasing, and integration gives

$$W = g(1) - g(0) = \sum_{t=0}^k (a_{t+1} - a_t) f(S_t). \quad (3)$$

We now expose actions only when they first occur on the response curve. Let ℓ_1 be the first index with $S_{\ell_1} \neq \emptyset$. Having chosen ℓ_r , let the cumulative set of actions seen so far be

$$T_r = \bigcup_{t=0}^{\ell_r} S_t$$

and let ℓ_{r+1} be the first index larger than ℓ_r for which $S_{\ell_{r+1}} \not\subseteq T_r$. If this process produces d epochs, set $\ell_{d+1} = k+1$ and $T_0 = \emptyset$. Every epoch introduces a new action, so $d \leq n$. Moreover, for $\ell_r \leq t < \ell_{r+1}$ we have $S_t \subseteq T_r$.

Let $B_r = T_r \setminus T_{r-1}$ be the block of newly appearing actions. Monotonicity and subadditivity imply

$$f(S_t) \leq f(T_r) \leq \sum_{j=1}^r f(B_j) \quad (\ell_r \leq t < \ell_{r+1}).$$

Thus $[a_{\ell_r}, a_{\ell_{r+1}})$ is an epoch during which every response uses only $T_r = B_1 \dot{\cup} \dots \dot{\cup} B_r$. Responses before the first epoch are empty. Partitioning (3) into these epochs, applying the preceding inequalities, and exchanging sums gives

$$\begin{aligned} W &\leq \sum_{r=1}^d (a_{\ell_{r+1}} - a_{\ell_r}) \sum_{j=1}^r f(B_j) \\ &= \sum_{j=1}^d (1 - a_{\ell_j}) f(B_j). \end{aligned}$$

No intermediate response introduces a new action. Hence every action in B_j first appears in S_{ℓ_j} , so $B_j \subseteq S_{\ell_j}$. Monotonicity therefore yields

$$(1 - a_{\ell_j}) f(B_j) \leq (1 - a_{\ell_j}) f(S_{\ell_j}) \leq P^*.$$

Summing over $d \leq n$ blocks proves the claim. $\square$

The upper-bound proof adapts the response-curve argument of [4]. The extension important here is that it uses no additivity or other structure of the cost function.

The welfare benchmark controls P^* without revealing the unknown response S^* . To recover the missing reward scale, choose an action of S^* with largest singleton reward. Subadditivity makes this singleton an n -approximation to $f(S^*)$, while all n possible singleton rewards can be queried in advance. Combining these observations gives the certificate that replaces the cost anchor used in previous work.

Lemma 6 (Reward-anchored scale). *Suppose $P^* > 0$. Let (α^*, S^*) be optimal and let $\delta^* = 1 - \alpha^*$ be the principal's optimal retained share. Choose an action $j^* \in S^*$ with largest singleton reward:*

$$j^* \in \arg \max_{j \in S^*} f(\{j\}).$$

Then

$$\frac{W}{n^2 f(\{j^*\})} \leq \delta^* \leq \min \left\{ 1, \frac{W}{f(\{j^*\})} \right\}. \quad (4)$$

The ratio between the upper and lower endpoints is at most n^2 .

Proof. Since $P^* > 0$, the set S^* contains an item of positive singleton reward: otherwise subadditivity would give $f(S^*) = 0$. Monotonicity, subadditivity, and the definition of j^* give

$$f(\{j^*\}) \leq f(S^*) \leq \sum_{j \in S^*} f(\{j\}) \leq n f(\{j^*\}). \quad (5)$$

By definition,

$$P^* = \delta^* f(S^*). \quad (6)$$

The right inequality in (4) follows from Lemma 5, (5), and (6): $\delta^* f(\{j^*\}) \leq P^* \leq W$, while $\delta^* \leq 1$.

For the left inequality, Lemma 5 and (5) imply

$$W \leq nP^* = n\delta^* f(S^*) \leq n^2 \delta^* f(\{j^*\}).$$

Finally, if $W/f(\{j^*\}) \leq 1$, the endpoint ratio is exactly n^2 ; otherwise it is $n^2 f(\{j^*\})/W < n^2$. $\square$

4.3 The resulting FPTAS

The oracle model supplies exactly the observable quantities in the certificate. A best-response query at $\alpha = 1$ returns a welfare-maximizing action set $T \in \arg \max_S \{f(S) - c(S)\}$, from which reward and cost values give $W = f(T) - c(T)$. Singleton reward queries enumerate all possible anchors.

The algorithm now directly implements the preceding scale bracket. One query at $\alpha = 1$ computes welfare, n singleton queries list all possible reward anchors, and one geometric grid is searched for each positive anchor. No response breakpoint is computed or approximated.

We parameterize a contract by the principal's retained share $\delta = 1 - \alpha$. Let $q = 1 - \varepsilon$ be the geometric contraction ratio, and let K be the number of grid steps needed to span a factor n^2 , namely the least nonnegative integer such that

$$q^K \leq \frac{1}{n^2}. \quad (7)$$

The shift by one grid position in Algorithm 1 ensures that every queried contract has $\alpha > 0$. This is immaterial for the general best-response oracle and ensures correct implementation by the standard supply oracle in the additive-reward special case.

Algorithm 1 Reward-anchored geometric search

Require: Actions $[n]$; value oracles for a normalized monotone subadditive reward f and a normalized nonnegative cost c .

Require: An exact best-response oracle returning S_α at each queried contract $\alpha \in [0, 1]$; accuracy $\varepsilon \in (0, 1)$.

Ensure: A contract $\hat{\alpha} \in [0, 1]$.

- 1: Query each action's singleton reward $a_i = f(\{i\})$, $i \in [n]$.
 - 2: Query the best-response oracle at $\alpha = 1$, denote its response by T , and compute $W = f(T) - c(T)$.
 - 3: **if** $W = 0$ **then**
 - 4: **return** $\alpha = 1$.
 - 5: Let $q = 1 - \varepsilon$ and choose the least $K \geq 0$ satisfying (7).
 - 6: **for** every i with $a_i > 0$ **do**
 - 7: Set the candidate bracket's upper endpoint $b_i \leftarrow \min\{1, W/a_i\}$.
 - 8: **for** $k = 1, \dots, K + 1$ **do**
 - 9: Set the retained share $\delta_{i,k} \leftarrow b_i q^k$ and contract share $\alpha_{i,k} \leftarrow 1 - \delta_{i,k}$.
 - 10: Query $S_{\alpha_{i,k}}$ and its value $f(S_{\alpha_{i,k}})$.
 - 11: Record $\delta_{i,k} f(S_{\alpha_{i,k}})$.
 - 12: **return** a queried contract with maximum recorded principal utility.
-

Proof of Theorems 1 and 2. If $W = 0$, every best response satisfies

$$P(\alpha) \leq f(S_\alpha) - c(S_\alpha) \leq W = 0,$$

where the first inequality follows from $c(S_\alpha) \leq \alpha f(S_\alpha)$ because $\emptyset$ is available. Thus the returned contract is optimal.

Assume $W > 0$ and consider the iteration $i = j^*$ supplied by Lemma 6. Let $b = b_{j^*}$ be the correct bracket's upper endpoint. The bracket gives $b \geq \delta^*$ and

$$\frac{b}{n^2} \leq \frac{W}{n^2 f(\{j^*\})} \leq \delta^*. \quad (8)$$

By (7), the last grid point satisfies $bq^{K+1} \leq q\delta^* < \delta^*$.

If $b = \delta^*$, the first queried point is $q\delta^*$. Otherwise, let k be the first queried grid index with $bq^k \leq \delta^*$. The preceding point is larger than δ^* , so

$$q\delta^* < bq^k \leq \delta^*. \quad (9)$$

In either case the algorithm queries some δ satisfying $q\delta^* \leq \delta \leq \delta^*$. For its contract $\alpha = 1 - \delta$, we have $\alpha \geq \alpha^*$. Lemma 4 therefore implies $f(S_\alpha) \geq f(S^*)$, and hence

$$P(\alpha) = \delta f(S_\alpha) \geq q\delta^* f(S^*) = (1 - \varepsilon)P^*.$$

The algorithm returns the best queried contract.

It remains to count queries. Since $-\log(1 - \varepsilon) \geq \varepsilon$,

$$K \leq \left\lceil \frac{2 \log n}{\varepsilon} \right\rceil \quad (n \geq 2).$$

Thus there are $O(n \log(n+1)/\varepsilon)$ best-response and value queries. If f is additive, all queried response values are computed from the n singleton values. Every queried δ is strictly smaller than one, so the corresponding $\alpha > 0$ best response is implemented by the supply query with prices $p_j = \alpha f(\{j\})$ and the correct tie-breaking. Only one additional cost-value query, used to compute W , is required. $\square$

5 Beyond the FPTAS: robustness and limits

The efficiency of the FPTAS rests on two features of the model. It uses exact best responses, and it searches only for the multiplicative scale of the optimal retained share rather than the identity of its breakpoint. The first feature is robust: additive response error produces only an additive loss in principal utility. The second has genuine limits: exponentially fine accuracy requires recovering the hidden breakpoint identity, and the n^2 localization width cannot be improved in general.

5.1 Robustness to approximate best responses

The reward-anchored search continues to work when the agent's response is computed only approximately. A τ -best-response oracle, queried at α , may return any set $\tilde{S}_\alpha$ satisfying

$$\alpha f(\tilde{S}_\alpha) - c(\tilde{S}_\alpha) \geq \max_S \{\alpha f(S) - c(S)\} - \tau.$$

The guarantee below is for the response selection implemented by the oracle; no consistency across queries is required. We compare the realized principal utility $(1 - \alpha)f(\tilde{S}_\alpha)$ with the exact-response benchmark P^* defined in Section 3.

Theorem 7 (Approximate-oracle robustness). *Under the assumptions of Theorem 2, suppose best-response queries are replaced by τ -best-response queries and exact reward and cost values remain available. For every $\varepsilon \in (0, 1)$, a deterministic algorithm makes*

$$O\left(\frac{n \log(n+1)}{\varepsilon}\right)$$

τ -best-response and reward-value queries, plus one cost-value query, and returns a queried contract and response with principal utility at least

$$(1 - \varepsilon)P^* - \frac{3\tau}{\varepsilon}.$$

To see the proof idea, query the approximate oracle at $\alpha = 1$. Its realized welfare gives an additive- τ estimate of W , which widens the scale bracket by only a constant factor. The grid then deliberately moves one step below the target retained share. The resulting separation from α^* creates enough agent-utility margin to absorb the response error, at a principal-utility cost of order τ/ε . Appendix A gives the full argument and constants.

5.2 Limits of scale localization

The equal-revenue family used for the exact lower bound of [6] has exponentially many critical contracts with the same principal utility. Its hidden perturbation changes the identity of the unique optimum while barely changing its scale. Ordinary approximation can ignore this identity, but accuracy comparable to the perturbation cannot.

Theorem 8 (Approximation requires accuracy dependence). *There is a sequence $\gamma_n = \Theta(2^{-n})$ such that any randomized algorithm which, with constant success probability, computes a $(1 - \gamma_n)$ -approximate contract for every instance with additive reward and monotone supermodular cost requires $2^{\Omega(n)}$ supply queries in expectation. The conclusion continues to hold with polynomially many cost-value queries.*

This establishes a high-accuracy boundary, not a lower bound for constant or inverse-polynomial accuracy. The construction and proof appear in Appendix B.

A separate boundary concerns the width of the certificate itself. Its n^2 factor combines $W \leq nP^*$ with $f(S^*) \leq n \max_{i \in S^*} f(\{i\})$. The following proposition shows that the two losses can occur simultaneously, while the first remains tight even in the monotone-supermodular cost class.

Proposition 9 (Tightness of reward-anchored localization). *(i) For every $m \geq 2$ and fixed $\eta \in (0, 1)$, there is an instance with $n = 2m$ actions, additive rewards, and arbitrary normalized nonnegative costs having a unique optimal principal contract (α^*, S^*) such that*

$$\frac{W}{(1 - \alpha^*) \max_{i \in S^*} f(\{i\})} = \frac{m(1 + \eta + m/2)}{1 + \eta} = \Omega(n^2).$$

- (ii) For every $n \geq 2$ and $r > 1$, there is an instance with normalized additive rewards and monotone supermodular costs satisfying

$$\frac{W}{P^*} = n - \frac{n-1}{r}.$$

The constructions are given in Appendix C. They establish tightness of the localization certificate, not a matching query lower bound, because the bracket width enters the algorithm only logarithmically.

6 Conclusion and discussion

We resolve the representation-independent approximation question for additive rewards and arbitrary set costs, and more generally for monotone subadditive rewards under best-response access. The resulting separation between exact and approximate query complexity is explained by reward-side localization: approximation needs the multiplicative scale of an optimal breakpoint, while exact optimization may require its hidden identity. The robustness and tightness results show both the reach and the limits of this explanation.

The main remaining question is whether representation-independent approximation with arbitrary costs extends to monotone rewards beyond subadditivity. Our proof uses subadditivity twice: to obtain the polynomial welfare–profit comparison $W \leq nP^*$ and to approximate the reward of an optimal response by one of its singleton rewards. Progress beyond this boundary therefore requires a different polynomial welfare gap, a different enumerable anchor, or an impossibility result showing that no such localization is possible.

Acknowledgments

OpenAI Codex assisted with proof development and verification. The authors independently checked all arguments and assume full responsibility for the content of this manuscript.

References

- [1] E. Baldwin, P. Dütting, M. Feldman, and M. Schlesinger. Combinatorial contracts through demand types. *arXiv preprint arXiv:2604.15125*, 2026.
- [2] R. Deo-Campo Vuong, S. Dughmi, N. Patel, and A. Prasad. On supermodular contracts and dense subgraphs. In *Proceedings of the 2024 ACM–SIAM Symposium on Discrete Algorithms (SODA)*, pages 109–132, 2024.
- [3] P. Dütting, T. Ezra, M. Feldman, and T. Kesselheim. Combinatorial contracts. In *Proceedings of the 62nd IEEE Symposium on Foundations of Computer Science (FOCS)*, pages 815–826, 2021.
- [4] P. Dütting, T. Ezra, M. Feldman, and T. Kesselheim. Multi-agent combinatorial contracts. In *Proceedings of the 2025 ACM–SIAM Symposium on Discrete Algorithms (SODA)*, pages 1857–1891, 2025.

- [5] P. Dütting, M. Feldman, and Y. Gal-Tzur. Combinatorial contracts beyond gross substitutes. In *Proceedings of the 2024 ACM–SIAM Symposium on Discrete Algorithms (SODA)*, pages 92–108, 2024.
- [6] P. Dütting, M. Feldman, Y. Gal-Tzur, and A. Rubinstein. When contracts get complex: Information-theoretic barriers. In *Proceedings of the 2026 ACM–SIAM Symposium on Discrete Algorithms (SODA)*, pages 6464–6493, 2026. Full version: *arXiv preprint arXiv:2403.09794*.
- [7] P. Dütting, M. Feldman, and I. Talgam-Cohen. Algorithmic contract theory: A survey. *Foundations and Trends in Theoretical Computer Science*, 16(3–4):211–411, 2024.
- [8] T. Ezra, M. Feldman, and M. Schlesinger. On the (in)approximability of combinatorial contracts. In *Proceedings of the 15th Innovations in Theoretical Computer Science Conference (ITCS)*, pages 44:1–44:22, 2024.
- [9] M. Feldman, Y. Gal-Tzur, T. Ponitka, and M. Schlesinger. One action too many: Inapproximability of budgeted combinatorial contracts. In *Proceedings of the 17th Innovations in Theoretical Computer Science Conference (ITCS)*, pages 58:1–58:24, 2026.
- [10] M. Feldman and L. Yashin. Ultra efficient contracts: Pushing the boundaries of tractable contract design. *arXiv preprint arXiv:2506.18008*, 2025; revised 2026.

A Proof of approximate-response robustness

Proof of Theorem 7. Query the approximate oracle at $\alpha = 1$, let T be its response, and let $L = \max\{0, f(T) - c(T)\}$ be the resulting lower estimate of optimal welfare. Since W is optimal welfare,

$$W - \tau \leq f(T) - c(T) \leq W.$$

If $L \leq \tau$, then $W \leq L + \tau \leq 2\tau$. Returning $\alpha = 1$ gives zero principal utility, which already satisfies the claimed bound because $P^* \leq W$.

Assume $L > \tau$ and let $U = L + \tau$ be the corresponding welfare upper bound. Then

$$L \leq W \leq U < 2L.$$

Let (α^*, S^*) be an exact optimal contract–response pair, let $\delta^* = 1 - \alpha^*$ be its retained share, and let $a = f(\{j^*\})$ be the largest singleton reward in S^* . As in Lemma 6,

$$\frac{W}{n^2 a} \leq \delta^* \leq \min\left\{1, \frac{W}{a}\right\}.$$

Let $b = \min\{1, U/a\}$ be the widened bracket’s upper endpoint. The preceding inequalities imply

$$\frac{b}{2n^2} \leq \delta^* \leq b. \quad (10)$$

Indeed, the upper bound follows from $W \leq U$. For the lower bound, $U < 2W$; this proves the claim directly when $b = U/a$, and when $b = 1$ it gives $W > a/2$.

Allocate $\rho = \varepsilon/3$ of the error budget to oracle error and let $q = 1 - \rho$ be the grid ratio. For every positive singleton reward a_i , search the grid $b_i, b_i q, b_i q^2, \dots$, where $b_i = \min\{1, U/a_i\}$, far enough to cover multiplicative width $2n^2$, and query one further point. For the correct anchor, let $k \geq 0$ be the least index such that $bq^k \leq \delta^*$. If $k = 0$, then $b = \delta^*$; otherwise minimality gives $q\delta^* < bq^k \leq \delta^*$. Hence the additional point $\delta = bq^{k+1}$ satisfies

$$q^2 \delta^* < \delta \leq q\delta^*. \quad (11)$$

This deliberate undershoot preserves at least a q^2 fraction of the principal’s retained share while creating the margin $\alpha - \alpha^* \geq \rho\delta^*$ needed to absorb response error. Let $\alpha = 1 - \delta$ and let $\tilde{S}_\alpha$ be any response returned by the approximate oracle. Approximate optimality at α and exact optimality of S^* at α^* give

$$\begin{aligned} \alpha f(\tilde{S}_\alpha) - c(\tilde{S}_\alpha) &\geq \alpha f(S^*) - c(S^*) - \tau, \\ \alpha^* f(S^*) - c(S^*) &\geq \alpha^* f(\tilde{S}_\alpha) - c(\tilde{S}_\alpha). \end{aligned}$$

Adding and using $\alpha - \alpha^* = \delta^* - \delta \geq \rho\delta^*$ yields

$$f(\tilde{S}_\alpha) \geq f(S^*) - \frac{\tau}{\rho\delta^*}.$$

Consequently, since $\delta > q^2 \delta^*$ and $\delta \leq q\delta^*$,

$$\delta f(\tilde{S}_\alpha) \geq q^2 P^* - \frac{q\tau}{\rho} \geq (1 - \varepsilon)P^* - \frac{3\tau}{\varepsilon}.$$

The last inequality uses $q^2 = (1 - \varepsilon/3)^2 \geq 1 - \varepsilon$. Returning the queried pair with greatest realized principal utility can only improve this bound.

Finally, covering a multiplicative interval of width $2n^2$ with ratio $q = 1 - \varepsilon/3$ takes $O(\log(n+1)/\varepsilon)$ queries per singleton anchor. The algorithm therefore uses the stated number of τ -best-response and reward-value queries, plus the one cost-value query used to compute L . $\square$

B Equal-revenue family and high-accuracy lower bound

The equal-revenue construction underlying the exact lower bound of [6] makes the separation in Corollary 3 especially transparent. It also provides an independent stress test for the two structural quantities used by our algorithm.

Let $N = 2^n - 1$ be the largest binary index. Assign each set $S \subseteq [n]$ its binary value $\sum_{i \in S} 2^{i-1}$, and let S_t denote the unique set with index $t \in \{0, \dots, N\}$; in particular, $S_0 = \emptyset$. Give item i reward $v_i = 2^{i-1}$, so that $f(S_t) = t$. The equal-revenue cost is defined by

$$c(S_0) = 0, \quad c(S_t) - c(S_{t-1}) = \frac{t-1}{t} \quad (1 \leq t \leq N).$$

It is monotone and supermodular. For each S_t , define its critical contract share by

$$\alpha_t = \frac{t-1}{t}.$$

This contract induces S_t for $1 \leq t \leq N$. As shown below, every such critical contract gives the principal the same utility, hence the name *equal revenue*.

Proposition 10 (Anatomy of the equal-revenue instance). *On the preceding instance,*

$$P^* = 1, \quad W = H_{2^n-1},$$

where $H_m = \sum_{h=1}^m 1/h$ is the m th harmonic number. Moreover, if $1 \leq t \leq N$ and j_t denotes a largest-reward action in S_t , i.e., $j_t \in \arg \max_{j \in S_t} v_j$, then

$$\frac{1}{2v_{j_t}} < 1 - \alpha_t \leq \frac{1}{v_{j_t}}. \quad (12)$$

Thus the welfare-profit gap is $\Theta(n)$, while a singleton reward locates the scale of every critical contract within a factor two.

Proof. By construction,

$$(1 - \alpha_t)f(S_t) = \frac{1}{t} \cdot t = 1.$$

To identify the response curve, let $u_t(\alpha) = \alpha t - c(S_t)$ be the agent's utility from S_t . The consecutive lines u_{t-1} and u_t intersect at

$$c(S_t) - c(S_{t-1}) = \alpha_t.$$

These intersection points strictly increase with t , so the upper envelope visits $S_0, S_1, \dots, S_N$ in this order. Thus the α_t are exactly the critical contracts, and $P^* = 1$. Telescoping the cost recurrence gives

$$c(S_t) = \sum_{h=1}^t \frac{h-1}{h} = t - H_t.$$

Hence $f(S_t) - c(S_t) = H_t$, which is maximized at $t = N$.

If 2^{k-1} is the highest power of two appearing in the binary representation of t , then $v_{j_t} = 2^{k-1} \leq t < 2^k = 2v_{j_t}$. Since $1 - \alpha_t = 1/t$, taking reciprocals yields (12). $\square$

The lower bound lowers the cost of one hidden set, making one of exponentially many nearly tied contracts uniquely optimal. Exact optimization must discover that set. At coarser relative accuracy, its small utility advantage can be ignored: Proposition 10 shows that every candidate breakpoint has a scale certified by one singleton reward, which our grid can find without learning its identity.

The next subsection locates the limit of this explanation. The hidden cost perturbation is $\Theta(4^{-n})$, but because it applies to a set of reward $\Theta(2^n)$, it creates a relative principal-utility advantage $\Theta(2^{-n})$. At accuracy comparable to that advantage, approximation must again identify the hidden set.

B.1 The high-accuracy query lower bound

The exact lower bound alone does not explain whether the dependence on $1/\varepsilon$ in our FPTAS is necessary. The same hidden-perturbation family gives a partial answer: once the requested relative error reaches the scale of the hidden perturbation, approximation again requires exponentially many queries.

We will use one simulation fact from Appendix E of [6]. For a nonnegative price vector p , let $p(S) = \sum_{i \in S} p_i$ be the total price of S . The σ -approximate supply $\mathcal{D}_\sigma(p)$ is the collection of sets whose price-minus-cost objective lies within σ of optimal:

$$\mathcal{D}_\sigma(p) = \left\{ S \subseteq [n] : p(S) - c(S) \geq \max_{T \subseteq [n]} \{p(T) - c(T)\} - \sigma \right\}.$$

For the equal-revenue cost above, if

$$0 < \sigma < \frac{1}{2} \min_{1 \leq t < N} (\alpha_{t+1} - \alpha_t),$$

then $\mathcal{D}_\sigma(p)$ has size $O(n^2)$ for every p and can be enumerated from the known base cost without further oracle calls, though the enumeration need not be computationally efficient. Consequently, if a perturbed cost differs from c on one set by at most σ , every exact supply response to the perturbed cost lies in $\mathcal{D}_\sigma(p)$; querying the perturbed cost on these candidates simulates the supply query with $O(n^2)$ value queries. This is the sparse-supply property used below.

Proof of Theorem 8. Fix $n \geq 2$, let $N = 2^n - 1$, and use the equal-revenue instance from Section B. Thus $f(S_t) = t$, $\alpha_t = (t - 1)/t$, and every critical contract gives principal utility one. Let $\mathcal{K}$ be the candidate set of hidden indices and let ζ be the amount by which the hidden set's cost is reduced:

$$\mathcal{K} = \{\lceil N/2 \rceil, \dots, N\}, \quad \zeta = \frac{1}{8N^2}.$$

For each hidden index $k \in \mathcal{K}$, define c_k by lowering only the cost of S_k by ζ . Since

$$\alpha_{t+1} - \alpha_t = \frac{1}{t(t+1)} \quad \text{and} \quad \zeta = \frac{1}{8N^2} < \frac{1}{2N(N-1)},$$

the preceding sparse-supply property applies with $\sigma = \zeta$.

These perturbations preserve nonnegativity, monotonicity, and supermodularity. For completeness, write $c(S_t) = t - H_t$. Its consecutive increments $d_t = c(S_t) - c(S_{t-1}) = 1 - 1/t$ are increasing. Every strict supermodular marginal gap has the following form. If the indices of $S \subset T$ differ by $h \geq 1$ and the added action has binary value a , then the gap is

$$\sum_{r=1}^a (d_{x+h+r} - d_{x+r}) = \sum_{r=1}^a \frac{h}{(x+r)(x+h+r)} \geq \frac{1}{N^2},$$

where x is the index of S . The four sets in such a marginal comparison are distinct, so changing one set value alters this positive gap by at most $\zeta < 1/N^2$. A monotonicity comparison involving the perturbed set has gap at least $1 - 1/k \geq 1/2$ before perturbation and therefore remains valid; all other inequalities are unchanged.

The line for S_k moves upward by ζ . Its intersection with the preceding response line shifts from α_k to $\alpha'_k = \alpha_k - \zeta$, because consecutive rewards differ by one. Hence its principal utility at entry becomes

$$(1 - \alpha'_k)f(S_k) = 1 + \zeta k \geq 1 + \frac{1}{16N}.$$

The small-perturbation inequality above preserves the order of the response lines. The lifted line for S_k enters at α'_k . If $k < N$, it remains active until its intersection with S_{k+1} , which shifts to $\alpha_{k+1} + \zeta$;

if $k = N$, it remains active through $\alpha = 1$. Every other response line enters at its original breakpoint, except S_{k+1} when that line exists, which enters later. Principal utility decreases with α while a fixed response is active. Therefore every response other than S_k yields utility at most one, whereas S_k yields its strictly larger maximum at α'_k . This makes α'_k the unique optimal contract under the stipulated tie-breaking.

Set the target relative error to $\gamma_n = 1/(32N)$. Since

$$(1 - \gamma_n) \left(1 + \frac{1}{16N} \right) > 1,$$

every successful $(1 - \gamma_n)$ -approximation must induce S_k and therefore identifies the hidden index.

It remains to transfer this identification requirement to supply queries. If the base cost c is known, a value query distinguishes c_k from c only when it queries the hidden set. With k uniform in $\mathcal{K}$, identification therefore needs $\Omega(N)$ value queries by Yao's principle. By the sparse-supply property established above, a supply query to c_k can be simulated by enumerating $\mathcal{D}_\zeta(p)$ and making $O(n^2)$ value queries to c_k . Indeed, an optimizer under c_k is within ζ of optimal under c , because the perturbation can improve the objective of only one set and by only ζ . Consequently, an algorithm making Q supply queries and polynomially many additional value queries yields $O(Qn^2) + \text{poly}(n)$ value queries. The $\Omega(N)$ identification lower bound implies

$$Q \geq \frac{N}{\text{poly}(n)} = 2^{\Omega(n)}.$$

□

C Tightness constructions

Proof of Proposition 9, part (i). Let the ground set be $A \dot{\cup} \{b_1, \dots, b_m\}$, where A contains m unit-reward actions and action b_r has reward $R_r = 2^r m$ for $r \in [m]$. Rewards are additive. Set

$$R_0 = m, \quad P_0 = 1 + \eta, \quad \alpha_0 = 1 - \frac{P_0}{m}, \quad c(A) = m - P_0.$$

For $r \geq 1$, recursively define

$$\alpha_r = 1 - \frac{1}{R_r}, \quad c(\{b_r\}) = c(\{b_{r-1}\}) + \alpha_r(R_r - R_{r-1}),$$

where $\{b_0\}$ denotes A and $c(\{b_0\}) = c(A)$. Every other nonempty set S receives cost $c(S) = 2f(S)$. These costs are nonnegative. Dividing every reward and cost by $f([n])$ leaves all responses and ratios unchanged if rewards must lie in $[0, 1]$.

The only lines that can appear on the agent's upper envelope are $\emptyset, A, \{b_1\}, \dots, \{b_m\}$. Their slopes are strictly increasing, consecutive lines intersect at

$$0 < \alpha_0 < \alpha_1 < \dots < \alpha_m < 1.$$

Thus they appear in this order. The principal receives $P_0 = 1 + \eta$ from A at α_0 , but only $(1 - \alpha_r)R_r = 1$ at every later intersection; utility decreases between intersections. Hence the unique optimum is $(\alpha^*, S^*) = (\alpha_0, A)$.

Let $W_0 = P_0$ and $W_r = R_r - c(\{b_r\})$. The recurrence gives

$$W_r - W_{r-1} = (1 - \alpha_r)(R_r - R_{r-1}) = \frac{1}{2}.$$

Therefore $W = P_0 + m/2$, while $1 - \alpha^* = P_0/m$ and $\max_{i \in S^*} f(\{i\}) = 1$. Substitution proves part (i). $\square$

Proof of Proposition 9, part (ii). Let

$$Z = \sum_{h=0}^{n-1} r^h, \quad v_i = \frac{r^{i-1}}{Z}, \quad P = v_1, \quad a_i = 1 - \frac{P}{v_i} = 1 - r^{-(i-1)}.$$

Define $d_1 = 0$ and, for $i \geq 2$,

$$d_i = d_{i-1} + a_i(v_i - v_{i-1}),$$

and set

$$c(S) = \sum_{i \in S} d_i + 2 \binom{|S|}{2}.$$

The marginal cost of adding i to S is $d_i + 2|S|$, so c is monotone and supermodular. Sets of size at least two have cost at least 2 but $\alpha f(S) \leq 1$, so they are never best responses. Since $(d_i - d_{i-1})/(v_i - v_{i-1}) = a_i$ and the a_i increase, the upper envelope visits the singletons in order. Each gives principal utility $(1 - a_i)v_i = P$, so $P^* = P$. Finally, telescoping at $\alpha = 1$ gives

$$\begin{aligned} W = v_n - d_n &= P + \sum_{i=2}^n (1 - a_i)(v_i - v_{i-1}) \\ &= P(1 + (n-1)(1 - 1/r)) = P \left(n - \frac{n-1}{r} \right). \end{aligned}$$

$\square$