

lab material enhancement

Week 4

Q7: List all titles(in table movies) that contain the word "man".

POSIX Regular Expressions

The pattern matching operators for POSIX regular expressions are as follows:

~: Matches the regular expression, case-sensitive.

~*: Matches the regular expression, case-insensitive.

!~: Does not match the regular expression, case-sensitive.

!~*: Does not match the regular expression, case-insensitive.

so we can also write as

```
select * from movies
where title ~* '\mman\M'
```

Week 5

Q2:List the cast of the American "Treasure Island" 1950 film (first name, surname, and display "Director" instead of "D" and "Actor" instead of "A"

2. List the cast of the American(us) "Treasure Island"(title) 1950 film (first name, surname, and display "Director" instead of "D" and "Actor" instead of "A"

	first_name	surname	credited_as
1	Lionel	Barrymore	Actor
2	Wallace	Beery	Actor
3	Nigel	Bruce	Actor
4	Jackie	Cooper	Actor
5	Victor	Fleming	Director
6	Lewis	Stone	Actor

The answer in the Question file mistakenly gives the cast of 1934 film "Treasure Island".

Week 7

Q8: List all year and "Events" (films released time, people births time, people deaths time) that occurred between 1930 and 1935 ,pushed into a subquery to add a sort key

```
SELECT year, event
FROM (
  SELECT m.year_released AS year,
  m.title || ' (' || c.country_name || ') was released' AS event,
  m.title AS sort_key
  FROM movies m
  JOIN
  countries c ON c.country_code = m.country
  WHERE m.year_released BETWEEN 1930 AND 1935
  UNION ALL
  SELECT born,
  trim(coalesce(first_name, '') || ' ' || surname || ' was born'),
  surname AS sort_key
  FROM people
  WHERE born BETWEEN 1930 AND 1935
  UNION ALL
  SELECT died,
  trim(coalesce(first_name, '') || ' ' || surname || ' died'),
  surname AS sort_key
  FROM people
  WHERE died BETWEEN 1930 AND 1935
)
x
ORDER BY year,sort_key;
```

better to take the sort_key as the event as sort key, instead of surname.

week 10

In this lab, several bad triggers were evoked.

Experiment 4: before + each row + table

```
CREATE TRIGGER check_before
BEFORE INSERT OR UPDATE OR DELETE ON emp
FOR EACH ROW
EXECUTE FUNCTION process_emp_check();--test, and see result in emp_log
insert into emp values (017,'贺小山', 7000, 1);
UPDATE emp set salary=8000 where id=017;
delete from emp where id=017;
CREATE TRIGGER check_before_insert
BEFORE INSERT ON emp
```

```
FOR EACH ROW
EXECUTE FUNCTION process_emp_check();
CREATE TRIGGER check_before_update
BEFORE UPDATE ON emp
FOR EACH ROW
EXECUTE FUNCTION process_emp_check();
CREATE TRIGGER check_before_delete
BEFORE DELETE ON emp
FOR EACH ROW
EXECUTE FUNCTION process_emp_check();
```

The code above will result in bad triggers, and will influence the operations afterwards and cause trouble. For me, I deleted every trigger I created after an Experiment was done. It's better to give a note for that or some may get confused.