ThumbnailSlide

SlideshowBox

Requirements

IDE: Adobe Flash CS3/CS4/CS5

Flash Player: 9+

Properties

Name	Туре	Description
autoSlideShow	Boolean	If set to <i>true</i> , allows for the image slide show to start automatically after the SlideshowBox component and the album template have been initialized.
		Changing the value of the property has affect regardless of whether the property is set from the SlideshowBox configuration panel (by checking the autoSlideShow option) or dynamically, by ActionScript code, while the album is playing.
		The default value is <i>false</i> .
backgroundColor	uint	The color of the background displayed by the album. The background is displayed only if the <i>backgroundVisible</i> property of the SlideshowBox component is set to <i>true</i> .
		The default value is 0x1C1C1C.
backgroundImage	String	The URL or file path and name of an image displayed as the background of the album. The background image is displayed only if the backgroundVisible property of the SlideshowBox component is set to true.
backgroundVisible	Boolean	A Boolean value that specifies whether the album template will display the background color or the background image. If it is set to false, the album will have a transparent background (the colored background or the background image will be invisible). The color of the album background can be set through the backgroundColor property while the background image can be specified through the backgroundImage property. The default value is true.
bold	Boolean	A Boolean value that, if set to <i>true</i> , sets the text from the title and description to bold. Please note that the font with its bold styling has to be embedded into the .swf file. If the <i>italic</i> property is also set to

		true, you would have to embed the bold-italic style of the font. To find out how to embed the font, please consult the Applying new fonts.pdf document.
		Note: The font settings from the SlideshowBox Panel will not apply to the Preview of the album within the SlideshowBox Panel. To view the font setting changes, you will have to compile your SlideshowBox project.
		The default value is false.
closeButtonLabel	String	The text for the <i>Close</i> button, used to close the large image view and return to the list of thumbnails. You can place your own text by setting this property.
controlLabelBold	Boolean	Sets the labels used as controls to bold. Please note that the font with its bold styling has to be embedded into the .swf file. If the controlLabelItalic property is also set to true, you would have to embed the bold-italic style of the font. To find out how to embed the font, please consult the Applying new fonts.pdf document.
		Note: The font settings from the SlideshowBox Panel will not apply to the Preview of the album within the SlideshowBox Panel. To view the font setting changes, you will have to compile your SlideshowBox project.
		The default value is false.
controlLabelFontName	String	Displays the control labels using a different font. Please note that the font with its corresponding styling has to be embedded into the .swf file. The styling is set by the <i>controlLabelBold</i> and <i>controlLabelItalic</i> properties. To find out how to embed the font, please consult the <i>Applying new fonts.pdf</i> document.
		Note: The font settings from the SlideshowBox Panel will not apply to the Preview of the album within the SlideshowBox Panel. To view the font setting changes, you will have to compile your SlideshowBox project.
controlLabelFontSize	uint	Sets the size for the current font used by the control labels.
		Note: The font settings from the SlideshowBox Panel will not apply to the Preview of the album within the SlideshowBox Panel. To view the font setting changes, you will have to compile your SlideshowBox project.
		The default value is 11.
controlLabelltalic	Boolean	Sets the labels used as controls to italic. Please note that the font with its italic styling has to be embedded into the .swf file. If the controlLabelBold property is also set to true, you would have to embed the bold-italic style of the font. To find out how to embed the font, please consult the Applying new fonts.pdf document.
		Note: The font settings from the SlideshowBox Panel will not apply to the Preview of the album within the SlideshowBox Panel. To view the font setting changes, you will have to compile your SlideshowBox

		project.
		The default value is <i>true</i> .
controlsColor	uint	This is the color of the control buttons. The control buttons are represented by label buttons.
		The default value is 0xFFFFFF.
fontName	String	Sets the text from the title and description to the specified font. Please note that the font with its appropriate styling has to be embedded into the .swf file. To find out how to embed the font, please consult the <i>Applying new fonts.pdf</i> document.
		Note: The font settings from the SlideshowBox Panel will not apply to the Preview of the album within the SlideshowBox Panel. To view the font setting changes, you will have to compile your SlideshowBox project.
fontSize	uint	Sets the size of the description text. The size of the title is either the same or is set automatically by the template, depending on the template.
		Note: The font settings from the SlideshowBox Panel will not apply to the Preview of the album within the SlideshowBox Panel. To view the font setting changes, you will have to compile your SlideshowBox project.
		The default value is 10.
fullScreenButton	Boolean	A Boolean value that specifies whether the full screen button will be displayed in the control bar. This button allows for the album to enter in full screen mode or normal screen mode.
		The default value is <i>true</i> .
fullScreenButtonLabel	String	The text for the <i>Full Screen</i> button, used to switch from normal screen to full screen. You can place your own text by setting this property.
italic	Boolean	A Boolean value that, if set to <i>true</i> , sets the text from the title and description to italic. Please note that the font with its italic styling has to be embedded into the .swf file. If the <i>bold</i> property is also set to <i>true</i> , you would have to embed the bold-italic style of the font. To find out how to embed the font, please consult the <i>Applying new fonts.pdf</i> document.
		Note: The font settings from the SlideshowBox Panel will not apply to the Preview of the album within the SlideshowBox Panel. To view the font setting changes, you will have to compile your SlideshowBox project.
		The default value is <i>false</i> .
lineColor	uint	The color of the two lines that displayed at the top and bottom of the thumbnails.

		The default value is 0x666666.
lineSpacing	Number	The top and bottom spacing between the thumbnail lines and the thumbnail images. The spacing is measured in pixels.
		The default value is 10 pixels.
load Original Images	Boolean	A Boolean value which specifies whether the images will be displayed with their original size or if they will be resized to fit the size of the album. This only happens if the images are larger than the size of the album.
		The default value is <i>false</i> .
navigationControls	Boolean	A Boolean value that specifies whether the control bar displays the navigation buttons or not. The navigation controls are the previous/next image buttons displayed in the control bar, used for navigating through the albums.
		The default value is <i>true</i> .
nextButtonLabel	String	The text for the <i>Next thumbnails</i> button, used to navigate through the list of thumbnails. You can place your own text by setting this property.
nextlmageLabel	String	The text for the <i>Next image</i> button, used to navigate through the list of large images. You can place your own text by setting this property.
normalScreenButtonLabel	String	The text for the <i>Normal Screen</i> button, used to switch from full screen to normal screen. You can place your own text by setting this property.
pause Button Label	String	The text for the <i>Pause</i> button, used to pause the image slideshow. You can place your own text by setting this property.
playButtonLabel	String	The text for the <i>Play</i> button, used to start the image slideshow. You can place your own text by setting this property.
preloader Position	String	Set the position of the wheel preloader. Possible values: topLeft, centered (in the center of the large image) or topRight. When the preloader position is set to top-right, the audio player will hide while the preloader is displayed, if there is any audio file set.
		The default value is <i>centered</i> .
previous Button Label	String	The text for the <i>Previous thumbnails</i> button, used to navigate through the list of thumbnails. You can place your own text by setting this property.
previous Image Label	String	The text for the <i>Previous image</i> button, used to navigate through the list of large images. You can place your own text by setting this property.
overrideFullScreenChange	Boolean	A Boolean value that allows for the user to override the

		The default value is 0 pixels.
		Note: The font settings from the SlideshowBox Panel will not apply to the Preview of the album within the SlideshowBox Panel. To view the font setting changes, you will have to compile your SlideshowBox project.
textTopOffset	Number	The top offset for the title and description text. The text can be positioned lower or higher than its default setting. Use this setting if you're not pleased with the position of the text inside the template.
		The default value is 0xFFFFFF.
textColor	uint	The color of the text for the image title and description.
		The default value is 6 seconds.
slideShowSpeed	Number	The time interval expressed in seconds at which the images will change during the slide show.
		The default value is <i>true</i> .
slideShowControls	Boolean	A Boolean value that specifies whether the control bar displays the slideshow buttons or not. The slide show controls are the play and pause slide show buttons displayed in the control bar.
		The default value is true.
showImageInfos	Boolean	A Boolean value that specifies whether the image information (title and description) will be displayed. The place where the title and description are displayed differs from one album to another.
		The default value is false.
showImageIndex	Boolean	A Boolean value which specifies whether the index of the currently displayed image will be shown. The image index will be displayed only if the album template supports this feature and if showlmageInfos is set to true.
		The default value is true.
scaleBackground	Boolean	A Boolean value that specifies whether the background image is displayed using scale-crop (the aspect ratio of the image is maintained) or whether it is displayed as it is, with its original size and centered on the album background. The background image is specified using the <i>backgroundlmage</i> property.
		The default value is false.
		the full screen changes and will remain at the same size after enterring full screen mode. If set to <i>false</i> , the component will handle the full screen event and when entering in full screen mode, it will resize to the full size of the screen, covering any other visual elements that the Flash application might contain in layers below the SlideshowBox component.
		FullScreenEvent.FULL_SCREEN event of the album and handle the full screen event separately. If set to true, the component will not react to

top Bottom Margin	Number	The empty space at the top and bottom of the album used as margins by the thumbnails. The list of thumbnails, including the two delimiting lines, will only be displayed within the space between those margins. The margins are calculated as percentage of the total album size. The default value is 40%.