

# A SIMPLE FPTAS FOR COUNTING EDGE COVERS

Chengyu Lin<sup>1</sup>   Jingcheng Liu<sup>1</sup>   Pinyan Lu<sup>2</sup>

<sup>1</sup>SHANGHAI JIAO TONG UNIVERSITY

<sup>2</sup>MICROSOFT RESEARCH ASIA

ACM-SIAM SYMPOSIUM ON DISCRETE ALGORITHMS, 2014

# Overview

## 1 Introduction

# Edge cover

## Definition

For an undirected input graph  $G = (V, E)$ , an **edge cover** of  $G$  is a set of edges  $C$  covering all vertices.

## Example





Figure : An edge cover for Petersen graph

# Edge cover

## Definition

For an undirected input graph  $G = (V, E)$ , an **edge cover** of  $G$  is a set of edges  $C$  covering all vertices.

## Example




**Figure :** An edge cover for Petersen graph, with edges chosen being highlighted in red.


# Relation to Matching

## Example

Find edge covers by maximal matching?



(a)  $G$  has a perfect matching.




(b)  $G$  doesn't have a perfect matching.


# Relation to Matching

## Example

Find edge covers by maximal matching?



(a)  $G$  has a perfect matching.




(b)  $G$  doesn't have a perfect matching.


# Relation to Matching

## Example

Find edge covers by maximal matching?



(a)  $G$  has a perfect matching.



(b)  $G$  doesn't have a perfect matching.

# Approximation Schemes

We are interested primarily in two type of polynomial time approximation scheme:

## Definition

(Informally) For given parameter  $\varepsilon > 0$  and an instance of a particular problem class, if the algorithm outputs a number  $\hat{N}$  such that  $(1 - \varepsilon)N \leq \hat{N} \leq (1 + \varepsilon)N$ , where  $N$  is the accurate answer of the problem instance, and the running time is bounded by  $\text{poly}(n, 1/\varepsilon)$  with  $n$  being the size of instance, this is called the **FPTAS (fully polynomial time approximation scheme)**.

A randomized relaxation of FPTAS is known as **FPRAS (fully polynomial time randomized approximation scheme)**, which uses random bits and only outputs  $\hat{N}$  to the desired precision with high probability.



# Approximation Schemes

We are interested primarily in two type of polynomial time approximation scheme:

## Definition

(Informally) For given parameter  $\varepsilon > 0$  and an instance of a particular problem class, if the algorithm outputs a number  $\hat{N}$  such that  $(1 - \varepsilon)N \leq \hat{N} \leq (1 + \varepsilon)N$ , where  $N$  is the accurate answer of the problem instance, and the running time is bounded by  $\text{poly}(n, 1/\varepsilon)$  with  $n$  being the size of instance, this is called the **FPTAS (fully polynomial time approximation scheme)**.

A randomized relaxation of FPTAS is known as **FPRAS (fully polynomial time randomized approximation scheme)**, which uses random bits and only outputs  $\hat{N}$  to the desired precision with high probability.