


**1a.**



Harris method



Brown method

Brown's method is better than Harris method because Brown's shows more corners and there are accurate.





**1b.** As  $r$  gets bigger, the number of corners decrease, and the corners are less condensed in an area. This is because  $r$  increases, hence the area of non-maximum suppression increases. (i.e. choose only one corner from a larger area). The number of corners decreases.

## CSC420 Assignment 2

Guanxiong Liu

1002077726

liuguanx

Nms_Brown_r=5	
Nms_Brown_r=1 0	
Nms_Brown_r=1 5	
Nms_Brown_r=2 0	


CSC420 Assignment 2

Guanxiong Liu

1002077726

liuguanx



**1c.**  $k=1.1$ ,  $\sigma=1.3$ , layers=40, threshold=20



**1d.** I use SURF algorithm to detect feature points because it is faster than SIFT. It is Speeded-Up Robust Features. It is basically a speeded-up version of SIFT. We know SIFT did a great job in detecting images' features, but it is a bit slow. SURF approximates LoG with Box Filter. Convolution with box filter can be calculated with the help of integral images and can be calculated in parallel, thus speed up the process.



CSC420 Assignment 2  
Guanxiong Liu  
1002077726  
liuguanx



CSC420 Assignment 2

Guanxiong Liu


1002077726

liuguanx

2a.



2b.




Threshold = 0.3(no match)

## CSC420 Assignment 2


Guanxiong Liu

1002077726

liuguanx



Threshold=0.4(under match)



Threshold = 0.48




## CSC420 Assignment 2


Guanxiong Liu

1002077726

liuguanx



Threshold=0.5 (overmatch)



2c. 2d.

## CSC420 Assignment 2


Guanxiong Liu

1002077726

liuguanx

The minimum  $k$  required for solving the transformation is 3. The best  $k$  in my trials is  $k=20$  for the best transformation.

K=3	[ 3.907e-01 -1.015e-01 8.313e-02 2.760e-01 4.946e+02 1.227e+02]
K=5	[ 3.916e-01 -1.019e-01 8.359e-02 2.756e-01 4.946e+02 1.227e+02]
K=7	[ 3.897e-01 -1.009e-01 8.771e-02 2.728e-01 4.947e+02 1.223e+02]
K=10	[ 3.845e-01 -9.528e-02 8.044e-02 2.809e-01 4.931e+02 1.197e+02]
K=15	[ 3.831e-01 -9.582e-02 7.994e-02 2.815e-01 4.940e+02 1.192e+02]
K=20	[ 3.806e-01 -9.483e-02 8.068e-02 2.815e-01 4.944e+02 1.188e+02]






CSC420 Assignment 2

Guanxiong Liu


1002077726

liuguanx

K=5



K=7




CSC420 Assignment 2

Guanxiong Liu


1002077726

liuguanx

K=10



K=15




## CSC420 Assignment 2

Guanxiong Liu


1002077726

liuguanx


K=20



**2e.** I extend the 3 RGB channels to the length=128 descriptors and become length=131. Add RGB value as an additional feature to the descriptors of the pixels. Thus, take colour into account.




RGB considered.




RGB not considered



CSC420 Assignment 2  
Guanxiong Liu  
1002077726  
liuguanx




Transform (RGB considered)




Transform (RGB not considered)

**3a.**



**3b.**



**3c.** The required number of iterations to recover the correct model with  $P \geq 0.99$  chance is 14389. The number of required iterations will not change because this is only one iteration, we need to find the hypothesis that gives us the largest number of inliers.