

# CS2310 Computer Programming

## LT05: Function

*Computer Science, City University of Hong Kong*  
*Semester A 2023-24*

# About Midterm

- Week 8 lecture time (27/10 Friday, 12:00)
- In classroom, on paper
  - Formal proof needed for request of absence
- One hour
- From Lec 1 (Intro) to Lec 6 (Array)
- 15% of final mark
- Sample questions and detailed announcement will be released shortly

# What's Function?

- A collection of statements that **perform a specific task**
- Functions are used to **break a problem down** into manageable pieces
  - KISS principle: "keep it simple, stupid!"
  - Break the problem down into small functions, each does only one simple task, and does it correctly
- Function allows programmer to focus on a function interface, **hiding details** of how it is implemented
- **Reuse of code**




# Today's Outline

- Defining a function
- Calling a function
- Declare a function (function prototype)
- Function overload
- Passing parameters
- Recursive functions

# Defining a Function

return\_type    function\_name    parameter\_list




```
void printHello (int n) {  
    for (int i=0; i<n; i++)  
        cout << "Hello\n";  
}
```

- **return\_type**: A function may return some value.  
A return\_type is the data type of the value the function returns. Some functions do not return any value. In this case, the return\_type is **void**.
- **function\_name**: The actual name of the function.
- **parameter\_list**: The input arguments. The parameter list refers to the type and order of parameters. A function may contain no parameters.

# Defining a Function

return\_type    function\_name    parameter\_list




```
int findMax (int x, int y) {  
    if (x > y)  
        return x;  
    else  
        return y;  
}
```

The diagram illustrates the components of a function definition. Three red arrows point from labels above to the corresponding parts of the code: one from 'return\_type' to 'int', one from 'function\_name' to 'findMax', and one from 'parameter\_list' to '(int x, int y)'.

- **return\_type**: A function may return some value.  
A return\_type is the data type of the value the function returns. Some functions do not return any value. In this case, the return\_type is **void**.
- **function\_name**: The actual name of the function.
- **parameter\_list**: The input arguments. The parameter list refers to the type and order of parameters. A function may contain no parameters.

# Defining a Function

return\_type    function\_name    parameter\_list



```
int findMax (int x, int y) {  
    if (x > y)  
        return x;  
    else  
        return y;  
}
```

- **return** statement

Syntax:

**return** expression;

**return**;

- when a return is encountered, the program will immediately go back to the calling function
- if expression exists, its value will be sent back to the calling function.
- if necessary, the returning value will be type converted to the type specified in the function definition

# Today's Outline

- Defining a function
- Calling a function
- Declare a function (function prototype)
- Function overload
- Passing parameters
- Recursive functions



# Calling a Function

- To make a function call, we only need to specify a function name and provide argument(s) in a pair of ( )

```
void main() {  
    int x=4;  
    printHello(x);  
    cout << "bye";  
}
```

```
void printHello(int n) {  
    int i;  
    for (i=0; i<n; i++)  
        cout << "Hello\n";  
}
```

# Calling a Function

- when calling a function, no need to specify parameter and return type
  - e.g., the following code will cause **syntax errors**

```
void main() {  
    int x=4;  
    void printHello(x);  
    cout << "bye";  
}
```

```
void main() {  
    int x=4;  
    printHello(int x);  
    cout << "bye";  
}
```

```
void printHello(int n) {  
    int i;  
    for (i=0; i<n; i++)  
        cout << "Hello\n";  
}
```

# Calling a Function (defined in library)

```
#include <iostream>           // tell the compiler that you are going to use functions
                                // defined in iostream library

using namespace std;
int main() {
    float area, side;
    cout << "Enter the area of a square: ";
    cin >> area;
    side = sqrt(area);        // pass area to the function sqrt which will return the
                                // square root of area


    cout << "The square has perimeter: " << 4*side;
    return 0;
}
```

# Function in C++ Library

- The C++ standard library provides a rich collection of functions
- Mathematical calculations (`#include <cmath>`)
- String manipulations (`#include <cstring>`)
- Input/output (`#include <iostream>`)
- Some functions are defined in multiple library in some platform
  - e.g. function `sqrt` is defined in both `cmath` and `iostream` in VS


# Flow of Function Call

- During program execution, when a **function name followed by parentheses** is encountered, the function is invoked and the program control is passed to that function;



# Flow of Function Call

- During program execution, when a **function name followed by parentheses** is encountered, the function is invoked and the program control is passed to that function;
- when the function ends, program control is returned to the statement immediately after the function call in the original function




# Flow of Function Call

1. program starts execution in main()
2. printHello is called
3. arguments passed to printHello


```
void main(){  
    int x=4;  
    printHello(x);  
    cout << "bye";  
}
```

```
void printHello(int n) {  
    int i;  
    for (i=0; i<n; i++)  
        cout << "Hello\n";  
}
```



# Flow of Function Call

1. program starts execution in main()
2. printHello is called
3. arguments passed to printHello
4. execute statements in printHello
5. control goes back to main() and "bye" is printed





# Function in Memory Stack

```
void f1() {  
    int x = 5;  
    int y = 6;  
    int z = f2(x, y);  
    cout << a << " " << z;  
}
```

```
int f2(int a, int b) {  
    int x = a + b;  
    int y = b - a;  
    a++;  
    return x*y;  
}
```

Each function has its own memory space which stores

- data (i.e., local variables and parameters)
- return address (address of the next instruction in the calling function)

## Memory Stack

address	f1:
0048:	return addr
0044:	x
0040:	y
0036:	z
	f2:
0032:	a
0028:	b
0024:	return addr
0020:	x
0016:	y
0012:	

# Today's Outline

- Defining a function
- Calling a function
- Declare a function (function prototype)
- Function overload
- Passing parameters
- Recursive functions

# Function Prototype

- A function should be defined **before** use

// CORRECT

```
int findMax(int x, int y) {  
    return (x > y) ? x:y;  
}  
  
void main() {  
    cout << findMax(3, 4);  
}
```

// SYNTAX ERROR

```
void main() {  
    cout << findMax(3, 4); // findMax undefined  
}  
  
int findMax(int x, int y) {  
    return x>y ? x:y;  
}
```

# Function Prototype

- A function should be defined **before** use

// CORRECT

```
int findMax(int x, int y) {  
    return (x > y) ? x:y;  
}  
  
void main() {  
    cout << findMax(3, 4);  
}
```

// SYNTAX ERROR

```
void main() {  
    cout << findMax(3, 4); // findMax undefined  
}  
  
int findMax(int x, int y) {  
    return x>y ? x:y;  
}
```

- Suppose we have 3 functions, where func1 calls func2, func2 calls func3, and func3 calls func1. In what order should the functions be defined?

# Function Prototype

- A function should be defined **before** use

// CORRECT

```
int findMax(int x, int y) {  
    return (x > y) ? x:y;  
}  
  
void main() {  
    cout << findMax(3, 4);  
}
```

// SYNTAX ERROR

```
void main() {  
    cout << findMax(3, 4); // findMax undefined  
}  
  
int findMax(int x, int y) {  
    return x>y ? x:y;  
}
```

- Suppose we have 3 functions, where func1 calls func2, func2 calls func3, and func3 calls func1. In what order should the functions be defined?
- C++ allows us to bypass this problem using *function prototypes*

# Function Prototype

- C++ allows us to *declare a function* and then call the function before defining it
- The declaration of the function is called *function prototype*, which
  - specifies the function name, parameters and return type
  - for example, the following statement declares foo as a function, there is no input and no return value

```
void foo (void);
```

# Function Prototype

```
// SYNTAX ERROR
void main() {
    cout << findMax(3, 4); // findMax undefined
}

int findMax(int x, int y) {
    return x>y ? x:y;
}
```

# Function Prototype

```
// SYNTAX ERROR
void main() {
    cout << findMax(3, 4); // findMax undefined
}

int findMax(int x, int y) {
    return x>y ? x:y;
}
```

```
// CORRECT
int findMax(int, int);

void main() {
    cout << findMax(3, 4);
}

int findMax(int x, int y) {
    return x>y ? x:y;
}
```

- `int findMax(int, int)` declares `findMax` as a function name, the return type is `int`, and there're two parameters and their types are `int`



# Function Prototype

```
// SYNTAX ERROR
void main() {
    cout << findMax(3, 4); // findMax undefined
}

int findMax(int x, int y) {
    return x>y ? x:y;
}
```

```
// CORRECT
int findMax(int n1, int n2);

void main() {
    cout << findMax(3, 4);
}

int findMax(int x, int y) {
    return x>y ? x:y;
}
```

- Another way to declare the prototype is: `int findMax(int n1, int n2);`
- However, the variable names are optional, and you can use different parameter names in the actual function definition

# Function Prototype

- `void` is used if a function takes no arguments
- Prototypes allow the compiler to check the code more thoroughly
- Arguments passed to function are coerced where necessary, e.g., `printDouble(4)` where the integer 4 will be *promoted* as a `double` type

```
#include <iostream>
using namespace std;

void printDouble(double);

void main() {
    int x=4;
    printDouble(x);
}

void printDouble(double d) {
    cout << fixed;
    cout << d << endl;
}
```

# Function Prototype

- In a large program, a function  $f$  may be used by many other functions written in different source files
  - where to declare function  $f$ ?

# Function Prototype


- In a large program, a function  $f$  may be used by many other functions written in different source files
  - where to declare function  $f$ ?
- In C++, function prototype and definition can be stored separately
- Header file (.h):
  - With extension .h, e..g, stdio.h, string.h
  - Contain function prototype only
  - To be included in the program that will call the function
- Implementation file (.cpp)
  - Contain function implementation (definition)

# Function Prototype

main.cpp

```
#include "mylib.h"

void main() {
    int x, y=2, z=3;
    x = calMin(y, z);
}
```



mylib.h

```
int calMin(int, int)
```

mylib.cpp

```
int calMin(int a, int b) {
    if (a>b)
        return b;
    else
        return a;
}
```

# Today's Outline

- Defining a function
- Calling a function
- Declare a function (function prototype)
- **Function overload**
- Passing parameters
- Recursive functions

# Function Overload

- *Overloading*: two or more functions with the *same name* but *different implementations*
- Two or more functions are said to be overloaded if they differ in
  - the number of arguments, OR
  - the type of arguments, OR
  - the order of arguments
- When an overloaded function is called, the compiler determines the most appropriate call by comparing function argument types

# Overload: Example-I

```
void printData(double x) {  
    cout << "Print double: " << x << endl;  
}  
  
void printData(float x) {  
    cout << "Print float: " << x << endl;  
}
```

```
int main() {  
    double a = 0;  
    float b = 0;  
    printData(a);  
    printData(b);  
    return 0;  
}
```



# Overload: Example-II

```
double sum(double x, double y) {  
    return x+y;  
}  
  
double sum(double x, double y, double z) {  
    return x+y+z;  
}
```

```
int main() {  
    double a, b, c;  
    cin >> a >> b >> c;  
    cout << sum(a, b) << endl;  
    cout << sum(a, b, c) << endl;  
    return 0;  
}
```

# Overload: Common Errors

```
int sum(int x, int y) {  
    return x+y;  
}  
int sum(int a, int b) {  
    return a+b;  
}  
int main() {  
    int a, b;  
    cin >> a >> b;  
    cout << sum(a, b);  
    return 0;  
}
```

```
int sum(int x, int y) {  
    return x+y;  
}  
char sum(int x, int y) {  
    return '0'+(char)(x+y);  
}  
int main() {  
    int a, b;  
    cin >> a >> b;  
    char s = sum(a, b);  
    cout << s;  
    return 0;  
}
```

# Overload: Common Errors

- **Ambiguous call:** when the compiler is unable to choose between two correctly overloaded functions
- Automatic type conversions are the main cause of ambiguity

```
void printData(double x) {  
    cout << "Print double: " << x << endl;  
}  
void printData(float x) {  
    cout << "Print float: " << x << endl;  
}  
int main() {  
    int a = 0;  
    printData(a);  
    return 0;  
}
```

# Overload: Common Errors

- **Ambiguous call:** when the compiler is unable to choose between two correctly overloaded functions
- Automatic type conversions are the main cause of ambiguity
- *Correction:* match the parameter type

```
void printData(double x) {  
    cout << "Print double: " << x << endl;  
}  
void printData(float x) {  
    cout << "Print float: " << x << endl;  
}  
int main() {  
    int float a = 0;  
    printData(a);  
    return 0;  
}
```

# Today's Outline

- Defining a function
- Calling a function
- Declare a function (function prototype)
- Function overload
- Passing parameters
- Recursive functions

# Argument vs Parameter

- **Parameter**: (a.k.a, *formal parameter*)
  - identifier that appears in function declaration
- **Argument**: (a.k.a, *actual parameter*)
  - expression that appears in a function call

```
void printHello(int n) {  
    int i;  
    for (i=0; i<n; i++)  
        cout << "Hello\n";  
}
```

```
void main() {  
    int x=4;  
    printHello(x);  
    cout << "bye";  
}
```

# Parameter Passing in C++

- There're different ways in which arguments can be passed into the called function
- Three most common methods
  - Pass-by-Value
  - Pass-by-Reference
  - Pass-by-Pointer (in later classes)


# Pass-by-Value

- the value of argument is *copied* to parameter

```
void f1() {  
    int x = 5;  
    int y = 6;  
    int z = f2(x, y);  
    cout << a << " " << z;  
}
```

```
int f2(int a, int b) {  
    int x = a + b;  
    int y = b - a;  
    a++;  
    return x*y;  
}
```

Memory Stack





# Pass-by-Value


- the value of argument is *copied* to parameter

```
void f1() {  
    int x = 5;  
    int y = 6;  
    int z = f2(x, y);  
    cout << a << " " << z;  
}
```

```
int f2(int a, int b) {  
    int x = a + b;  
    int y = b - a;  
    a++;  
    return x*y;  
}
```

- when `a++` is executed in `f2`, only the memory storage of `f2` is modified

Memory Stack



# Pass-by-Value

```
void func(int y) {  
    y=4;  
}  
  
void main(){  
    int y=3;  
    func(y);  
    cout << y << endl;  
}
```

- **y** and **y** are two different variables stored in *different* places in memory
  - **y** (parameter) is a local variable in func
  - **y** (argument) is a local variable in main

# Pass-by-Value

```
void func(int y) {  
    y=4; // modify y in func(), not the one in main()  
}  
  
void main(){  
    int y=3;  
    func(y);  
    cout << y << endl; // print 3, y remains unchanged  
}
```

- **y** and **y** are two different variables stored in *different* places in memory
  - **y** (parameter) is a local variable in func
  - **y** (argument) is a local variable in main
- => Modifying **y** in func doesn't affect **y**

# Pass-by-Value

```
void func(int y) {  
    y=4; // modify the value of x to 4  
    return y;  
}  
  
void main(){  
    int y=3;  
    func(y); y=func();  
    cout << y << endl; // print 4  
}
```

- How to modify y in func()?
- By assigning the return value of f(y) to y
- After function call, y gets a value of 4

# Pass-by-Value: Exercises

- What's the output of the following program?

```
void f(int y, int x) {  
    cout << "x=" << x << endl;  
    cout << "y=" << y << endl;  
}  
  
void main(){  
    int x=3, y=4;  
    f(x, y);  
}
```

# Pass-by-Value: Exercises

- Finding the max of 3 numbers, i, j, k

```
void main() {  
    int i,j,k;  
    int max;  
    cin >> i >> j >> k;  
  
    // find the max of i, j, k  
    ____ = findMax(____, ____);  
    ____ = findMax(____, ____);  
  
    cout << "max is " << max;  
}
```

```
int findMax(int n1, int n2) {  
    if (n1>n2)  
        return n1;  
    else  
        return n2;  
}
```

# Pass-by-Value: Exercises

- Finding the max of 3 numbers, i, j, k

```
void main() {  
    int i,j,k;  
    int max;  
    cin >> i >> j >> k;  
  
    // find the max of i, j, k  
    max = findMax(i, j);  
    max = findMax(k, max);  
  
    cout << "max is " << max;  
}
```

```
int findMax(int n1, int n2) {  
    if (n1>n2)  
        return n1;  
    else  
        return n2;  
}
```

# Pass-by-Reference

- Argument *address* is passed to the parameter
- *Argument can be updated inside the function*
- Add '&' in front of the parameter that to be pass by reference

```
void swap(int &a, int &b) {  
    int tmp = a;  
    a = b;  
    b = tmp;  
}
```

```
void main() {  
    int x=1, y=3;  
    swap(x, y);  
    cout << "x:" << x << ", y:" << y << endl;  
}
```

- More details will be explained in future lecture (pointer)




# Pass-by-Reference

```
void f1() {  
    int x = 5;  
    int y = 6;  
    int z = f2(x, y);  
    cout << a << " " << z;  
}
```

```
int f2(int &a, int &b) {  
    int x = a + b;  
    int y = b - a;  
    a++;  
    return x*y;  
}
```

- the address of x (0044) is passed to f2

## Memory Stack



# Pass-by-Reference

```
void f1() {  
    int x = 5;  
    int y = 6;  
    int z = f2(x, y);  
    cout << a << " " << z;  
}
```

```
int f2(int &a, int &b) {  
    int x = a + b;  
    int y = b - a;  
    a++;  
    return x*y;  
}
```

- the address of x (0044) is passed to f2
- when a++ is executed in f2, the value stored in 0044 (i.e., x in f1) is modified

## Memory Stack

address	f1:
0048:	return addr
0044:	x = 6
0040:	y = 6
0036:	z
	f2:
0032:	a:0044
0028:	b:0040
0024:	return addr
0020:	x
0016:	y
0012:	

# Parameter Passing: Default Parameters

- We can provide some default values for certain parameters
- Example

```
void f(int a, int b=0) { // parameter b with a default value 0
    cout << a << " " << b << endl;
}
void main() {
    f(1, 2);
    f(3); // you can call f without providing argument for b, in this case,
          // the default value 0 will be used for b in f
}
```

# Parameter Passing: Default Parameters

- All the default parameters MUST locate at the **right side** of normal parameters
- Invalid example

```
void f(int a, int b=0, int c) { // invalid definition, default parameter b
                                // located at left side of normal parameter c
    cout << a << " " << b << endl;
}
void main() {
    f(1, 2);
    f(3);
}
```

# Today's Outline

- Defining a function
- Calling a function
- Declare a function (function prototype)
- Passing parameters
- Recursive functions

# Recursions

- One basic problem solving technique is to break the task into subtasks
- If a subtask is a smaller version of the original task, you can solve the original task using a recursive function
- A recursive function is one that **invokes itself**, either directly or indirectly

# Example: Factorial

- The factorial of  $n$  is defined as

$$0! = 1$$

$$n! = n * (n-1) * \dots * 2 * 1, \text{ for } n > 0$$

- A recurrence relation: (induction)

$$n! = n * (n-1)!, \quad \text{for } n > 0$$

- e.g.,

$$3! = 3 * 2$$

$$= 3 * 2 * 1!$$

$$= 3 * 2 * 1 * 0!$$

$$= 3 * 2 * 1 * 1$$

# Iterative vs Recursive

## Iterative

```
int factorial(int n) {  
    int i, fact=1;  
    for (i=1; i<=n; i++) {  
        fact = i*fact;  
    }  
    return fact;  
}
```



# Iterative vs Recursive

## Iterative

```
int factorial(int n) {  
    int i, fact=1;  
    for (i=1; i<=n; i++) {  
        fact = i*fact;  
    }  
    return fact;  
}
```

## Recursive

```
int factorial(int n) {  
    if (n==0)  
        return 1;  
    return n*factorial(n-1);  
}
```

# Example: Vertical Number

- Input: one (non-negative) integer
- Output: integer with one digit per line, from left to right

Input	Output
12345	1 2 3 4 5
7894	7 8 9 4
4	4

# Example: Vertical Number

- An *iterative* logic flow: use a *for* loop to print each digit, from left to right
  - First, you need to know how many digits does the number have
    - i.e., how many rounds does your loop need to iterate
  - Second, you must be able to get a digit at a specific position
    - i.e., to print the i-th digit from the right in the i-th loop iteration

Input	Output
12345	1
	2
	3
	4
	5
7894	7
	8
	9
	4
4	4

# Example: Vertical Number

- An *iterative* logic flow: use a *for* loop to print each digit, from left to right
  - First, you need to know how many digits does the number have
    - i.e., how many rounds does your loop need to iterate
  - Second, you must be able to get a digit at a specific position
    - i.e., to print the i-th digit from the right in the i-th loop iteration
- *Let's develop two functions*

Input	Output
12345	1
	2
	3
	4
	5
7894	7
	8
	9
	4
4	4

# Example: Vertical Number

- How to count the number of digits in a number?

```
int countDigits(int num) {  
    int n = 1;  
  
    while ((num / pow(10, n-1)) != 0) // pow(x, y) return the result of xy as a float  
        n++;  
  
    return n;  
}
```

# Example: Vertical Number

- How to count the number of digits in a number?

*// Any problems in this code ??*

```
int countDigits(int num) {  
    int n = 1;  
  
    while ((num / pow(10, n-1)) != 0) // pow(x, y) return the result of xy as a float  
        n++;  
  
    return n;  
}
```

# Example: Vertical Number

- How to count the number of digits in a number?

*// Any problems in this code ??*

```
int countDigits(int num) {  
    int n = 1;  
  
    while ((num / pow(10, n-1)) != 0) // pow(x, y) return the result of xy as a float  
        n++;  
    // To consider the special case when num == 0  
    return max(n, 1);  
}
```

# Example: Vertical Number

- How to count the number of digits in a number?

*// Any problems in this code ??*

```
int countDigits(int num) {  
    int n = 1;  
    // Watch out implicit type conversion  
    while ((int)(num / pow(10, n-1)) != 0) // pow(x, y) return the result of xy as a float  
        n++;  
    // To consider the special case when num == 0  
    return max(n, 1);  
}
```



# Example: Vertical Number

- How to get the  $i$ -th rightmost digits of a number?

```
int getDigit(int num, int i) {  
    // Move num to the right by  $i-1$  digit(s)  
    int tmp = num / pow(10, i-1);  
    // Return the rightmost digit  
    return tmp % 10;  
}
```

# Example: Vertical Number

- Put functions together

```
int main() {  
    int num;  
    cout << "Please enter a non-negative integer: ";  
    cin >> num;  
    int numOfDigits = countDigits(num);  
    for (int i = 0; i < numOfDigits; i++)  
        cout << getDigit(num, numOfDigits-i) << endl;  
}
```

Input	Output
12345	1 2 3 4 5
7894	7 8 9 4
4	4

# Example: Vertical Number

- A *recursive* logic flow:

Given a non-negative integer of  $n$  digits

$$d_n d_{n-1} \dots d_1$$

- **STEP-1:** Solve a smaller version of the problem
  - i.e., print vertical number for  $d_n d_{n-1} \dots d_2$
- **STEP-2:** Print  $d_1$

Input	Output
12345	1 2 3 4 5
7894	7 8 9 4
4	4

# Example: Vertical Number

```
int main() {  
    int num;  
    cout << "Please enter a non-negative integer: ";  
    cin >> num;  
    printVertical(num);  
}
```

Input	Output
12345	1 2 3 4 5
7894	7 8 9 4
4	4

# Example: Vertical Number

```
void printVertical(int num) {  
    if (num >= 10) // has more than one digits  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}  
  
int main() {  
    int num;  
    cout << "Please enter a non-negative integer: ";  
    cin >> num;  
    printVertical(num);  
}
```

Input	Output
12345	1 2 3 4 5
7894	7 8 9 4
4	4

7894

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

789

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

7894

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

789

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

78

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

7894

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

789

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

78

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

7

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```



7894

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

789

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

78

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

7

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

7

7894

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

789

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

78

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

7  
8

7

7

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

7894

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

789

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    >cout << num % 10 << endl;  
}
```

7  
8  
9

78

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

7  
8

7

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

7

7894

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    > cout << num % 10 << endl;  
}
```

7  
8  
9  
4

789

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

7  
8  
9

78


```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

7  
8

7

```
void printVertical(int num) {  
    if (num >= 10)  
        printVertical(num/10);  
    cout << num % 10 << endl;  
}
```

7



# Guidelines for Recursive Functions

- Identify the **parameters**
  - e.g., *n* in the factorial, *num* in printVertical
- Find out a recurrence relation between the current problem and **a smaller version of itself** (in terms of smaller parameters)
  - e.g.,  $\text{factorial}(n) = n * \text{factorial}(n-1)$
- Find out the **base cases** and their solutions
  - e.g., for factorial  $n=0$ ; for printVertical, *num* has only one digit
  - Omitting the base case is one of the common mistakes in writing recursive functions

# Checkpoints

1. There is no infinite recursion (check **exist condition**)
2. The break down of the problem works correctly
3. For each of cases that involve recursion, if all recursive calls perform their actions correctly, then the entire case performs correctly.

# Checkpoints

	Factorial	Vertical Number
Exit condition	$n == 0$	$n < 10$
Problem break down	$\text{factorial}(n) = n * \text{factorial}(n-1)$  e.g. $n=2 \rightarrow 2! = 2 * 1!$ $n=3 \rightarrow 3! = 3 * 2!$ $n=4 \rightarrow 4! = 4 * 3!$	$\text{printDigits}(n/10);$ $\text{cout} << n \% 10;$  e.g. $n=78 \rightarrow 7$ was printed $n=789 \rightarrow 7, 8$ were printed $n=7894 \rightarrow 7, 8, 9$ were printed
If all stopping case are correct	$n!$ is returned	$n$ digits are printed



# Efficiency of Recursion

- Generally speaking, non-recursive versions will execute more efficiently (**time/space**)
  - Overhead involved in entering and exiting blocks is avoided in non-recursive solutions.
  - Also have a number of local variables and temporaries that do not have to be saved and restored via a stack.
- There are conflicts between
  - Machine efficiency and
  - Programmer efficiency

# Exercise-I: Fibonacci Number

- The Fibonacci numbers, commonly denoted  $F(n)$ , form a sequence, called the Fibonacci sequence, such that each number is the sum of the two preceding ones, starting from 0 and 1. That is,

$$F(0) = 0, F(1) = 1$$

$$F(n) = F(n-1) + F(n-2), \text{ for } n > 1$$

- Given  $n$ , calculate  $F(n)$ .

Example:


- Input:  $n = 4$
- Output:  $F(4) = 3$

# Exercise-II: Guessing Number


- Write a program to guess the number in the user's mind.
- Each round of guessing, the program should guess a number and ask the user if it is the correct number. If it is, the user should type 'Y'. Otherwise, the user should type '>' or '<' to indicate whether the guessed number is greater or smaller than the correct number.
- Solve the problem with recursion

# Exercise-III: Tower of Hanoi

- 3 towers and  $n$  disks
- the smallest disk is on top and the largest is on the bottom
- you need to move all of the disks from the first tower to the second tower
- the third tower can be used to temporarily hold disks
- only one disk can be moved at a time.
- NO larger disk is allowed atop a smaller disk




# Exercise-III: Tower of Hanoi



# Exercise-III: Tower of Hanoi

- Decompose the problem



# Exercise-III: Tower of Hanoi

```
// a:from tower, b:to tower, c: auxiliary tower
// n: number of disks to move

void Hanoi(int n, char a, char b, char c) {
    if (n == 1)                // base case
        Move(a, b);
    else {                      // recursion
        Hanoi(n-1, a, c, b); // Move top n-1 disks from A to C using B as auxiliary
        Move(a, b);          // Move the last disk from A to B
        Hanoi(n-1, c, b, a); // Move the n-1 disks on C to B using A as auxiliary
    }
}

void Move(char a, char b) {
    cout << "Move from " << a << " to " << b << endl;
}
```

# Summary

- Define, call, and declare functions
- Parameter passing
  - by value
  - By reference
- Recursive functions