

HVAC EQUIPMENT LIST

暖通设备表

PROJECT:	
PROJECT NO.:	0
UNIT:	Manufacturing Building生产栋
DOCUMENT NO.	ED-300-HVA-EQL-000-0001
REV.: 0a	SHEET: 2 of 11

No.	Tag No.	Type	Specification	Q'ty	Size (L*W*H)	Weight		E.Power				Remarks
				PC	mm	Unit Kg	Total Kg	Phase Φ	Volt V	Motor kw	Total kw	
A. Heating/Cooling Source 以下所有空调设备标注制冷能力均基于:室外温度34.4℃, 焓值=100kj/kg,出水温度6℃。												
1	CH-300-001A/B/C	Air Cooled Chiller Chilled Water Type 风冷冷水机组(单冷)	Cooling capacity冷量:700kW Capacity control range 能量调节范围: 10%~100% Refrigerant 制冷剂: R32 Compressor 压缩机: hermetic scroll compressor 全封闭涡旋压缩机 Chilled water temperature冷冻水温度: 6/11℃ Efficiency class能效等级: Class 1 Protection grade防护等级: IP55 COP≥3.4, CSPF≥4.3 Refrigeration operating environment	3	Maximum最大尺寸 6100*2380*2640(H)	4500	13500	3	380	262	786	服务于本项目 安装在屋面 每台单独供电 变频机组
2	PU-300-001A~D	Circulating Chilled Water Pump 循环冷冻水泵	Volume水量: 135m3/h Head 扬程: 30m Protection grade防护等级: IP54	4	Maximum最大尺寸 1000*500*800(H)	500	2000	3	380	18.5	55.5	服务于本项目 安装在3F空调机房内 3用1备
3	CPT-300-001	Constant Pressure Replenishing Device 补水定压装置	Diaphragm air pressure tank 隔膜罐, Tank Volume体积:>= 300 L c/w safety relief valve, necessary fittings, valves, piping and control/electrical cabinet etc.带安全阀、必要的部件、阀门、管道及控制 /电气柜等	1	HOLD	500	500	-	-	-	-	服务于本项目 安装在3F空调机房内 无水泵补水 补水为生活水, 水压P=0.3MPa (Hold)
4	DMU-300-001	Dosing Medicine Device 加药装置	循环水量: 0~400m3/h Dosage Tank 加药桶: 200Lx2	1	1850*1200*2000H	1600	1600	3	380	1	1	服务于本项目 安装在3F空调机房内
5	HS-300-001	Buffer Tank 缓冲罐	Chilled Water: 10m3×1 Design Pressure设计压力: 1.0MPa Material材质: SS304 With Pressure gauge, Termometer, Automatic exhaust valve 带压力表, 温度计及自动排气阀	1	2000*2000*3000H	13000	13000	-	-	-	-	服务于本项目 安装在3F空调机房内 带保温层

HVAC EQUIPMENT LIST
暖通设备表

PROJECT:	
PROJECT NO.:	0
UNIT:	Manufacturing Building生产栋
DOCUMENT NO.	ED-300-HVA-EQL-000-0001
REV.: 0a	SHEET: 3 of 11

No.	Tag No.	Type	Specification	Q'ty	Size (L*W*H)	Weight		E.Power				Remarks
				PC	mm	Unit Kg	Total Kg	Phase Φ	Volt V	Motor kw	Total kw	
B. Air Conditioning 以下所有空调设备标注制冷能力均基于:夏季室外温度34.4℃, 焓值=100kj/kg, 供水温度6℃/11℃; 冬季室外温度-2.5℃, 77%, 供回水温度60℃/50℃, 室内23±3, 45±5%												
1	MAU-300-001	Modular Fresh Air Handling Unit 组合式新风空调机组	Air Flow Rate总风量: 71000m³/h Fresh Air supply新风量: 71000m³/h, Run-around Coil capacity 乙二醇溶液热回收量: 165KW(夏季)365KW (冬季) Run-around Coil efficiency 热回收效率: ≥60% Pre-heating capcity热量(60/50℃): 735kW, Pre-cooling capacity预冷量(6/11℃):1260kW, Re-cooling capacity再冷量 (6/11℃):360kW Re-heating capcity再热量(60/50℃): 330kW, Static pressure机外静压: 1000Pa, Protection grade防护等级: IP55, humidifying湿膜加湿: 480kg/h (Wet master 效率>90%) Self-contain motorized damper 带同开同关电动风阀 风机变频 VFD-fan 初、中效过滤新风段 (G4+F9), 乙二醇溶液热回收段、预热段, 表冷段, 加湿段、再冷段、加热段, 送风机段, 高效过滤段 (H13), 出风段 self-contain motorized control valve and Temperature/Humidity control system 带电动水阀及温湿度控制系统	1	Maximum最大尺寸 13500*3600*2800(H)	6000	6000	3	380	110	110	服务于本项目 安装在2F空调机房 事故电源

HVAC EQUIPMENT LIST
暖通设备表

PROJECT:	
PROJECT NO.:	0
UNIT:	Manufacturing Building生产栋
DOCUMENT NO:	ED-300-HVA-EQL-000-0001
REV.: 0a	SHEET: 4 of 11

No.	Tag No.	Type	Specification	Q'ty	Size (L*W*H) mm	Weight		E.Power				Remarks
				PC		Unit Kg	Total Kg	Phase Φ	Volt V	Motor kw	Total kw	
2	MAU-300-002	Modular Fresh Air Handling Unit 组合式新风空调机组	Air Flow Rate总风量: 31500m³/h Fresh Air supply新风量: 31500m³/h, Run-around Coil capacity 乙二醇溶液热回收量: 28~56KW(夏季)/63~126KW(冬季) Run-around Coil efficiency 热回收效率: ≥60% Pre-heating capcity热量(60/50℃): 320kW, Pre-cooling capacity预冷量(6/11℃):435kW, Re-cooling capacity再冷量 (6/11℃):275kW Re-heating capcity再热量(60/50℃): 145kW,(盘管外置) Static pressure机外静压: 1000Pa, Protection grade防护等级: IP55, humidifying湿膜加湿: 210kg/h (Wet master 效率>90%) Self-contain motorized damper 带同开同关电动风阀 风机变频 VFD-fan 初、中效过滤新风段 (G4+F9), 乙二醇溶液热回收段、预热段, 表冷段, 加湿段, 再冷段、再热段、送风机段, 高效过滤段 (H13), 出风段 self-contain motorized control valve and Temperature/Humidity control system 带电动水阀及温湿度控制系统	1	Maximum最大尺寸 12500*2600*2250(H)	4000	4000	3	380	45	45	服务于本项目 安装在3F空调机房 事故电源

HVAC EQUIPMENT LIST
暖通设备表

PROJECT:	
PROJECT NO.:	0
UNIT:	Manufacturing Building生产栋
DOCUMENT NO.	ED-300-HVA-EQL-000-0001
REV.: 0a	SHEET: 5 of 11

No.	Tag No.	Type	Specification	Q'ty	Size (L*W*H) mm	Weight		E.Power				Remarks
						Unit	Total	Phase	Volt	Motor	Total	
				PC		Kg	Kg	Φ	V	kw	kw	
3	MAU-300-003	Modular Fresh Air Handling Unit 组合式新风空调机组	Air Flow Rate总风量: 2700~4650m³/h Fresh Air supply新风量: 2700~4650m³/h, Cooling capacity冷量(6/11°C):86kW, Heating capcity再热量(60/50°C): 50kW, Static pressure机外静压: 500Pa, Protection grade防护等级: IP55, Self-contain motorized damper 带同开同关电 动风阀 风机变频 VFD-fan 初、中效过滤新风段 (G4+F6), 表冷段, 加热 段, 送风机段, 出风段 self-contain motorized control valve and Temperature/Humidity control system 带电动水阀及温湿度控制系统	1	Maximum最大尺寸 4000*1200*1000(H)	2000	2000	3	380	11	11	服务于本项目 安装在3F空调机房 事故电源 平时服务于更衣间、缠包间、门厅 门斗失压时兼顾门斗正压送风用

HVAC EQUIPMENT LIST
暖通设备表

PROJECT:	
PROJECT NO.:	0
UNIT:	Manufacturing Building生产栋
DOCUMENT NO.	ED-300-HVA-EQL-000-0001
REV.: 0a	SHEET: 6 of 11

No.	Tag No.	Type	Specification	Q'ty	Size (L*W*H) mm	Weight		E.Power				Remarks
				PC		Unit Kg	Total Kg	Phase Φ	Volt V	Motor kw	Total kw	
4	FFU-300-101~104	Ex-proof Fan Filter Unite 防爆风机过滤单元	Air Flow Rate总风量: 2000m³/h Static pressure风机总静压: 300Pa, Protection grade防护等级: IP55, Noise 噪音: <48dB(A) Filter过滤器: U16(≥99.99995@0.1µm) Initial Pressure Loss初压损: 120Pa@0.45m/s 1170*1170*70mm(带加强筋型式) PTFE/FM certificated Continuously Variable Transmission 无极调速 Aluminum-zinc-coated box镀铝锌外壳箱体 双面EPDM灰色密封垫片, 双面护面网, 含运 行指示灯和故障指示灯, 风机入口加初效保护 棉 安装方式:垫片机械式密封安装 EBM DC motor EBM 直流电机 电脑群组控制 Explosive-proof grade防爆等级: ExdIBT4 Gb	4	Maximum最大尺寸 1175*1175*270(H)	70	280	1	220	0.3	1.2	服务于 Air lock 3 安装在门斗三吊顶上 事故电源

HVAC EQUIPMENT LIST
暖通设备表

PROJECT:	
PROJECT NO.:	0
UNIT:	Manufacturing Building生产栋
DOCUMENT NO	ED-300-HVA-EQL-000-0001
REV.: 0a	SHEET: 7 of 11

No.	Tag No.	Type	Specification	Q'ty	Size (L*W*H) mm	Weight		E.Power				Remarks
				PC		Unit Kg	Total Kg	Phase Φ	Volt V	Motor kw	Total kw	
5	HRU-300-001	Heating Recovery Unit 热回收系统	Type 型式: Run-around Coil System 溶液循环式热回收 'Fresh Air Flow Rate新风量: 71000m³/h (盘管 内置于MAU-300-001) Temperatrue/Humidity新风温湿度: 34.4°C/28.3°C (夏) 极端38.8°C -2.5°C/77% (冬) 极端-8.3°C Exhaust Air Flow Rate排风量: 70280m³/h (盘 管置于EF-300-001A/B排风主管) Temperatrue排风干、温球温度: 23±2°C/45±5% (全年) Efficiency效率: > 60% Run-around Coil capacity乙二醇溶液热回收量: Summer 夏季:165kW, Winter 冬季 :365kW, Circulating Chilled Water Pump 循环冷冻水泵 Medium 介质: 28% Ethylene glycol solution 乙二醇水溶液 'Volume水量: XXm³/h(HOLD) Head 扬程: 10m	1	Maximum最大尺寸 XX*XX*XX(H) (泵组尺寸HOLD)	100	100	3	380	3	3	服务于本项目 安装在2F空调机房 水泵一开一备 带控制系统含电控柜、控制阀门、各 类传感器等

HVAC EQUIPMENT LIST
暖通设备表

PROJECT:	
PROJECT NO.:	0
UNIT:	Manufacturing Building生产栋
DOCUMENT NO.	ED-300-HVA-EQL-000-0001
REV.: 0a	SHEET: 8 of 11

No.	Tag No.	Type	Specification	Q'ty PC	Size (L*W*H) mm	Weight		E.Power				Remarks
						Unit Kg	Total Kg	Phase Φ	Volt V	Motor kw	Total kw	
6	HRU-300-002	Heating Recovery Unit 热回收系统	Type 型式: Run-around Coil System 溶液循环式热回收 'Fresh Air Flow Rate新风量: 31500m³/h (盘管 内置于MAU-300-002) Temperatrue/Humidity新风温湿度: 34.4°C/28.3°C (夏) 极端38.8°C -2.5°C/77% (冬) 极端-8.3°C Exhaust Air Flow Rate排风 量:12300~24500m³/h (盘管置于EF-300- 002A/B排风主管) Temperatrue排风干、湿球温度: 23±2°C/45±5% (全年) Efficiency效率: > 60% Run-around Coil capacity乙二醇溶液热回收量: Summer 夏季:28~56kW, Winter 冬季 :63~126kW, Circulating Chilled Water Pump 循环冷冻水泵 Medium 介质: 28% Ethylene glycol solution 乙二醇水溶液 'Volume水量: XXm³/h(HOLD)	1	Maximum最大尺寸 XX*XX*XX(H) (泵组尺寸HOLD)	100	100	3	380	3	3	服务于Future 本期不采购 安装在3F空调机房 水泵一开一备 带控制系统含电控柜、控制阀门、各 类传感器等
C. FAN												
1	EF-300-002A/B	Ex-proof Centrifugal Fan Box 防爆型离心风机箱	Volume风量: 12300~24500m³/h, Static pressure静压: 800Pa Noise噪音≤71 dB(A) Protection grade防护等级: IP55 Explosive-proof grade防爆等级: Ex db IIB T4 Gb 风机变频VFD Fan EFF.风机能效: Class 1(GB 19761-2020) Motor EFF.电机能效: Class 1(GB18613-2020)	2	1100*1100*1100	327	654	3	380	15	30	服务于Manufacturing Room 制造室 安装在屋面 一开一备 事故电源

红框内为非洁 净区设备			HVAC EQUIPMENT LIST 暖通设备表						PROJECT:			
									PROJECT NO.:		0	
									UNIT:		Manufacturing Building生产栋	
									DOCUMENT NO.:		ED-300-HVA-EQL-000-0001	
									REV.: 0a		SHEET:	
No.	Tag No.	Type	Specification	Q'ty	Size (L*W*H)	Weight		E.Power				Remarks
				PC	mm	Unit Kg	Total Kg	Phase Φ	Volt V	Motor kw	Total kw	
2	EF-300-001A/B	Ex-proof Centrifugal Fan Box 防爆型离心风机箱	Volume风量:70280m3/h, Static pressure静压: 800Pa Noise噪音≤80 dB(A) Protection grade防护等级: IP55 Explosive-proof grade防爆等级: Ex db IIB T4 Gb Fan EFF.风机能效: Class 1(GB 19761-2020) Motor EFF.电机能效: Class 1(GB18613-2020)	2	1830*1700*1550	630	1260	3	380	30	30	服务于Bottling Room装瓶室 安装在屋面 一开一备 事故电源
3	EF-300-202	Ex-proof Sidewall Exhaust Fan 防爆型边墙排风机	Volume风量: 1650m3/h, Static pressure静压: 50Pa Noise噪音≤62 dB(A) Protection grade防护等级: IP55 Explosive-proof grade防爆等级: Ex db IIB T4 Gb Fan EFF.风机能效: Class 1(GB 19761-2020) Motor EFF.电机能效: Class 1(GB18613-2020)	1	400*400*465	34	34	3	380	0.12	0.12	服务于EV Machine Room 电梯机房 安装在设备间外墙
4	EF-300-103/104	Ceiling Ventilator 金属天花管道换气扇	Volume风量: 430m3/h, Static pressure静压: 200Pa, Noise噪声: ≤42 dB(A), Protection grade防护等级: IP44, Fan EEG风机能效: 1级 (GB 32049-2015) 配止回阀及外气口Ø150	2	368*368*258	5.5	11	1	220	0.07	0.14	服务于Toilet (M/W)男女卫生间 安装在卫生间室内
5	EF-300-201A~B	Sidewall Exhaust Fan 边墙排风机	Volume风量: 4000m3/h, Static pressure静压: 50Pa Noise噪声: ≤68dB(A) Protection grade防护等级: IP55 Fan EEG风机能效: 1级 (GB 19761-2020) Motor EEG电机能效: 1级 (GB18613-2020) 配45度防雨弯头、防虫网及止回阀	2	1000*600*600	52.5	105	3	380	0.37	0.74	服务于2F HVAC Room1 暖通设备间 一 安装在机房外墙
6	EF-300-301A~B	Sidewall Exhaust Fan 边墙排风机	Volume风量: 4000m3/h, Static pressure静压: 50Pa Noise噪声: ≤68dB(A) Protection grade防护等级: IP55 Fan EEG风机能效: 1级 (GB 19761-2020) Motor EEG电机能效: 1级 (GB18613-2020) 配45度防雨弯头、防虫网及止回阀	2	1000*600*600	52.5	105	3	380	0.37	0.74	服务于3F HVAC Room 2 暖通设备间 二 安装在机房外墙

HVAC EQUIPMENT LIST
暖通设备表

PROJECT:	
PROJECT NO.:	0
UNIT:	Manufacturing Building生产栋
DOCUMENT NO.	ED-300-HVA-EQL-000-0001
REV.: 0a	SHEET: 10 of 11

No.	Tag No.	Type	Specification	Q'ty	Size (L*W*H) mm	Weight		E.Power				Remarks
				PC		Unit Kg	Total Kg	Phase Φ	Volt V	Motor kw	Total kw	
7	EF-300-102	Explosion-proof Sidewall Exhaust Fan 防爆型边墙排风机	Volume风量: 3750m3/h, Static pressure静压: 100Pa Noise噪声: ≤68dB(A) Explosive-proof grade防爆等级: Exd IIBT4 Gb 电机直联 Protection grade防护等级: IP55 Fan EEG风机能效: 1级 (GB 19761-2020) Motor EEG电机能效: 1级 (GB18613-2020) 配45度防雨弯头、防虫网及止回阀	1	1150*650*650	59	59	3	380	0.37	0.37	服务于manufacturing room (future) 制造室（预留） 安装在外墙
8	EF-300-101	Ex-proof Sidewall Exhaust Fan 防爆型边墙排风机	Volume风量: 360m3/h, Static pressure静压: 50Pa Noise噪声: ≤66dB(A) Protection grade防护等级: IP55 Explosive-proof grade防爆等级: Ex db IIB T4 Gb Fan EEG风机能效: 1级 (GB 19761-2020) Motor EEG电机能效: 1级 (GB18613-2020) 配45度防雨弯头、防虫网及止回阀	1	965*550*550	48	48	3	380	0.25	0.25	服务于Holding Room 准备间 安装在外墙
9	SF-300-301A/B	Explosion-proof Sidewall Exhaust Fan 防爆型边墙排风机	Volume风量:850m3/h, Static pressure静压: 50Pa Noise噪音≤60 dB(A) Protection grade防护等级: IP55 Explosive-proof grade防爆等级: Ex db IIB T4 Gb Fan EFF.风机能效: Class 1(GB 19761-2020) Motor EFF.电机能效: Class 1(GB18613-2020) 配90度防雨弯头、防虫网及止回阀	2	965*550*550	48	96	3	380	0.25	0.5	服务于 Air Lock 6 门斗六 安装在外墙 事故电源
10	EF-300-105	Ex-proof Sidewall Exhaust Fan 防爆型边墙排风机	Volume风量: 1100m3/h, Static pressure静压: 150Pa Noise噪声: ≤66dB(A) Explosive-proof grade防爆等级: Exd IIBT4 Gb 电机直联 Protection grade防护等级: IP55 Fan EEG风机能效: 1级 (GB 19761-2020) Motor EEG电机能效: 1级 (GB18613-2020) 配45度防雨弯头、防虫网及止回阀	1	965*550*550	48	48	3	380	0.25	0.25	服务于Product Wrapping Room缠包间 安装在外墙 事故电源

HVAC EQUIPMENT LIST
暖通设备表

PROJECT:	
PROJECT NO.:	0
UNIT:	Manufacturing Building生产栋
DOCUMENT NO.	ED-300-HVA-EQL-000-0001
REV.: 0a	SHEET: 11 of 11

No.	Tag No.	Type	Specification	Q'ty PC	Size (L*W*H) mm	Weight		E.Power				Remarks
						Unit Kg	Total Kg	Phase Φ	Volt V	Motor kw	Total kw	
11	EF-300-106	Ex-proof Sidewall Exhaust Fan 防爆型边墙排风机	Volume风量: 1500m3/h, Static pressure静压: 150Pa Noise噪声: ≤66dB(A) Explosive-proof grade防爆等级: Exd IIBT4 Gb 电机直联 Protection grade防护等级: IP55 Fan EEG风机能效: 1级 (GB 19761-2020) Motor EEG电机能效: 1级 (GB18613-2020) 配45度防雨弯头、防虫网及止回阀	1	965*550*550	48	48	3	380	0.25	0.25	服务于Product Wrapping Room缠包间 安装在外墙 事故电源
12	EF-300-107	Ceiling Ventilator 金属天花管道换气扇	Volume风量: 210m3/h, Static pressure静压: 120Pa, Noise噪声: ≤40 dB(A), Protection grade防护等级: IP44, Fan EEG风机能效: 1级 (GB 32049-2015) 配止回阀及外气口Ø100	1	300*300*208	4.2	4.2	1	220	0.032	0.032	服务于Storage RM 储藏室 安装在储藏室室内