Algorithm Cheat Sheet — All Templates + Java Syntax

Conventions, Skeleton & Core API

Generic Test Harness

```
class Question {
    // —— PROBLEM-SOLVING PROCESS

    // 1. INPUT / OUTPUT   : types, sizes,
ranges; what to return; examples.
    // 2. HIGH-LEVEL ALGO : pick the
pattern (two-ptr / BFS / DP / ...); state
the idea in 1 line.
    // 3. IMPLEMENTATION  : data
structures, loop/recursion, invariants.
    // 4. EDGE CASES      : empty, size
0/1, duplicates, negatives, overflow,
all-same, not-found.
    // 5. COMPLEXITY      : time & space;
is it within limits?
    // 6. OPTIMIZATION    : reduce
time/space (hashing, two-pointer, rolling
array, pruning, early exit).
    //

    private int data;
    public Question(int data) {
        this.data = data;
    }
    public void solve() {
        // TODO
    }
}
public class Solution {
    public static void main(String[]
args) {
        Question q = new Question(0);
        q.solve();
    }
}
```

Naming Conventions (enforced across all template files)

Common Java API Cheat-Sheet

```
Map<Integer, Integer> map    = new
HashMap<>();      // key → value
Map<Integer, List<Integer>> adj = new
HashMap<>();  // adjacency / buckets
Set<Integer> set             = new
HashSet<>();     // membership
List<Integer> list           = new
ArrayList<>();     // dynamic array
Deque<Integer> stack = new ArrayDeque<>
();          // STACK: push / pop / peek
Deque<Integer> queue = new ArrayDeque<>
();          // QUEUE: offer / poll /
peek

// (ArrayDeque beats java.util.Stack /
LinkedList)
PriorityQueue<Integer> minHeap = new
PriorityQueue<>();
// min-heap (default)
PriorityQueue<Integer> maxHeap = new
PriorityQueue<>
(Collections.reverseOrder()); // max-heap
PriorityQueue<int[]>   pq      = new
PriorityQueue<>((a, b) -> a[1] - b[1]);
// by field, min-first
TreeMap<Integer, Integer> tmap = new
TreeMap<>();    // sorted keys:
floor/ceiling/first/last
TreeSet<Integer> tset          = new
TreeSet<>();    // sorted set:
floor/ceiling/higher/lower
LinkedHashSet<Integer> lset    = new
LinkedHashSet<>(); // insertion-ordered
set (LFU buckets)
Random rand                    = new
Random();       // rand.nextInt(n) →
0..n-1 (RandomizedSet)
int[]       arr   = new int[n];
// defaults to 0
boolean[]   seen = new boolean[n];
// defaults to false
int[][]     grid = new int[m][n];
// 2D, all 0
int[]       dr   = {1,-1,0,0}, dc =
{0,0,1,-1};  // DOWN,UP,RIGHT,LEFT;
iterate for(dir=0..3) i+dr[dir],j+dc[dir]
```

```
// —— Map ——
map.put(k, v);
map.getOrDefault(k, 0);
// safe read with default
map.merge(k, 1, Integer::sum);
// ← counting frequency (most common)
map.computeIfAbsent(k, x -> new
ArrayList<>()).add(v); // ← build
adjacency / buckets
map.putIfAbsent(k, v);
// ← write only first occurrence (keep
earliest index)
map.containsKey(k);  map.remove(k);
for (Map.Entry<Integer,Integer> e :
map.entrySet()) { e.getKey();
e.getValue(); e.setValue(v); }
map.keySet();  map.values();
// —— Set ——
set.add(x);  set.contains(x);
set.remove(x);
// —— List ——
list.add(x);  list.get(i);  list.set(i,
x);
list.remove(list.size() - 1);
// ← pop in backtracking
list.size();  list.isEmpty();
list.addAll(other);
Collections.sort(list);
// ascending
list.sort((a, b) -> b - a);
// custom / descending
Collections.reverse(list);
// ← reverse path after building it
backwards
```

```
// Deque as STACK (LIFO)            //
Deque as QUEUE (FIFO)
stack.push(x);
queue.offer(x);
int top = stack.pop();               int
head = queue.poll();
int look = stack.peek();             int
look = queue.peek();
stack.isEmpty();
queue.isEmpty();
// Deque BOTH ENDS — needed for the
MONOTONE DEQUE (sliding-window max/min)
// and for addFirst-style level building
(zigzag BFS).
deque.offerLast(x);   deque.pollLast();
deque.peekLast();   // back
(push/pop/peek tail)
deque.offerFirst(x);  deque.pollFirst();
deque.peekFirst();  // front
(push/pop/peek head)
deque.addLast(x);     deque.addFirst(x);
// same as offer*, throw if capacity-
bound
// PriorityQueue (heap)
pq.offer(x);  int best = pq.poll();  int
look = pq.peek();  pq.size();
pq.remove(x); // ← O(n) removal of an
arbitrary element (lazy-deletion
alternative in #480)
```

```
Integer.MAX_VALUE;   //  2147483647
(2^31 - 1)    — sentinel for "min so far"
Integer.MIN_VALUE;   // -2147483648
(-2^31)       — sentinel for "max so far"
Long.MAX_VALUE;      // when sums can
overflow int, accumulate in long
int k = i + (j - i) / 2;             //
← avoid (i + j) overflow in binary search
Integer.compare(a, b);               //
← overflow-safe comparator; use instead
of (a - b)
(a, b) -> Integer.compare(a[1], b[1]);//
← safe PriorityQueue/Arrays.sort
comparator
Double.compare(a, b);                //
← comparator for double[] heaps
(probability, median)
```

```
ch - 'a';                            //
'a'..'z'  → 0..25   (lowercase bucket
index)
ch - '0';                            //
'0'..'9'  → 0..9    (digit value)
(char) ('a' + i);                    //
0..25 → 'a'..'z'
num = num * 10 + (ch - '0');         // ←
build a number digit by digit
Integer.parseInt("123");             //
String → int (throws on bad input)
Integer.valueOf(123);                //
int → Integer (boxed)
String.valueOf(123);                 //
int/char/etc → String
Character.getNumericValue('7');      //
char → 7
// char classification
Character.isDigit(ch);
Character.isLetter(ch);
Character.isLetterOrDigit(ch);
Character.isWhitespace(ch);
Character.toLowerCase(ch);
Character.toUpperCase(ch);
```

```
s.length();  s.charAt(i);  s.substring(i,
j);        // [i, j)
s.toCharArray();  s.split(" ");
s.equals(t);  s.compareTo(t);
s.indexOf("ab");  s.isEmpty();
s.startsWith("ab");  s.endsWith("z");
s.contains("x"); // prefix / suffix /
substring tests
s.toLowerCase();  s.toUpperCase();
// case-normalize (e.g. case-insensitive
compare)
s.trim();  s.replace('a', 'b');
s.repeat(n);         // strip ends / swap
chars / repeat
StringBuilder builder = new
StringBuilder();
builder.append(x);  builder.reverse();
builder.toString();
builder.charAt(i);  builder.setCharAt(i,
c);  builder.deleteCharAt(i);
builder.length();
String.join(",", list);
// list → "a,b,c"
```

```
Arrays.sort(arr);
// ascending in place
Arrays.sort(intervals, (a, b) -> a[0] -
b[0]);       // 2D by first field
Arrays.fill(dp, Integer.MAX_VALUE);
// seed a dp/dist array
Arrays.equals(window, need);
// ← element-wise array compare (anagram
check)
Arrays.copyOf(arr, len);
Arrays.copyOfRange(arr, i, j);
System.arraycopy(src, srcPos, dst,
dstPos, len);     // ← fast block copy
(merge step)
Arrays.asList(1, 2, 3);
// fixed-size List view
int sum = Arrays.stream(arr).sum();
int max =
Arrays.stream(arr).max().getAsInt();
// List<Integer> ↔ int[]
int[] a =
list.stream().mapToInt(Integer::intValue)
.toArray();
List<Integer> l =
Arrays.stream(a).boxed().collect(Collecto
rs.toList());
```

```
Math.max(a, b);  Math.min(a, b);
Math.abs(x);
Math.pow(a, b);  Math.sqrt(x);
Math.ceil(x);  Math.floor(x);
n & (n - 1);            // clear lowest set
bit
n & (-n);               // isolate lowest
set bit
1 << i;                 // bit i set  (use
1L << i for i ≥ 31)
(n >> i) & 1;           // read bit i
(n & 1) == 0;           // ← even   (last
bit 0)
(n & 1) == 1;           // ← odd    (last
bit 1)
n >> 1;                 // ← divide by 2
(drop last bit);  n << 1 = multiply by 2
Integer.bitCount(n);  // # of set bits
Integer.toBinaryString(n);
```

```
tmap.firstKey();  tmap.lastKey();
tmap.floorKey(x);    // largest key ≤ x
tmap.ceilingKey(x);  // smallest key ≥ x
tmap.lowerKey(x);    // largest key < x
tmap.higherKey(x);   // smallest key > x
tset.floor(x);  tset.ceiling(x);
tset.lower(x);  tset.higher(x);
tset.first();  tset.last();
```

```
// —— NEGATIVE-SAFE MODULO —— replaces
the manual ((x % n) + n) % n
Math.floorMod(x, n);                   //
always in [0, n-1] even when x < 0
(prefix-sum % k)
// —— int[] INSTEAD OF HashMap for a
bounded key space ——
int[] count = new int[26];             //
O(1) no-boxing freq vs
HashMap<Character,Integer>
count[ch - 'a']++;                     //
also faster to compare: Arrays.equals(a,
b)
// —— 1D ROLLING ARRAY for DP —— drop a
dimension when row i only needs row i-1
int[] dp = new int[n + 1];             //
O(n) space instead of O(m·n)
for (...) for (int j = target; j >= w; j-
-) dp[j] += dp[j - w];  // 0/1 knapsack:
iterate j DOWN
// —— FIXED-SIZE HEAP for top-k —— O(n
log k) beats sorting O(n log n)
if (heap.size() > k) heap.poll();      //
keep only k best; min-heap for "k
largest"
// —— LAZY DELETION over pq.remove(obj)
—— pq.remove is O(n); skip stale entries
instead
if (entry[0] != dist[node]) continue; //
Dijkstra: ignore outdated heap entries
// —— ArrayDeque over Stack / LinkedList
—— faster, no synchronization, both ends
O(1)
Deque<Integer> stack = new ArrayDeque<>
();   // never use java.util.Stack
// —— StringBuilder over String += in a
loop —— O(n) vs O(n²)
StringBuilder builder = new
StringBuilder();      // append, then
builder.toString() once
// —— EARLY EXIT / PRUNING —— return the
moment the answer is decided
if (found) return result;              //
e.g. backtracking bounds
```

Template Index

Two Pointers

Pattern 1 — Opposite Two Pointers

```
int i = 0, j = n - 1;
while (i < j) {
    if (condition == target) {
        /* record */ i++; j--;
    } else if (tooSmall) {
        i++;
    } else {
        j--;
    }
}
```

Sliding Window

The Three Templates

```
int i = 0;
for (int j = 0; j < n; j++) {
    // 1. add nums[j] to state
    if (j - i + 1 == k) {
        // 2. record (window is exactly
size k)
        // 3. remove nums[i] from state
        i++;
    }
}
int i = 0, result = 0;
for (int j = 0; j < n; j++) {
    // 1. add nums[j] to state
    while (/* window exceeds constraint
*/) {
        i++;
    }
    result = Math.max(result, j - i + 1);
}
int i = 0, result = Integer.MAX_VALUE;
for (int j = 0; j < n; j++) {
    // 1. add nums[j] to state
    while (/* window VALID */) {
        result = Math.min(result, j - i +
1);
        i++;
    }
}
```

Frequency Map Trick (used by 567 and 76)

```
if (need[s.charAt(j)]-- > 0) required--;
if (need[s.charAt(i)]++ >= 0) required++;
i++;
```

Prefix Sum + HashMap

Core Template

```
Map<Long, Integer> map = new HashMap<>();
map.put(0L, ???);
long sum = 0;
for (int i = 0; i < nums.length; i++) {
    sum += nums[i];
    long lookup = transform(sum);
    map.put(storeKey(sum),
storeValue(i)); // what to store (sum or
sum%k → count or index)
}
```

Binary Search

The Only Template — `[i, j)`, find first k with `condition(k)`

```
int i = 0, j = nums.length;
while (i < j) {
    int k = i + (j - i) / 2;
    if (!condition(k)) {
        i = k + 1;
    } else {
        j = k;
    }
}
```

How to Choose

Sorting

Template 1 — Merge Sort

```
public void mergeSort(int[] nums) {
    mergeSort(nums, 0, nums.length, new
int[nums.length]);
}
private void mergeSort(int[] nums, int
start, int end, int[] temp) {
    if (end - start <= 1) return;
    int mid = start + (end - start) / 2;
    mergeSort(nums, start, mid, temp);
    mergeSort(nums, mid,   end, temp);
    merge(nums, start, mid, end, temp);
}
private void merge(int[] nums, int start,
int mid, int end, int[] temp) {
    int i = start, j = mid, k = start;
    while (i < mid || j < end) {
        if (j >= end || (i < mid &&
nums[i] <= nums[j])) {
            temp[k++] = nums[i++];
        } else {
            temp[k++] = nums[j++];
        }
    }
    for (i = start; i < end; i++) nums[i]
= temp[i];
}
```

Template 2 — Quick Sort (3-way Dutch Flag Partition)

```
public void quickSort(int[] nums) {
    quickSort(nums, 0, nums.length);
}
private void quickSort(int[] nums, int
start, int end) {
    if (end - start <= 1) return;
    int pivot = nums[start + (end -
start) / 2];
    int i = start, k = start, j = end -
1;
    while (k <= j) {
        if (nums[k] < pivot) {
            swap(nums, k++, i++);
        } else if (nums[k] == pivot) {
            k++;
        } else {
            swap(nums, k, j--);
        }
    }
    quickSort(nums, start, i);
    quickSort(nums, k, end);
}
private void swap(int[] nums, int i, int
j) {
    int t = nums[i]; nums[i] = nums[j];
nums[j] = t;
}
```

Template 3 — Quick Select (partial sort — k-th element)

```
private int quickSelect(int[] nums, int
start, int end, int target) {
    int pivot = nums[start + (end -
start) / 2];
    int i = start, k = start, j = end -
1;
    while (k <= j) {
        if (nums[k] < pivot) {
            swap(nums, k++, i++);
        } else if (nums[k] == pivot) {
            k++;
        } else {
            swap(nums, k, j--);
        }
    }
    if (target < i) {
        return quickSelect(nums, start,
i, target);
    } else if (target < k) {
        return pivot;
    } else {
        return quickSelect(nums, k, end,
target);
    }
}
```

Template 4 — Counting Sort

```
public void countingSort(int[] arr) {
    if (arr.length == 0) return;
    int min =
Arrays.stream(arr).min().getAsInt();
    int max =
Arrays.stream(arr).max().getAsInt();
    int[] buckets = new int[max - min +
1];
    for (int x : arr) buckets[x - min]++;
    int i = 0;
    for (int v = 0; v < buckets.length;
v++)
        while (buckets[v]-- > 0) arr[i++]
= v + min;
}
```

Linked List

When to Use — Signal → Pattern

All Four Templates

```
// 1. DELETE / FILTER  — sentinel guards
head removal; previous tracks last kept
node
ListNode sentinel = new ListNode(0);
sentinel.next = head;
ListNode previous = sentinel, current =
head;
while (current != null) {
    if (shouldDelete(current)) {
        previous.next = current.next;
    } else {
        previous = current;
    }
    current = current.next;
}
return sentinel.next;
// 2. REVERSAL — re-wire one node at a
time
ListNode previous = null, current = head;
while (current != null) {
    ListNode next = current.next;
    current.next = previous;
    previous = current;
    current = next;
}
return previous;
// 3. FAST / SLOW — two pointers at
different speeds
ListNode slow = head, fast = head;
while (fast != null && fast.next != null)
{
    slow = slow.next;
    fast = fast.next.next;
}
// 4. MERGE — sentinel collects nodes
from two lists in order
ListNode sentinel = new ListNode(0);
ListNode current = sentinel;
while (a != null && b != null) {
    if (a.val <= b.val) {
        current.next = a;
        a = a.next;
    } else {
        current.next = b;
        b = b.next;
    }
    current = current.next;
}
current.next = (a != null) ? a : b;
return sentinel.next;
```

String

Core Idioms

```
// 1. CHAR COUNT — lowercase letters
int[] count = new int[26];
for (char ch : s.toCharArray()) count[ch
- 'a']++;
// 2. CHAR COUNT — digits 0-9
int[] count = new int[10];
for (char ch : s.toCharArray()) count[ch
- '0']++;
// 3. CHAR TO INTEGER — build number
digit by digit
int num = 0;
for (int i = 0; i < s.length(); i++)
    num = num * 10 + (s.charAt(i) - '0');
// 4. ANAGRAM HASH KEY — frequency-based
(bucket sort style) O(k) vs sort O(k log
k)
String hashKey(String s) {
    int[] count = new int[26];
    for (char ch : s.toCharArray())
count[ch - 'a']++;
    StringBuilder builder = new
StringBuilder();
    for (int i = 0; i < 26; i++) {
        builder.append((char)('a' + i));
        builder.append(count[i]);
    }
    return builder.toString();
}
char[] chars = s.toCharArray();
Arrays.sort(chars);
String key = new String(chars);
// 5. BUCKET SORT — sort by frequency
without comparison sort
int[] count = new int[128];
for (char ch : s.toCharArray())
count[ch]++;
List<Character>[] buckets = new
List[s.length() + 1]; // index =
frequency
for (int i = 0; i < 128; i++) {
    if (count[i] > 0) {
        int freq = count[i];
        if (buckets[freq] == null)
buckets[freq] = new ArrayList<>();
        buckets[freq].add((char) i);
    }
}
StringBuilder builder = new
StringBuilder();
for (int freq = buckets.length - 1; freq
> 0; freq--) {
    if (buckets[freq] == null) continue;
    for (char ch : buckets[freq])
        for (int i = 0; i < freq; i++)
builder.append(ch);
}
// 6. EXPAND FROM CENTER — palindrome
check in O(1) space
int expand(String s, int i, int j) {
    while (i >= 0 && j < s.length() &&
s.charAt(i) == s.charAt(j)) { i--; j++; }
    return j - i - 1;
}
```

Stack / Queue / Heap

All Templates

```
// 1. STACK (LIFO) — use ArrayDeque, not
Stack class
Deque<Integer> stack = new ArrayDeque<>
();
stack.push(x);
stack.pop();
stack.peek();
// 2A. MONOTONE DECREASING STACK — next
GREATER element
Deque<Integer> stack = new ArrayDeque<>
();
for (int i = 0; i < n; i++) {
    while (!stack.isEmpty() &&
nums[stack.peek()] < nums[i])
        result[stack.pop()] = nums[i];
    stack.push(i);
}
// 2B. MONOTONE INCREASING STACK — next
SMALLER element / span width
Deque<Integer> stack = new ArrayDeque<>
();
for (int i = 0; i < n; i++) {
    while (!stack.isEmpty() &&
nums[stack.peek()] > nums[i]) {
        int height = nums[stack.pop()];
        int width  = stack.isEmpty() ? i
: i - stack.peek() - 1;
    }
    stack.push(i);
}
// 3. MONOTONE DEQUE — sliding window
max/min
Deque<Integer> queue = new ArrayDeque<>
();
for (int i = 0; i < n; i++) {
    while (!queue.isEmpty() &&
nums[queue.peekLast()] <= nums[i])
        queue.pollLast();
    queue.offerLast(i);
    if (queue.peekFirst() < i - k + 1)
queue.pollFirst();
    if (i >= k - 1) result[i - k + 1] =
nums[queue.peekFirst()];
}
// 4. PRIORITY QUEUE
PriorityQueue<Integer> minPQ = new
PriorityQueue<>();
PriorityQueue<Integer> maxPQ = new
PriorityQueue<>
(Collections.reverseOrder()); // max-heap
PriorityQueue<int[]>    pq    = new
PriorityQueue<>((a, b) -> a[1] - b[1]);
// custom: sort by index 1
pq.offer(x);
pq.poll();
pq.peek();
// 5. TWO HEAPS — maintain median in
O(log n)
PriorityQueue<Integer> maxHeap = new
PriorityQueue<>
(Collections.reverseOrder());
PriorityQueue<Integer> minHeap = new
PriorityQueue<>();
void addNum(int num) {
    maxHeap.offer(num);
    minHeap.offer(maxHeap.poll());
    if (maxHeap.size() < minHeap.size())
        maxHeap.offer(minHeap.poll());
}
double findMedian() {
    return maxHeap.size() >
minHeap.size()
        ? maxHeap.peek()
        : (maxHeap.peek() +
minHeap.peek()) / 2.0;
}
```

BFS (Tree)

The Template — Level-Aware BFS

```
Queue<TreeNode> queue = new ArrayDeque<>
();
queue.offer(root);
int level = 0;
while (!queue.isEmpty()) {
    int size = queue.size();
    level++;
    for (int i = 0; i < size; i++) {
        TreeNode node = queue.poll();
        if (node.left  != null)
queue.offer(node.left);
        if (node.right != null)
queue.offer(node.right);
    }
}
```

When to Use — Signal → Pattern

The One Rule — Snapshot Level Size First

```
Always snapshot the level size BEFORE the
inner for loop:
    int size = queue.size();
    for (int i = 0; i < size; i++) { ...
}
Without the snapshot, newly added
children mix with the current level
and i == size-1 / i == 0 checks become
meaningless.
```

DFS / Backtracking

When to Use — Signal → Pattern

All Templates

```
// 1. PROCESS CHILDREN FIRST, COMBINE AT
NODE (post-order)
private int dfs(TreeNode node) {
    if (node == null) return BASE;
    int left  = dfs(node.left);
    int right = dfs(node.right);
    return ...;
}
// 2. PROCESS NODE FIRST, PASS STATE DOWN
(pre-order)
private void dfs(TreeNode node, int
accumulated) {
    if (node == null) return;
    accumulated += node.val;
    if (isLeaf(node)) { /* record */
return; }
    dfs(node.left,  accumulated);
    dfs(node.right, accumulated);
}
// 3. TREE — GLOBAL ANSWER (return up the
best single arm; update global across
both arms)
int answer = Integer.MIN_VALUE;
private int dfs(TreeNode node) {
    if (node == null) return 0;
    int left  = Math.max(0,
dfs(node.left));
    int right = Math.max(0,
dfs(node.right));
    answer = Math.max(answer, left +
right + node.val);
    return Math.max(left, right) +
node.val;
}
// 4. GRID DFS — mark visited by mutating
grid; 4-directional flood fill
private void dfs(int[][] grid, int r, int
c) {
    if (r < 0 || r >= grid.length || c <
0 || c >= grid[0].length) return;
    if (grid[r][c] != TARGET) return;
    grid[r][c] = VISITED;
    dfs(grid, r+1, c); dfs(grid, r-1, c);
    dfs(grid, r, c+1); dfs(grid, r, c-1);
}
// 5. GRAPH DFS — 3-color visited:
0=unseen 1=in-stack 2=done
int[] state;
private boolean dfs(int node) {
    if (state[node] == 1) return true;
    if (state[node] == 2) return false;
    state[node] = 1;
    for (int neighbor : graph.get(node))
        if (dfs(neighbor)) return true;
    state[node] = 2;
    return false;
}
// 6. BACKTRACKING — choose / recurse /
undo
private void backtrack(int start,
List<Integer> current) {
    if (baseCase) { result.add(new
ArrayList<>(current)); return; }
    for (int i = start; i < n; i++) {
        if (skipCondition(i)) continue;
        current.add(nums[i]);
        backtrack(next, current);
        current.remove(current.size()-1);
    }
}
```

Graph

Complexity Legend

```
BFS / DFS          O(V + E)
visit each vertex and edge once
Topo sort (Kahn)   O(V + E)
each node enqueued once, each edge
relaxed once
Union-Find         ~O(n·α(n)) ≈ O(n)   α =
inverse Ackermann, effectively constant
Dijkstra           O((V + E) log V)
non-negative weights ONLY
```

Graph Representation

```
List<List<Integer>> graph = new
ArrayList<>();
for (int i = 0; i < n; i++) graph.add(new
ArrayList<>());
for (int[] edge : edges) {
    graph.get(edge[0]).add(edge[1]);
    graph.get(edge[1]).add(edge[0]);
}
List<List<int[]>> graph = new ArrayList<>
();
for (int i = 0; i < n; i++) graph.add(new
ArrayList<>());
for (int[] edge : edges)
    graph.get(edge[0]).add(new int[]
{edge[1], edge[2]});
int[] dr = {1, -1, 0,  0};
int[] dc = {0,  0, 1, -1};
```

Core Templates

```
// 1. BFS — shortest path / level order
(track distance by level-size snapshot)
Queue<Integer> queue = new ArrayDeque<>
();
boolean[] visited = new boolean[n];
queue.offer(start);
visited[start] = true;
int level = 0;
while (!queue.isEmpty()) {
    int size = queue.size();
    for (int i = 0; i < size; i++) {
        int node = queue.poll();
        for (int neighbor :
graph.get(node)) {
            if (!visited[neighbor]) {
                visited[neighbor] = true;
                queue.offer(neighbor);
            }
        }
    }
    level++;
}
// 2. TOPOLOGICAL SORT — Kahn's BFS
int[] inDegree = new int[n];
for (int[] edge : edges)
inDegree[edge[1]]++;
Queue<Integer> queue = new ArrayDeque<>
();
for (int i = 0; i < n; i++) if
(inDegree[i] == 0) queue.offer(i);
List<Integer> order = new ArrayList<>();
while (!queue.isEmpty()) {
    int node = queue.poll();
    order.add(node);
    for (int neighbor : graph.get(node))
        if (--inDegree[neighbor] == 0)
queue.offer(neighbor);
}
// 3. UNION FIND
int[] parent, rank;
void init(int n) {
    parent = new int[n]; rank = new
int[n];
    for (int i = 0; i < n; i++) parent[i]
= i;
}
int find(int x) {
    if (parent[x] != x) parent[x] =
find(parent[x]);
    return parent[x];
}
boolean union(int x, int y) {
    int px = find(x), py = find(y);
    if (px == py) return false;
    if (rank[px] < rank[py]) { int t =
px; px = py; py = t; }
    parent[py] = px;
    if (rank[px] == rank[py]) rank[px]++;
    return true;
}
// 4. DIJKSTRA — shortest path (non-
negative weights)
int[] dist = new int[n];
Arrays.fill(dist, Integer.MAX_VALUE);
dist[src] = 0;
PriorityQueue<int[]> pq = new
PriorityQueue<>((a, b) -> a[1] - b[1]);
pq.offer(new int[]{src, 0});
while (!pq.isEmpty()) {
    int[] current = pq.poll();
    int node = current[0], d =
current[1];
    if (d > dist[node]) continue;
    for (int[] nb : graph.get(node)) {
        int next = nb[0], w = nb[1];
        if (dist[node] + w < dist[next])
{
            dist[next] = dist[node] + w;
            pq.offer(new int[]{next,
dist[next]});
        }
    }
}
// 5. BIPARTITE CHECK — BFS 2-coloring
int[] color = new int[n];
Arrays.fill(color, -1);
Queue<Integer> queue = new ArrayDeque<>
();
for (int start = 0; start < n; start++) {
    if (color[start] != -1) continue;
    color[start] = 0;
    queue.offer(start);
    while (!queue.isEmpty()) {
        int node = queue.poll();
        for (int neighbor :
graph.get(node)) {
            if (color[neighbor] == -1) {
color[neighbor] = 1 - color[node];
queue.offer(neighbor); }
            else if (color[neighbor] ==
color[node]) return false;
        }
    }
}
return true;
```

Greedy

Two Interval Templates

```
MERGE DIRECTION RULE (for merge-style
problems like #56, where both keys work):
    Sort by START  →  traverse FORWARD
(i = 0 → n-1), extend the END of last
kept
    Sort by END    →  traverse BACKWARD
(i = n-1 → 0), extend the START of last
kept
    These two are exact mirror images.
See #56 for both written out side by
side.
    (NOTE: this mirror only applies to
merging. Template 1 below sorts by end
but
     still sweeps FORWARD — there the
goal is counting, not merging.)
TEMPLATE 1 — Sort by END time, sweep
forward, track end of last kept interval
             Use when: maximizing count
of non-overlapping intervals
             Greedy insight: earliest-
finishing interval leaves most room for
future ones
TEMPLATE 2 — Sort by START time, sweep
forward, merge when overlapping
             Use when: merging/counting
overlapping intervals
             Greedy insight: processing
in start order → each interval only needs
to
             compare with the last merged
result
```

```
Arrays.sort(intervals, (a, b) -> a[1] -
b[1]);
int lastEnd = Integer.MIN_VALUE;
for (int[] interval : intervals) {
    if (interval[0] >= lastEnd) {
        lastEnd = interval[1];
    } else {
    }
}
Arrays.sort(intervals, (a, b) -> a[0] -
b[0]);
List<int[]> result = new ArrayList<>();
for (int[] interval : intervals) {
    if (result.isEmpty() ||
result.get(result.size()-1)[1] <
interval[0]) {
        result.add(interval);
    } else {
        result.get(result.size()-1)[1] =

Math.max(result.get(result.size()-1)[1],
interval[1]);
    }
}
Arrays.sort(intervals, (a, b) -> a[0] -
b[0]);
PriorityQueue<Integer> pq = new
PriorityQueue<>();
for (int[] interval : intervals) {
    if (!pq.isEmpty() && pq.peek() <=
interval[0])
        pq.poll();
    pq.offer(interval[1]);
}
```

Dynamic Programming

All Six Templates

```
// 1. LINEAR 1D — each cell depends on a
fixed number of previous cells
int[] dp = new int[n + 1];
dp[0] = base;
for (int i = 1; i <= n; i++)
    dp[i] = f(dp[i-1], dp[i-2], ...);
// 2A. LOOK-BACK 1D — dp[i] depends on
all j < i
int[] dp = new int[n];
for (int i = 0; i < n; i++) {
    for (int j = 0; j < i; j++) {
        dp[i] = f(dp[i], dp[j]);
    }
}
// 3. 2D SEQUENCE — match consumes both,
mismatch drops one side. WHEN: LCS / edit
// 4. INTERVAL DP — short ranges first (i
right-to-left, j from i+1; dp[i+1][*]
ready).
// 5. GRID DP — each cell accumulates
from cells it could arrive from
(up/left).
// 6. STATE MACHINE — named states
updated from yesterday's states each
step.
```

```
Want count or min/max?
├── Count (dp[j] += dp[j - num])
│   ├── 0/1 (each item once):    j
descending → #416, #494
│   └── Unbounded (reuse):       j
ascending  → #518
│       └── Ordered (permuts):   target
outer, nums inner → #377
└── Min/Max (dp[j] = min/max(...))
    ├── 0/1 minimize:            j
descending → #474 (maximize)
    └── Unbounded minimize:      j
ascending  → #322
```

```
// —— 0/1 KNAPSACK —— each item at most
once
int[] dp = new int[target + 1];
dp[0] = 1;
for (int i = 0; i < nums.length; i++) {
    for (int j = target; j >= nums[i]; j-
-)
        dp[j] += dp[j - nums[i]];
}
// —— UNBOUNDED KNAPSACK —— each item
reusable
int[] dp = new int[target + 1];
dp[0] = 1;
for (int i = 0; i < nums.length; i++) {
    for (int j = nums[i]; j <= target;
j++)
        dp[j] += dp[j - nums[i]];
}
// —— PERMUTATION COUNT —— order matters
(Combination Sum IV)
int[] dp = new int[target + 1];
dp[0] = 1;
for (int j = 1; j <= target; j++) {
    for (int num : nums) {
        if (j >= num) dp[j] += dp[j -
num];
    }
}
```

```
int[][] dp = new int[m + 1][n + 1];
for (int i = 1; i <= m; i++) {
    for (int j = 1; j <= n; j++) {
        if (s1.charAt(i-1) ==
s2.charAt(j-1)) {
            dp[i][j] = dp[i-1][j-1] + 1;
        } else {
            dp[i][j] = combine(dp[i-1]
[j], dp[i][j-1], dp[i-1][j-1]);
        }
    }
}
```

```
int[][] dp = new int[n][n];
for (int i = 0; i < n; i++) dp[i][i] =
base_case;
for (int i = n - 1; i >= 0; i--) {
    for (int j = i + 1; j < n; j++) {
        dp[i][j] = ...;
    }
}
```

```
int[][] dp = new int[n][n];
for (int i = 0; i < n; i++) dp[i][i] =
base_case;
for (int i = 0; i < n; i++) {
    for (int j = i - 1; j >= 0; j--) {
        dp[i][j] = ...;
    }
}
```

```
int[][] dp = new int[n][n];
for (int i = 0; i < n; i++) dp[i][0] = 1;
for (int i = 1; i < n; i++) {
    for (int j = 1; j <= i; j++) {
        dp[i][j] = ...;
    }
}
```

```
int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
int[][] dp = new int[rows][cols];
for (int i = 0; i < rows; i++)
    for (int j = 0; j < cols; j++)
        dp[i][j] = grid[i][j] + f(dp[i-1]
[j], dp[i][j-1]);
int[][] memo = new int[rows][cols];
for (int i = 0; i < rows; i++)
    for (int j = 0; j < cols; j++)
        dfs(grid, i, j, memo, dr, dc);
```

```
cash      = max profit when NOT holding
(free to buy or idle)
hold      = max profit when HOLDING stock
(bought it at some cost)
cooldown  = max profit right after
selling (can't buy today)
```

```
                     buy
sell                 re-buy condition
#121 (1 tx):         hold = max(hold, -
price)                 no re-buy (ignore
cash)
#122 (unlimited):    hold = max(hold, cash
- price)           re-buy with full cash
#123 (2 tx):         chain: buy2 uses
sell1 cash             4 states chained
#309 (cooldown):     hold = max(hold,
cooldown - price)      must wait 1 day
#714 (fee):          hold = max(hold, cash
- price)           pay fee on sell
```

Bit Manipulation

Canonical Template

```
// —— XOR CANCEL —— pairs cancel; lone
element survives
int result = 0;
for (int num : nums) result ^= num;
// —— BIT OPERATIONS ——
boolean isSet  = ((n >> i) & 1) == 1;
int set        = n | (1 << i);
int clear      = n & ~(1 << i);
int toggle     = n ^ (1 << i);
int lowest     = n & (-n);
boolean isPow2 = n > 0 && (n & (n-1)) ==
0;
// —— COUNT SET BITS —— Brian Kernighan:
each iteration removes one set bit
int count = 0;
while (n != 0) { count++; n &= (n - 1); }
// —— BITMASK AS SET —— 26-bit integer
represents presence of 26 letters
int mask = 0;
for (char c : word.toCharArray()) mask |=
(1 << (c - 'a'));
if ((mask[i] & mask[j]) == 0) { /* no
shared letter */ }
```

Variations

```
int ones = 0, twos = 0;
for (int num : nums) {
    ones = (ones ^ num) & ~twos;
    twos = (twos ^ num) & ~ones;
}
int xor  = 0;
for (int num : nums) xor ^= num;
int diff = xor & (-xor);
int a = 0;
for (int num : nums)
    if ((num & diff) != 0) a ^= num;
int b = xor ^ a;
int[] dp = new int[n + 1];
for (int i = 1; i <= n; i++)
    dp[i] = dp[i >> 1] + (i & 1);
int shift = 0;
while (left != right) { left >>= 1; right
>>= 1; shift++; }
return left << shift;
int add(int a, int b) {
    while (b != 0) {
        int carry = a & b;
        a = a ^ b;
        b = carry << 1;
    }
    return a;
}
```

Design

Canonical Template — HashMap + Doubly Linked List (LRU)

```
class CacheNode {
    int key, value;
    CacheNode previous, next;
    CacheNode(int key, int value) {
this.key = key; this.value = value; }
}
// —— SENTINEL NODES —— head (MRU side) ↔
... ↔ tail (LRU side)
CacheNode head = new CacheNode(0, 0),
tail = new CacheNode(0, 0);
head.next = tail; tail.previous = head;
// —— REMOVE NODE ——
void remove(CacheNode node) {
    node.previous.next = node.next;
    node.next.previous = node.previous;
}
// —— INSERT AFTER HEAD (= mark as MRU)
——
void insertAfterHead(CacheNode node) {
    node.next = head.next;
    node.previous = head;
    head.next.previous = node;
    head.next = node;
}
// —— LRU EVICTION —— tail.previous is
LRU
CacheNode lru = tail.previous;
remove(lru);
map.remove(lru.key);
```

Variations

Math

Canonical Templates

```
// —— DIGIT EXTRACTION LOOP —— peel
digits right-to-left
while (n != 0) {
    int digit = n % 10;
    n /= 10;
}
// —— FAST POWER (exponentiation by
squaring) ——
double fastPow(double x, long n) {
    double result = 1;
    while (n > 0) {
        if ((n & 1) == 1) result *= x;
        x *= x;
        n >>= 1;
    }
    return result;
}
// —— BASE CONVERSION —— generic base b,
0-indexed
StringBuilder builder = new
StringBuilder();
while (num > 0) {
    builder.append(num % b);
    num /= b;
}
builder.reverse();
int value = 0;
for (int digit : digits) value = value *
b + digit;
// —— SIEVE OF ERATOSTHENES —— mark
composites up to n
boolean[] composite = new boolean[n];
for (int i = 2; i * i < n; i++) {
    if (composite[i]) continue;
    for (int j = i * i; j < n; j += i)
        composite[j] = true;
}
```