Algorithm Cheat Sheet — All Templates + Java Syntax

Conventions, Skeleton & Core API

Generic Test Harness

```
class Question {
    // — PROBLEM-SOLVING PROCESS
    //
    // 1. INPUT / OUTPUT : types, sizes, ranges; what to return; examples.
    // 2. HIGH-LEVEL ALGO : pick the pattern ( two-ptr / BFS / DP / ...); state the idea in 1 line.
    // 3. IMPLEMENTATION : data structures, loop/recursion, invariants.
    // 4. EDGE CASES : empty, size 0/1, duplicates, negatives, overflow, all-same, not-found.
    // 5. COMPLEXITY : time & space; is it within limits?
    // 6. OPTIMIZATION : reduce time/space (hashing, two-pointer, rolling array, pruning, early exit).
    //
    // ------------------------------------------------------------
    private int data;
    public Question(int data) {
        this.data = data;
    }
    public void solve() {
        // TODO
    }
}
public class Solution {
    public static void main(String[] args) {
        Question q = new Question(0);
        q.solve();
    }
}
```

Naming Conventions (enforced across all template files)

Common Java API Cheat-Sheet

```
Map<Integer, Integer> map   = new HashMap<>();          // key -> value
Map<Integer, List<Integer>> adj = new HashMap<>();      // adjacency / buckets
Set<Integer> set            = new HashSet<>();          // membership
List<Integer> list          = new ArrayList<>();        // dynamic array
Deque<Integer> stack = new ArrayDeque<>();              // STACK: push / pop / peek
Deque<Integer> queue = new ArrayDeque<>();              // QUEUE: offer / poll / peek

// (ArrayDeque beats java.util.Stack / LinkedList)
PriorityQueue<Integer> minHeap = new PriorityQueue<>();          // min-heap (default)
PriorityQueue<Integer> maxHeap = new PriorityQueue<>(Collections.reverseOrder()); // max-heap
PriorityQueue<int[]>   pq      = new PriorityQueue<>((a, b) -> a[1] - b[1]);  // by field, min-first
TreeMap<Integer, Integer> tmap = new TreeMap<>();       // sorted keys: floor/ceiling/first/last
TreeSet<Integer> tset          = new TreeSet<>();       // sorted set: floor/ceiling/higher/lower
LinkedHashSet<Integer> lset    = new LinkedHashSet<>(); // insertion-ordered set (LFU buckets)
Random rand                    = new Random();          // rand.nextInt(n) -> 0..n-1 (RandomizedSet)
int[]   arr = new int[n];                               // defaults to 0
boolean[] seen = new boolean[n];                        // defaults to false
int[][] grid = new int[m][n];                           // 2D, all 0
int[]   dr = {1,-1,0,0}, dc = {0,0,1,-1};              // DOWN,UP,RIGHT,LEFT; iterate for(dir=0..3) i=dr[dir],j=dc[dir]
```

```
// — Map —
map.put(k, v);
map.getOrDefault(k, 0);
// safe read with default
map.merge(k, 1, Integer::sum);
// — counting frequency (most common)
map.computeIfAbsent(k, v -> new ArrayList<>()).add(v); // — get-or-create a bucket, then mutate
map.putIfAbsent(k, v);
// — keep FIRST occurrence (e.g. value-earliest index)
// putIfAbsent(k,v)        : value is EAGER (built up front); inserts only if k absent;
//                           RETURNS the OLD value (null if was absent). Use to keep first write.
// computeIfAbsent(k, f)   : value is LAZY (f runs only if k absent); inserts & RETURNS the new value (existing or just-made) — chain '.add(...)' on it.
//                           Idiom for adjacency lists / buckets — no allocation when present:
map.containsKey(k);  map.remove(k);
for (Map.Entry<Integer, Integer> e : map.entrySet()) { e.getKey(); e.getValue(); }
e.setValue(v);  e.setKey(k);  map.values();
// — Set —
set.add(x);  set.contains(x);  set.remove(x);
// — List —
list.add(x);  list.get(i);  list.set(i, x);
list.remove(list.size() - 1);
// — pop in backtracking
list.size();  list.isEmpty();  list.addAll(other);
Collections.reverse(list);
// — reverse path after backtracking
// ascending, b) so b - a);
// custom / descending
Collections.reverseOrder();
// — reverse path after backtracking
// backwards
```

```
// Deque as STACK (LIFO)          //
Deque as QUEUE (FIFO)
stack.push(x);
queue.offer(x);
int top = stack.pop();                  int
head = queue.poll();
int look = stack.peek();                int
look = queue.peek();
stack.isEmpty();
queue.isEmpty();
// Deque BOTH ENDS — needed for the
MONOTONE DEQUE (sliding-window max/min)
// and for add/remove at both ends
(zigzag BFS).
deque.offerLast(x);   deque.pollLast();
deque.peekLast();     // back
(push/pop/peek tail)
deque.offerFirst(x);  deque.pollFirst();
deque.peekFirst();    // front
(push/pop/peek head)
deque.addLast(x);     deque.addFirst(x);
// same as offer, throw if capacity-bound
// PriorityQueue (heap)
pq.offer(x);  int best = pq.poll();  int look = pq.peek();  pq.size();
pq.remove(x);  // O(n) removal of an arbitrary element (lazy-deletion alternative in #480)
```

```
Integer.MAX_VALUE;  // 2147483647
(2^31 - 1) — use as sentinel for "min so far"
Integer.MIN_VALUE;  // -2147483648
(-2^31) — use as sentinel for "max so far"
Long.MAX_VALUE;     // when sums can overflow int, accumulate in long
int k = i + (j - i) / 2;
// avoid (i + j) overflow in binary search
Integer.compare(a, b);          //
— overflow-safe comparator; use instead of (a - b)
(a, b) -> Integer.compare(a[1], b[1]);// — safe PriorityQueue/Arrays.sort comparator
Double.compare(a, b);           //
— comparator for double[] heaps (probability, median)
```

```
ch - 'a';                       //
'a'..'z' -> 0..25   (lowercase bucket index)
ch - '0';                       //
'0'..'9' -> 0..9    (digit value)
(char) ('a' + i);               //
0..25 -> 'a'..'z'
num = num * 10 + (ch - '0');    //
— build a number digit by digit
Integer.parseInt("123");        //
String -> int (throws on bad input)
Integer.valueOf(123);           //
int -> Integer (boxed)
String.valueOf(123);            //
int -> String
Character.getNumericValue('7'); //
char -> 7
// char classification
Character.isDigit(ch);
Character.isLetter(ch);
Character.isLetterOrDigit(ch);
Character.isWhitespace(ch);
Character.toLowerCase(ch);
Character.toUpperCase(ch);
```

```
s.length();  s.charAt(i);  s.substring(i, j);  // (i, j]
s.toCharArray();  s.split(" ");
s.equals(t);  s.compareTo(t);
s.indexOf(t);  s.lastIndexOf(t);
s.startsWith("ab");  s.endsWith("x");
s.contains("mid");  // prefer .substring(...) for
substring tests
s.toLowerCase();  s.toUpperCase();
// case-normalize (e.g. case-insensitive compare)
s.trim();  s.replace('a', 'b');
s.repeat(n);  // strip ends / swap chars / repeat
StringBuilder sb = new StringBuilder();
builder.append(x);  builder.reverse();
builder.toString();
builder.charAt(i);  builder.setCharAt(i, c);  builder.deleteCharAt(i);
builder.length();
String.join(",", list);
// list -> "a,b,c"
```

```
Arrays.sort(arr);
// ascending in place
Arrays.sort(intervals, (a, b) -> a[0] - b[0]);  // sort 2D by first field
Arrays.fill(dp, Integer.MAX_VALUE);
// seed a dp/dist array
Arrays.equals(a1, a2);  Arrays.deepEquals(a, b);
// — element-wise array compare (anagram check)
Arrays.copyOf(arr, len);
Arrays.copyOfRange(arr, i, j);
System.arraycopy(src, srcPos, dst, dstPos, len);  // — fast block copy (merge step)
Arrays.asList(1, 2, 3);
// fixed-size List view
int sum = Arrays.stream(arr).sum();
int max = Arrays.stream(arr).max().getAsInt();
// List -> array
Object[] arr = list.toArray();
// -> Object[]
Integer[] box = list.toArray(new Integer[0]);  // -> typed Integer[]
int[] a = list.stream().mapToInt(Integer::intValue).toArray();  // -> primitive int[]
// int[] -> List<Integer>
List<Integer> L = Arrays.stream(a).boxed().collect(Collectors.toList());  // or: toList() (Java 16+)
```

```
Math.max(a, b);  Math.min(a, b);
Math.abs(x);
Math.pow(b, e);  Math.sqrt(x);
Math.ceil(x);  Math.floor(x);
n & (n - 1);                    // clear lowest set bit
n & (-n);                       // isolate lowest set bit
1L << i for i ≥ 31)
(n >> i) & 1;                   // read bit i
(n & 1) == 0;                   // even   (last bit 0)
(n & 1) == 1;                   // odd    (last bit 1)
n >> 1;                         // divide by 2 (drop last bit);  n << 1 = multiply by 2
Integer.bitCount(n);  // # of set bits
Integer.toBinaryString(n);
```

```
// — NEGATIVE-SAFE MODULO — replaces the manual ((x % n) + n) % n
Math.floorMod(x, n);            //
always in [0, n-1) even when x < 0
(prefix-sum % k)
// — int[] INSTEAD OF HashMap for a bounded key space —
int[] count = new int[26];      //
O(1) no-boxing freq vs HashMap<Character,Integer>
count[ch - 'a']++;              //
also faster to compare: Arrays.equals(a, b)
// — IO ROLLING ARRAY for DP — drop a dimension when row i only needs row i-1
int[] dp = new int[n + 1];
// O(n) space instead of O(m·n)
for (...; ...; for (int j = target; j >= w; j--)
    dp[j] += dp[j - w];  // 0/1 knapsack: iterate j DOWN
// — FIXED-SIZE HEAP for top-k — O(n log k) beats sorting O(n log n)
if (heap.size() > k) heap.poll();
// keep only k best; min-heap for "k largest"
// — LAZY DELETION over pq.remove(obj) — O(n) remove is O(n); skip stale entries instead
if (entry[0] != dist[node]) continue;  // Dijkstra: ignore outdated heap entries
// — ArrayDeque over Stack / LinkedList — faster, no synchronization, both ends O(1)
Deque<Integer> stack = new ArrayDeque<>();  // never use java.util.Stack
// — StringBuilder over String += in a loop — O(n) vs O(n²)
StringBuilder builder = new StringBuilder();  // append, then builder.toString() once
// — EARLY EXIT / PRUNING — return the moment the answer is decided
if (found) return result;       //
e.g. backtracking bounds
```

Template Index

Two Pointers

Pattern 1 — Opposite Two Pointers

Variables:
i = left pointer · j = right pointer · scan range [i, j] closed

Pseudocode:

```
set i to the left end, j to the right end
while the pointers haven't crossed:
    if the current pair hits the target:
        record it, then step both ends inward
    else if the value is too small:
        move the left end right to grow it
    else (too large):
        move the right end left to shrink it
```

```
int i = 0, j = n - 1;
while (i < j) {
    if (condition == target) {
        /* record */ ++i; --j;
    } else if (tooSmall) {
        ++i;
    } else {
        --j;
    }
}
```

Sliding Window

The Three Templates

Variables:
i = left edge (inclusive) · j = right edge / loop variable (inclusive), window = [i, j]. size = j − i + 1 · n = array length · k = target window size / result = answer (max length, or min length seeded to MAX)

Pseudocode:

```
FIXED window of size k:
    i = 0
    for j = 0..n-1:
        add nums[j] to window state
        if window size (j − i + 1) == k:
            record the window's result
        if size k)
            remove nums[i] from state; i = i + 1

MAX variable window (longest valid):
    i = 0;  result = 0
    for j = 0..n-1:
        add nums[j] to state
        while window violates the constraint:
            remove nums[i] from state; i = i + 1
        result = max(result, j − i + 1)
    (window is valid here)

MIN variable window (shortest valid):
    i = 0;  result = +infinity
    for j = 0..n-1:
        add nums[j] to state
        while window is valid:
            result = min(result, j − i + 1)
            remove nums[i] from state; i = i + 1   (then shrink to try smaller)
    (record while still valid)
```

```
int i = 0;
for (int j = 0; j < n; j++) {
    // 1. add nums[j] to state
    if (j - i >= k) {
        // 2. record (window is exactly size k)
        // 3. remove nums[i] from state
        i++;
    }
}
int i = 0, result = 0;
for (int j = 0; j < n; j++) {
    // 1. add nums[j] to state
    while (/* window exceeds constraint */) {
        i++;
    }
    result = Math.max(result, j - i + 1);
}
int i = 0, result = Integer.MAX_VALUE;
for (int j = 0; j < n; j++) {
    // 1. add nums[j] to state
    while (/* a window VALID */) {
        result = Math.min(result, j - i + 1);
        i++;
    }
}
```

Frequency Map Trick (used by 567 and 76)

Variables:
need[c] = how many more of char c the window still needs (positive = still short, zero/negative = surplus) · required = total chars still missing; hits 0 when the window covers all of t · i is left edge, j = right edge

Pseudocode:

```
Expanding (add char at j):
    if need[c] was still positive (> 0):
    required = required − 1   (filled one more needed slot)
    need[c] = need[c] − 1

Shrinking (remove char at i):
    if need[char] was already 0 or surplus (>= 0):
    required = required + 1  (now short one)
    need[char] = need[char] + 1
    i = i + 1
```

```
if (need[s.charAt(j)] >= 0) required--;
if (need[s.charAt(j)]+1 >= 0) required++;
i++;
```

Prefix Sum + HashMap

Core Template

Variables:
map = prefixSum→count or index seen so far · sum = running prefix sum · target = the complement prefix we search for · i = current scan position

Pseudocode:

```
create empty map of prefix → (count or first index)
seed map with prefix 0 (count=1 for counting, -1 for length)
sum = 0
for each index i:
    add nums[i] to sum
    (or sum = transform(sum))          // sum-k, sumK, etc.
    look up map.get(lookup) to update result
    store sum (or sumK) into map with count or index i
```

```
Map<Long, Integer> map = new HashMap<>();
map.put(0L, ???);
long sum = 0;
for (int i = 0; i < nums.length; i++) {
    sum += nums[i];
    long lookup = transform(sum);
    map.put(storeKey(sum), ...);
storeValue(i));  // what to store (sum or sumK − count or index)
}
```

Binary Search

The Only Template — (i , j), find first k with condition(k)

Variables:
[i, j) = half-open search range · k = midpoint · condition(k) = monotone test (false…false→TRUE…true) · **answer = i**
, always = [0, length) (i == length ⇒ nothing satisfied it).

Pseudocode:

```
i = 0, j = length        # half-open [i, j)
; for answer=space use [min, max+1)
while range non-empty (i < j):
    k = midpoint of i and j
    if condition(k) is false: answer is to the right, set i = k+1
    else: k might be the answer, set j = k
```

Sorting

Template 1 — Merge Sort

Variables:
[start, end) half-open range being sorted · mid = split point · temp = scratch buffer · i = left scan pointer [start,mid) · j = right scan pointer [mid,end) · k = write pointer into temp

Pseudocode:

```
mergeSort(nums, start, end):
    if range has 0 or 1 elements: return
// already sorted
    mid = midpoint of [start, end)
    mergeSort left half  [start, mid)
    mergeSort right half [mid, end)
    merge the two sorted halves

merge:
    i = start, j = mid, k = start
    while either half has elements left:
        pick smaller front of the two halves (left wins ties → stable)
        write it to temp[k], advance that half's pointer and k
    copy temp back into nums[start, end)
```

```
public void mergeSort(int[] nums) {
    mergeSort(nums, 0, nums.length, new int[nums.length]);
}
private void mergeSort(int[] nums, int start, int end, int[] temp) {
    if (end - start <= 1) return;
    int mid = start + (end - start) / 2;
    mergeSort(nums, start, mid, temp);
    mergeSort(nums, mid,   end, temp);
    merge(nums, start, mid, end, temp);
}
private void merge(int[] nums, int start, int mid, int end, int[] temp) {
    int i = start, j = mid, k = start;
    while (i < mid || j < end) {
        if (j == end || (i < mid && nums[i] <= nums[j])) {
            temp[k++] = nums[i++];
        } else {
            temp[k++] = nums[j++];
        }
    }
    for (i = start; i < end; i++) nums[i] = temp[i];
}
```

Template 2 — Quick Sort (3-way Dutch Flag Partition)

Variables:
[start, end) half-open range · pivot = chosen partition value · i = boundary of <pivot region · j = scan pointer · j = boundary of >pivot region (from the right)

Pseudocode:

```
quickSort(nums, start, end):
    if range has 0 or 1 elements: return
    choose a pivot value from the range
    i = start, k = start, j = end
    while k < j:
        if nums[k] < pivot:  swap into <region, advance k and i
        else if nums[k] == pivot: advance k
        else (nums[k] > pivot): swap into >region, shrink j (don't advance k)
    recurse on <region [start, i)
    recurse on >region [k, end)          // ==pivot middle is final
```

```
public void quickSort(int[] nums) {
    quickSort(nums, 0, nums.length);
}
private void quickSort(int[] nums, int start, int end) {
    if (end - start <= 1) return;
    int pivot = nums[start + (end - start) / 2];
    int i = start, k = start, j = end - 1;
    while (k <= j) {
        if (nums[k] < pivot) {
            swap(nums, k++, i++);
        } else if (nums[k] == pivot) {
            k++;
        } else {
            swap(nums, k, j--);
        }
    }
    quickSort(nums, start, i);
    quickSort(nums, k, end);
}
private void swap(int[] nums, int i, int j) {
    int t = nums[i]; nums[i] = nums[j]; nums[j] = t;
}
```

Template 3 — Quick Select (partial sort — k-th element)

Variables:
[start, end) half-open range · target = 0-indexed position we want settled · pivot = partition value · i = boundary of <pivot region · k = scan/cursor pointer · j = boundary of >pivot region

Pseudocode:

```
quickSelect(nums, start, end, target):
    pick a pivot value from the range
    partition into [start,i)<p | [i,k)==p | [k,end)>p
    if same 3-way as before
    if target < i:          recurse into left [start, i)
    else if target < k:     target sits in <==pivot region -> return pivot
    else:                   recurse into right [k, end)
```

```
private int quickSelect(int[] nums, int start, int end, int target) {
    int pivot = nums[start + (end - start) / 2];
    int i = start, k = start, j = end - 1;
    while (k <= j) {
        if (nums[k] < pivot) {
            swap(nums, k++, i++);
        } else if (nums[k] == pivot) {
            k++;
        } else {
            swap(nums, k, j--);
        }
    }
    if (target < i) {
        return quickSelect(nums, start, i, target);
    } else if (target < k) {
        return pivot;
    } else {
        return quickSelect(nums, k, end, target);
    }
}
```

Template 4 — Counting Sort

Variables:
minMax = value range bounds · buckets[v-min] = count of value v · i = write pointer back into arr · v = current value index into buckets

Linked List

When to Use — Signal → Pattern

All Four Templates

Variables:
sentinel = dummy node before head · previous = last kept node · current = node under inspection · next = saved successor · fast/fast = 1×/2× walkers · a/b = the two input lists

Pseudocode:

```
make sentinel pointing at head; previous = sentinel, current = head
while current exists:
    if current should be deleted: rewire previous.next to skip current
    else: advance previous to current
    advance current
return sentinel.next
previous = null, current = head
while current exists:
    save next = current.next
    point current backward at previous
    advance previous to current, current to next
return previous as new head
slow = head, fast = head
while fast and fast.next exist:
    advance slow one step, fast two steps
make sentinel; current = sentinel
while both a and b exist:
    splice the smaller head onto current; advance it
    advance current
attach whichever list remains
return sentinel.next
```

```
// 1. DELETE / FILTER — sentinel guards head removal; previous tracks last kept node
ListNode sentinel = new ListNode(0);
sentinel.next = head;
ListNode previous = sentinel, current = head;
while (current != null) {
    if (shouldDelete(current)) {
        previous.next = current.next;
    } else {
        previous = current;
    }
    current = current.next;
}
return sentinel.next;
// 2. REVERSAL — rewire one node at a time
ListNode previous = null, current = head;
while (current != null) {
    ListNode next = current.next;
    current.next = previous;
    previous = current;
    current = next;
}
return previous;
// 3. FAST / SLOW — two pointers at different speeds
ListNode slow = head, fast = head;
while (fast != null && fast.next != null) {
    slow = slow.next;
    fast = fast.next.next;
}
// 4. MERGE — sentinel collects nodes from two lists in order
ListNode sentinel = new ListNode(0);
ListNode current = sentinel;
while (a != null && b != null) {
    if (a.val <= b.val) {
        current.next = a;
        a = a.next;
    } else {
        current.next = b;
        b = b.next;
    }
    current = current.next;
}
current.next = (a != null) ? a : b;
return sentinel.next;
```

String

Core Idioms

Variables:
count = frequency vector (index = char/digit bucket) · ch - 'a' = 0–25 bucket index · ch - '0' = 0–9 digit value · num = number built so far · builder = encoded/result string · buckets = lists shaped by frequency · expand(i,j) = palindrome length from a center

Pseudocode:

```
idion = char count for letters:
  make count of size 26
  for each char: count[ch-'a'] += 1
idion 2 — char count for digits:
  make count of size 10
  for each char: count[ch-'0'] += 1
idiom 3 — char to integer:
  num = 0
  for each char left to right: num = num*10 + (ch - '0')
idiom 4 — anagram hash key (frequency-based):
  count the 26 letters of s
  build a string from each letter label followed by its count
  return it (same key for all anagrams)
  alternative: sort the chars and use the sorted string as key
idiom 5 — bucket sort by frequency:
  count all ASCII chars
  make buckets indexed by frequency
  for each char with count>0: add to buckets[its count]
  walk buckets from highest frequency down, append each char that many times
idiom 6 — expand from center:
  while i in bounds and j in bounds and chars at i and j match: move i left, j right
  return j − i − 1 (length of palindrome found)
```

Graph

Complexity Legend

BFS / DFS		visit
each vertex and edge once		each
Topo sort (Kahn)	O(V + E)	each node enqueued once, each edge relaxed once
Union-Find	~O(n·α(n)) ≈ O(n)	α = inverse Ackermann, effectively constant
Dijkstra	O((V + E) log V)	non-negative weights ONLY

Graph Representation

```
List<List<Integer>> graph = new ArrayList<>();
for (int i = 0; i < n; i++) graph.add(new ArrayList<>());
for (int[] edge : edges) {
    graph.get(edge[0]).add(edge[1]);
    graph.get(edge[1]).add(edge[0]);
}
List<List<int[]>> graph = new ArrayList<>();
for (int i = 0; i < n; i++) graph.add(new ArrayList<>());
for (int[] edge : edges)
    graph.get(edge[0]).add(new int[]{edge[1], edge[2]});
int[] dr = {1, -1, 0, 0};
int[] dc = {0, 0, 1, -1};
```

```
TreeNode[] nodes = new ArrayDeque<>();
queue.offer(root);
level = 0;
while (!queue.isEmpty()) {
    int size = queue.size();
    level++;
    for (int i = 0; i < size; i++) {
        TreeNode node = queue.poll();
        if (node.left != null)
queue.offer(node.left);
        if (node.right != null)
queue.offer(node.right);
    }
}
```

When to Use — Signal → Pattern

The One Rule — Snapshot Level Size First

Always snapshot the level size BEFORE the inner for loop:

```
int size = queue.size();
for (int i = 0; i < size; i++) { ... }
```

Without the snapshot, newly added children mix with the current level and `i == size-1` / `i == 0` checks become meaningless.

DFS / Backtracking

When to Use — Signal → Pattern

All Templates

Variables:
node = current tree node · accumulated/current = state carried down a path · answer/global = best cross-node result · grid[r][c] = cell value · visited[r][c] = seen-this-path · unseen / !in-stack / 2 done · start = first eligible index · current = in-progress candidate · nums[i] = element being chosen

Pseudocode:

```
if node null: return BASE; left=dfs(left); right=dfs(right); return
combine(left, right, node.val)
if node == c: return existing
if leaf: record; dfs[left,accumulated];
dfs[right,accumulated]; return
if node null: return 0;
left=max(0,dfs(left));
right=max(0,dfs(right));
answer=max(answer, left+right+node.val);
return max(left,right)+node.val
if node == null or node == TARGET: return; mark VISITED; recurse into 4 neighbors
if state==2: return; if state==1: safe; mark in-stack; recurse neighbors (cycle? return);
mark state = 2
if base: record copy; for i from start: skip dups; choose nums[i]; recurse(i+1); undo
```

```
// 1. PROCESS CHILDREN FIRST, COMBINE AT NODE (post-order)
private int dfs(TreeNode node) {
    if (node == null) return BASE;
    int left  = dfs(node.left);
    int right = dfs(node.right);
    return ...;
}
// 2. BOTH NODE FIRST, PASS STATE DOWN (pre-order)
private void dfs(TreeNode node, int accumulated) {
    if (node == null) return;
    accumulated += node.val;
    if (isLeaf(node)) { /* record */ return; }
    dfs(node.left,  accumulated);
    dfs(node.right, accumulated);
}
// 3. TREE — GLOBAL ANSWER (return up the best single arm; update global across both)
int answer = Integer.MIN_VALUE;
private int dfs(TreeNode node) {
    if (node == null) return 0;
    int left  = Math.max(0, dfs(node.left));
    int right = Math.max(0, dfs(node.right));
    answer = Math.max(answer, left + right + node.val);
    return Math.max(left, right) + node.val;
}
// 4. GRID DFS — mark visited by mutating grid; 4-directional flood fill
private void dfs(int[][] grid, int r, int c) {
    if (r < 0 || r >= grid.length || c < 0 || c >= grid[0].length) return;
    if (grid[r][c] != TARGET) return;
    grid[r][c] = VISITED;
    dfs(grid, r+1, c); dfs(grid, r-1, c);
    dfs(grid, r, c+1); dfs(grid, r, c-1);
}
// 5. GRAPH DFS — 3-color visited: 0=unseen 1=in-stack 2=done
int[] state;
private boolean dfs(int node) {
    if (state[node] == 1) return true;
    if (state[node] == 2) return false;
    state[node] = 1;
    for (int neighbor : graph.get(node))
        if (dfs(neighbor)) return true;
    state[node] = 2;
    return false;
}
// 6. BACKTRACKING — choose / recurse / undo
private void backtrack(int start, List<Integer> current) {
    if (/* base case */) result.add(new ArrayList<>(current)); return;
    for (int i = start; i < n; i++) {
        if (/* skip condition */) continue;
        current.add(nums[i]);
        backtrack(i+1, current);
        current.remove(current.size()-1);
    }
}
```

Stack / Queue / Heap

All Templates

Variables:
stack = LIFO ArrayDeque (holds indices for monotone variants) · queue = monotone deque (front = window answer) · minPQ/maxPQ = priority queue (heap) · maxHeap = lower half, minHeap = upper half for median

Pseudocode:

```
STACK: push/pop/peek all at the front (LIFO)
MONO-DECREASING (next greater): while current > stack top, pop and record current as its answer; push index
MONO-INCREASING (next smaller / span): while current < stack top, pop and compute width to near boundary; push index
MONO-DEQUE (window max): drop back while smaller than current, push; drop front if out of window; front = window max
PRIORITY QUEUE: offer(x); poll() removes the min (or max with reverse comparator)
TWO HEAPS: push to maxHeap, then shift its top to minHeap; rebalance so maxHeap >= minHeap; median from the tops
```

```
// 1. STACK (LIFO) — use ArrayDeque, not Stack class
Deque<Integer> stack = new ArrayDeque<>();
stack.push(x);
stack.pop();
stack.peek();
// 2a. MONOTONE DECREASING STACK — next GREATER element
Deque<Integer> stack = new ArrayDeque<>();
for (int i = 0; i < n; i++) {
    while (!stack.isEmpty() && nums[i] > nums[stack.peek()])
        result[stack.pop()] = nums[i];
    stack.push(i);
}
// 2b. MONOTONE INCREASING STACK — next SMALLER element / span width
Deque<Integer> stack = new ArrayDeque<>();
for (int i = 0; i < n; i++) {
    while (!stack.isEmpty() && nums[i] < nums[stack.peek()])
        result[stack.pop()] = i - stack.peek() - 1;
    stack.push(i);
}
// 3. MONOTONE DEQUE — sliding window max/min
Deque<Integer> queue = new ArrayDeque<>();
for (int i = 0; i < n; i++) {
    while (!queue.isEmpty() && nums[queue.peekLast()] <= nums[i])
        queue.pollLast();
    queue.offerLast(i);
    if (queue.peekFirst() < i - k + 1)
queue.pollFirst();
    if (i >= k - 1) result[i - k + 1] = nums[queue.peekFirst()];
}
// 4. PRIORITY QUEUE
PriorityQueue<Integer> minPQ = new PriorityQueue<>();
PriorityQueue<Integer> maxPQ = new PriorityQueue<>(Collections.reverseOrder()); // max-heap
PriorityQueue<int[]> pq = new PriorityQueue<>((a, b) -> a[1] - b[1]);
// custom: sort by index 1
pq.offer(x);
pq.poll();
pq.peek();
// 5. TWO HEAPS — maintain median in O(log n)
PriorityQueue<Integer> maxHeap = new PriorityQueue<>(Collections.reverseOrder());
PriorityQueue<Integer> minHeap = new PriorityQueue<>();
void addNum(int num) {
    maxHeap.offer(num);
    minHeap.offer(maxHeap.poll());
    if (maxHeap.size() < minHeap.size())
        maxHeap.offer(minHeap.poll());
}
double findMedian() {
    return maxHeap.size() > minHeap.size()
        ? maxHeap.peek()
        : (maxHeap.peek() + minHeap.peek()) / 2.0;
}
```

BFS (Tree)

The Template — Level-Aware BFS

Variables:
queue = nodes waiting to be processed · size = level snapshot (count of nodes in the current level) · level = current depth counter · node = node polled this step · i = index within the level

```
Queue<TreeNode> queue = new ArrayDeque<>();
queue.offer(root);
level = 0;
while (!queue.isEmpty()) {
    int size = queue.size();
    level++;
    for (int i = 0; i < size; i++) {
        TreeNode node = queue.poll();
        if (node.left != null)
queue.offer(node.left);
        if (node.right != null)
queue.offer(node.right);
    }
}
```

When to Use — Signal → Pattern

The One Rule — Snapshot Level Size First

Always snapshot the level size BEFORE the inner for loop:

```
int size = queue.size();
for (int i = 0; i < size; i++) { ... }
```

Without the snapshot, newly added children mix with the current level and `i == size-1` / `i == 0` checks become meaningless.

DFS / Backtracking

When to Use — Signal → Pattern

All Templates

Variables:
node = current tree node · accumulated/current = state carried down a path · answer/global = best cross-node result · grid[r][c] = cell value · visited[r][c] = seen-this-path · unseen / !in-stack / 2 done · start = first eligible index · current = in-progress candidate · nums[i] = element being chosen

Pseudocode:

```
if node null: return BASE; left=dfs(left); right=dfs(right); return
combine(left, right, node.val)
if node == c: return existing
if leaf: record; dfs[left,accumulated]; dfs[right,accumulated]; return
if node null: return 0;
left=max(0,dfs(left));
right=max(0,dfs(right));
answer=max(answer, left+right+node.val);
return max(left,right)+node.val
if node == null or node == TARGET: return; mark VISITED; recurse into 4 neighbors
if state==2: return; if state==1: safe; mark in-stack; recurse neighbors (cycle? return);
mark state = 2
if base: record copy; for i from start: skip dups; choose nums[i]; recurse(i+1); undo
```

```
// 1. PROCESS CHILDREN FIRST, COMBINE AT NODE (post-order)
private int dfs(TreeNode node) {
    if (node == null) return BASE;
    int left  = dfs(node.left);
    int right = dfs(node.right);
    return ...;
}
// 2. BOTH NODE FIRST, PASS STATE DOWN (pre-order)
private void dfs(TreeNode node, int accumulated) {
    if (node == null) return;
    accumulated += node.val;
    if (isLeaf(node)) { /* record */ return; }
    dfs(node.left,  accumulated);
    dfs(node.right, accumulated);
}
// 3. TREE — GLOBAL ANSWER (return up the best single arm; update global across both)
int answer = Integer.MIN_VALUE;
private int dfs(TreeNode node) {
    if (node == null) return 0;
    int left  = Math.max(0, dfs(node.left));
    int right = Math.max(0, dfs(node.right));
    answer = Math.max(answer, left + right + node.val);
    return Math.max(left, right) + node.val;
}
// 4. GRID DFS — mark visited by mutating grid; 4-directional flood fill
private void dfs(int[][] grid, int r, int c) {
    if (r < 0 || r >= grid.length || c < 0 || c >= grid[0].length) return;
    if (grid[r][c] != TARGET) return;
    grid[r][c] = VISITED;
    dfs(grid, r+1, c); dfs(grid, r-1, c);
    dfs(grid, r, c+1); dfs(grid, r, c-1);
}
// 5. GRAPH DFS — 3-color visited: 0=unseen 1=in-stack 2=done
int[] state;
private boolean dfs(int node) {
    if (state[node] == 1) return true;
    if (state[node] == 2) return false;
    state[node] = 1;
    for (int neighbor : graph.get(node))
        if (dfs(neighbor)) return true;
    state[node] = 2;
    return false;
}
// 6. BACKTRACKING — choose / recurse / undo
private void backtrack(int start, List<Integer> current) {
    if (/* base case */) result.add(new ArrayList<>(current)); return;
    for (int i = start; i < n; i++) {
        if (/* skip condition */) continue;
        current.add(nums[i]);
        backtrack(i+1, current);
        current.remove(current.size()-1);
    }
}
```

Greedy

Two Interval Templates

MERGE DIRECTION RULE (for merge-style problems like #56, where both keys work):
- Sort by START → traverse FORWARD (i = 0 → n), extend the END of last kept
- Sort by END → traverse BACKWARD (i = n-1 → 0), extend the START of last kept

These two are exact mirror images. See #56 for both versions side by side.

(NOTE: this mirror only applies to merging. Insert-style must be sorts by end but still sweeps FORWARD — there the goal is counting, not merging.)

TEMPLATE 1 — Sort by END time, sweep forward, track end of last kept interval
- Use when: maximizing count of non-overlapping intervals
- Greedy insight: earliest-finishing interval leaves most room for future ones

TEMPLATE 2 — Sort by START time, sweep forward, merge when overlapping
- Use when: merging/counting overlapping intervals
- Greedy insight: processing in start order = each interval only needs to compare with the last merged result

Variables:
intervals = list of [start, end] · lastEnd = end of last kept interval · result = merged output · pq = min-heap of active ends

Pseudocode:

```
TEMPLATE 1 (sort by end, count non-overlapping):
  sort intervals by END time
  lastEnd = -infinity
  for each interval:
    if interval.start >= lastEnd:  # no overlap
        lastEnd = interval.end
        keep interval (count++ or add)
    else:
        drop it (overlap)

TEMPLATE 2 (sort by start, merge):
  sort intervals by START time
  for each interval:
    if result empty OR last kept end < interval.start:
        add interval as new
    else:
        extend last kept end = max(last end, interval.end)

TEMPLATE 3 (sort by start + min-heap of ends):
  sort intervals by START time
  for each interval:
    if heap nonempty AND earliest end <= interval.start:
        pop heap          # reuse freed resource
    push interval.end     # occupy a resource
  heap size = resources needed
```

```
Arrays.sort(intervals, (a, b) -> a[1] - b[1]);
int lastEnd = Integer.MIN_VALUE;
for (int[] interval : intervals) {
    if (interval[0] >= lastEnd) {
        lastEnd = interval[1];
    } else {
    }
}
// Arrays.sort(intervals, (a, b) -> a[0] - b[0]);
List<int[]> result = new ArrayList<>();
for (int[] interval : intervals) {
    if (result.isEmpty() || result.get(result.size()-1)[1] < interval[0]) {
        result.add(interval);
    } else {
        result.get(result.size()-1)[1] = Math.max(result.get(result.size()-1)[1], interval[1]);
    }
}
Arrays.sort(intervals, (a, b) -> a[0] - b[0]);
PriorityQueue<Integer> pq = new PriorityQueue<>();
for (int[] interval : intervals) {
    while (!pq.isEmpty() && pq.peek() <= interval[0])
        pq.poll();
    pq.offer(interval[1]);
}
// pq.size();
```

Dynamic Programming

All Six Templates

Variables:
dp[i] = the answer for the subproblem at index/state i (meaning varies per family: ways/cost/length/feasibility ending at or reaching i) · n = problem size · target/j = knapsack capacity dimension.

Pseudocode:

```
LINEAR 1D:   dp[i] = fixed recipe over dp[i-1], dp[i-2]  Fibonacci, best ending at i
LOOK-BACK:   dp[i] = best/sum/count over a fixed window of the last k values
2D SEQUENCE: match consumes both strings (diagonal), mismatch drops one side
INTERVAL:    solve short ranges first, combine via a split point inside the range
GRID:        each cell accumulates from cells it could arrive from (up/left)
STATE MACHINE: name a few states, update each from yesterday's states every step
```

```
// 1. LINEAR 1D — each cell depends on a few previous cells
int[] dp = new int[n + 1];
dp[0] = base;
for (int i = 1; i <= n; i++)
    dp[i] = f(dp[i-1], dp[i-2], ...);
// KADANE (max subarray, #53) = Linear-1D where dp[i] = best sum ENDING at i
// 2A. LOOK-BACK 1D — dp[i] depends on dp[i-1], dp[i-2], ...
int[] dp = new int[n];
dp[0] = f(nums[0]);
for (int i = 1; i < n; i++) {
    dp[i] = f(dp[i-1], dp[i-2], ...);
}
// 3. 2D SEQUENCE — match consumes both, mismatch drops one side. WHEN: LCS / edit
// 4. INTERVAL DP — short ranges first (i right-to-left, j from i+1); dp[i][j+1] ready).
// 5. GRID DP — each cell accumulates from cells it could arrive from (up/left).
// 6. STATE MACHINE — named states updated from yesterday's states each step.
```

Graph

Core Templates

Variables:
queue = BFS frontier · visited[] = seen flags · level = current distance