

Binary Search Templates

Binary search appears in two forms: searching an **array index**, or searching an **answer value**.

Master Quick Reference

#	Name	Description	Intuition	Time	Space	Key Implementation
704	Binary Search	Given a sorted array and a target, return its index. Return -1 if not found.	The target is one specific value; halve a closed range until you sit on it (or the range empties).	$O(\log n)$	$O(1)$	Standard
34	Find First and Last Position of Element in Sorted Array	Return <code>[first, last]</code> index of target. Return <code>{-1, -1}</code> if absent.	Find the boundary where " $< \text{target}$ " flips to " $\geq \text{target}$ " (first position), and the next boundary just past target.	$O(\log n)$	$O(1)$	Standard
35	Search Insert Position	Return the index where target is or would be inserted to keep the array sorted.	The insert position is the first index whose value is $\geq \text{target}$ — exactly <code>lowerBound</code> .	$O(\log n)$	$O(1)$	Standard
33	Search in Rotated Sorted Array	Array was sorted then rotated at an unknown pivot. Find target index, or -1.	Even rotated, one half is always sorted; check if target lies in that half and discard the other.	$O(\log n)$	$O(1)$	Standard
162	Find Peak Element	Return any index where <code>arr[k] > arr[k-1]</code> and <code>arr[k] > arr[k+1]</code> . Edges are $-\infty$.	Always walk uphill — an upward slope guarantees a peak to the right, so the slope direction is the "condition".	$O(\log n)$	$O(1)$	Standard
875	Koko Eating Bananas	Minimum eating speed so Koko finishes all piles in h hours (one pile per hour, at most speed bananas eaten).	Feasibility is monotonic in speed (faster always works), so binary search the speed axis for the smallest that finishes in time.	$O(n \log(\max(\text{piles})))$	$O(1)$	Standard
1011	Capacity to Ship Packages Within D Days	Minimum ship capacity to deliver all packages (in order) within d days.	Bigger capacity is always feasible, so binary search capacity for the smallest that ships within the day budget.	$O(n \log(\sum(\text{weights})))$	$O(1)$	Standard
410	Split Array Largest Sum	Split array into m non-empty subarrays to minimize the largest subarray sum.	A larger allowed max-sum needs fewer parts, so binary search that cap for the smallest splittable into $\leq m$ parts.	$O(n \log(\sum(\text{nums})))$	$O(1)$	Standard
1283	Find the Smallest Divisor Given a Threshold	Smallest positive divisor such that <code>sum of ceil(nums[i] / divisor) <= threshold</code> .	A bigger divisor shrinks the sum, so the condition flips false $\rightarrow$ true; binary search for the smallest divisor that fits the threshold.	$O(n \log(\max(\text{nums})))$	$O(1)$	Standard
1231	Divide Chocolate $\leftarrow$ MAXIMIZE (the one that differs)	Cut chocolate into k+1 pieces; keep the minimum-sweetness piece. Maximize that minimum.	A larger target-minimum yields fewer pieces, so the condition flips true $\rightarrow$ false; binary search for the largest minimum still giving $\geq k+1$ pieces.	$O(n \log(\sum(s)))$	$O(1)$	Standard
4	Median of Two Sorted Arrays	Find the median of two sorted arrays of sizes m and n in $O(\log(m+n))$ time.	Pick a split of the smaller array; the rest of the split is forced. Shrink the partition until the left half's max $\leq$ the right half's min, then the median falls out of the boundary values.	$O(\log(\min(m, n)))$	$O(1)$	search smaller array

#	Name	Description	Intuition	Time	Space	Key Implementation
69	Sqrt(x)	Compute the integer square root of a non-negative integer x without using sqrt().	The condition <code>k*k <= x</code> holds true...true then flips false as k grows; find the largest k still true. Ceiling mid avoids the infinite loop at <code>i+1 == j</code> .	$O(\log x)$	$O(1)$	Standard
74	Search a 2D Matrix	Search for a target in an $m \times n$ matrix where each row is sorted and each row's first element > previous row's last.	The layout means the whole matrix reads as a single sorted sequence; map a flat index to <code>(row, col)</code> and run a standard closed binary search.	$O(\log(m*n))$	$O(1)$	flatten index to 2D
81	Search in Rotated Sorted Array II	Search in a sorted, rotated array that may contain duplicates.	Duplicates can make both ends equal to the midpoint so neither half looks sorted; in that ambiguous case shrink both bounds by one and retry.	$O(\log n)$ average, $O(n)$ worst	$O(1)$	ambiguous duplicates
153	Find Minimum in Rotated Sorted Array	Find the minimum element in a sorted, rotated array with no duplicates.	The minimum is the single point where the order breaks; if <code>arr[k] > arr[j]</code> the break is to the right, otherwise the min is at k or left.	$O(\log n)$	$O(1)$	compare to right end
240	Search a 2D Matrix II	Search for a target in an $m \times n$ matrix where rows and columns are both sorted.	From the top-right, moving left strictly decreases and moving down strictly increases, so each comparison eliminates a full row or column.	$O(m + n)$	$O(1)$	start top-right corner
278	First Bad Version	Find the first bad version using a provided <code>isBadVersion(n)</code> API. Minimize API calls.	Versions are good...good then bad...bad once corrupted; this is the classic first-true boundary search.	$O(\log n)$	$O(1)$	Standard
374	Guess Number Higher or Lower	Guess the number between 1 and n using a provided <code>guess()</code> API. Minimize calls.	<code>guess(k)</code> tells you which half holds the answer (<code>-1</code> lower, <code>1</code> higher); halve the closed range until it returns 0.	$O(\log n)$	$O(1)$	Standard
475	Heaters	Given house and heater positions, find the minimum heater radius so every house is covered by some heater.	Each house needs the closest heater; the required radius is the largest of those closest distances. Find each house's nearest heater by binary search.	$O((m + n) \log m)$	$O(1)$	also check left neighbor
540	Single Element in a Sorted Array	Find the single non-duplicate element in a sorted array where all others appear twice. $O(\log n)$.	Before the unique element each pair starts at an even index; after it, the parity shifts. Force the midpoint even and check whether its partner matches to pick a half.	$O(\log n)$	$O(1)$	force k even
658	Find K Closest Elements	Find k integers in a sorted array closest to x, ordered by closeness then value.	The answer is a contiguous window of size k; search for its start by comparing the distances of the two window edges to x and sliding toward the closer side.	$O(\log(n - k) + k)$	$O(k)$	search window start
719	Find K-th Smallest Pair Distance	Find the k-th smallest absolute distance among all pairs in the array.	The count of pairs with distance $\leq d$ is monotonic in d, so binary search the distance axis; count pairs $\leq d$ with a sliding window over the sorted array.	$O(n \log n + n \log(\maxDist))$	$O(1)$	search distance value

#	Name	Description	Intuition	Time	Space	Key Implementation
852	Peak Index in a Mountain Array	Find the peak index in a mountain array (element greater than both neighbors).	An upward slope means the peak is strictly to the right; a downward slope means the peak is here or to the left.	$O(\log n)$	$O(1)$	Standard
1060	Missing Element in Sorted Array	Find the kth missing number in a sorted array.	Missing count at each index increases monotonically, so binary search for the first index whose missing count is $\geq k$, then offset from the previous element.	$O(\log n)$	$O(1)$	kth missing beyond array end
1428	Leftmost Column with at Least a One	Find the leftmost column with at least one '1' in a binary matrix (rows sorted, accessed via BinaryMatrix API).	Each row is sorted 0...0 1...1; starting top-right, move left on a 1 (column might be even further left) and down on a 0, tracking the leftmost 1 seen.	$O(\text{rows} + \text{cols})$	$O(1)$	start top-right corner
1482	Minimum Number of Days to Make m Bouquets	Find the minimum number of days to make m bouquets of k adjacent flowers.	Waiting more days only adds bloomed flowers, so feasibility is monotonic; binary search the day axis and greedily count adjacent runs of bloomed flowers.	$O(n \log(\max(\text{bloomDay})))$	$O(1)$	impossible if not enough flowers
1539	Kth Missing Positive Number	Find the kth missing positive integer.	At each index the number of missing positives so far is <code>arr[k] - (k+1)</code> ; binary search the first index whose missing count is $\geq k$, then offset.	$O(\log n)$	$O(1)$	i missing-free slots + k
1818	Minimum Absolute Sum Difference	Find the minimum absolute sum difference after one substitution.	Total cost is the sum of absolute differences; one swap can only help where the closest available num1 value beats the current difference. Find that closest value by binary search and track the best gain.	$O(n \log n)$	$O(n)$	also check left neighbor
1891	Cutting Ribbons	Find the maximum ribbon length such that m ribbons of that length can be cut.	Longer pieces produce fewer ribbons, so the count flips true→false as length grows; find the largest length still giving enough ribbons. Ceiling mid avoids the infinite loop.	$O(n \log(\max(\text{ribbons})))$	$O(1)$	closed [i, j], result tracked

* #162 uses `j = n-1` (not `n`) — loop reads `arr[k+1]`, out of bounds if `j = n`.

All Four Templates

```
// 1. CLOSED [i, j] – exact match, return on hit
// MENTAL MODEL: target is a specific value sitting at some index; shrink a fully-closed range until you
// WHEN: "find this exact value in a sorted array"
int i = 0, j = n - 1;
while (i <= j) {
    int k = i + (j - i) / 2;
    if (arr[k] == target) {
        return k;
    } else if (arr[k] < target) {
        i = k + 1;
    } else {
        j = k - 1;
    }
}
return -1;

// 2. HALF-OPEN [i, j) – boundary search, answer falls out of i
// MENTAL MODEL: the predicate is false...false TRUE...true; find the FIRST position that satisfies the c
// WHEN: "first/last position", "insert position", "first index where condition holds"
int i = 0, j = n;          // j = n (or n-1 for #162)
while (i < j) {
    int k = i + (j - i) / 2;
    if (arr[k] < target) {
        i = k + 1;    // lowerBound: <
    } else {
        j = k;        // upperBound: swap < for <=
    }
}
return i;

// 3. ANSWER SPACE MINIMIZE – smallest k where condition(k) is true
// MENTAL MODEL: condition goes false→TRUE as k grows (bigger k = more feasible); find the smallest k tha
// WHEN: "minimum X such that feasible(X)" – min speed, min capacity, smallest divisor
int i = minPossible, j = maxPossible;
while (i < j) {
    int k = i + (j - i) / 2;          // floor mid
    if (condition(k)) {
        j = k;
    } else {
        i = k + 1;
    }
}
return i;

// 4. ANSWER SPACE MAXIMIZE – largest k where condition(k) is true
// MENTAL MODEL: condition goes TRUE→false as k grows (bigger k = less feasible); find the largest k stil
// WHEN: "maximum X such that feasible(X)" – max min-piece, max guarantee
int i = minPossible, j = maxPossible;
while (i < j) {
    int k = i + (j - i + 1) / 2;      // ceiling mid ← avoids infinite loop
    if (condition(k)) {
        i = k;
    } else {
        j = k - 1;
    }
}
return i;
```

How to Choose

Signal	Template
Sorted array, find exact value	Closed — return on <code>arr[k] == target</code>
First/last position, insert position	Half-open <code>lowerBound</code> / <code>upperBound</code>
Rotated array or slope search	Closed — pick sorted half each step
"minimum X such that feasible(X)"	Answer space MINIMIZE — floor mid
"maximum X such that feasible(X)"	Answer space MAXIMIZE — ceiling mid

Part 1 — Binary Search on Array Index

Detail Table

#	Name	Description	Interval	On <code>arr[k]==target</code>	Shrink left	Shrink right	Return
704	Binary Search	Find index of target; -1 if absent	Closed	<code>return k</code>	<code>i = k+1</code>	<code>j = k-1</code>	<code>-1</code>
34	First & Last Position	First and last index of target	Half-open	—	<code>i = k+1</code>	<code>j = k</code>	<code>{lower, upper-1}</code>
35	Search Insert Position	Index where target is or would be inserted	Half-open	—	<code>i = k+1</code>	<code>j = k</code>	<code>i</code>
33	Search in Rotated Array	Find target after unknown-pivot rotation	Closed	<code>return k</code>	<code>i = k+1</code>	<code>j = k-1</code>	<code>-1</code>
162	Find Peak Element	Any local peak index	Half-open*	—	<code>i = k+1</code>	<code>j = k</code>	<code>i</code>

#704 Binary Search

Description: Given a sorted array and a target, return its index. Return -1 if not found.

Template: Closed `[i, j]` — return immediately on exact hit.

Intuition: The target is one specific value; halve a closed range until you sit on it (or the range empties).

```
class Solution {
    public int search(int[] arr, int target) {
        int i = 0, j = arr.length - 1;
        while (i <= j) {
            int k = i + (j - i) / 2;
            if (arr[k] == target) {
                return k;
            } else if (arr[k] < target) {
                i = k + 1;
            } else {
                j = k - 1;
            }
        }
        return -1;
    }
}
```

Time $O(\log n)$ | **Space** $O(1)$

#34 Find First and Last Position of Element in Sorted Array

Description: Return `[first, last]` index of target. Return `{-1, -1}` if absent.

Template: Half-open `[i, j)`. `lowerBound` vs `upperBound` differ by one char: `<` vs `<=`.

Intuition: Find the boundary where "`< target`" flips to "`≥ target`" (first position), and the next boundary just past target.

```
class Solution {
    public int[] searchRange(int[] arr, int target) {
        int i = lowerBound(arr, target);
        if (i == arr.length || arr[i] != target) return new int[]{-1, -1};
        return new int[]{i, upperBound(arr, target) - 1};
    }
    private int lowerBound(int[] arr, int target) {
        int i = 0, j = arr.length;
        while (i < j) {
            int k = i + (j - i) / 2;
            if (arr[k] < target) {
                i = k + 1; // must go right
            } else {
                j = k; // k might be answer
            }
        }
        return i;
    }
    private int upperBound(int[] arr, int target) {
        int i = 0, j = arr.length;
        while (i < j) {
            int k = i + (j - i) / 2;
            if (arr[k] <= target) {
                i = k + 1; // still <= target, go right
            } else {
                j = k;
            }
        }
        return i;
    }
}
```

Time $O(\log n)$ | **Space** $O(1)$

#35 Search Insert Position

Description: Return the index where target is or would be inserted to keep the array sorted.

Template: Half-open `[i, j)` — identical to `lowerBound` from #34.

Intuition: The insert position is the first index whose value is $\geq$ target — exactly `lowerBound`.

```

class Solution {
    public int searchInsert(int[] arr, int target) {
        int i = 0, j = arr.length;
        while (i < j) {
            int k = i + (j - i) / 2;
            if (arr[k] < target) {
                i = k + 1;
            } else {
                j = k;
            }
        }
        return i;
    }
}

```

Time $O(\log n)$ | **Space** $O(1)$

#33 Search in Rotated Sorted Array

Description: Array was sorted then rotated at an unknown pivot. Find target index, or -1.

Template: Closed $[i, j]$. One half is always sorted — identify which, then test if target lies in it.

Intuition: Even rotated, one half is always sorted; check if target lies in that half and discard the other.

```

class Solution {
    public int search(int[] arr, int target) {
        int i = 0, j = arr.length - 1;
        while (i <= j) {
            int k = i + (j - i) / 2;
            if (arr[k] == target) return k;
            if (arr[i] <= arr[k]) { // left half [i..k] is sorted
                if (arr[i] <= target && target < arr[k]) {
                    j = k - 1;
                } else {
                    i = k + 1;
                }
            } else { // right half [k..j] is sorted
                if (arr[k] < target && target <= arr[j]) {
                    i = k + 1;
                } else {
                    j = k - 1;
                }
            }
        }
        return -1;
    }
}

```

Time $O(\log n)$ | **Space** $O(1)$

$arr[i] \leq arr[k]$ (not $<$) handles the edge case where $i == k$.

#162 Find Peak Element

Description: Return any index where $arr[k] > arr[k-1]$ and $arr[k] > arr[k+1]$. Edges are $-\infty$.

Template: Half-open $[i, j)$ with $j = n-1$. Binary search on slope: upward $\rightarrow$ peak is right, downward $\rightarrow$ peak is here or left.

Intuition: Always walk uphill — an upward slope guarantees a peak to the right, so the slope direction is the "condition".

```

class Solution {
    public int findPeakElement(int[] arr) {
        int i = 0, j = arr.length - 1;
        while (i < j) {
            int k = i + (j - i) / 2;
            if (arr[k] < arr[k + 1]) {
                i = k + 1; // slope up → go right
            } else {
                j = k;      // slope down → peak at k or left
            }
        }
        return i;
    }
}

```

Time $O(\log n)$ | **Space** $O(1)$

Part 2 — Binary Search on Answer Space

Search on the **answer value** itself, not an array index. All use half-open `[i, j)` with `while (i < j)`.

Detail Table

#	Name	Description	Variant	i init	j init	Mid	Condition true	Condition false	Helper checks
875	Koko Eating Bananas	Min speed to finish all piles in h hours	MINIMIZE	1	max(piles)	floor	j = k	i = k+1	hours <= h
1011	Ship Within D Days	Min capacity to ship all packages in d days	MINIMIZE	max(w)	sum(w)	floor	j = k	i = k+1	days <= d
410	Split Array Largest Sum	Min largest sum splitting array into m parts	MINIMIZE	max(nums)	sum(nums)	floor	j = k	i = k+1	parts <= m
1283	Smallest Divisor	Smallest divisor so ceil-div-sum ≤ threshold	MINIMIZE	1	max(nums)	floor	j = k	i = k+1	divSum <= threshold
1231	Divide Chocolate	Max min-sweetness cutting into k+1 pieces	MAXIMIZE	min(s)	sum(s)/(k+1)	ceiling	i = k	j = k-1	pieces >= k+1

875 / 1011 / 410 / 1283 → identical structure, differ only in search bounds and condition helper.
 1231 → only one that flips (MAXIMIZE): ceiling mid, `i = k` on success.

#875 Koko Eating Bananas

Description: Minimum eating speed so Koko finishes all piles in h hours (one pile per hour, at most `speed` bananas eaten).
Search space: `[1, max(piles)]`

Intuition: Feasibility is monotonic in speed (faster always works), so binary search the speed axis for the smallest that finishes in time.

```
class Solution {
    public int minEatingSpeed(int[] piles, int h) {
        int i = 1, j = Arrays.stream(piles).max().getAsInt();
        while (i < j) {
            int k = i + (j - i) / 2;
            if (canFinish(piles, k, h)) {
                j = k;
            } else {
                i = k + 1;
            }
        }
        return i;
    }
    private boolean canFinish(int[] piles, int speed, int h) {
        int hours = 0;
        for (int p : piles) hours += (p + speed - 1) / speed;
        return hours <= h;
    }
}
```

Time $O(n \log(\max(\text{piles})))$ | **Space** $O(1)$

#1011 Capacity to Ship Packages Within D Days

Description: Minimum ship capacity to deliver all packages (in order) within d days.

Search space: $[\max(\text{weights}), \text{sum}(\text{weights})]$ — must fit heaviest; worst case ships one per day.

Intuition: Bigger capacity is always feasible, so binary search capacity for the smallest that ships within the day budget.

```
class Solution {
    public int shipWithinDays(int[] weights, int days) {
        int i = Arrays.stream(weights).max().getAsInt();
        int j = Arrays.stream(weights).sum();
        while (i < j) {
            int k = i + (j - i) / 2;
            if (canShip(weights, k, days)) {
                j = k;
            } else {
                i = k + 1;
            }
        }
        return i;
    }
    private boolean canShip(int[] weights, int cap, int days) {
        int d = 1, load = 0;
        for (int w : weights) {
            if (load + w > cap) { d++; load = 0; }
            load += w;
        }
        return d <= days;
    }
}
```

Time $O(n \log(\text{sum}(\text{weights})))$ | **Space** $O(1)$

#410 Split Array Largest Sum

Description: Split array into m non-empty subarrays to minimize the largest subarray sum.

Search space: `[max(nums), sum(nums)]` — identical bounds to #1011.

Intuition: A larger allowed max-sum needs fewer parts, so binary search that cap for the smallest splittable into $\leq m$ parts.

```
class Solution {
    public int splitArray(int[] nums, int m) {
        int i = Arrays.stream(nums).max().getAsInt();
        int j = Arrays.stream(nums).sum();
        while (i < j) {
            int k = i + (j - i) / 2;
            if (canSplit(nums, k, m)) {
                j = k;
            } else {
                i = k + 1;
            }
        }
        return i;
    }
    private boolean canSplit(int[] nums, int cap, int m) {
        int parts = 1, sum = 0;
        for (int n : nums) {
            if (sum + n > cap) { parts++; sum = 0; }
            sum += n;
        }
        return parts <= m;
    }
}
```

Time $O(n \log(\text{sum}(\text{nums})))$ | **Space** $O(1)$

#1283 Find the Smallest Divisor Given a Threshold

Description: Smallest positive divisor such that `sum of ceil(nums[i] / divisor) <= threshold`.

Search space: `[1, max(nums)]`

Intuition: A bigger divisor shrinks the sum, so the condition flips false→true; binary search for the smallest divisor that fits the threshold.

```
class Solution {
    public int smallestDivisor(int[] nums, int threshold) {
        int i = 1, j = Arrays.stream(nums).max().getAsInt();
        while (i < j) {
            int k = i + (j - i) / 2;
            if (divSum(nums, k) <= threshold) {
                j = k;
            } else {
                i = k + 1;
            }
        }
        return i;
    }
    private int divSum(int[] nums, int d) {
        int sum = 0;
        for (int n : nums) sum += (n + d - 1) / d;
        return sum;
    }
}
```

Time $O(n \log(\text{max}(\text{nums})))$ | **Space** $O(1)$

#1231 Divide Chocolate ← MAXIMIZE (the one that differs)

Description: Cut chocolate into $k+1$ pieces; keep the minimum-sweetness piece. Maximize that minimum.

Search space: $[\min(s), \text{sum}(s)/(k+1)]$

Intuition: A larger target-minimum yields fewer pieces, so the condition flips true→false; binary search for the largest minimum still giving $\geq k+1$ pieces.

Ceiling mid is required. Concrete trace: with floor mid, $i=4, j=5 \rightarrow \text{mid}=4 \rightarrow$ on success $i=4 \rightarrow$ infinite loop; ceiling mid $i+(j-i+1)/2 \rightarrow \text{mid}=5 \rightarrow i=5 \rightarrow$ exits.

```
class Solution {
    public int maximizeSweetness(int[] s, int k) {
        int i = Arrays.stream(s).min().getAsInt();
        int j = Arrays.stream(s).sum() / (k + 1);
        while (i < j) {
            int m = i + (j - i + 1) / 2; // ceiling: guarantees progress when j == i+1
            if (canDivide(s, k + 1, m)) {
                i = m;
            } else {
                j = m - 1;
            }
        }
        return i;
    }
    private boolean canDivide(int[] s, int pieces, int minSweet) {
        int count = 0, sum = 0;
        for (int x : s) {
            sum += x;
            if (sum >= minSweet) { count++; sum = 0; }
        }
        return count >= pieces;
    }
}
```

Time $O(n \log(\text{sum}(s)))$ | **Space** $O(1)$

MINIMIZE vs MAXIMIZE Side by Side

	MINIMIZE (875,1011,410,1283)	MAXIMIZE (1231)
Mid:	floor $i + (j-i) / 2$	ceiling $i + (j-i+1) / 2$
If condition true:	$j = k$	$i = k$
If condition false:	$i = k + 1$	$j = k - 1$
Condition checks:	$\leq$ budget (feasible)	$\geq$ count (enough pieces)

Why ceiling for MAXIMIZE: when $i+1 == j$:

- floor gives $k = i \rightarrow$ if true, $i = i \rightarrow$ **infinite loop**
- ceiling gives $k = j \rightarrow$ if true, $i = j \rightarrow$ loop ends ✓

Additional Reference Problems

#4 Median of Two Sorted Arrays

Description: Find the median of two sorted arrays of sizes m and n in $O(\log(m+n))$ time.

Template: Half-open $[i, j)$ — binary search the partition point in the smaller array.

Intuition: Pick a split of the smaller array; the rest of the split is forced. Shrink the partition until the left half's $\max \leq$ the right half's $\min$, then the median falls out of the boundary values.

```
class Solution {
    public double findMedianSortedArrays(int[] nums1, int[] nums2) {
        if (nums1.length > nums2.length) { // ← VARIATION: search smaller array
            return findMedianSortedArrays(nums2, nums1);
        }
        int m = nums1.length, n = nums2.length;
        int half = (m + n + 1) / 2;
        int i = 0, j = m;
        while (i <= j) { // ← VARIATION: closed [i, j] on partition
            int k = i + (j - i) / 2; // cut in nums1
            int cut2 = half - k; // cut in nums2
            int left1 = (k == 0) ? Integer.MIN_VALUE : nums1[k - 1];
            int right1 = (k == m) ? Integer.MAX_VALUE : nums1[k];
            int left2 = (cut2 == 0) ? Integer.MIN_VALUE : nums2[cut2 - 1];
            int right2 = (cut2 == n) ? Integer.MAX_VALUE : nums2[cut2];
            if (left1 <= right2 && left2 <= right1) {
                if (((m + n) & 1) == 1) {
                    return Math.max(left1, left2);
                } else {
                    return (Math.max(left1, left2) + Math.min(right1, right2)) / 2.0;
                }
            } else if (left1 > right2) {
                j = k - 1;
            } else {
                i = k + 1;
            }
        }
        return 0.0;
    }
}
```

Time $O(\log(\min(m, n)))$ | **Space** $O(1)$

#69 Sqrt(x)

Description: Compute the integer square root of a non-negative integer x without using `sqrt()`.

Template: Answer space MAXIMIZE — largest k with $k*k \leq x$.

Intuition: The condition $k*k \leq x$ holds true...true then flips false as k grows; find the largest k still true. Ceiling mid avoids the infinite loop at $i+1 == j$.

```

class Solution {
    public int mySqrt(int x) {
        if (x < 2) {
            return x;
        }
        int i = 1, j = x;
        while (i < j) {
            int k = i + (j - i + 1) / 2;           // ceiling mid (MAXIMIZE)
            if ((long) k * k <= x) {
                i = k;
            } else {
                j = k - 1;
            }
        }
        return i;
    }
}

```

Time $O(\log x)$ | **Space** $O(1)$

#74 Search a 2D Matrix

Description: Search for a target in an $m \times n$ matrix where each row is sorted and each row's first element > previous row's last.

Template: Closed `[i, j]` — treat the matrix as one flat sorted array of length $m*n$.

Intuition: The layout means the whole matrix reads as a single sorted sequence; map a flat index to `(row, col)` and run a standard closed binary search.

```

class Solution {
    public boolean searchMatrix(int[][] matrix, int target) {
        int m = matrix.length, n = matrix[0].length;
        int i = 0, j = m * n - 1;
        while (i <= j) {
            int k = i + (j - i) / 2;
            int value = matrix[k / n][k % n];           // ← VARIATION: flatten index to 2D
            if (value == target) {
                return true;
            } else if (value < target) {
                i = k + 1;
            } else {
                j = k - 1;
            }
        }
        return false;
    }
}

```

Time $O(\log(m*n))$ | **Space** $O(1)$

#81 Search in Rotated Sorted Array II

Description: Search in a sorted, rotated array that may contain duplicates.

Template: Closed `[i, j]` — like #33, but duplicates force a linear shrink when `arr[i] == arr[k] == arr[j]`.

Intuition: Duplicates can make both ends equal to the midpoint so neither half looks sorted; in that ambiguous case shrink both bounds by one and retry.

```

class Solution {
    public boolean search(int[] arr, int target) {
        int i = 0, j = arr.length - 1;
        while (i <= j) {
            int k = i + (j - i) / 2;
            if (arr[k] == target) {
                return true;
            }
            if (arr[i] == arr[k] && arr[k] == arr[j]) { // ← VARIATION: ambiguous duplicates
                i++;
                j--;
            } else if (arr[i] <= arr[k]) { // left half sorted
                if (arr[i] <= target && target < arr[k]) {
                    j = k - 1;
                } else {
                    i = k + 1;
                }
            } else { // right half sorted
                if (arr[k] < target && target <= arr[j]) {
                    i = k + 1;
                } else {
                    j = k - 1;
                }
            }
        }
        return false;
    }
}

```

Time $O(\log n)$ average, $O(n)$ worst | **Space** $O(1)$

#153 Find Minimum in Rotated Sorted Array

Description: Find the minimum element in a sorted, rotated array with no duplicates.

Template: Half-open `[i, j]` on slope — compare midpoint to the right end to pick the unsorted half.

Intuition: The minimum is the single point where the order breaks; if `arr[k] > arr[j]` the break is to the right, otherwise the min is at `k` or left.

```

class Solution {
    public int findMin(int[] arr) {
        int i = 0, j = arr.length - 1;
        while (i < j) {
            int k = i + (j - i) / 2;
            if (arr[k] > arr[j]) { // ← VARIATION: compare to right end
                i = k + 1;
            } else {
                j = k;
            }
        }
        return arr[i];
    }
}

```

Time $O(\log n)$ | **Space** $O(1)$

#240 Search a 2D Matrix II

Description: Search for a target in an $m \times n$ matrix where rows and columns are both sorted.

Template: Staircase search from the top-right corner (not a halving binary search, but the canonical $O(m+n)$ solution).

Intuition: From the top-right, moving left strictly decreases and moving down strictly increases, so each comparison eliminates a full row or column.

```
class Solution {
    public boolean searchMatrix(int[][] matrix, int target) {
        int row = 0, col = matrix[0].length - 1; // ← VARIATION: start top-right corner
        while (row < matrix.length && col >= 0) {
            int value = matrix[row][col];
            if (value == target) {
                return true;
            } else if (value > target) {
                col--;
            } else {
                row++;
            }
        }
        return false;
    }
}
```

Time $O(m + n)$ | **Space** $O(1)$

#278 First Bad Version

Description: Find the first bad version using a provided `isBadVersion(n)` API. Minimize API calls.

Template: Half-open `[i, j]` — find the first index where `isBadVersion` flips false→true.

Intuition: Versions are good...good then bad...bad once corrupted; this is the classic first-true boundary search.

```
/* The isBadVersion API is defined in the parent class VersionControl.
boolean isBadVersion(int version); */
public class Solution extends VersionControl {
    public int firstBadVersion(int n) {
        int i = 1, j = n;
        while (i < j) {
            int k = i + (j - i) / 2;
            if (isBadVersion(k)) {
                j = k;
            } else {
                i = k + 1;
            }
        }
        return i;
    }
}
```

Time $O(\log n)$ | **Space** $O(1)$

#374 Guess Number Higher or Lower

Description: Guess the number between 1 and n using a provided `guess()` API. Minimize calls.

Template: Closed `[i, j]` — return on the exact hit when `guess` returns 0.

Intuition: `guess(k)` tells you which half holds the answer (`-1` lower, `1` higher); halve the closed range until it returns 0.

```

/* The guess API is defined in the parent class GuessGame.
   int guess(int num); returns -1, 1, or 0. */
public class Solution extends GuessGame {
    public int guessNumber(int n) {
        int i = 1, j = n;
        while (i <= j) {
            int k = i + (j - i) / 2;
            int response = guess(k);
            if (response == 0) {
                return k;
            } else if (response < 0) {           // my guess is too high
                j = k - 1;
            } else {
                i = k + 1;
            }
        }
        return -1;
    }
}

```

Time $O(\log n)$ | **Space** $O(1)$

#475 Heaters

Description: Given house and heater positions, find the minimum heater radius so every house is covered by some heater.

Template: Closed $[i, j]$ — for each house, binary search the nearest heater; the answer is the max over all houses of the closest distance.

Intuition: Each house needs the closest heater; the required radius is the largest of those closest distances. Find each house's nearest heater by binary search.

```

class Solution {
    public int findRadius(int[] houses, int[] heaters) {
        Arrays.sort(heaters);
        int result = 0;
        for (int house : houses) {
            int i = 0, j = heaters.length - 1;
            while (i < j) {                       // find first heater >= house
                int k = i + (j - i) / 2;
                if (heaters[k] < house) {
                    i = k + 1;
                } else {
                    j = k;
                }
            }
            int distance = Math.abs(heaters[i] - house);
            if (i > 0) {                           // ← VARIATION: also check left neighbor
                distance = Math.min(distance, house - heaters[i - 1]);
            }
            result = Math.max(result, distance);
        }
        return result;
    }
}

```

Time $O((m + n) \log m)$ | **Space** $O(1)$

#540 Single Element in a Sorted Array

Description: Find the single non-duplicate element in a sorted array where all others appear twice. $O(\log n)$.

Template: Half-open `[i, j]` on even indices — a pair starting at an even index is intact iff it lies before the single element.

Intuition: Before the unique element each pair starts at an even index; after it, the parity shifts. Force the midpoint even and check whether its partner matches to pick a half.

```
class Solution {
    public int singleNonDuplicate(int[] arr) {
        int i = 0, j = arr.length - 1;
        while (i < j) {
            int k = i + (j - i) / 2;
            if ((k & 1) == 1) { // ← VARIATION: force k even
                k--;
            }
            if (arr[k] == arr[k + 1]) { // pair intact → single is to the right
                i = k + 2;
            } else {
                j = k;
            }
        }
        return arr[i];
    }
}
```

Time $O(\log n)$ | **Space** $O(1)$

#658 Find K Closest Elements

Description: Find k integers in a sorted array closest to x , ordered by closeness then value.

Template: Half-open `[i, j]` — binary search the left boundary of the size- k window.

Intuition: The answer is a contiguous window of size k ; search for its start by comparing the distances of the two window edges to x and sliding toward the closer side.

```
class Solution {
    public List<Integer> findClosestElements(int[] arr, int k, int x) {
        int i = 0, j = arr.length - k; // ← VARIATION: search window start
        while (i < j) {
            int mid = i + (j - i) / 2;
            if (x - arr[mid] > arr[mid + k] - x) { // right edge is closer → move right
                i = mid + 1;
            } else {
                j = mid;
            }
        }
        List<Integer> result = new ArrayList<>();
        for (int p = i; p < i + k; p++) {
            result.add(arr[p]);
        }
        return result;
    }
}
```

Time $O(\log(n - k) + k)$ | **Space** $O(k)$

#719 Find K-th Smallest Pair Distance

Description: Find the k-th smallest absolute distance among all pairs in the array.

Template: Answer space MINIMIZE — smallest distance d with at least k pairs $\leq$ d.

Intuition: The count of pairs with distance $\leq$ d is monotonic in d, so binary search the distance axis; count pairs $\leq$ d with a sliding window over the sorted array.

```
class Solution {
    public int smallestDistancePair(int[] nums, int k) {
        Arrays.sort(nums);
        int i = 0, j = nums[nums.length - 1] - nums[0]; // ← VARIATION: search distance value
        while (i < j) {
            int mid = i + (j - i) / 2;
            if (countPairs(nums, mid) >= k) {
                j = mid;
            } else {
                i = mid + 1;
            }
        }
        return i;
    }
    private int countPairs(int[] nums, int maxDist) {
        int count = 0, left = 0;
        for (int right = 0; right < nums.length; right++) {
            while (nums[right] - nums[left] > maxDist) {
                left++;
            }
            count += right - left;
        }
        return count;
    }
}
```

Time $O(n \log n + n \log(\text{maxDist}))$ | **Space** $O(1)$

#852 Peak Index in a Mountain Array

Description: Find the peak index in a mountain array (element greater than both neighbors).

Template: Half-open $[i, j]$ on slope — walk uphill toward the peak.

Intuition: An upward slope means the peak is strictly to the right; a downward slope means the peak is here or to the left.

```
class Solution {
    public int peakIndexInMountainArray(int[] arr) {
        int i = 0, j = arr.length - 1;
        while (i < j) {
            int k = i + (j - i) / 2;
            if (arr[k] < arr[k + 1]) { // slope up → go right
                i = k + 1;
            } else {
                j = k;
            }
        }
        return i;
    }
}
```

Time $O(\log n)$ | **Space** $O(1)$

#1060 Missing Element in Sorted Array

Description: Find the kth missing number in a sorted array.

Template: Half-open `[i, j]` — the count of missing numbers before index `k` is `arr[k] - arr[0] - k`, which is monotonic.

Intuition: Missing count at each index increases monotonically, so binary search for the first index whose missing count is $\geq k$, then offset from the previous element.

```
class Solution {
    public int missingElement(int[] nums, int k) {
        int n = nums.length;
        int i = 0, j = n - 1;
        while (i < j) { // first index with missing count >= k
            int mid = i + (j - i) / 2;
            if (missingCount(nums, mid) >= k) {
                j = mid;
            } else {
                i = mid + 1;
            }
        }
        if (missingCount(nums, i) < k) { // ← VARIATION: kth missing beyond array end
            return nums[n - 1] + (k - missingCount(nums, n - 1));
        }
        return nums[i - 1] + (k - missingCount(nums, i - 1));
    }
    private int missingCount(int[] nums, int index) {
        return nums[index] - nums[0] - index;
    }
}
```

Time $O(\log n)$ | **Space** $O(1)$

#1428 Leftmost Column with at Least a One

Description: Find the leftmost column with at least one '1' in a binary matrix (rows sorted, accessed via BinaryMatrix API).

Template: Staircase walk from the top-right corner across rows that are individually sorted.

Intuition: Each row is sorted 0...0 1...1; starting top-right, move left on a 1 (column might be even further left) and down on a 0, tracking the leftmost 1 seen.

```

/* interface BinaryMatrix {
    public int get(int row, int col);
    public List<Integer> dimensions();
} */
class Solution {
    public int leftMostColumnWithOne(BinaryMatrix binaryMatrix) {
        List<Integer> dim = binaryMatrix.dimensions();
        int rows = dim.get(0), cols = dim.get(1);
        int row = 0, col = cols - 1; // ← VARIATION: start top-right corner
        int result = -1;
        while (row < rows && col >= 0) {
            if (binaryMatrix.get(row, col) == 1) {
                result = col;
                col--;
            } else {
                row++;
            }
        }
        return result;
    }
}

```

Time $O(\text{rows} + \text{cols})$ | **Space** $O(1)$

#1482 Minimum Number of Days to Make m Bouquets

Description: Find the minimum number of days to make m bouquets of k adjacent flowers.

Template: Answer space MINIMIZE — smallest day count d that yields $\geq m$ bouquets.

Intuition: Waiting more days only adds bloomed flowers, so feasibility is monotonic; binary search the day axis and greedily count adjacent runs of bloomed flowers.

```

class Solution {
    public int minDays(int[] bloomDay, int m, int k) {
        long need = (long) m * k;
        if (need > bloomDay.length) { // ← VARIATION: impossible if not enough fl
            return -1;
        }
        int i = Arrays.stream(bloomDay).min().getAsInt();
        int j = Arrays.stream(bloomDay).max().getAsInt();
        while (i < j) {
            int k2 = i + (j - i) / 2;
            if (canMake(bloomDay, m, k, k2)) {
                j = k2;
            } else {
                i = k2 + 1;
            }
        }
        return i;
    }
    private boolean canMake(int[] bloomDay, int m, int k, int day) {
        int bouquets = 0, adjacent = 0;
        for (int bloom : bloomDay) {
            if (bloom <= day) {
                adjacent++;
                if (adjacent == k) {
                    bouquets++;
                    adjacent = 0;
                }
            } else {
                adjacent = 0;
            }
        }
        return bouquets >= m;
    }
}

```

Time $O(n \log(\max(\text{bloomDay})))$ | **Space** $O(1)$

#1539 Kth Missing Positive Number

Description: Find the kth missing positive integer.

Template: Half-open $[i, j]$ — missing count before index k is $\text{arr}[k] - (k + 1)$, monotonic non-decreasing.

Intuition: At each index the number of missing positives so far is $\text{arr}[k] - (k+1)$; binary search the first index whose missing count is $\geq k$, then offset.

```

class Solution {
    public int findKthPositive(int[] arr, int k) {
        int i = 0, j = arr.length;
        while (i < j) { // first index with missing count >= k
            int mid = i + (j - i) / 2;
            if (arr[mid] - (mid + 1) >= k) {
                j = mid;
            } else {
                i = mid + 1;
            }
        }
        return i + k; // ← VARIATION: i missing-free slots + k
    }
}

```

Time $O(\log n)$ | **Space** $O(1)$

#1818 Minimum Absolute Sum Difference

Description: Find the minimum absolute sum difference after one substitution.

Template: Closed `[i, j]` — for each element binary search a sorted copy of `nums1` for the value closest to `nums2[i]`.

Intuition: Total cost is the sum of absolute differences; one swap can only help where the closest available `nums1` value beats the current difference. Find that closest value by binary search and track the best gain.

```
class Solution {
    public int minAbsoluteSumDiff(int[] nums1, int[] nums2) {
        int MOD = 1_000_000_007;
        int n = nums1.length;
        int[] sorted = nums1.clone();
        Arrays.sort(sorted);
        long total = 0;
        int maxGain = 0;
        for (int p = 0; p < n; p++) {
            int diff = Math.abs(nums1[p] - nums2[p]);
            total += diff;
            int target = nums2[p];
            int i = 0, j = sorted.length - 1;
            while (i < j) {
                // first value >= target
                int k = i + (j - i) / 2;
                if (sorted[k] < target) {
                    i = k + 1;
                } else {
                    j = k;
                }
            }
            int best = diff;
            best = Math.min(best, Math.abs(sorted[i] - target));
            if (i > 0) {
                // ← VARIATION: also check left neighbor
                best = Math.min(best, Math.abs(sorted[i - 1] - target));
            }
            maxGain = Math.max(maxGain, diff - best);
        }
        return (int) ((total - maxGain) % MOD);
    }
}
```

Time $O(n \log n)$ | **Space** $O(n)$

#1891 Cutting Ribbons

Description: Find the maximum ribbon length such that m ribbons of that length can be cut.

Template: Answer space MAXIMIZE — largest length k that still yields $\geq m$ ribbons.

Intuition: Longer pieces produce fewer ribbons, so the count flips true→false as length grows; find the largest length still giving enough ribbons. Ceiling mid avoids the infinite loop.

```

class Solution {
    public int maxLength(int[] ribbons, int k) {
        int j = 0;
        for (int ribbon : ribbons) {
            j = Math.max(j, ribbon);
        }
        int i = 1;
        int result = 0;
        while (i <= j) {
            // ← VARIATION: closed [i, j], result track
            int mid = i + (j - i) / 2;
            if (countRibbons(ribbons, mid) >= k) {
                result = mid;
                i = mid + 1;
            } else {
                j = mid - 1;
            }
        }
        return result;
    }
    private long countRibbons(int[] ribbons, int length) {
        long count = 0;
        for (int ribbon : ribbons) {
            count += ribbon / length;
        }
        return count;
    }
}

```

Time $O(n \log(\max(\text{ribbons})))$ | **Space** $O(1)$