

BFS Templates — Tree

Core structure: `Queue<TreeNode> queue = new ArrayDeque<>()`.

One template: snapshot the level size, then drain exactly that many nodes per level.

The Template — Level-Aware BFS

Variables: `queue` = nodes waiting to be processed · `size` = level snapshot (count of nodes in the current level) · `level` = current depth counter · `node` = node polled this step · `i` = index within the level **Pseudocode:**

```
make an empty queue
put root in the queue
level = 0
while the queue is not empty:
    size = how many nodes are in the queue right now (one whole level)
    level = level + 1
    repeat size times (index i = 0..size-1):
        node = take the front of the queue
        process node (level known; i==0 -> first, i==size-1 -> last)
        if node has a left child, add it to the queue
        if node has a right child, add it to the queue
```

```
// LEVEL-AWARE PROCESSING — snapshot size to make per-level decisions
// the queue holds exactly one full level; freeze its size, then drain just that many. — WHEN: "level
Queue<TreeNode> queue = new ArrayDeque<>();
queue.offer(root);
int level = 0;
while (!queue.isEmpty()) {
    int size = queue.size();          // ← snapshot: all nodes currently in queue = this level
    level++;
    for (int i = 0; i < size; i++) {
        TreeNode node = queue.poll();
        // process node (know: level, i==0 → first, i==size-1 → last)
        if (node.left != null) queue.offer(node.left);
        if (node.right != null) queue.offer(node.right);
    }
}
```

Always snapshot `size` first — it's how you know where each level ends. (If you truly don't need levels, just drop the `size` loop and poll node-by-node.)

When to Use — Signal → Pattern

Problem signal phrase	Pattern / group
"level order", "values per level", "each row"	Group 1 — collect entire level
"average / max / sum of each level"	Group 2 — aggregate per level
"right side view" (last in level), "bottom-left" (first in level)	Group 2 — record boundary node (<code>i==size-1</code> / <code>i==0</code>)
"minimum depth", "first level that satisfies X"	Group 3 — early return on condition
"connect next pointers at the same level"	Group 4 — wire nodes within a level
"same depth, different parent" (cousins), per-node metadata	Group 5 — track per-node metadata
"maximum width of a level" (counting null gaps)	Group 6 — position indexing

The One Rule — Snapshot Level Size First

Always snapshot the level size BEFORE the inner for loop:

```
int size = queue.size();
for (int i = 0; i < size; i++) { ... }
```

Without the snapshot, newly added children mix with the current level
and `i == size-1` / `i == 0` checks become meaningless.

Quick Reference Table

#	Name	Description	Intuition	Time	Space	Key Implementation
102	Binary Tree Level Order Traversal	Return all node values level by level, left to right.		O(n)	O(n)	Standard
107	Binary Tree Level Order Traversal II	Same as #102 but return levels from bottom to top.		O(n)	O(n)	Standard
103	Binary Tree Zigzag Level Order Traversal	Level 1 left-to-right, level 2 right-to-left, alternating.		O(n)	O(n)	Standard
637	Average of Levels in Binary Tree	Return the average value of nodes at each level.		O(n)	O(n)	Standard
199	Binary Tree Right Side View	Return the value of the rightmost node at each level.		O(n)	O(n)	Standard
513	Find Bottom Left Tree Value	Return the leftmost value in the last level (deepest row).		O(n)	O(n)	Standard
515	Find Largest Value in Each Tree Row	Return the maximum value found at each level.		O(n)	O(n)	Standard
1161	Maximum Level Sum of a Binary Tree	Return the smallest level number (1-indexed) whose node sum is maximum.		O(n)	O(n)	Standard
111	Minimum Depth of Binary Tree	Minimum number of nodes from root to the nearest leaf.	BFS reaches nodes in depth order, so the first leaf it dequeues is necessarily the shallowest.	O(n)	O(n)	Standard
116	Populating Next Right Pointers in Each Node	Connect each node's <code>next</code> to the node immediately to its right at the same level. Tree is a perfect binary tree.	BFS already visits a level left to right, so just chain each node to the one polled before it.	O(n)	O(n)	Standard
117	Populating Next Right Pointers in Each Node II	Same as #116 but the tree can be any binary tree (not necessarily perfect).		O(n)	O(n)	Standard
993	Cousins in Binary Tree	Two nodes <code>x</code> and <code>y</code> are cousins if they are at the same depth but have different parents. Return true if <code>x</code> and <code>y</code> are cousins.	cousins must surface in the <i>same</i> BFS level; if only one shows up per level, their depths differ.	O(n)	O(n)	Standard
662	Maximum Width of Binary Tree	Return the maximum width of any level of a binary tree. Width is defined as the length between the leftmost and rightmost non-null nodes, including all the null nodes in between.		O(n)	O(n)	BFS with position tracking. Assign each node a position: root=1, left child of node at pos <code>p</code> gets <code>2*p</code> , right child gets <code>2*p+1</code> . Width of level = <code>lastPos - firstPos + 1</code> . Normalize by subtracting <code>firstPos</code> of each level to prevent overflow.

Group 1 — Collect Entire Level

#102 Binary Tree Level Order Traversal

Description: Return all node values level by level, left to right.

Variables: `result` = list of levels · `queue` = BFS queue · `size` = level snapshot · `level` = values collected for this level · `node` = node polled · `i` = index within level **Pseudocode:**

```
result = empty list
if root is null, return result
queue = new queue, put root in it
while queue not empty:
    size = current queue size (this whole level)
    level = empty list
    repeat size times (i = 0..size-1):
        node = poll front of queue
        append node value to level
        if node.left exists, add to queue
        if node.right exists, add to queue
    append level to result
return result
```

```
class Solution {
    public List<List<Integer>> levelOrder(TreeNode root) {
        List<List<Integer>> result = new ArrayList<>();
        if (root == null) return result;
        Queue<TreeNode> queue = new ArrayDeque<>();
        queue.offer(root);
        while (!queue.isEmpty()) {
            int size = queue.size();
            List<Integer> level = new ArrayList<>();
            for (int i = 0; i < size; i++) {
                TreeNode node = queue.poll();
                level.add(node.val);
                if (node.left != null) queue.offer(node.left);
                if (node.right != null) queue.offer(node.right);
            }
            result.add(level);
        }
        return result;
    }
}
```

Time $O(n)$ | **Space** $O(n)$

#107 Binary Tree Level Order Traversal II

Description: Same as #102 but return levels from bottom to top.

Key: `LinkedList` as result — `addFirst` prepends each level, producing bottom-up order without a final reverse.

Variables: `result` = `LinkedList` of levels (prepended) · `queue` = BFS queue · `size` = level snapshot · `level` = values for this level · `node` = node polled · `i` = index within level **Pseudocode:**

```

result = empty linked list
if root is null, return result
queue = new queue, put root in it
while queue not empty:
    size = current queue size (this whole level)
    level = empty list
    repeat size times (i = 0..size-1):
        node = poll front of queue
        append node value to level
        if node.left exists, add to queue
        if node.right exists, add to queue
    prepend level to result (addFirst -> bottom-up order)
return result

```

```

class Solution {
    public List<List<Integer>> levelOrderBottom(TreeNode root) {
        LinkedList<List<Integer>> result = new LinkedList<>();
        if (root == null) return result;
        Queue<TreeNode> queue = new ArrayDeque<>();
        queue.offer(root);
        while (!queue.isEmpty()) {
            int size = queue.size();
            List<Integer> level = new ArrayList<>();
            for (int i = 0; i < size; i++) {
                TreeNode node = queue.poll();
                level.add(node.val);
                if (node.left != null) queue.offer(node.left);
                if (node.right != null) queue.offer(node.right);
            }
            result.addFirst(level);    // prepend -> bottom-up order
        }
        return result;
    }
}

```

Time $O(n)$ | **Space** $O(n)$

#103 Binary Tree Zigzag Level Order Traversal

Description: Level 1 left-to-right, level 2 right-to-left, alternating.

Key: `LinkedList<Integer>` per level as a deque — `addLast` for left-to-right, `addFirst` for right-to-left. Flip flag after each level.

Variables: `result` = list of levels · `queue` = BFS queue · `leftToRight` = direction flag for this level · `size` = level snapshot · `level` = deque of values for this level · `node` = node polled · `i` = index within level **Pseudocode:**

```

result = empty list
if root is null, return result
queue = new queue, put root in it
leftToRight = true
while queue not empty:
    size = current queue size (this whole level)
    level = empty deque
    repeat size times (i = 0..size-1):
        node = poll front of queue
        if leftToRight: append node value to back of level
        else:          append node value to front of level
        if node.left exists, add to queue
        if node.right exists, add to queue
    append level to result
    flip leftToRight
return result

```

```

class Solution {
    public List<List<Integer>> zigzagLevelOrder(TreeNode root) {
        List<List<Integer>> result = new ArrayList<>();
        if (root == null) return result;
        Queue<TreeNode> queue = new ArrayDeque<>();
        queue.offer(root);
        boolean leftToRight = true;
        while (!queue.isEmpty()) {
            int size = queue.size();
            LinkedList<Integer> level = new LinkedList<>();
            for (int i = 0; i < size; i++) {
                TreeNode node = queue.poll();
                if (leftToRight) {
                    level.addLast(node.val);
                } else {
                    level.addFirst(node.val);
                }
                if (node.left != null) queue.offer(node.left);
                if (node.right != null) queue.offer(node.right);
            }
            result.add(level);
            leftToRight = !leftToRight;
        }
        return result;
    }
}

```

Time $O(n)$ | **Space** $O(n)$

#637 Average of Levels in Binary Tree

Description: Return the average value of nodes at each level.

Variables: `result` = list of per-level averages · `queue` = BFS queue · `size` = level snapshot (also the divisor) · `sum` = running sum of this level · `node` = node polled · `i` = index within level **Pseudocode:**

```

result = empty list
queue = new queue, put root in it
while queue not empty:
    size = current queue size (this whole level)
    sum = 0
    repeat size times (i = 0..size-1):
        node = poll front of queue
        sum = sum + node value
        if node.left exists, add to queue
        if node.right exists, add to queue
    append sum / size to result
return result

```

```

class Solution {
    public List<Double> averageOfLevels(TreeNode root) {
        List<Double> result = new ArrayList<>();
        Queue<TreeNode> queue = new ArrayDeque<>();
        queue.offer(root);
        while (!queue.isEmpty()) {
            int size = queue.size();
            double sum = 0;
            for (int i = 0; i < size; i++) {
                TreeNode node = queue.poll();
                sum += node.val;
                if (node.left != null) queue.offer(node.left);
                if (node.right != null) queue.offer(node.right);
            }
            result.add(sum / size);
        }
        return result;
    }
}

```

Time $O(n)$ | **Space** $O(n)$

Group 2 — Record First / Last / Max in Each Level

All share the same outer loop. Only the `if` inside the `for` changes.

#199 Binary Tree Right Side View

Description: Return the value of the rightmost node at each level.

Key: record when `i == size - 1`.

Variables: `result` = rightmost value per level · `queue` = BFS queue · `size` = level snapshot · `node` = node polled · `i` = index within level (record when `i == size-1`, the last node) **Pseudocode:**

```

result = empty list
if root is null, return result
queue = new queue, put root in it
while queue not empty:
    size = current queue size (this whole level)
    repeat size times (i = 0..size-1):
        node = poll front of queue
        if i == size-1: append node value to result    (last in level)
        if node.left exists, add to queue
        if node.right exists, add to queue
return result

```

```

class Solution {
    public List<Integer> rightSideView(TreeNode root) {
        List<Integer> result = new ArrayList<>();
        if (root == null) return result;
        Queue<TreeNode> queue = new ArrayDeque<>();
        queue.offer(root);
        while (!queue.isEmpty()) {
            int size = queue.size();
            for (int i = 0; i < size; i++) {
                TreeNode node = queue.poll();
                if (i == size - 1) result.add(node.val);    // last in level
                if (node.left != null) queue.offer(node.left);
                if (node.right != null) queue.offer(node.right);
            }
        }
        return result;
    }
}

```

Time $O(n)$ | **Space** $O(n)$

#513 Find Bottom Left Tree Value

Description: Return the leftmost value in the last level (deepest row).

Key: record when `i == 0` every level — after the loop, `bottomLeft` holds the first node of the final level.

Variables: `queue` = BFS queue · `bottomLeft` = first value of the latest level seen (overwritten each level) · `size` = level snapshot · `node` = node polled · `i` = index within level (record when `i == 0`, the first node) **Pseudocode:**

```

queue = new queue, put root in it
bottomLeft = root value
while queue not empty:
    size = current queue size (this whole level)
    repeat size times (i = 0..size-1):
        node = poll front of queue
        if i == 0: bottomLeft = node value    (first in level, overwritten each level)
        if node.left exists, add to queue
        if node.right exists, add to queue
return bottomLeft    (first node of the last level)

```



```

class Solution {
    public int findBottomLeftValue(TreeNode root) {
        Queue<TreeNode> queue = new ArrayDeque<>();
        queue.offer(root);
        int bottomLeft = root.val;
        while (!queue.isEmpty()) {
            int size = queue.size();
            for (int i = 0; i < size; i++) {
                TreeNode node = queue.poll();
                if (i == 0) bottomLeft = node.val; // first in level – overwritten each level
                if (node.left != null) queue.offer(node.left);
                if (node.right != null) queue.offer(node.right);
            }
        }
        return bottomLeft;
    }
}

```

Time $O(n)$ | **Space** $O(n)$

#515 Find Largest Value in Each Tree Row

Description: Return the maximum value found at each level.

Variables: `result` = max value per level · `queue` = BFS queue · `size` = level snapshot · `max` = running maximum for this level · `node` = node polled · `i` = index within level **Pseudocode:**

```

result = empty list
if root is null, return result
queue = new queue, put root in it
while queue not empty:
    size = current queue size (this whole level)
    max = negative infinity
    repeat size times (i = 0..size-1):
        node = poll front of queue
        max = larger of (max, node value)
        if node.left exists, add to queue
        if node.right exists, add to queue
    append max to result
return result

```

```

class Solution {
    public List<Integer> largestValues(TreeNode root) {
        List<Integer> result = new ArrayList<>();
        if (root == null) return result;
        Queue<TreeNode> queue = new ArrayDeque<>();
        queue.offer(root);
        while (!queue.isEmpty()) {
            int size = queue.size();
            int max = Integer.MIN_VALUE;
            for (int i = 0; i < size; i++) {
                TreeNode node = queue.poll();
                max = Math.max(max, node.val);
                if (node.left != null) queue.offer(node.left);
                if (node.right != null) queue.offer(node.right);
            }
            result.add(max);
        }
        return result;
    }
}

```

Time $O(n)$ | **Space** $O(n)$

#1161 Maximum Level Sum of a Binary Tree

Description: Return the smallest level number (1-indexed) whose node sum is maximum.

Variables: `queue` = BFS queue · `maxSum` = best level sum so far · `maxLevel` = level number of that best sum · `level` = current level (1-indexed) · `size` = level snapshot · `sum` = sum of this level · `node` = node polled · `i` = index within level

Pseudocode:

```

queue = new queue, put root in it
maxSum = negative infinity; maxLevel = 1; level = 0
while queue not empty:
    size = current queue size (this whole level)
    level = level + 1
    sum = 0
    repeat size times (i = 0..size-1):
        node = poll front of queue
        sum = sum + node value
        if node.left exists, add to queue
        if node.right exists, add to queue
    if sum > maxSum: maxSum = sum; maxLevel = level
return maxLevel

```

```

class Solution {
    public int maxLevelSum(TreeNode root) {
        Queue<TreeNode> queue = new ArrayDeque<>();
        queue.offer(root);
        int maxSum = Integer.MIN_VALUE, maxLevel = 1, level = 0;
        while (!queue.isEmpty()) {
            int size = queue.size();
            level++;
            int sum = 0;
            for (int i = 0; i < size; i++) {
                TreeNode node = queue.poll();
                sum += node.val;
                if (node.left != null) queue.offer(node.left);
                if (node.right != null) queue.offer(node.right);
            }
            if (sum > maxSum) { maxSum = sum; maxLevel = level; }
        }
        return maxLevel;
    }
}

```

Time $O(n)$ | **Space** $O(n)$

Group 3 — Early Return on Condition

#111 Minimum Depth of Binary Tree

Description: Minimum number of nodes from root to the nearest leaf.

Key: BFS is optimal here (DFS must visit the whole tree). Return `depth` the moment the first leaf is dequeued — that is guaranteed to be the shallowest.

Intuition: BFS reaches nodes in depth order, so the first leaf it dequeues is necessarily the shallowest.

Variables: `queue` = BFS queue · `depth` = current level depth (1-indexed) · `size` = level snapshot · `node` = node polled · `i` = index within level **Pseudocode:**

```

if root is null, return 0
queue = new queue, put root in it
depth = 0
while queue not empty:
    size = current queue size (this whole level)
    depth = depth + 1
    repeat size times (i = 0..size-1):
        node = poll front of queue
        if node has no children: return depth    (first leaf = shallowest)
        if node.left exists, add to queue
        if node.right exists, add to queue
return depth

```

```

class Solution {
    public int minDepth(TreeNode root) {
        if (root == null) return 0;
        Queue<TreeNode> queue = new ArrayDeque<>();
        queue.offer(root);
        int depth = 0;
        while (!queue.isEmpty()) {
            int size = queue.size();
            depth++;
            for (int i = 0; i < size; i++) {
                TreeNode node = queue.poll();
                if (node.left == null && node.right == null) return depth; // first leaf
                if (node.left != null) queue.offer(node.left);
                if (node.right != null) queue.offer(node.right);
            }
        }
        return depth;
    }
}

```

Time O(n) | Space O(n)

Group 4 — Connect Nodes Within a Level

#116 Populating Next Right Pointers in Each Node

Description: Connect each node's `next` to the node immediately to its right at the same level. Tree is a perfect binary tree.

Key: `previous` tracks the last node seen in the current level — wire `previous.next = node` before advancing. Reset `previous = null` at each level start.

Intuition: BFS already visits a level left to right, so just chain each node to the one polled before it.

Variables: `queue` = BFS queue · `size` = level snapshot · `previous` = last node seen in this level (reset to null each level) · `node` = node polled · `i` = index within level **Pseudocode:**

```

if root is null, return null
queue = new queue, put root in it
while queue not empty:
    size = current queue size (this whole level)
    previous = null
    repeat size times (i = 0..size-1):
        node = poll front of queue
        if previous is not null: previous.next = node    (chain within level)
        previous = node
        if node.left exists, add to queue
        if node.right exists, add to queue
return root

```

```

class Solution {
    public Node connect(Node root) {
        if (root == null) return null;
        Queue<Node> queue = new ArrayDeque<>();
        queue.offer(root);
        while (!queue.isEmpty()) {
            int size = queue.size();
            Node previous = null;
            for (int i = 0; i < size; i++) {
                Node node = queue.poll();
                if (previous != null) previous.next = node;
                previous = node;
                if (node.left != null) queue.offer(node.left);
                if (node.right != null) queue.offer(node.right);
            }
        }
        return root;
    }
}

```

Time $O(n)$ | **Space** $O(n)$

#117 Populating Next Right Pointers in Each Node II

Description: Same as #116 but the tree can be any binary tree (not necessarily perfect).

Key: the BFS solution is **identical** to #116 — the `size` snapshot handles uneven levels automatically.

Variables: `queue` = BFS queue · `size` = level snapshot (handles uneven levels) · `previous` = last node seen in this level (reset to null each level) · `node` = node polled · `i` = index within level **Pseudocode:**

```

if root is null, return null
queue = new queue, put root in it
while queue not empty:
    size = current queue size (this whole level)
    previous = null
    repeat size times (i = 0..size-1):
        node = poll front of queue
        if previous is not null: previous.next = node    (chain within level)
        previous = node
        if node.left exists, add to queue
        if node.right exists, add to queue
return root

```

```

class Solution {
    public Node connect(Node root) {
        if (root == null) return null;
        Queue<Node> queue = new ArrayDeque<>();
        queue.offer(root);
        while (!queue.isEmpty()) {
            int size = queue.size();
            Node previous = null;
            for (int i = 0; i < size; i++) {
                Node node = queue.poll();
                if (previous != null) previous.next = node;
                previous = node;
                if (node.left != null) queue.offer(node.left);
                if (node.right != null) queue.offer(node.right);
            }
        }
        return root;
    }
}

```

Time O(n) | Space O(n)

Group 5 — Track Per-Node Metadata

#993 Cousins in Binary Tree

Description: Two nodes `x` and `y` are cousins if they are at the same depth but have different parents. Return true if `x` and `y` are cousins.

Key: for each node polled, check if its children are `x` or `y`. After each full level, if both parents found → check `xParent != yParent`. If only one found → different depths → false.

Intuition: cousins must surface in the *same* BFS level; if only one shows up per level, their depths differ.

Variables: `queue` = BFS queue · `size` = level snapshot · `xParent` / `yParent` = parents of `x`/`y` found in this level (null if not yet) · `node` = node polled · `i` = index within level **Pseudocode:**

```

queue = new queue, put root in it
while queue not empty:
    size = current queue size (this whole level)
    xParent = null; yParent = null
    repeat size times (i = 0..size-1):
        node = poll front of queue
        if node.left exists:
            add node.left to queue
            if node.left value == x: xParent = node
            if node.left value == y: yParent = node
        if node.right exists:
            add node.right to queue
            if node.right value == x: xParent = node
            if node.right value == y: yParent = node
    if both parents found: return xParent != yParent    (same depth -> cousins iff different parent)
    if exactly one parent found: return false           (different depths)
return false

```

```

class Solution {
    public boolean isCousins(TreeNode root, int x, int y) {
        Queue<TreeNode> queue = new ArrayDeque<>();
        queue.offer(root);
        while (!queue.isEmpty()) {
            int size = queue.size();
            TreeNode xParent = null, yParent = null;
            for (int i = 0; i < size; i++) {
                TreeNode node = queue.poll();
                if (node.left != null) {
                    queue.offer(node.left);
                    if (node.left.val == x) xParent = node;
                    if (node.left.val == y) yParent = node;
                }
                if (node.right != null) {
                    queue.offer(node.right);
                    if (node.right.val == x) xParent = node;
                    if (node.right.val == y) yParent = node;
                }
            }
            if (xParent != null && yParent != null) return xParent != yParent;
            if (xParent != null || yParent != null) return false; // one found → different depths
        }
        return false;
    }
}

```

Time O(n) | **Space** O(n)

Side-by-Side: 199 vs 513

Both record one node per level. The only difference is which node:

	#199 Right Side View	#513 Bottom Left Value
Record condition:	i == size - 1 (last)	i == 0 (first)
Update per level:	result.add(node.val)	bottomLeft = node.val (overwrite)
Return:	List<Integer>	bottomLeft after all levels done

Side-by-Side: 102 vs 103 vs 107

All collect every node in every level. Only the insertion order changes:

	#102 Level Order	#103 Zigzag	#107 Bottom-Up
Level container:	ArrayList<Integer>	LinkedList<Integer>	ArrayList<Integer>
Add node:	level.add(val)	addLast/addFirst	level.add(val)
Add to result:	result.add(level)	result.add(level)	result.addFirst(level)
Extra state:	—	boolean leftToRight	result is LinkedList

Pattern Summary

What changes per level	Key variable	Example problems
Collect all values	List<Integer> level	102, 107, 103
Compute aggregate	int sum / int max	637, 515, 1161
Record boundary node	check i == 0 or i == size-1	199, 513
Return on first match	return depth	111
Wire nodes together	Node previous	116, 117
Track parent metadata	TreeNode xParent, yParent	993

The One Rule (recap)

Snapshot the level size **before** the inner `for` loop — see "The One Rule" at the top of this file for the full explanation.

Group 6 — Position Indexing

#662 Maximum Width of Binary Tree

Description: Return the maximum width of any level of a binary tree. Width is defined as the length between the leftmost and rightmost non-null nodes, including all the null nodes in between.

Variation: BFS with position tracking. Assign each node a position: root=1, left child of node at pos `p` gets `2*p`, right child gets `2*p+1`. Width of level = `lastPos - firstPos + 1`. Normalize by subtracting `firstPos` of each level to prevent overflow.

Variables: `maxWidth` = best width found · `queue` = BFS queue of nodes · `indices` = parallel queue of heap-style positions · `size` = level snapshot · `first` = leftmost position of this level (normalize against it) · `last` = rightmost normalized position seen · `node` = node polled · `pos` = normalized position of node · `i` = index within level

Pseudocode:

```
if root is null, return 0
maxWidth = 0
queue = new queue with root; indices = new queue with position 0
while queue not empty:
    size = current queue size (this whole level)
    first = front position in indices; last = 0
    repeat size times (i = 0..size-1):
        node = poll front of queue
        pos = poll front of indices minus first    (normalize to avoid overflow)
        last = pos
        if node.left exists: add node.left to queue, add 2*pos to indices
        if node.right exists: add node.right to queue, add 2*pos+1 to indices
    maxWidth = larger of (maxWidth, last + 1)    (width = last - first(0) + 1)
return maxWidth
```



```

class Solution {
    public int widthOfBinaryTree(TreeNode root) {
        if (root == null) return 0;
        int maxWidth = 0;
        Queue<TreeNode> queue = new ArrayDeque<>(); // canonical BFS queue + size snapshot
        Queue<Long> indices = new ArrayDeque<>(); // heap-style position per node
        queue.offer(root);
        indices.offer(0L);
        while (!queue.isEmpty()) {
            int size = queue.size(); // ← snapshot: all nodes at this level
            long first = indices.peek(), last = 0;
            for (int i = 0; i < size; i++) {
                TreeNode node = queue.poll();
                long pos = indices.poll() - first; // ← VARIATION: normalize to prevent overflow
                last = pos;
                if (node.left != null) { queue.offer(node.left); indices.offer(2 * pos); } // left
                if (node.right != null) { queue.offer(node.right); indices.offer(2 * pos + 1); } // right
            }
            maxWidth = (int) Math.max(maxWidth, last + 1); // width = lastPos - firstPos(0) + 1
        }
        return maxWidth;
    }
}

```

Time $O(n)$ | **Space** $O(n)$