

# Bit Manipulation Templates

---

---

## Quick Reference Table

| #   | Name                         | Description                                                                                                        | Intuition                                                                                                                                                                                                                | Time                            | Space  | Key Implementation                                                                                                                                                                      |
|-----|------------------------------|--------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 136 | Single Number                | Array where every element appears twice except one. Find it.                                                       | XOR is its own inverse, so every duplicated pair cancels to 0 and only the lone element is left standing.                                                                                                                | $O(n)$                          | $O(1)$ | Standard                                                                                                                                                                                |
| 268 | Missing Number               | Array of $n$ distinct numbers from $[0, n]$ with one missing. Find it.                                             | XOR-ing every index against every value pairs each present number with its index — the missing number's index has no partner to cancel.                                                                                  | $O(n)$                          | $O(1)$ | XOR each index $i$ with <code>nums[i]</code> . Indices $0..n$ XOR'd with the $n$ elements — the missing index has no pair.                                                              |
| 137 | Single Number II             | Every element appears three times except one. Find it.                                                             | XOR cancels pairs (mod 2); here we need a counter mod 3, so two state bits ( <code>ones</code> , <code>twos</code> ) cycle each bit through $1 \rightarrow 2 \rightarrow 0$ and the survivor sits in <code>ones</code> . | $O(n)$                          | $O(1)$ | Two-state XOR machine. <code>ones</code> tracks bits seen 1 mod 3 times, <code>twos</code> tracks bits seen 2 mod 3 times. When a bit reaches 3, it clears from both.                   |
| 260 | Single Number III            | Two elements appear exactly once; all others appear twice. Find both.                                              | XOR of all leaves $a \oplus b$ ; any set bit in it is a bit where $a$ and $b$ differ, so it splits the array into two groups each holding one unique.                                                                    | $O(n)$                          | $O(1)$ | XOR all $\rightarrow$ get $a \oplus b$ . Use lowest set bit of $a \oplus b$ to partition nums into two groups (one containing $a$ , one containing $b$ ). XOR each group independently. |
| 191 | Number of 1 Bits             | Return the number of set bits in an unsigned integer.                                                              | Each $n \& (n-1)$ erases exactly one set bit, so the loop runs once per set bit — no need to scan all 32 positions.                                                                                                      | $O(k)$ $k$ = number of set bits | $O(1)$ | Standard                                                                                                                                                                                |
| 338 | Counting Bits                | Return an array <code>result</code> where <code>result[i]</code> = number of 1 bits in $i$ , for $i$ in $[0, n]$ . | $i$ has the same set bits as $i \gg 1$ plus possibly its own last bit, so reuse the already-computed smaller answer instead of recounting.                                                                               | $O(n)$                          | $O(n)$ | DP relation — $i \gg 1$ is $i$ with last bit removed (already computed), plus the last bit $i \& 1$ .                                                                                   |
| 190 | Reverse Bits                 | Reverse the 32 bits of an unsigned integer.                                                                        | Peel the lowest bit off $n$ and stack it onto <code>result</code> from the bottom — after 32 shifts the bit order is fully mirrored.                                                                                     | $O(32) = O(1)$                  | $O(1)$ | Fixed 32 iterations — each time take the LSB of $n$ , append it to <code>result</code> , then shift both.                                                                               |
| 201 | Bitwise AND of Numbers Range | Return the AND of all numbers in <code>[left, right]</code> .                                                      | AND only keeps bits that are 1 in every number; the low bits flip somewhere in the range, so only the common high-bit prefix of <code>left</code> and <code>right</code> survives.                                       | $O(\log n)$                     | $O(1)$ | right-shift both until equal to find shared prefix; shift back.                                                                                                                         |
| 371 | Sum of Two Integers          | Return $a + b$ without using <code>+</code> or <code>-</code> .                                                    | Addition splits into a carry-free sum (XOR) and the carries (AND shifted left); feed the carry back until nothing carries over.                                                                                          | $O(32) = O(1)$                  | $O(1)$ | XOR computes bit sum without carry; AND shifted left computes carry. Repeat until no carry.                                                                                             |

| #   | Name                            | Description                                                                                                                                                                                                        | Intuition                                                                                                                                                                                                             | Time                                              | Space              | Key Implementation                                                                                                                                                                                                                    |
|-----|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 318 | Maximum Product of Word Lengths | Given a list of words, find the maximum product $\text{len}(a) * \text{len}(b)$ where $a$ and $b$ share no common letters.                                                                                         | Compress each word's letter set into a 26-bit integer so "share a letter?" becomes a single AND, replacing slow character-by-character comparison.                                                                    | $O(n^2 + n \cdot k)$ $k = \text{avg word length}$ | $O(n)$             | encode each word as a 26-bit integer where bit $i = 1$ if letter 'a' + $i$ appears. Two words share a letter iff their bitmasks have any common bit ( $\text{mask}[i] \& \text{mask}[j] \neq 0$ ).                                    |
| 231 | Power of Two                    | Given an integer $n$ , return true if it is a power of two.                                                                                                                                                        | A power of two is a single 1 bit, and $n \& (n-1)$ clears that one bit to 0 — anything else leaves bits behind.                                                                                                       | $O(1)$                                            | $O(1)$             | single-bit property of powers of 2                                                                                                                                                                                                    |
| 342 | Power of Four                   | Given an integer $n$ , return true if it is a power of four.                                                                                                                                                       | Powers of four are powers of two (one set bit) whose bit sits at an even position; masking against the odd-position mask $0xAAAAAAAA$ must give 0.                                                                    | $O(1)$                                            | $O(1)$             | Power of four must be power of two (one set bit) AND that bit must be at an even bit position (0, 2, 4, 6, ...). Mask $0xAAAAAAAA$ has bits set at ALL odd positions; if $n \& 0xAAAAAAAA == 0$ , the set bit is at an even position. |
| 287 | Find the Duplicate Number       | Given an array of $n+1$ integers where each is in $[1, n]$ , find the duplicate. No extra space, no modifying the array.                                                                                           | Following $i \rightarrow \text{nums}[i]$ turns the array into a linked list; a duplicate value means two indices point to the same node, forming a cycle whose entry is the duplicate.                                | $O(n)$                                            | $O(1)$             | Floyd's Cycle Detection. Treat the array as a linked list where $\text{nums}[i]$ is the next node. Since there's a duplicate, two indices point to the same value → creates a cycle. Find cycle entry = duplicate.                    |
| 405 | Convert a Number to Hexadecimal | Given an integer $\text{num}$ , return its hexadecimal representation as a lowercase string. For negative numbers use two's complement.                                                                            | Hex is base 16, so each group of 4 bits maps to one hex digit; mask the lowest 4 bits with $\text{num} \& 15$ and shift right 4 at a time, using an unsigned shift so the two's-complement sign bit fills with zeros. | $O(8) = O(1)$                                     | $O(1)$             | Standard                                                                                                                                                                                                                              |
| 461 | Hamming Distance                | Given two integers $x$ and $y$ , return the Hamming distance — the number of bit positions where they differ.                                                                                                      | XOR sets exactly the bits where $x$ and $y$ differ, so the answer is just the number of set bits in $x \wedge y$ .                                                                                                    | $O(k)$ $k = \text{differing bits}$                | $O(1)$             | Standard                                                                                                                                                                                                                              |
| 476 | Number Complement               | Given a positive integer $\text{num}$ , return its complement: flip every bit up to and including the most significant set bit.                                                                                    | Build a mask of all 1s spanning the bit width of $\text{num}$ (from the MSB down to bit 0), then XOR — flipping exactly the meaningful bits while leaving the leading zeros untouched.                                | $O(\log \text{num})$                              | $O(1)$             | Standard                                                                                                                                                                                                                              |
| 957 | Prison Cells After N Days       | 8 prison cells ( $\text{cells}[i]$ is 0 or 1) update each day: a cell becomes 1 if both neighbors are equal, else 0. The two end cells always become 0 (they lack two neighbors). Return the state after $n$ days. | With only 8 cells the state space is finite, so the configuration must cycle; detect the cycle length and reduce $n$ modulo it to avoid simulating huge day counts.                                                   | $O(\min(n, \text{cycle}) \cdot 8)$                | $O(\text{states})$ | Standard                                                                                                                                                                                                                              |

# Canonical Template

**Variables:** `result` = XOR accumulator (lone survivor) · `n` = number being inspected/edited · `i` = bit position · `count` = set-bit counter · `mask` = 26-bit letter-presence set · masks: `1 << i` selects bit `i`, `n & (n-1)` clears lowest set bit, `n & (-n)` isolates lowest set bit **Pseudocode:**

## XOR CANCEL:

```
result = 0
for each num in nums: result = result XOR num    (pairs cancel, lone survives)
```

## BIT OPERATIONS on `n` at position `i`:

```
isSet = bit i of n is 1          -> (n >> i) & 1 == 1
set    = turn bit i on           -> n | (1 << i)
clear  = turn bit i off          -> n & ~(1 << i)
toggle = flip bit i              -> n ^ (1 << i)
lowest = isolate lowest set bit  -> n & (-n)
isPow2 = n > 0 and clearing lowest set bit gives 0
```

## COUNT SET BITS (Brian Kernighan):

```
count = 0
while n != 0: count = count + 1; n = n & (n-1)    (each step removes one set bit)
```

## BITMASK AS SET:

```
mask = 0
for each char c in word: mask = mask | (1 << (c - 'a'))
two words share no letter when (mask[i] & mask[j]) == 0
```

```
// bits are a set/counter – XOR cancels duplicates, AND/OR/shift edit individual bits. – WHEN: "appear"
// — XOR CANCEL — pairs cancel; lone element survives
```

```
int result = 0;
for (int num : nums) result ^= num;
```

```
// — BIT OPERATIONS —
```

```
boolean isSet = ((n >> i) & 1) == 1;    // check if bit i is set
int set      = n | (1 << i);             // set bit i
int clear    = n & ~(1 << i);            // clear bit i
int toggle   = n ^ (1 << i);             // toggle bit i
int lowest   = n & (-n);                  // isolate lowest set bit
boolean isPow2 = n > 0 && (n & (n-1)) == 0;
```

```
// — COUNT SET BITS — Brian Kernighan: each iteration removes one set bit
```

```
// WHY n & (n-1) clears the lowest set bit:
```

```
// n      = ...1000  (lowest set bit at this position)
// n-1    = ...0111  (borrow flips that bit to 0 and all lower bits to 1)
// n&(n-1)=...0000  (AND keeps higher bits, wipes the lowest set bit + below)
```

```
int count = 0;
while (n != 0) { count++; n &= (n - 1); } // n & (n-1) clears lowest set bit
```

```
// — BITMASK AS SET — 26-bit integer represents presence of 26 letters
```

```
int mask = 0;
for (char c : word.toCharArray()) mask |= (1 << (c - 'a'));
// check no overlap between two words:
if ((mask[i] & mask[j]) == 0) { /* no shared letter */ }
```

# Variations

**Variables:** `ones / twos` = bits seen 1 / 2 times mod 3 · `xor` = `a ^ b` of the two uniques · `diff` = lowest differing bit (`xor & -xor`) · `a / b` = the two unique values · `dp[]` = set-bit counts by number · `shift` = bits dropped to reach common prefix · `carry` = AND-derived carry bits **Pseudocode:**

VARIATION 1 (mod-3 state machine, Single Number II):

```
ones = 0; twos = 0
for each num: ones = (ones XOR num) AND NOT twos; twos = (twos XOR num) AND NOT ones
after loop, ones holds the element appearing once
```

VARIATION 2 (split XOR into two groups, Single Number III):

```
xor = XOR of all nums           (= a XOR b)
diff = xor AND (-xor)           (lowest bit where a and b differ)
a = 0; for each num: if (num AND diff) != 0: a = a XOR num   (XOR one group)
b = xor XOR a                   (the other unique)
```

VARIATION 3 (DP relation, Counting Bits):

```
dp = array of size n+1
for i = 1..n: dp[i] = dp[i >> 1] + (i AND 1)   (drop last bit, add it back)
```

VARIATION 4 (common prefix, Bitwise AND of Range):

```
shift = 0
while left != right: left >>= 1; right >>= 1; shift = shift + 1
return left << shift           (shared high-bit prefix restored)
```

VARIATION 5 (carry loop, Sum of Two Integers):

```
while b != 0:
    carry = a AND b           (positions that carry)
    a = a XOR b               (sum without carry)
    b = carry << 1           (carry moves one bit left)
return a
```

```

// VARIATION 1: mod-3 state machine (Single Number II)
// MENTAL MODEL: extend XOR from mod-2 (cancel pairs) to mod-3 (cancel triples);
//                ones/twos track bits seen 1 or 2 times mod 3.
// Instead of XOR canceling pairs (mod 2), cancel triples (mod 3)
// ones = bits seen exactly 1 mod 3 times; twos = bits seen exactly 2 mod 3 times
int ones = 0, twos = 0;
for (int num : nums) {
    ones = (ones ^ num) & ~twos;    // ← add to ones if not already in twos
    twos = (twos ^ num) & ~ones;    // ← add to twos if not already in ones
}
// After all: ones holds the element appearing once (0 mod 3 remainder = survive)

// VARIATION 2: split XOR into two groups (Single Number III)
// Two unique elements a, b. XOR of all = a ^ b.
// Use lowest set bit of (a^b) to split nums into two groups → each group has one unique.
int xor = 0;
for (int num : nums) xor ^= num;    // xor = a ^ b
int diff = xor & (-xor);             // ← lowest set bit that differs between a and b
int a = 0;
for (int num : nums)
    if ((num & diff) != 0) a ^= num; // ← XOR one group → one unique element
int b = xor ^ a;                     // ← the other unique element

// VARIATION 3: DP relation (Counting Bits)
// dp[i] = dp[i/2] + last bit of i
// i >> 1 = i without last bit (same or fewer ones); last bit = i & 1
int[] dp = new int[n + 1];
for (int i = 1; i <= n; i++)
    dp[i] = dp[i >> 1] + (i & 1);    // ← right-shift halves the problem

// VARIATION 4: common prefix (Bitwise AND of Range)
// AND of any range [left, right]: bits that differ between left and right get cleared.
// Right-shift both until equal → find shared high-bit prefix → shift back.
int shift = 0;
while (left != right) { left >>= 1; right >>= 1; shift++; }
return left << shift;               // ← shift back to original magnitude

// VARIATION 5: carry loop (Sum of Two Integers)
// XOR gives bit sum without carry; AND shifted left gives carry.
// Repeat until no carry remains.
int add(int a, int b) {
    while (b != 0) {
        int carry = a & b;           // ← carry bits
        a = a ^ b;                   // ← partial sum (no carry)
        b = carry << 1;              // ← carry propagated one position left
    }
    return a;
}

```

## Part 1 — XOR Cancel

### #136 Single Number

**Description:** Array where every element appears twice except one. Find it.

**Intuition:** XOR is its own inverse, so every duplicated pair cancels to 0 and only the lone element is left standing.

**Algorithm:** XOR all — every pair cancels ( $a \oplus a = 0$ ), leaving the single element.

**Variables:** `result` = XOR accumulator — paired values cancel, the lone value survives · `num` = current element

**Pseudocode:**

```
result = 0
for each num in nums:
    result = result XOR num    (a XOR a = 0, so duplicate pairs vanish)
return result                (only the single element remains)
```

```
class Solution {
    public int singleNumber(int[] nums) {
        int result = 0;
        for (int num : nums) result ^= num;    // pairs cancel; lone element survives
        return result;
    }
}
```

**Time**  $O(n)$  | **Space**  $O(1)$

## #268 Missing Number

**Description:** Array of  $n$  distinct numbers from  $[0, n]$  with one missing. Find it.

**Intuition:** XOR-ing every index against every value pairs each present number with its index — the missing number's index has no partner to cancel.

**Variation:** XOR each index `i` with `nums[i]`. Indices  $0..n$  XOR'd with the  $n$  elements — the missing index has no pair.

**Variables:** `result` = XOR accumulator seeded with  $n$  (the absent last index) · `i` = index · `nums[i]` = value at that index

**Pseudocode:**

```
result = n                (start with the largest index, which has no value slot)
for i = 0..n-1:
    result = result XOR i XOR nums[i]    (each present value cancels its index)
return result              (only the missing number's index has no partner)
```

```
class Solution {
    public int missingNumber(int[] nums) {
        int result = nums.length;                // start with n (last index)
        for (int i = 0; i < nums.length; i++)
            result ^= i ^ nums[i];                // ← VARIATION: XOR index with value
        return result;
    }
}
```

**Time**  $O(n)$  | **Space**  $O(1)$

## #137 Single Number II

**Description:** Every element appears three times except one. Find it.

**Intuition:** XOR cancels pairs (mod 2); here we need a counter mod 3, so two state bits (`ones`, `twos`) cycle each bit through  $1 \rightarrow 2 \rightarrow 0$  and the survivor sits in `ones`.

**Variation:** Two-state XOR machine. `ones` tracks bits seen 1 mod 3 times, `twos` tracks bits seen 2 mod 3 times. When a bit reaches 3, it clears from both.

**Variables:** `ones` = bits seen 1 time mod 3 · `twos` = bits seen 2 times mod 3 · `num` = current element (a bit reaching 3 occurrences clears from both) **Pseudocode:**

```

ones = 0; twos = 0
for each num in nums:
    ones = (ones XOR num) AND NOT twos    (add bit to ones unless it is already in twos)
    twos = (twos XOR num) AND NOT ones    (add bit to twos unless it is now in ones)
return ones                               (bits at count 0 mod 3 survive here = the single element)

```

```

class Solution {
    public int singleNumber(int[] nums) {
        int ones = 0, twos = 0;
        for (int num : nums) {
            ones = (ones ^ num) & ~twos;    // ← VARIATION: add to ones only if not in twos
            twos = (twos ^ num) & ~ones;    // ← VARIATION: add to twos only if not in ones
        }
        return ones;                       // ones holds the element seen exactly once
    }
}

```

**Time**  $O(n)$  | **Space**  $O(1)$

## #260 Single Number III

**Description:** Two elements appear exactly once; all others appear twice. Find both.

**Intuition:** XOR of all leaves  $a \oplus b$ ; any set bit in it is a bit where  $a$  and  $b$  differ, so it splits the array into two groups each holding one unique.

**Variation:** XOR all  $\rightarrow$  get  $a \oplus b$ . Use lowest set bit of  $a \oplus b$  to partition nums into two groups (one containing  $a$ , one containing  $b$ ). XOR each group independently.

**Variables:**  $xor$  = XOR of all =  $a \oplus b$  ·  $diff$  = lowest set bit of  $xor$  (a bit where  $a$  and  $b$  differ) ·  $a$  = unique value isolated from the group whose  $diff$  bit is set ·  $num$  = current element **Pseudocode:**

```

xor = 0
for each num: xor = xor XOR num            (everything else cancels -> xor = a XOR b)
diff = xor AND (-xor)                     (isolate one bit where a and b differ)
a = 0
for each num:
    if (num AND diff) != 0: a = a XOR num (XOR only the group with that bit set)
return [a, xor XOR a]                     (the other unique is xor XOR a)

```

```

class Solution {
    public int[] singleNumber(int[] nums) {
        int xor = 0;
        for (int num : nums) xor ^= num;    // xor = a ^ b

        int diff = xor & (-xor);            // ← VARIATION: isolate lowest bit that differs
        int a = 0;
        for (int num : nums)
            if ((num & diff) != 0) a ^= num; // ← VARIATION: XOR only one group
        return new int[]{a, xor ^ a};       // b = (a^b) ^ a
    }
}

```

**Time**  $O(n)$  | **Space**  $O(1)$



## Part 2 — Bit Counting

### #191 Number of 1 Bits

**Description:** Return the number of set bits in an unsigned integer.

**Intuition:** Each  $n \& (n-1)$  erases exactly one set bit, so the loop runs once per set bit — no need to scan all 32 positions.

**Algorithm:** Brian Kernighan —  $n \& (n-1)$  clears the lowest set bit each iteration.

**Variables:**  $n$  = number being whittled down ·  $count$  = set bits cleared so far ( $n \& (n-1)$  removes the lowest set bit each step) **Pseudocode:**

```
count = 0
while n != 0:
    count = count + 1
    n = n AND (n - 1)      (clears the lowest set bit)
return count              (loop ran once per set bit)
```

```
public class Solution {
    public int hammingWeight(int n) {
        int count = 0;
        while (n != 0) {
            count++;
            n &= (n - 1);    // ← clears lowest set bit; loop runs exactly hamming-weight times
        }
        return count;
    }
}
```

**Time**  $O(k)$   $k$  = number of set bits | **Space**  $O(1)$

### #338 Counting Bits

**Description:** Return an array `result` where `result[i]` = number of 1 bits in `i`, for  $i$  in  $[0, n]$ .

**Intuition:**  $i$  has the same set bits as  $i \gg 1$  plus possibly its own last bit, so reuse the already-computed smaller answer instead of recounting.

**Variation:** DP relation —  $i \gg 1$  is  $i$  with last bit removed (already computed), plus the last bit  $i \& 1$ .

**Variables:** `dp[]` = set-bit count for each number  $0..n$  ·  $i$  = current number ( $i \gg 1$  is the already-solved smaller number,  $i \& 1$  is its last bit) **Pseudocode:**

```
dp = array of size n+1 (dp[0] = 0)
for i = 1..n:
    dp[i] = dp[i >> 1] + (i AND 1)    (count of i without its last bit, plus that bit)
return dp
```

```
class Solution {
    public int[] countBits(int n) {
        int[] dp = new int[n + 1];
        for (int i = 1; i <= n; i++)
            dp[i] = dp[i >> 1] + (i & 1);    // ← VARIATION: dp[i/2] + last bit
        return dp;
    }
}
```

Time  $O(n)$  | Space  $O(n)$

---

## #190 Reverse Bits

---

**Description:** Reverse the 32 bits of an unsigned integer.

**Intuition:** Peel the lowest bit off `n` and stack it onto `result` from the bottom — after 32 shifts the bit order is fully mirrored.

**Variation:** Fixed 32 iterations — each time take the LSB of `n`, append it to `result`, then shift both.

**Variables:** `result` = mirrored bits being built from the bottom up · `n` = source bits being peeled from the bottom · `i` = iteration counter (always 32) **Pseudocode:**

```
result = 0
repeat 32 times (i = 0..31):
    result = (result << 1) OR (n AND 1)    (shift result up, drop in n's lowest bit)
    n = n >> 1                            (advance to next source bit)
return result
```

```
public class Solution {
    public int reverseBits(int n) {
        int result = 0;
        for (int i = 0; i < 32; i++) {      // ← VARIATION: always 32 iterations (fixed-width)
            result = (result << 1) | (n & 1); // append LSB of n to result
            n >>= 1;
        }
        return result;
    }
}
```

Time  $O(32) = O(1)$  | Space  $O(1)$

---

## Part 3 — Range / Arithmetic

---

### #201 Bitwise AND of Numbers Range

---

**Description:** Return the AND of all numbers in `[left, right]`.

**Intuition:** AND only keeps bits that are 1 in every number; the low bits flip somewhere in the range, so only the common high-bit prefix of `left` and `right` survives.

**Key insight:** any two adjacent numbers in the range differ in at least the lowest bit. AND of a range clears all bits that differ across any pair in the range. The result is the common high-bit prefix of `left` and `right`.

**Variation:** right-shift both until equal to find shared prefix; shift back.

**Variables:** `left / right` = range endpoints, shifted right until they match · `shift` = number of low bits dropped (restored at the end) **Pseudocode:**

```
shift = 0
while left != right:                (low bits differ -> they get cleared by AND)
    left = left >> 1
    right = right >> 1
    shift = shift + 1
return left << shift                (shared high-bit prefix, shifted back into place)
```

```

class Solution {
    public int rangeBitwiseAnd(int left, int right) {
        int shift = 0;
        while (left != right) {          // ← VARIATION: shift until common prefix found
            left  >>= 1;
            right >>= 1;
            shift++;
        }
        return left << shift;           // ← restore to original magnitude
    }
}

```

**Time**  $O(\log n)$  | **Space**  $O(1)$

## #371 Sum of Two Integers

**Description:** Return  $a + b$  without using  $+$  or  $-$ .

**Intuition:** Addition splits into a carry-free sum (XOR) and the carries (AND shifted left); feed the carry back until nothing carries over.

**Variation:** XOR computes bit sum without carry; AND shifted left computes carry. Repeat until no carry.

**Variables:**  $a$  = running partial sum (no carry) ·  $b$  = pending carry to add next ·  $carry$  = bit positions where both currently have 1 **Pseudocode:**

```

while b != 0:                (still have carry to fold in)
    carry = a AND b          (positions that generate a carry)
    a = a XOR b              (sum of the bits ignoring carry)
    b = carry << 1           (carry takes effect one position to the left)
return a                     (no carry left -> a is the sum)

```

```

class Solution {
    public int getSum(int a, int b) {
        while (b != 0) {
            int carry = a & b;          // ← VARIATION: carry = bits where both are 1
            a = a ^ b;                  // ← VARIATION: partial sum (no carry propagation)
            b = carry << 1;             // ← VARIATION: carry propagates one bit left
        }
        return a;
    }
}

```

**Time**  $O(32) = O(1)$  | **Space**  $O(1)$

## Part 4 — Bitmask as Set

### #318 Maximum Product of Word Lengths

**Description:** Given a list of words, find the maximum product  $\text{len}(a) * \text{len}(b)$  where  $a$  and  $b$  share no common letters.

**Intuition:** Compress each word's letter set into a 26-bit integer so "share a letter?" becomes a single AND, replacing slow character-by-character comparison.

**Variation:** encode each word as a 26-bit integer where bit  $i = 1$  if letter  $'a' + i$  appears. Two words share a letter iff their bitmasks have any common bit ( $\text{mask}[i] \& \text{mask}[j] \neq 0$ ).

**Variables:** `masks[]` = 26-bit letter-set per word (bit `i` set if letter 'a'+`i` appears) · `i / j` = word indices being compared ·  
`max` = best product of lengths so far (disjoint sets have `AND == 0`) **Pseudocode:**

```
build masks: for each word i, for each char c, set bit (c - 'a') in masks[i]
max = 0
for i = 0..n-1:
    for j = i+1..n-1:
        if (masks[i] AND masks[j]) == 0:            (no shared letter)
            max = larger of (max, len(word i) * len(word j))
return max
```

```
class Solution {
    public int maxProduct(String[] words) {
        int n = words.length;
        int[] masks = new int[n];
        for (int i = 0; i < n; i++)
            for (char c : words[i].toCharArray())
                masks[i] |= (1 << (c - 'a')); // ← VARIATION: 26-bit bitmask per word

        int max = 0;
        for (int i = 0; i < n; i++)
            for (int j = i + 1; j < n; j++)
                if ((masks[i] & masks[j]) == 0) // ← VARIATION: no shared letters = AND is zero
                    max = Math.max(max, words[i].length() * words[j].length());
        return max;
    }
}
```

**Time**  $O(n^2 + n \cdot k)$   $k$  = avg word length | **Space**  $O(n)$

## Bit Trick Cheat Sheet

```
n & (n-1)           // clear lowest set bit → count bits, check power of 2
n & (-n)            // isolate lowest set bit → split into groups
n ^ n = 0           // same value cancels → XOR pairs
n ^ 0 = n           // identity → XOR with index
(n >> i) & 1        // check bit i
n | (1 << i)        // set bit i
n & ~(1 << i)       // clear bit i
n ^ (1 << i)        // toggle bit i
i >> 1              // divide by 2 (fast)
i & 1               // last bit (0 = even, 1 = odd)

// --- Divisibility by powers of two ---
(n & 1) == 0        // divisible by 2 (even) ← LSB is the 2^0 place
(n & 1) == 1        // NOT divisible by 2 (odd)
(n & ((1 << k) - 1)) // remainder of n / 2^k ; == 0 means divisible by 2^k
(n & 3) == 0        // divisible by 4 (k = 2)
(n & 7) == 0        // divisible by 8 (k = 3)
// Note: n & 1 is safe for NEGATIVE numbers (two's complement) where
//         n % 2 returns -1 for odd negatives. Prefer & 1 for parity.
```

## Pattern Chooser

| Signal                                            | Technique                                                                       | Time                  |
|---------------------------------------------------|---------------------------------------------------------------------------------|-----------------------|
| "appears odd/once, rest appear even/twice"        | XOR all                                                                         | $O(n)$                |
| "appears once, rest appear 3 times"               | mod-3 state machine ( ones , twos )                                             | $O(n)$                |
| "two unique elements"                             | XOR $\rightarrow$ split by <code>xor &amp; (-xor)</code>                        | $O(n)$                |
| Count set bits                                    | Brian Kernighan <code>n &amp;= (n-1)</code>                                     | $O(k)$ $k$ = set bits |
| Count bits for all $0..n$                         | DP: <code>dp[i] = dp[i&gt;&gt;1] + (i&amp;1)</code>                             | $O(n)$                |
| AND of a range                                    | Right-shift to find common prefix                                               | $O(\log n)$           |
| Add without +                                     | XOR + carry loop                                                                | $O(1)$ (32 iters)     |
| "no shared characters between two strings"        | 26-bit bitmask, check <code>AND == 0</code>                                     | $O(n^2)$ pairwise     |
| "is n a power of two?"                            | <code>n &gt; 0 &amp;&amp; (n &amp; (n-1)) == 0</code>                           | $O(1)$                |
| "is n a power of four?"                           | Power of 2 AND set bit at even position: <code>(n &amp; 0xAAAAAAAA) == 0</code> | $O(1)$                |
| "find duplicate, no extra space, no modification" | Floyd's cycle detection on array-as-linked-list                                 | $O(n)$                |

## Part 5 — Power Checks & Cycle Detection

### #231 Power of Two

**Description:** Given an integer `n`, return true if it is a power of two.

**Intuition:** A power of two is a single 1 bit, and `n & (n-1)` clears that one bit to 0 — anything else leaves bits behind.

**Algorithm:** A power of two has exactly one set bit. Check `n > 0` and `n & (n-1) == 0` (clearing the lowest set bit results in 0 only if there was one bit).

**Variables:** `n` = number tested (`n & (n-1)` clears its single set bit, leaving 0 only when exactly one bit was set)

**Pseudocode:**

```
return true when:
    n > 0                (must be positive)
    AND (n AND (n-1)) == 0 (clearing the lone set bit leaves nothing)
```

```
class Solution {
    public boolean isPowerOfTwo(int n) {
        return n > 0 && (n & (n - 1)) == 0; // ← VARIATION: single-bit property of powers of 2
    }
}
```

**Time**  $O(1)$  | **Space**  $O(1)$

### #342 Power of Four

**Description:** Given an integer `n`, return true if it is a power of four.

**Intuition:** Powers of four are powers of two (one set bit) whose bit sits at an even position; masking against the odd-position mask `0xAAAAAAAA` must give 0.

**Variation:** Power of four must be power of two (one set bit) AND that bit must be at an even bit position (0, 2, 4, 6, ...). Mask `0xAAAAAAAA` has bits set at ALL odd positions; if `n & 0xAAAAAAAA == 0`, the set bit is at an even position.

**Variables:** `n` = number tested · mask `0xAAAAAAAA` = all odd bit positions (a power of four's lone bit must sit at an even position, so AND with this mask is 0) **Pseudocode:**

```
return true when all hold:
    n > 0
    (n AND (n-1)) == 0          (exactly one set bit -> power of two)
    (n AND 0xAAAAAAAA) == 0    (that bit is at an even position -> power of four)
```

```
class Solution {
    public boolean isPowerOfFour(int n) {
        // 0xAAAAAAAA = 1010 1010 ... 1010 (bits at odd positions 1,3,5,...31)
        return n > 0 && (n & (n-1)) == 0          // ← power of 2: exactly one set bit
            && (n & 0xAAAAAAAA) == 0;           // ← VARIATION: set bit at even position (4^k has bit
    }
}
```

**Time**  $O(1)$  | **Space**  $O(1)$

## #287 Find the Duplicate Number

**Description:** Given an array of `n+1` integers where each is in `[1, n]`, find the duplicate. No extra space, no modifying the array.

**Intuition:** Following `i → nums[i]` turns the array into a linked list; a duplicate value means two indices point to the same node, forming a cycle whose entry is the duplicate.

**Variation:** Floyd's Cycle Detection. Treat the array as a linked list where `nums[i]` is the next node. Since there's a duplicate, two indices point to the same value → creates a cycle. Find cycle entry = duplicate.

**Variables:** `slow` = single-step pointer · `fast` = double-step pointer (`nums[i]` acts as the "next" link; the cycle entry is the duplicate) **Pseudocode:**

```
Phase 1 – find a meeting point inside the cycle:
    slow = nums[0]; fast = nums[0]
    do: slow = nums[slow]; fast = nums[nums[fast]]    until slow == fast

Phase 2 – find the cycle entrance:
    slow = nums[0]
    while slow != fast: slow = nums[slow]; fast = nums[fast]
    return slow      (cycle entry = the duplicate value)
```

```

class Solution {
    public int findDuplicate(int[] nums) {
        // Phase 1: find intersection point in cycle
        int slow = nums[0], fast = nums[0];
        do {
            slow = nums[slow];           // ← VARIATION: Floyd's cycle, not XOR
            fast = nums[nums[fast]];
        } while (slow != fast);
        // Phase 2: find cycle entry (= duplicate)
        slow = nums[0];
        while (slow != fast) {
            slow = nums[slow];
            fast = nums[fast];
        }
        return slow;
    }
}

```

**Time**  $O(n)$  | **Space**  $O(1)$

## Additional Reference Problems

### #405 Convert a Number to Hexadecimal

**Description:** Given an integer `num`, return its hexadecimal representation as a lowercase string. For negative numbers use two's complement.

**Intuition:** Hex is base 16, so each group of 4 bits maps to one hex digit; mask the lowest 4 bits with `num & 15` and shift right 4 at a time, using an unsigned shift so the two's-complement sign bit fills with zeros.

**Algorithm:** Repeatedly take `num & 0xF` to read the lowest nibble, map it to a hex char, then unsigned-right-shift `num >> 4`. Stop when `num` becomes 0.

**Variables:** `num` = number being consumed 4 bits at a time · `digits` = hex digit lookup table · `nibble` = lowest 4 bits (`num & 15`) = one hex digit · `builder` = digits collected low-to-high (reversed at the end) **Pseudocode:**

```

if num == 0: return "0"
digits = "0123456789abcdef"
builder = empty
while num != 0:
    nibble = num AND 15           (lowest 4 bits = one hex digit)
    append digits[nibble] to builder
    num = num >> 4                (unsigned shift fills sign bit with 0)
return builder reversed          (we appended least-significant digit first)

```

```

class Solution {
    public String toHex(int num) {
        if (num == 0) {
            return "0";
        }
        char[] digits = "0123456789abcdef".toCharArray();
        StringBuilder builder = new StringBuilder();
        while (num != 0) {
            int nibble = num & 15; // ← lowest 4 bits = one hex digit
            builder.append(digits[nibble]);
            num >>= 4; // unsigned shift handles negatives (two's complement)
        }
        return builder.reverse().toString();
    }
}

```

**Time**  $O(8) = O(1)$  | **Space**  $O(1)$

## #461 Hamming Distance

**Description:** Given two integers  $x$  and  $y$ , return the Hamming distance — the number of bit positions where they differ.

**Intuition:** XOR sets exactly the bits where  $x$  and  $y$  differ, so the answer is just the number of set bits in  $x \oplus y$ .

**Algorithm:** Compute  $x \oplus y$ , then count its set bits with Brian Kernighan ( $n \& (n-1)$  clears the lowest set bit each iteration).

**Variables:**  $n = x \oplus y$  (1 exactly where the two differ) ·  $\text{count}$  = differing bits counted ( $n \& (n-1)$  clears one set bit per step) **Pseudocode:**

```

n = x XOR y           (set bits mark positions where x and y differ)
count = 0
while n != 0:
    count = count + 1
    n = n AND (n - 1)  (clear lowest set bit)
return count

```

```

class Solution {
    public int hammingDistance(int x, int y) {
        int n = x ^ y; // differing bits become 1
        int count = 0;
        while (n != 0) {
            count++;
            n &= (n - 1); // ← clears lowest set bit each iteration
        }
        return count;
    }
}

```

**Time**  $O(k)$   $k$  = differing bits | **Space**  $O(1)$

## #476 Number Complement

**Description:** Given a positive integer  $\text{num}$ , return its complement: flip every bit up to and including the most significant set bit.



**Intuition:** Build a mask of all 1s spanning the bit width of `num` (from the MSB down to bit 0), then XOR — flipping exactly the meaningful bits while leaving the leading zeros untouched.

**Algorithm:** Grow a mask `1 << i` until it covers all bits of `num` (`mask < num`), forming `(1 << bitLength) - 1`; XOR `num` with that mask to flip only the relevant bits.

**Variables:** `num` = input whose meaningful bits get flipped · `mask` = all-ones mask spanning `num`'s bit width · `i` = bit position being added to the mask **Pseudocode:**

```
mask = 0; i = 0
while (1 << i) <= num:           (extend mask up to num's most significant bit)
    set bit i in mask
    i = i + 1
return num XOR mask              (flips every bit within num's width, leaves leading zeros)
```

```
class Solution {
    public int findComplement(int num) {
        int mask = 0;
        int i = 0;
        while ((1 << i) <= num) {           // ← extend mask to num's bit width
            mask |= (1 << i);               // set bit i in the all-ones mask
            i++;
        }
        return num ^ mask;                  // XOR flips every bit within the mask
    }
}
```

**Time**  $O(\log \text{num})$  | **Space**  $O(1)$

---

## #957 Prison Cells After N Days

**Description:** 8 prison cells (`cells[i]` is 0 or 1) update each day: a cell becomes 1 if both neighbors are equal, else 0. The two end cells always become 0 (they lack two neighbors). Return the state after `n` days.

**Intuition:** With only 8 cells the state space is finite, so the configuration must cycle; detect the cycle length and reduce `n` modulo it to avoid simulating huge day counts.

**Algorithm:** Encode the 8 cells as an 8-bit integer. Simulate one day with bit operations (a cell is 1 iff its neighbors match, i.e. their XOR is 0), recording seen states in a map. On the first repeat, reduce remaining days modulo the cycle length, then finish the leftover days.

**Variables:** `state` = 8 cells packed into an 8-bit integer · `n` = remaining days · `seen` = map from state → the `n` value when first seen (to measure cycle length) · `result[]` = unpacked cells · `nextDay` helper uses `left / right` neighbor bits, setting cell `i` when they are equal **Pseudocode:**

```

pack cells into state: for i = 0..7, if cells[i]==1 set bit i of state
seen = empty map
while n > 0:
    if state already in seen:
        n = n mod (seen[state] - n)          (skip whole repeated cycles)
    else:
        seen[state] = n
    if n > 0:
        state = nextDay(state)
        n = n - 1
unpack: for i = 0..7, result[i] = bit i of state
return result

nextDay(state):
    next = 0
    for i = 1..6:                          (end cells 0 and 7 always become 0)
        left  = bit (i-1) of state
        right = bit (i+1) of state
        if (left XOR right) == 0: set bit i of next    (neighbors equal)
    return next

```

```

import java.util.HashMap;
import java.util.Map;

class Solution {
    public int[] prisonAfterNDays(int[] cells, int n) {
        int state = 0;
        for (int i = 0; i < 8; i++) {
            if (cells[i] == 1) {
                state |= (1 << i);          // pack cells into an 8-bit integer
            }
        }
        Map<Integer, Integer> seen = new HashMap<>();
        while (n > 0) {
            if (seen.containsKey(state)) {
                n %= seen.get(state) - n;    // ← cycle found: skip whole cycles
            } else {
                seen.put(state, n);
            }
            if (n > 0) {
                state = nextDay(state);
                n--;
            }
        }
        int[] result = new int[8];
        for (int i = 0; i < 8; i++) {
            result[i] = (state >> i) & 1;    // unpack bits back into cells
        }
        return result;
    }

    private int nextDay(int state) {
        int next = 0;
        for (int i = 1; i < 7; i++) {
            // end cells (0 and 7) always become 0
            int left = (state >> (i - 1)) & 1;
            int right = (state >> (i + 1)) & 1;
            if ((left ^ right) == 0) {
                // neighbors equal → cell becomes 1
                next |= (1 << i);
            }
        }
        return next;
    }
}

```

**Time**  $O(\min(n, \text{cycle}) \cdot 8)$  | **Space**  $O(\text{states})$