

Graph Algorithm Templates

`Queue<Integer> queue = new ArrayDeque<>()` throughout.

Six algorithms — each with a canonical template and representative problems.

Complexity Legend

BFS / DFS	$O(V + E)$	visit each vertex and edge once
Topo sort (Kahn)	$O(V + E)$	each node enqueued once, each edge relaxed once
Union-Find	$\sim O(n \cdot \alpha(n)) \approx O(n)$	α = inverse Ackermann, effectively constant
Dijkstra	$O((V + E) \log V)$	non-negative weights ONLY

Quick Reference Table

#	Name	Description	Intuition	Time	Space	Key Implementation
994	Rotting Oranges	Grid of <code>0</code> (empty), <code>1</code> (fresh), <code>2</code> (rotten). Each minute rotten oranges infect adjacent fresh ones. Return minutes until no fresh remain, or <code>-1</code> .		$O(V+E)$	$O(V)$	Standard
542	01 Matrix	For each cell, return the distance to the nearest <code>0</code> .		$O(m \cdot n)$	$O(m \cdot n)$	Standard
127	Word Ladder	Minimum number of transformations from <code>beginWord</code> to <code>endWord</code> , changing one letter at a time. Each intermediate word must be in <code>wordList</code> .		$O(N \cdot L \cdot 26)$ where N = words, L = word length	$O(N \cdot L)$	Standard
130	Surrounded Regions	Flip all <code>'0'</code> regions not connected to the border to <code>'X'</code> .		$O(m \cdot n)$	$O(m \cdot n)$	Standard
417	Pacific Atlantic Water Flow	Return all cells from which water can flow to both the Pacific (top/left border) and Atlantic (bottom/right border).		$O(m \cdot n)$	$O(m \cdot n)$	Standard
207	Course Schedule	Can you finish all courses given prerequisites? Detect if there is a directed cycle.		$O(V+E)$	$O(V+E)$	Standard
210	Course Schedule II	Return a valid order to take all courses. Return <code>[]</code> if impossible.		$O(V+E)$	$O(V+E)$	Standard
310	Minimum Height Trees	Find all roots that minimize tree height. At most 2 answers — they are the center node(s) of the longest path.	the best root sits at the center of the longest path; peeling leaves layer by layer converges there.	$O(V+E)$	$O(V+E)$	Standard
547	Number of Provinces	Count the number of connected components (provinces) in an undirected graph given as an adjacency matrix.	start with <code>n</code> separate sets; every successful merge drops the count by one.	$O(n^2 \cdot \alpha(n))$	$O(n)$	Standard
684	Redundant Connection	Find the edge that creates a cycle in an undirected graph that would otherwise be a tree.	if both endpoints are already in the same set, this edge closes a cycle — it's the redundant one.	$O(n \cdot \alpha(n))$	$O(n)$	Standard
1319	Number of Operations to Make Network Connected	Minimum cable moves to connect all <code>n</code> computers. Return <code>-1</code> if impossible.	each redundant cable can be moved to bridge one gap, so <code>components - 1</code> moves suffice if you	$O(E \cdot \alpha(n))$	$O(n)$	Standard

#	Name	Description	Intuition	Time	Space	Key Implementation
			have enough spare cables.			
743	Network Delay Time	Time for a signal from <code>k</code> to reach all <code>n</code> nodes. Return -1 if unreachable.	every node is reached by its shortest delay; the network is "done" when the slowest of those arrives.	$O((V+E)\log V)$	$O(V+E)$	Standard
787	Cheapest Flights Within K Stops	Cheapest price from <code>src</code> to <code>dst</code> using at most <code>k</code> stops (<code>k+1</code> edges).	each round lets paths grow by one more edge, so <code>k+1</code> rounds caps the path at <code>k</code> stops.	$O(k \cdot E)$	$O(V)$	Standard
1514	Path with Maximum Probability	Find the path from <code>start</code> to <code>end</code> with maximum success probability (product of edge probabilities).	probabilities in $[0,1]$ only shrink when multiplied, so the "closest" (highest-probability) node settles first — Dijkstra still applies.	$O((V+E)\log V)$	$O(V+E)$	Standard
785	Is Graph Bipartite?	Can graph nodes be split into two groups where every edge connects nodes in different groups?	paint each neighbor the opposite color; a clash means an odd-length cycle, which can't be 2-colored.	$O(V+E)$	$O(V)$	Standard
1584	Min Cost to Connect All Points	Connect all points (on a 2D plane) with minimum total Manhattan distance. Return that total cost.	grow one tree, always swallowing the cheapest edge that reaches a node not yet in it.	$O(n^2 \log n)$	$O(n^2)$	Standard
1631	Path With Minimum Effort	Find a path from top-left $[0,0]$ to bottom-right $[m-1,n-1]$ that minimizes the maximum absolute difference between adjacent cells.		$O(m \cdot n \cdot \log(m \cdot n))$	$O(m \cdot n)$	Modified Dijkstra. Instead of summing edge weights, the "cost" of a path is the maximum edge cost. Priority queue ordered by effort; <code>effort[r][c]</code> = minimum over all paths of their max-abs-diff.
269	Alien Dictionary	Given a sorted list of alien words, determine the order of characters in the alien alphabet. Return the order as a string, or empty string if invalid.		$O(C)$ where C = total characters across all words	$O(1)$ (at most 26 nodes)	Build a directed graph of character ordering. Compare each adjacent pair of words to find the first differing character → that gives an edge. Then topological sort. Return empty if there's a cycle or if shorter word is a prefix of longer word in wrong order.
261	Graph Valid Tree	Given <code>n</code> nodes labeled $0..n-1$ and a list of undirected edges, determine if they form a valid tree (connected, no cycles).		$O(n \cdot \alpha(n)) \approx O(n)$	$O(n)$	A valid tree has exactly <code>n-1</code> edges. Use Union Find to detect cycles. If any edge connects two nodes already in the same component → cycle → not a tree.
323	Number of Connected Components in an Undirected Graph	Given <code>n</code> nodes and a list of undirected edges, return the number of connected components.		$O(n \cdot \alpha(n)) \approx O(n)$	$O(n)$	decrement on merge

#	Name	Description	Intuition	Time	Space	Key Implementation
286	Walls and Gates	Each cell is a gate (0), wall (-1), or empty (INF = 2147483647). Fill each empty room with distance to its nearest gate.		$O(m \cdot n)$	$O(m \cdot n)$	multi-source BFS — seed the queue with every gate at distance 0, then expand outward simultaneously.
721	Accounts Merge	Each account has a name and a list of emails. Merge accounts that share any email. Return merged accounts with emails sorted.		$O(n \cdot a)$ with sorting $O(n \log n)$	$O(n)$	Union Find over emails. Assign each unique email an integer id, union all emails within the same account, then group emails by their root.
827	Making A Large Island	In a binary grid you may change at most one 0 to 1. Return the size of the largest island possible.		$O(m \cdot n)$	$O(m \cdot n)$	two passes. First DFS-color each island with a unique id (starting at 2) and record its size. Then for every 0, sum the sizes of distinct neighboring islands + 1.
909	Snakes and Ladders	On an $n \times n$ board numbered in boustrophedon (zigzag) order, find the minimum dice moves (1-6) from square 1 to square n^2 . Ladders/snakes teleport you.		$O(n^2)$	$O(n^2)$	BFS over square numbers. Convert a square number to (row, col) accounting for the zigzag layout.
1091	Shortest Path in Binary Matrix	In an $n \times n$ binary grid, find the length of the shortest clear path (cells of 0) from top-left to bottom-right, moving in 8 directions.		$O(m \cdot n)$	$O(m \cdot n)$	standard BFS but with 8-directional movement (includes diagonals).
126	Word Ladder II	Find all shortest transformation sequences from <code>beginWord</code> to <code>endWord</code> , changing one letter at a time, each intermediate word in <code>wordList</code> .	BFS level-by-level builds a parent (predecessor) map of which words lead to which; once <code>endWord</code> is reached, DFS backtracks through parents to reconstruct every shortest path.	$O(N \cdot L \cdot 26)$ BFS + paths	$O(N \cdot L)$	Standard
133	Clone Graph	Deep-copy an undirected graph where each node has a value and a list of neighbors.	Use a map from original node to its clone to avoid re-cloning and to wire neighbors correctly; BFS the graph, creating clones on first sight.	$O(V+E)$	$O(V)$	Standard
277	Find the Celebrity	Among <code>n</code> people, find the celebrity: known by everyone, knows nobody. <code>knows(a, b)</code> is the API.	A single linear scan narrows to one candidate (if <code>candidate</code> knows <code>i</code> , the candidate can't be the celebrity, so <code>i</code> becomes the	$O(n)$	$O(1)$	Standard

#	Name	Description	Intuition	Time	Space	Key Implementation
			new candidate); a second pass verifies.			
296	Best Meeting Point	Given a grid where 1 marks a home, find the minimum total Manhattan distance to a single meeting point.	Manhattan distance separates into independent x and y components; the optimal coordinate on each axis is the median of the occupied coordinates.	$O(m \cdot n)$	$O(m \cdot n)$	Standard
305	Number of Islands II	Land cells are added one at a time to a water grid; after each addition return the current number of islands.		$O(k \cdot \alpha(m \cdot n))$	$O(m \cdot n)$	Online Union-Find — when a cell becomes land, union it with any already-land 4-neighbors; track component count.
317	Shortest Distance from All Buildings	Find the empty land cell 0 minimizing total walking distance to every building 1 (2 = obstacle).	BFS from each building, accumulating distances into every reachable empty cell and counting how many buildings reach it; the answer is the minimum total among cells reachable by all buildings.	$O(B \cdot m \cdot n)$ where B = buildings	$O(m \cdot n)$	Standard
399	Evaluate Division	Given equations $a/b = \text{value}$, answer queries c/d . Return -1.0 if undeterminable.	Treat variables as nodes and ratios as weighted directed edges; the answer to a query is the product of edge weights along any path from numerator to denominator.	$O(Q \cdot (V+E))$	$O(V+E)$	Standard
407	Trapping Rain Water II	Given a 2D height map, compute how much water it can trap after raining.		$O(m \cdot n \cdot \log(m \cdot n))$	$O(m \cdot n)$	Dijkstra-style BFS from the border inward using a min-heap of boundary heights; water level at a cell is the highest of the minimum boundary it must pass — pop the lowest wall first.
463	Island Perimeter	Given a grid with exactly one island, return its perimeter.	Each land cell contributes 4 sides, minus 2 for every shared edge with an adjacent land cell (counted once per pair).	$O(m \cdot n)$	$O(1)$	Standard
529	Minesweeper	Reveal a cell on a Minesweeper board. 'M' mine, 'E' unrevealed empty, 'B' revealed blank, digit = adjacent mine count.		$O(m \cdot n)$	$O(m \cdot n)$	BFS/DFS flood fill with 8 directions; if the clicked cell is a mine, mark 'X' ; otherwise count adjacent mines, and only recurse when count is 0.
694	Number of Distinct Islands	Count islands that are distinct by shape (translations are the same, rotations are not).		$O(m \cdot n)$	$O(m \cdot n)$	DFS recording the path signature (the direction taken at each step plus a backtrack marker); two islands with

#	Name	Description	Intuition	Time	Space	Key Implementation
						identical signatures have the same shape.
733	Flood Fill	Starting at <code>(sr, sc)</code> , change all connected same-color pixels to <code>color</code> .		$O(m \cdot n)$	$O(m \cdot n)$	Standard
752	Open the Lock	A 4-wheel lock starts at <code>"0000"</code> ; each move turns one wheel ± 1 . Find minimum moves to reach <code>target</code> , avoiding <code>deadends</code> .		$O(10^4 \cdot 8)$	$O(10^4)$	BFS over the 4-digit state space; each state has 8 neighbors (each wheel up or down). Treat deadends as visited.
778	Swim in Rising Water	At time <code>t</code> you can stand on any cell with elevation $\leq t$. Find the least time to swim from <code>(0,0)</code> to <code>(n-1,n-1)</code> .		$O(n^2 \cdot \log(n))$	$O(n^2)$	Modified Dijkstra — minimize the maximum elevation along the path (not the sum). Min-heap ordered by current max elevation.
797	All Paths From Source to Target	In a DAG given as adjacency list <code>graph</code> , return all paths from node <code>0</code> to node <code>n-1</code> .	Since it is a DAG with no cycles, plain DFS backtracking enumerates every path; no visited set is needed.	$O(2^V \cdot V)$	$O(V)$	Standard
802	Find Eventual Safe States	A node is safe if every path from it eventually reaches a terminal node (no outgoing edges). Return all safe nodes sorted.		$O(V+E)$	$O(V+E)$	Topological sort on the reversed graph (Kahn's) — start from terminal nodes (out-degree 0); a node becomes safe once all its outgoing edges lead to safe nodes.
815	Bus Routes	<code>routes[i]</code> is the stops served by bus <code>i</code> . Find the minimum number of buses to travel from <code>source</code> to <code>target</code> .		$O(\text{sum of route lengths})$	$O(\text{sum of route lengths})$	BFS where the "nodes" are buses (routes); build stop→routes index, then BFS route-to-route through shared stops, counting buses taken.
847	Shortest Path Visiting All Nodes	Find the length of the shortest path in an undirected graph that visits every node (may revisit nodes/edges).		$O(2^n \cdot n^2)$	$O(2^n \cdot n)$	BFS over states <code>(node, visitedMask)</code> where <code>mask</code> is a bitmask of visited nodes; the goal is any state with all bits set. Start BFS from every node simultaneously.
851	Loud and Rich	<code>richer[i] = [a, b]</code> means <code>a</code> is richer than <code>b</code> ; <code>quiet[i]</code> is the quietness of person <code>i</code> . For each person find the quietest person among everyone at least as rich (themselves included).		$O(V+E)$	$O(V+E)$	Topological sort (Kahn's) on the richer→poorer graph; propagate the quietest-known answer from richer people down to poorer ones in topo order.
886	Possible Bipartition	Given <code>dislikes</code> pairs, split <code>n</code> people into two groups so disliking people are never in the same group.		$O(V+E)$	$O(V+E)$	Standard

#	Name	Description	Intuition	Time	Space	Key Implementation
913	Cat and Mouse	A mouse (start node 1) and cat (start node 2) move on a graph; mouse wins by reaching node 0, cat wins by catching the mouse, else draw. Return 0/1/2 with optimal play.		$O(V^3)$	$O(V^2)$	Game-theory BFS over states (mouse, cat, turn) ; start from known terminal states and propagate results backward (retrograde analysis) by counting undecided moves.
934	Shortest Bridge	A grid has exactly two islands of 1 s. Find the minimum number of 0 s to flip to connect them.		$O(n^2)$	$O(n^2)$	DFS to mark the first island (seeding a BFS queue with its cells), then multi-source BFS expanding outward until reaching the second island; BFS levels = bridge length.
1034	Coloring A Border	Color the border cells of the connected component containing (row, col) with color. A border cell touches the grid edge or a cell of a different original color.		$O(m \cdot n)$	$O(m \cdot n)$	BFS over same-color connected cells; mark a cell as a border when it has fewer than 4 same-component neighbors, recolor borders after traversal.
1102	Path With Maximum Minimum Value	Find a path from top-left to bottom-right maximizing the minimum cell value along the path (4-directional).		$O(m \cdot n \cdot \log(m \cdot n))$	$O(m \cdot n)$	Modified Dijkstra with a max-heap — the path "score" is the minimum cell value seen; greedily expand the highest-scoring frontier first.
1136	Parallel Courses	Courses 1..n with prerequisite relations ; in each semester take all courses whose prerequisites are done. Return minimum semesters, or -1 if impossible.		$O(V+E)$	$O(V+E)$	Topological sort (Kahn's) processed level-by-level — each BFS level is one semester; if not all courses are processed, a cycle exists.
1162	As Far from Land as Possible	In a grid of 0 (water) and 1 (land), find the water cell whose distance to the nearest land is maximized; return that distance, or -1.		$O(n^2)$	$O(n^2)$	Multi-source BFS seeded with all land cells; the last BFS level expanded gives the maximum distance.
1197	Minimum Knight Moves	On an infinite chessboard, find the minimum knight moves from (0,0) to (x, y) .		$O(\max(x,y)^2)$	$O(\max(x,y)^2)$	BFS over knight moves (8 jump offsets); exploit symmetry by working in the first quadrant to bound the visited set.
1202	Smallest String With Swaps	Given index pairs that may be swapped any number of times, return the lexicographically smallest string achievable.		$O(n \cdot \log(n) + E \cdot \alpha(n))$	$O(n)$	Union-Find groups swappable indices into connected components; within each component, sort the characters and place them back in ascending index order.
1245	Tree Diameter	Given the edges of an undirected tree, return its diameter (the number		$O(V+E)$	$O(V+E)$	Two BFS passes — BFS from any node finds the farthest node u ; a second BFS from

#	Name	Description	Intuition	Time	Space	Key Implementation
		of edges on the longest path between any two nodes).				u gives the diameter as the maximum distance.
1293	Shortest Path in a Grid with Obstacles Elimination	Find the shortest path from (0,0) to (m-1,n-1) in a grid where you may eliminate at most k obstacles (1 s).		O(m·n·k)	O(m·n)	BFS over states (row, col, remainingK); the visited set tracks the best remaining eliminations per cell so a cell can be revisited with more budget.
1559	Detect Cycles in 2D Grid	Return true if the grid contains a cycle of length ≥ 4 made of the same character.		O(m·n·α(m·n))	O(m·n)	Union-Find over grid cells — for each cell union it with its up and left same-character neighbors; if a union finds them already connected, a cycle exists.
1743	Restore the Array From Adjacent Pairs	Given all adjacent pairs of an array (in any order), reconstruct the original array.		O(n)	O(n)	Build an adjacency graph; the two endpoints have a single neighbor. Start from an endpoint and walk the path, avoiding the previous node.

Graph Representation

```
// Adjacency list (most common)
List<List<Integer>> graph = new ArrayList<>();
for (int i = 0; i < n; i++) graph.add(new ArrayList<>());
for (int[] edge : edges) {
    graph.get(edge[0]).add(edge[1]);
    graph.get(edge[1]).add(edge[0]);    // omit for directed
}

// Weighted adjacency list: int[] = {neighbor, weight}
List<List<int[]>> graph = new ArrayList<>();
for (int i = 0; i < n; i++) graph.add(new ArrayList<>());
for (int[] edge : edges)
    graph.get(edge[0]).add(new int[]{edge[1], edge[2]});

// Grid 4-directional neighbors
int[] dr = {1, -1, 0, 0};
int[] dc = {0, 0, 1, -1};
```

Core Templates

Variables: queue = BFS frontier · visited[] = seen flags · level = current distance ring · inDegree[] = remaining prerequisites per node · order = topo result · parent[] / rank[] = union-find forest · dist[] = shortest distance · pq = min-heap on cost · color[] = 2-coloring (-1/0/1) **Pseudocode:**

```
BFS: mark start visited, enqueue; while queue, snapshot level size, pop each, push unvisited neighbors, i
TOPO: count inDegree per edge, enqueue all zero-inDegree, pop into order and decrement neighbors, enqueue
UNION-FIND: init parent[i]=i; find follows parent to root with path compression; union links roots by ran
DIJKSTRA: dist[src]=0, push src; pop closest, skip if stale, relax each neighbor and push improved
BIPARTITE: color each component start 0, BFS painting neighbors opposite, return false on same-color clas
```

```

// 1. BFS – shortest path / level order (track distance by level-size snapshot)
// explore in rings of equal distance; snapshot the level size so each ring = one step. – WHEN: "fewes
Queue<Integer> queue = new ArrayDeque<>();
boolean[] visited = new boolean[n];
queue.offer(start);
visited[start] = true;
int level = 0;
while (!queue.isEmpty()) {
    int size = queue.size();                // ← snapshot: all nodes at this distance
    for (int i = 0; i < size; i++) {
        int node = queue.poll();
        // process node (distance == level)
        for (int neighbor : graph.get(node)) {
            if (!visited[neighbor]) {
                visited[neighbor] = true;
                queue.offer(neighbor);
            }
        }
    }
    level++;
}

// 2. TOPOLOGICAL SORT – Kahn's BFS
// peel off nodes with no remaining prerequisites; if any get stuck, a cycle exists. – WHEN: "valid or
int[] inDegree = new int[n];
for (int[] edge : edges) inDegree[edge[1]]++;
Queue<Integer> queue = new ArrayDeque<>();
for (int i = 0; i < n; i++) if (inDegree[i] == 0) queue.offer(i);
List<Integer> order = new ArrayList<>();
while (!queue.isEmpty()) {
    int node = queue.poll();
    order.add(node);
    for (int neighbor : graph.get(node))
        if (--inDegree[neighbor] == 0) queue.offer(neighbor);
}
// order.size() == n → no cycle

// 3. UNION FIND
// each set points to one representative; merge sets by linking roots, query by finding roots. – WHEN:
int[] parent, rank;
void init(int n) {
    parent = new int[n]; rank = new int[n];
    for (int i = 0; i < n; i++) parent[i] = i;
}
int find(int x) {
    if (parent[x] != x) parent[x] = find(parent[x]); // path compression
    return parent[x];
}
boolean union(int x, int y) {
    int px = find(x), py = find(y);
    if (px == py) return false;
    if (rank[px] < rank[py]) { int t = px; px = py; py = t; }
    parent[py] = px;
    if (rank[px] == rank[py]) rank[px]++;
    return true;
}

// 4. DIJKSTRA – shortest path (non-negative weights)
// greedily settle the closest unfinished node; non-negative weights guarantee it's final. – WHEN: "sh
int[] dist = new int[n];
Arrays.fill(dist, Integer.MAX_VALUE);
dist[src] = 0;
PriorityQueue<int[]> pq = new PriorityQueue<>((a, b) -> a[1] - b[1]); // min-heap on cost

```

```

pq.offer(new int[]{src, 0});
while (!pq.isEmpty()) {
    int[] current = pq.poll();
    int node = current[0], d = current[1];
    if (d > dist[node]) continue; // stale entry
    for (int[] nb : graph.get(node)) {
        int next = nb[0], w = nb[1];
        if (dist[node] + w < dist[next]) {
            dist[next] = dist[node] + w;
            pq.offer(new int[]{next, dist[next]});
        }
    }
}

// 5. BIPARTITE CHECK – BFS 2-coloring
// paint neighbors the opposite color; a neighbor that's already your color means an odd cycle. – WHEN
int[] color = new int[n];
Arrays.fill(color, -1);
Queue<Integer> queue = new ArrayDeque<>();
for (int start = 0; start < n; start++) {
    if (color[start] != -1) continue;
    color[start] = 0;
    queue.offer(start);
    while (!queue.isEmpty()) {
        int node = queue.poll();
        for (int neighbor : graph.get(node)) {
            if (color[neighbor] == -1) { color[neighbor] = 1 - color[node]; queue.offer(neighbor); }
            else if (color[neighbor] == color[node]) return false; // conflict
        }
    }
}
return true;

```

Part 1 — BFS Shortest Path

Single-Source vs Multi-Source

Single-source: one starting node, find distances to all others
 Multi-source: seed queue with ALL starting nodes at once → BFS fans out from all simultaneously
 → avoids nested loops, handles "nearest X" questions in $O(n)$

#994 Rotting Oranges

Description: Grid of 0 (empty), 1 (fresh), 2 (rotten). Each minute rotten oranges infect adjacent fresh ones. Return minutes until no fresh remain, or -1.

Algorithm: Multi-source BFS — seed queue with all rotten cells simultaneously.

Variables: queue = cells rotting this round · fresh = count of fresh oranges left · dr / dc = 4-direction offsets · minutes = elapsed time **Pseudocode:**

```

scan grid: enqueue every rotten cell, count fresh
while queue not empty and fresh remain:
    advance one minute, snapshot level size
    for each rotten cell, rot fresh 4-neighbors, enqueue them, decrement fresh
return minutes if no fresh left else -1

```

```

class Solution {
    public int orangesRotting(int[][] grid) {
        int rows = grid.length, cols = grid[0].length;
        Queue<int[]> queue = new ArrayDeque<>();
        int fresh = 0;
        for (int r = 0; r < rows; r++)
            for (int c = 0; c < cols; c++) {
                if (grid[r][c] == 2) queue.offer(new int[]{r, c});
                if (grid[r][c] == 1) fresh++;
            }
        int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
        int minutes = 0;
        while (!queue.isEmpty() && fresh > 0) {
            minutes++;
            int size = queue.size();
            for (int i = 0; i < size; i++) {
                int[] current = queue.poll();
                for (int d = 0; d < 4; d++) {
                    int nr = current[0]+dr[d], nc = current[1]+dc[d];
                    if (nr >= 0 && nr < rows && nc >= 0 && nc < cols && grid[nr][nc] == 1) {
                        grid[nr][nc] = 2;
                        queue.offer(new int[]{nr, nc});
                        fresh--;
                    }
                }
            }
        }
        return fresh == 0 ? minutes : -1;
    }
}

```

Time $O(V+E)$ | **Space** $O(V)$

#542 01 Matrix

Description: For each cell, return the distance to the nearest 0.

Algorithm: Multi-source BFS from all 0 cells simultaneously. Initialize $\text{dist}[r][c] = \text{MAX}$ for 1 cells.

Variables: $\text{dist}[][]$ = distance to nearest 0 · queue = BFS frontier of 0-cells · dr / dc = 4-direction offsets

Pseudocode:

```

seed queue with all 0-cells (dist 0); set every 1-cell dist to MAX
while queue: pop cell, for each neighbor if dist+1 improves it, update and enqueue
return dist

```

```

class Solution {
    public int[][] updateMatrix(int[][] mat) {
        int rows = mat.length, cols = mat[0].length;
        int[][] dist = new int[rows][cols];
        Queue<int[]> queue = new ArrayDeque<>();
        for (int r = 0; r < rows; r++)
            for (int c = 0; c < cols; c++) {
                if (mat[r][c] == 0) {
                    queue.offer(new int[]{r, c});
                } else {
                    dist[r][c] = Integer.MAX_VALUE;
                }
            }
        int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
        while (!queue.isEmpty()) {
            int[] current = queue.poll();
            for (int d = 0; d < 4; d++) {
                int nr = current[0]+dr[d], nc = current[1]+dc[d];
                if (nr >= 0 && nr < rows && nc >= 0 && nc < cols
                    && dist[current[0]][current[1]] + 1 < dist[nr][nc]) {
                    dist[nr][nc] = dist[current[0]][current[1]] + 1;
                    queue.offer(new int[]{nr, nc});
                }
            }
        }
        return dist;
    }
}

```

Time $O(m \cdot n)$ | **Space** $O(m \cdot n)$

#127 Word Ladder

Description: Minimum number of transformations from `beginWord` to `endWord`, changing one letter at a time. Each intermediate word must be in `wordList`.

Algorithm: BFS on word states. Remove words from set when visited to prevent re-visiting.

Variables: `wordSet` = remaining usable words (doubles as visited) · `queue` = words at current BFS level · `steps` = transformations so far · `word` = char array being mutated **Pseudocode:**

```

load wordList into set; if endWord absent return 0
enqueue beginWord, remove it from set, steps=1
while queue: for each word at this level, try every position×26 letters
    if mutated word equals endWord return steps+1
    if in set, remove it and enqueue
increment steps each level; return 0 if exhausted

```

```

class Solution {
    public int ladderLength(String beginWord, String endWord, List<String> wordList) {
        Set<String> wordSet = new HashSet<>(wordList);
        if (!wordSet.contains(endWord)) return 0;
        Queue<String> queue = new ArrayDeque<>();
        queue.offer(beginWord);
        wordSet.remove(beginWord);
        int steps = 1;
        while (!queue.isEmpty()) {
            int size = queue.size();
            for (int i = 0; i < size; i++) {
                char[] word = queue.poll().toCharArray();
                for (int j = 0; j < word.length; j++) {
                    char original = word[j];
                    for (char c = 'a'; c <= 'z'; c++) {
                        word[j] = c;
                        String next = new String(word);
                        if (next.equals(endWord)) return steps + 1;
                        if (wordSet.contains(next)) {
                            wordSet.remove(next);
                            queue.offer(next);
                        }
                    }
                    word[j] = original;
                }
            }
            steps++;
        }
        return 0;
    }
}

```

Time $O(N \cdot L \cdot 26)$ where N = words, L = word length | **Space** $O(N \cdot L)$

#130 Surrounded Regions

Description: Flip all '0' regions not connected to the border to 'X'.

Algorithm: Multi-source BFS from all border '0' cells. Mark reachable as safe ('S'), then flip all remaining '0' to 'X' and restore 'S' to '0'.

Variables: queue = border-connected O-cells · 'S' = temporary safe marker · dr / dc = 4-direction offsets

Pseudocode:

```

enqueue every border '0', mark it 'S'
BFS outward marking all connected '0' as 'S'
final sweep: 'S' becomes '0' (safe), everything else '0' becomes 'X'

```

```

class Solution {
    public void solve(char[][] board) {
        int rows = board.length, cols = board[0].length;
        Queue<int[]> queue = new ArrayDeque<>();
        for (int r = 0; r < rows; r++)
            for (int c = 0; c < cols; c++)
                if ((r == 0 || r == rows-1 || c == 0 || c == cols-1) && board[r][c] == '0') {
                    board[r][c] = 'S';
                    queue.offer(new int[]{r, c});
                }
        int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
        while (!queue.isEmpty()) {
            int[] current = queue.poll();
            for (int d = 0; d < 4; d++) {
                int nr = current[0]+dr[d], nc = current[1]+dc[d];
                if (nr >= 0 && nr < rows && nc >= 0 && nc < cols && board[nr][nc] == '0') {
                    board[nr][nc] = 'S';
                    queue.offer(new int[]{nr, nc});
                }
            }
        }
        for (int r = 0; r < rows; r++)
            for (int c = 0; c < cols; c++)
                board[r][c] = board[r][c] == 'S' ? '0' : 'X';
    }
}

```

Time $O(m \cdot n)$ | **Space** $O(m \cdot n)$

#417 Pacific Atlantic Water Flow

Description: Return all cells from which water can flow to both the Pacific (top/left border) and Atlantic (bottom/right border).

Algorithm: Two separate multi-source BFS — one from each ocean's border cells, moving **uphill** (water flows down, so reachable cells going up = cells that drain down to ocean). Answer = intersection of both reachable sets.

Variables: `pac[][]` / `atl[][]` = cells that can reach each ocean · `pacQ` / `atlQ` = BFS queues seeded from each ocean's border · `result` = cells reaching both **Pseudocode:**

seed `pacQ`+`pac` with top/left border, `atlQ`+`atl` with bottom/right border

BFS each ocean uphill: move to neighbor only if its height $\geq$ current (water could flow down to here)

collect every cell marked in both `pac` and `atl`

```

class Solution {
    int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};

    public List<List<Integer>> pacificAtlantic(int[][] h) {
        int rows = h.length, cols = h[0].length;
        boolean[][] pac = new boolean[rows][cols];
        boolean[][] atl = new boolean[rows][cols];
        Queue<int[]> pacQ = new ArrayDeque<>(), atlQ = new ArrayDeque<>();
        for (int r = 0; r < rows; r++) {
            pac[r][0] = atl[r][cols-1] = true;
            pacQ.offer(new int[]{r, 0});
            atlQ.offer(new int[]{r, cols-1});
        }
        for (int c = 0; c < cols; c++) {
            pac[0][c] = atl[rows-1][c] = true;
            pacQ.offer(new int[]{0, c});
            atlQ.offer(new int[]{rows-1, c});
        }
        bfs(h, pacQ, pac);
        bfs(h, atlQ, atl);
        List<List<Integer>> result = new ArrayList<>();
        for (int r = 0; r < rows; r++)
            for (int c = 0; c < cols; c++)
                if (pac[r][c] && atl[r][c]) result.add(Arrays.asList(r, c));
        return result;
    }

    private void bfs(int[][] h, Queue<int[]> queue, boolean[][] visited) {
        while (!queue.isEmpty()) {
            int[] current = queue.poll();
            for (int d = 0; d < 4; d++) {
                int nr = current[0]+dr[d], nc = current[1]+dc[d];
                if (nr >= 0 && nr < h.length && nc >= 0 && nc < h[0].length
                    && !visited[nr][nc] && h[nr][nc] >= h[current[0]][current[1]]) {
                    visited[nr][nc] = true;
                    queue.offer(new int[]{nr, nc});
                }
            }
        }
    }
}

```

Time $O(m \cdot n)$ | **Space** $O(m \cdot n)$

Part 2 — Topological Sort (Kahn's BFS)

Core idea: repeatedly remove nodes with `inDegree == 0` (no prerequisites). If all nodes removed $\rightarrow$ no cycle. Post-order in DFS = reverse of `order` here.

#207 Course Schedule

Description: Can you finish all courses given prerequisites? Detect if there is a directed cycle.

Variables: `graph` = prereq $\rightarrow$ dependent edges · `inDegree[]` = unmet prerequisites per course · `queue` = courses ready to take · `processed` = courses taken **Pseudocode:**

```

build graph edge p[1]→p[0], counting inDegree[p[0]]
enqueue every course with inDegree 0
pop, increment processed, decrement neighbors' inDegree, enqueue new zeros
return processed == numCourses (all taken → no cycle)

```

```

class Solution {
    public boolean canFinish(int numCourses, int[][] prerequisites) {
        List<List<Integer>> graph = new ArrayList<>();
        int[] inDegree = new int[numCourses];
        for (int i = 0; i < numCourses; i++) graph.add(new ArrayList<>());
        for (int[] p : prerequisites) {
            graph.get(p[1]).add(p[0]);
            inDegree[p[0]]++;
        }
        Queue<Integer> queue = new ArrayDeque<>();
        for (int i = 0; i < numCourses; i++) if (inDegree[i] == 0) queue.offer(i);
        int processed = 0;
        while (!queue.isEmpty()) {
            int node = queue.poll();
            processed++;
            for (int neighbor : graph.get(node))
                if (--inDegree[neighbor] == 0) queue.offer(neighbor);
        }
        return processed == numCourses;    // all processed → no cycle
    }
}

```

Time $O(V+E)$ | **Space** $O(V+E)$

#210 Course Schedule II

Description: Return a valid order to take all courses. Return `[]` if impossible.

Variables: `graph` = prereq → dependent edges · `inDegree[]` = unmet prerequisites · `queue` = ready courses · `order[]` = taking sequence · `idx` = fill position **Pseudocode:**

```

build graph + inDegree (same as #207)
enqueue all inDegree=0 courses
pop into order[idx++], relax neighbors, enqueue new zeros
return order if idx == numCourses else empty array (cycle)

```

```

class Solution {
    public int[] findOrder(int numCourses, int[][] prerequisites) {
        List<List<Integer>> graph = new ArrayList<>();
        int[] inDegree = new int[numCourses];
        for (int i = 0; i < numCourses; i++) graph.add(new ArrayList<>());
        for (int[] p : prerequisites) {
            graph.get(p[1]).add(p[0]);
            inDegree[p[0]]++;
        }
        Queue<Integer> queue = new ArrayDeque<>();
        for (int i = 0; i < numCourses; i++) if (inDegree[i] == 0) queue.offer(i);
        int[] order = new int[numCourses];
        int idx = 0;
        while (!queue.isEmpty()) {
            int node = queue.poll();
            order[idx++] = node;
            for (int neighbor : graph.get(node))
                if (--inDegree[neighbor] == 0) queue.offer(neighbor);
        }
        return idx == numCourses ? order : new int[]{};
    }
}

```

Time $O(V+E)$ | **Space** $O(V+E)$

#310 Minimum Height Trees

Description: Find all roots that minimize tree height. At most 2 answers — they are the center node(s) of the longest path.

Algorithm: Iteratively trim leaves (degree-1 nodes) until ≤ 2 nodes remain — same as topo sort but on undirected tree.

Intuition: the best root sits at the center of the longest path; peeling leaves layer by layer converges there.

Variables: `graph` = adjacency sets · `queue` = current leaves (degree 1) · `remaining` = nodes not yet trimmed

Pseudocode:

```

if n==1 return [0]
build undirected adjacency sets; enqueue all degree-1 leaves
while remaining > 2: subtract this leaf layer, for each leaf remove it from its neighbor; if neighbor now
return nodes left in queue (1 or 2 centers)

```

```

class Solution {
    public List<Integer> findMinHeightTrees(int n, int[][] edges) {
        if (n == 1) return Collections.singletonList(0);
        List<Set<Integer>> graph = new ArrayList<>();
        for (int i = 0; i < n; i++) graph.add(new HashSet<>());
        for (int[] e : edges) { graph.get(e[0]).add(e[1]); graph.get(e[1]).add(e[0]); }
        Queue<Integer> queue = new ArrayDeque<>();
        for (int i = 0; i < n; i++) if (graph.get(i).size() == 1) queue.offer(i);
        int remaining = n;
        while (remaining > 2) {
            int size = queue.size();
            remaining -= size;
            for (int i = 0; i < size; i++) {
                int leaf = queue.poll();
                int neighbor = graph.get(leaf).iterator().next();
                graph.get(neighbor).remove(leaf);
                if (graph.get(neighbor).size() == 1) queue.offer(neighbor);
            }
        }
        return new ArrayList<>(queue);
    }
}

```

Time $O(V+E)$ | **Space** $O(V+E)$

207 vs 210 — Side by Side

	#207 (boolean)	#210 (order)
Track:	int processed	int[] order, int idx
Return:	processed == n	idx == n ? order : []
Difference:	just count	also record node into order[]

Part 3 — Union Find

Template (always the same three methods):

Variables: `parent[]` = each node's parent (root represents its set) · `rank[]` = tree-height hint for balanced merging ·
`x / y` = nodes to relate · `px / py` = their roots **Pseudocode:**

```

init: every node is its own parent (n singleton sets)
find(x): walk to root, compress path so each node points straight at root
union(x,y): find both roots; if equal return false (already joined); else attach smaller-rank root under

```

```

int[] parent, rank;

void init(int n) {
    parent = new int[n];
    rank = new int[n];
    for (int i = 0; i < n; i++) parent[i] = i;
}

int find(int x) {
    if (parent[x] != x) parent[x] = find(parent[x]); // path compression
    return parent[x];
}

boolean union(int x, int y) { // returns false if already connected
    int px = find(x), py = find(y);
    if (px == py) return false;
    if (rank[px] < rank[py]) { int t = px; px = py; py = t; }
    parent[py] = px;
    if (rank[px] == rank[py]) rank[px]++;
    return true;
}

```

#547 Number of Provinces

Description: Count the number of connected components (provinces) in an undirected graph given as an adjacency matrix.

Intuition: start with `n` separate sets; every successful merge drops the count by one.

Variables: `parent[]` / `rank[]` = union-find forest · `components` = current province count **Pseudocode:**

```

init each city its own set, components = n
for every connected pair (i,j): if union succeeds, components--
return components

```

```

class Solution {
    int[] parent, rank;
    public int findCircleNum(int[][] isConnected) {
        int n = isConnected.length;
        parent = new int[n]; rank = new int[n];
        for (int i = 0; i < n; i++) parent[i] = i;
        int components = n;
        for (int i = 0; i < n; i++)
            for (int j = i+1; j < n; j++)
                if (isConnected[i][j] == 1 && union(i, j)) components--;
        return components;
    }
    int find(int x) { return parent[x] == x ? x : (parent[x] = find(parent[x])); }
    boolean union(int x, int y) {
        int px = find(x), py = find(y);
        if (px == py) return false;
        if (rank[px] < rank[py]) { int t = px; px = py; py = t; }
        parent[py] = px;
        if (rank[px] == rank[py]) rank[px]++;
        return true;
    }
}

```

Time $O(n^2 \cdot \alpha(n))$ | **Space** $O(n)$

#684 Redundant Connection

Description: Find the edge that creates a cycle in an undirected graph that would otherwise be a tree.

Key: try to union each edge in order. The first edge where both nodes already share a root is the redundant one.

Intuition: if both endpoints are already in the same set, this edge closes a cycle — it's the redundant one.

Variables: `parent[] / rank[]` = union-find forest · `edge` = current candidate edge **Pseudocode:**

```
init each node its own set (1..n)
for each edge in order: try to union its endpoints
    if union returns false (same root), this edge closes a cycle → return it
```

```
class Solution {
    int[] parent, rank;
    public int[] findRedundantConnection(int[][] edges) {
        int n = edges.length;
        parent = new int[n+1]; rank = new int[n+1];
        for (int i = 0; i <= n; i++) parent[i] = i;
        for (int[] edge : edges)
            if (!union(edge[0], edge[1])) return edge; // already connected → cycle
        return new int[]{};
    }
    int find(int x) { return parent[x] == x ? x : (parent[x] = find(parent[x])); }
    boolean union(int x, int y) {
        int px = find(x), py = find(y);
        if (px == py) return false;
        if (rank[px] < rank[py]) { int t = px; px = py; py = t; }
        parent[py] = px;
        if (rank[px] == rank[py]) rank[px]++;
        return true;
    }
}
```

Time $O(n \cdot \alpha(n))$ | **Space** $O(n)$

#1319 Number of Operations to Make Network Connected

Description: Minimum cable moves to connect all `n` computers. Return -1 if impossible.

Key: need at least `n-1` edges for `n` nodes. Count extra edges (cycles); count components. Answer = `components - 1` if enough extras exist.

Intuition: each redundant cable can be moved to bridge one gap, so `components - 1` moves suffice if you have enough spare cables.

Variables: `parent[] / rank[]` = union-find forest · `components` = connected groups remaining **Pseudocode:**

```
if fewer than n-1 cables, return -1 (impossible)
init each computer its own set, components = n
for each cable: if union succeeds, components--
return components - 1 (moves needed to bridge gaps)
```

```

class Solution {
    int[] parent, rank;
    public int makeConnected(int n, int[][] connections) {
        if (connections.length < n - 1) return -1; // not enough cables
        parent = new int[n]; rank = new int[n];
        for (int i = 0; i < n; i++) parent[i] = i;
        int components = n;
        for (int[] c : connections) if (union(c[0], c[1])) components--;
        return components - 1;
    }
    int find(int x) { return parent[x] == x ? x : (parent[x] = find(parent[x])); }
    boolean union(int x, int y) {
        int px = find(x), py = find(y);
        if (px == py) return false;
        if (rank[px] < rank[py]) { int t = px; px = py; py = t; }
        parent[py] = px;
        if (rank[px] == rank[py]) rank[px]++;
        return true;
    }
}

```

Time $O(E \cdot \alpha(n))$ | **Space** $O(n)$

Part 4 — Dijkstra / Bellman-Ford

#743 Network Delay Time

Description: Time for a signal from `k` to reach all `n` nodes. Return -1 if unreachable.

Algorithm: Dijkstra from source `k`. Answer = max of all shortest distances.

Intuition: every node is reached by its shortest delay; the network is "done" when the slowest of those arrives.

Variables: `graph` = weighted adjacency (neighbor, time) · `dist[]` = shortest delay to each node · `pq` = min-heap on delay · `maxDist` = slowest arrival **Pseudocode:**

```

build weighted graph; dist[k]=0, push (k,0)
pop closest node; skip if its entry is stale
relax each neighbor, push improved distances
after settling, take max over all dist; return -1 if any unreachable

```

```

class Solution {
    public int networkDelayTime(int[][] times, int n, int k) {
        List<List<int[]>> graph = new ArrayList<>();
        for (int i = 0; i <= n; i++) graph.add(new ArrayList<>());
        for (int[] t : times) graph.get(t[0]).add(new int[]{t[1], t[2]});
        int[] dist = new int[n+1];
        Arrays.fill(dist, Integer.MAX_VALUE);
        dist[k] = 0;
        PriorityQueue<int[]> pq = new PriorityQueue<>((a, b) -> a[1] - b[1]);
        pq.offer(new int[]{k, 0});
        while (!pq.isEmpty()) {
            int[] current = pq.poll();
            int node = current[0], d = current[1];
            if (d > dist[node]) continue;
            for (int[] nb : graph.get(node)) {
                int next = nb[0], w = nb[1];
                if (dist[node] + w < dist[next]) {
                    dist[next] = dist[node] + w;
                    pq.offer(new int[]{next, dist[next]});
                }
            }
        }
        int maxDist = 0;
        for (int i = 1; i <= n; i++) {
            if (dist[i] == Integer.MAX_VALUE) return -1;
            maxDist = Math.max(maxDist, dist[i]);
        }
        return maxDist;
    }
}

```

Time $O((V+E)\log V)$ | **Space** $O(V+E)$

#787 Cheapest Flights Within K Stops

Description: Cheapest price from `src` to `dst` using at most `k` stops ($k+1$ edges).

Algorithm: Bellman-Ford with exactly $k+1$ relaxation rounds. Use a copy `temp[]` each round to prevent using the same edge twice in one round.

Intuition: each round lets paths grow by one more edge, so $k+1$ rounds caps the path at `k` stops.

Variables: `dist[]` = cheapest price found so far · `temp[]` = snapshot per round (prevents using same round's edges twice) · `round` = edges allowed **Pseudocode:**

```

dist[src]=0, rest MAX
repeat k+1 rounds (k stops = k+1 edges):
    copy dist into temp; for each flight u->v, relax temp[v] from dist[u]+w
    swap dist = temp
return dist[dst] or -1 if unreachable

```

```

class Solution {
    public int findCheapestPrice(int n, int[][] flights, int src, int dst, int k) {
        int[] dist = new int[n];
        Arrays.fill(dist, Integer.MAX_VALUE);
        dist[src] = 0;
        for (int round = 0; round <= k; round++) {           // k stops = k+1 edges
            int[] temp = Arrays.copyOf(dist, n);
            for (int[] f : flights) {
                int u = f[0], v = f[1], w = f[2];
                if (dist[u] != Integer.MAX_VALUE && dist[u] + w < temp[v])
                    temp[v] = dist[u] + w;
            }
            dist = temp;
        }
        return dist[dst] == Integer.MAX_VALUE ? -1 : dist[dst];
    }
}

```

Time $O(k \cdot E)$ | **Space** $O(V)$

#1514 Path with Maximum Probability

Description: Find the path from `start` to `end` with maximum success probability (product of edge probabilities).

Algorithm: Dijkstra with **max-heap** (maximize probability instead of minimize distance). Multiply probabilities instead of adding weights.

Intuition: probabilities in $[0,1]$ only shrink when multiplied, so the "closest" (highest-probability) node settles first — Dijkstra still applies.

Variables: `graph` = weighted adjacency (neighbor, prob) · `prob[]` = best probability to each node · `pq` = max-heap on probability
Pseudocode:

```

build undirected weighted graph; prob[start]=1, push (start,1)
pop highest-probability node; if it's end, return its probability
skip stale entries; for each neighbor multiply probabilities, push if improved
return 0 if end never reached

```

```

class Solution {
    public double maxProbability(int n, int[][] edges, double[] succProb, int start, int end) {
        List<List<double[]>> graph = new ArrayList<>();
        for (int i = 0; i < n; i++) graph.add(new ArrayList<>());
        for (int i = 0; i < edges.length; i++) {
            int u = edges[i][0], v = edges[i][1];
            graph.get(u).add(new double[]{v, succProb[i]});
            graph.get(v).add(new double[]{u, succProb[i]});
        }
        double[] prob = new double[n];
        prob[start] = 1.0;
        PriorityQueue<double[]> pq = new PriorityQueue<>((a, b) -> Double.compare(b[1], a[1])); // max-
        pq.offer(new double[]{start, 1.0});
        while (!pq.isEmpty()) {
            double[] current = pq.poll();
            int node = (int) current[0];
            double p = current[1];
            if (node == end) return p;
            if (p < prob[node]) continue;
            for (double[] nb : graph.get(node)) {
                int next = (int) nb[0];
                double newProb = p * nb[1];
                if (newProb > prob[next]) {
                    prob[next] = newProb;
                    pq.offer(new double[]{next, newProb});
                }
            }
        }
        return 0.0;
    }
}

```

Time $O((V+E)\log V)$ | **Space** $O(V+E)$

Part 5 — Bipartite Check

#785 Is Graph Bipartite?

Description: Can graph nodes be split into two groups where every edge connects nodes in different groups?

Algorithm: BFS 2-coloring. If any neighbor has the same color as the current node → not bipartite.

Key: run BFS from every unvisited node (graph may be disconnected).

Intuition: paint each neighbor the opposite color; a clash means an odd-length cycle, which can't be 2-colored.

Variables: `color[]` = -1 unvisited / 0 / 1 · `queue` = BFS frontier · `start` = component seed **Pseudocode:**

```

color all -1
for each uncolored start: color 0, BFS
    for each neighbor: if uncolored paint opposite and enqueue; if same color as node return false
return true

```

```

class Solution {
    public boolean isBipartite(int[][] graph) {
        int n = graph.length;
        int[] color = new int[n];
        Arrays.fill(color, -1);
        Queue<Integer> queue = new ArrayDeque<>();
        for (int start = 0; start < n; start++) {
            if (color[start] != -1) continue;
            color[start] = 0;
            queue.offer(start);
            while (!queue.isEmpty()) {
                int node = queue.poll();
                for (int neighbor : graph[node]) {
                    if (color[neighbor] == -1) {
                        color[neighbor] = 1 - color[node];
                        queue.offer(neighbor);
                    } else if (color[neighbor] == color[node]) {
                        return false;
                    }
                }
            }
        }
        return true;
    }
}

```

Time $O(V+E)$ | Space $O(V)$

Part 6 — Minimum Spanning Tree (Prim's)

#1584 Min Cost to Connect All Points

Description: Connect all points (on a 2D plane) with minimum total Manhattan distance. Return that total cost.

Algorithm: Prim's MST — always add the cheapest edge from the growing tree to a new node.

Key: `minEdge[i]` tracks the cheapest known edge from any tree node to node `i`. Update lazily via priority queue; skip nodes already in MST.

Intuition: grow one tree, always swallowing the cheapest edge that reaches a node not yet in it.

Variables: `inMST[]` = node already in tree · `minEdge[]` = cheapest known edge to each node · `pq` = min-heap on edge cost · `total` = accumulated MST weight **Pseudocode:**

```

minEdge[0]=0, push (0,0)
pop cheapest (node,cost); skip if already in MST
add node to MST, total += cost
for every node not in MST: compute Manhattan dist; if cheaper than minEdge, update and push
return total

```

```

class Solution {
    public int minCostConnectPoints(int[][] points) {
        int n = points.length;
        boolean[] inMST = new boolean[n];
        int[] minEdge = new int[n];
        Arrays.fill(minEdge, Integer.MAX_VALUE);
        minEdge[0] = 0;
        PriorityQueue<int[]> pq = new PriorityQueue<>((a, b) -> a[1] - b[1]);
        pq.offer(new int[]{0, 0});
        int total = 0;
        while (!pq.isEmpty()) {
            int[] current = pq.poll();
            int node = current[0], cost = current[1];
            if (inMST[node]) continue;
            inMST[node] = true;
            total += cost;
            for (int next = 0; next < n; next++) {
                if (!inMST[next]) {
                    int dist = Math.abs(points[node][0]-points[next][0])
                        + Math.abs(points[node][1]-points[next][1]);
                    if (dist < minEdge[next]) {
                        minEdge[next] = dist;
                        pq.offer(new int[]{next, dist});
                    }
                }
            }
        }
        return total;
    }
}

```

Time $O(n^2 \log n)$ | **Space** $O(n^2)$

Algorithm Chooser

Signal in problem	Algorithm
Shortest path, unweighted / unit weight	BFS
Shortest path, non-negative weights	Dijkstra
Connected components, cycle detection	Union Find
Directed cycle / valid ordering	Topological Sort (Kahn's)
2-colorable graph	Bipartite BFS coloring
"nearest X for all cells"	Multi-source BFS

Stale Entry Pattern (Dijkstra)

```

int[] current = pq.poll();
int node = current[0], d = current[1];
if (d > dist[node]) continue; // ← this node was already relaxed to a better distance

```

Without this check, stale entries in the heap cause re-processing and wrong results.

It replaces a `visited[]` array — simpler and correct because a better distance always wins.

Part 7 — Modified Dijkstra / Topological Sort on Chars / Union Find Variants

#1631 Path With Minimum Effort

Description: Find a path from top-left $[0,0]$ to bottom-right $[m-1,n-1]$ that minimizes the maximum absolute difference between adjacent cells.

Variation: Modified Dijkstra. Instead of summing edge weights, the "cost" of a path is the maximum edge cost. Priority queue ordered by effort; $\text{effort}[r][c]$ = minimum over all paths of their max-abs-diff.

Variables: $\text{effort}[][]$ = min possible max-step to each cell · pq = min-heap on effort, holds $\{\text{effort}, \text{row}, \text{col}\}$ · dr / dc = 4-direction offsets **Pseudocode:**

```
effort[0][0]=0, push (0,0,0)
pop smallest-effort cell; if it's destination return its effort; skip stale
for each neighbor: newEffort = max(current effort, |height diff|) ← max, not sum
    if newEffort improves neighbor, update and push
```

```
class Solution {
    public int minimumEffortPath(int[][] heights) {
        int m = heights.length, n = heights[0].length;
        int[][] effort = new int[m][n];
        for (int[] row : effort) Arrays.fill(row, Integer.MAX_VALUE);
        effort[0][0] = 0;
        PriorityQueue<int[]> pq = new PriorityQueue<>((a, b) -> a[0] - b[0]);
        pq.offer(new int[]{0, 0, 0}); // [effort, row, col]
        int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
        while (!pq.isEmpty()) {
            int[] current = pq.poll();
            int e = current[0], r = current[1], c = current[2];
            if (r == m-1 && c == n-1) return e;
            if (e > effort[r][c]) continue; // stale entry
            for (int dir = 0; dir < 4; dir++) {
                int nr = r + dr[dir], nc = c + dc[dir];
                if (nr >= 0 && nr < m && nc >= 0 && nc < n) {
                    int newEffort = Math.max(e, Math.abs(heights[nr][nc] - heights[r][c])); // ← VARIA
                    if (newEffort < effort[nr][nc]) {
                        effort[nr][nc] = newEffort;
                        pq.offer(new int[]{newEffort, nr, nc});
                    }
                }
            }
        }
        return 0;
    }
}
```

Time $O(m \cdot n \cdot \log(m \cdot n))$ | **Space** $O(m \cdot n)$

#269 Alien Dictionary

Description: Given a sorted list of alien words, determine the order of characters in the alien alphabet. Return the order as a string, or empty string if invalid.

Variation: Build a directed graph of character ordering. Compare each adjacent pair of words to find the first differing character → that gives an edge. Then topological sort. Return empty if there's a cycle or if shorter word is a prefix of longer word in wrong order.

Variables: `graph` = char → chars that follow it · `inDegree` = unmet predecessors per char · `queue` = chars ready to place · `result` = ordering built **Pseudocode:**

```
register every char with empty edges and inDegree 0
for each adjacent word pair: if prefix-violation (w1 longer but starts with w2) return ""
    else find first differing char → edge w1c→w2c, bump inDegree once
enqueue all inDegree=0 chars; topo-pop into result, relax neighbors
return result if it covers all chars else "" (cycle)
```

```
class Solution {
    public String alienOrder(String[] words) {
        Map<Character, Set<Character>> graph = new HashMap<>();
        Map<Character, Integer> inDegree = new HashMap<>();
        for (String word : words)
            for (char c : word.toCharArray()) {
                graph.putIfAbsent(c, new HashSet<>());
                inDegree.putIfAbsent(c, 0);
            }
        for (int i = 0; i < words.length - 1; i++) {
            String w1 = words[i], w2 = words[i+1];
            if (w1.length() > w2.length() && w1.startsWith(w2)) return ""; // ← VARIATION: invalid pre
            for (int j = 0; j < Math.min(w1.length(), w2.length()); j++) {
                if (w1.charAt(j) != w2.charAt(j)) {
                    if (!graph.get(w1.charAt(j)).contains(w2.charAt(j))) {
                        graph.get(w1.charAt(j)).add(w2.charAt(j));
                        inDegree.merge(w2.charAt(j), 1, Integer::sum);
                    }
                    break;
                }
            }
        }
        Queue<Character> queue = new ArrayDeque<>();
        for (char c : inDegree.keySet()) if (inDegree.get(c) == 0) queue.offer(c);
        StringBuilder result = new StringBuilder();
        while (!queue.isEmpty()) {
            char c = queue.poll();
            result.append(c);
            for (char next : graph.get(c)) {
                inDegree.merge(next, -1, Integer::sum);
                if (inDegree.get(next) == 0) queue.offer(next);
            }
        }
        return result.length() == inDegree.size() ? result.toString() : ""; // ← cycle check
    }
}
```

Time $O(C)$ where C = total characters across all words | **Space** $O(1)$ (at most 26 nodes)

#261 Graph Valid Tree

Description: Given n nodes labeled $0..n-1$ and a list of undirected edges, determine if they form a valid tree (connected, no cycles).

Variation: A valid tree has exactly $n-1$ edges. Use Union Find to detect cycles. If any edge connects two nodes already in the same component → cycle → not a tree.

Variables: `parent[] / rank[]` = union-find forest · `edge` = current edge **Pseudocode:**

```
a tree needs exactly n-1 edges; if not, return false
init each node its own set
for each edge: union endpoints; if union fails (same root → cycle) return false
return true (n-1 edges + no cycle = connected tree)
```

```
class Solution {
    int[] parent, rank;

    public boolean validTree(int n, int[][] edges) {
        if (edges.length != n - 1) return false; // ← VARIATION: tree must have exactly n-1 edges
        parent = new int[n]; rank = new int[n];
        for (int i = 0; i < n; i++) parent[i] = i;
        for (int[] edge : edges)
            if (!union(edge[0], edge[1])) return false; // ← cycle detected → not a tree
        return true;
    }

    int find(int x) { return parent[x] == x ? x : (parent[x] = find(parent[x])); }

    boolean union(int x, int y) {
        int px = find(x), py = find(y);
        if (px == py) return false;
        if (rank[px] < rank[py]) { int t = px; px = py; py = t; }
        parent[py] = px;
        if (rank[px] == rank[py]) rank[px]++;
        return true;
    }
}
```

Time $O(n \cdot \alpha(n)) \approx O(n)$ | **Space** $O(n)$

#323 Number of Connected Components in an Undirected Graph

Description: Given `n` nodes and a list of undirected edges, return the number of connected components.

Algorithm: Union Find. Start with `n` components. Each successful union (merging two previously separate components) decrements the count by 1.

Variables: `parent[] / rank[]` = union-find forest · `components` = component count **Pseudocode:**

```
init each node its own set, components = n
for each edge: if union merges two distinct sets, components--
return components
```

```

class Solution {
    int[] parent, rank;

    public int countComponents(int n, int[][] edges) {
        parent = new int[n]; rank = new int[n];
        for (int i = 0; i < n; i++) parent[i] = i;           // ← start with n isolated components
        int components = n;
        for (int[] edge : edges)
            if (union(edge[0], edge[1])) components--;      // ← VARIATION: decrement on merge
        return components;
    }

    int find(int x) { return parent[x] == x ? x : (parent[x] = find(parent[x])); }

    boolean union(int x, int y) {
        int px = find(x), py = find(y);
        if (px == py) return false;
        if (rank[px] < rank[py]) { int t = px; px = py; py = t; }
        parent[py] = px;
        if (rank[px] == rank[py]) rank[px]++;
        return true;
    }
}

```

Time $O(n \cdot \alpha(n)) \approx O(n)$ | **Space** $O(n)$

#286 Walls and Gates

Description: Each cell is a gate (0), wall (-1), or empty (INF = 2147483647). Fill each empty room with distance to its nearest gate. **Variation:** multi-source BFS — seed the queue with every gate at distance 0, then expand outward simultaneously.

Variables: queue = gate-rooted BFS frontier · dr / dc = 4-direction offsets · rooms[][] = distances written in place

Pseudocode:

```

enqueue all gate cells (value 0)
BFS: pop cell, for each empty (still MAX) neighbor set it to current+1 and enqueue
distances fill outward, each room getting its nearest gate's distance

```

```

class Solution {
    public void wallsAndGates(int[][] rooms) {
        if (rooms.length == 0) return;
        int m = rooms.length, n = rooms[0].length;
        Queue<int[]> queue = new ArrayDeque<>();
        for (int i = 0; i < m; i++)
            for (int j = 0; j < n; j++)
                if (rooms[i][j] == 0) queue.offer(new int[]{i, j}); // ← VARIATION: seed ALL gates
        int[] dr = {1, -1, 0, 0}, dc = {0, 0, 1, -1};
        while (!queue.isEmpty()) {
            int[] cell = queue.poll();
            for (int dir = 0; dir < 4; dir++) {
                int ni = cell[0] + dr[dir], nj = cell[1] + dc[dir];
                if (ni < 0 || ni >= m || nj < 0 || nj >= n || rooms[ni][nj] != Integer.MAX_VALUE) continue;
                rooms[ni][nj] = rooms[cell[0]][cell[1]] + 1;
                queue.offer(new int[]{ni, nj});
            }
        }
    }
}

```

Time $O(m \cdot n)$ | **Space** $O(m \cdot n)$

#721 Accounts Merge

Description: Each account has a name and a list of emails. Merge accounts that share any email. Return merged accounts with emails sorted. **Variation:** Union Find over emails. Assign each unique email an integer id, union all emails within the same account, then group emails by their root.

Variables: `emailToId` = email $\rightarrow$ integer id · `emailToName` = email $\rightarrow$ owner · `parent[]` = union-find over email ids · `groups` = root id $\rightarrow$ its emails **Pseudocode:**

```
assign each unique email an id; record its owner name
init union-find; within each account union first email's id with every other email's id
group all emails by their root id
per group: sort emails, prepend the owner name, add to result
```

```
class Solution {
    private int[] parent;
    public List<List<String>> accountsMerge(List<List<String>> accounts) {
        Map<String, Integer> emailToId = new HashMap<>();
        Map<String, String> emailToName = new HashMap<>();
        int id = 0;
        for (List<String> account : accounts)
            for (int i = 1; i < account.size(); i++) {
                String email = account.get(i);
                if (!emailToId.containsKey(email)) emailToId.put(email, id++);
                emailToName.put(email, account.get(0));
            }
        parent = new int[id];
        for (int i = 0; i < id; i++) parent[i] = i;
        for (List<String> account : accounts)
            for (int i = 2; i < account.size(); i++)
                union(emailToId.get(account.get(1)), emailToId.get(account.get(i))); // ← VARIATION: u
        Map<Integer, List<String>> groups = new HashMap<>();
        for (String email : emailToId.keySet())
            groups.computeIfAbsent(find(emailToId.get(email)), x -> new ArrayList<>()).add(email);
        List<List<String>> result = new ArrayList<>();
        for (List<String> emails : groups.values()) {
            Collections.sort(emails);
            List<String> merged = new ArrayList<>();
            merged.add(emailToName.get(emails.get(0)));
            merged.addAll(emails);
            result.add(merged);
        }
        return result;
    }
    private int find(int x) { return parent[x] == x ? x : (parent[x] = find(parent[x])); }
    private void union(int x, int y) { parent[find(x)] = find(y); }
}
```

Time $O(n \cdot \alpha)$ with sorting $O(n \log n)$ | **Space** $O(n)$

#827 Making A Large Island

Description: In a binary grid you may change at most one 0 to 1. Return the size of the largest island possible. **Variation:** two passes. First DFS-color each island with a unique id (starting at 2) and record its size. Then for every 0, sum the sizes of distinct neighboring islands + 1.

Variables: `id` = next island label (starts 2) · `size` = island id → cell count · `seen` = distinct island ids around a 0-cell · `total` = candidate island size if this 0 flips **Pseudocode:**

pass 1: DFS each '1' island, paint it a unique id, record its size
pass 2: for each '0', look at 4 neighbors, sum sizes of distinct neighboring islands + 1
track the running max over island sizes and all flip candidates

```
class Solution {
    private int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
    public int largestIsland(int[][] grid) {
        int n = grid.length, id = 2;
        Map<Integer, Integer> size = new HashMap<>();
        for (int i = 0; i < n; i++)
            for (int j = 0; j < n; j++)
                if (grid[i][j] == 1) size.put(id, dfs(grid, i, j, id++)); // ← VARIATION: color + reco
        int max = size.values().stream().mapToInt(x -> x).max().orElse(0);
        for (int i = 0; i < n; i++)
            for (int j = 0; j < n; j++)
                if (grid[i][j] == 0) {
                    Set<Integer> seen = new HashSet<>();
                    int total = 1;
                    for (int dir = 0; dir < 4; dir++) {
                        int ni = i + dr[dir], nj = j + dc[dir];
                        if (ni < 0 || ni >= n || nj < 0 || nj >= n || grid[ni][nj] <= 1) continue;
                        if (seen.add(grid[ni][nj])) total += size.get(grid[ni][nj]); // ← VARIATION: s
                    }
                    max = Math.max(max, total);
                }
        return max;
    }
    private int dfs(int[][] grid, int i, int j, int id) {
        if (i < 0 || i >= grid.length || j < 0 || j >= grid.length || grid[i][j] != 1) return 0;
        grid[i][j] = id;
        int count = 1;
        for (int dir = 0; dir < 4; dir++) count += dfs(grid, i + dr[dir], j + dc[dir], id);
        return count;
    }
}
```

Time $O(m \cdot n)$ | **Space** $O(m \cdot n)$

#909 Snakes and Ladders

Description: On an $n \times n$ board numbered in boustrophedon (zigzag) order, find the minimum dice moves (1-6) from square 1 to square n^2 . Ladders/snakes teleport you. **Variation:** BFS over square numbers. Convert a square number to (row, col) accounting for the zigzag layout.

Variables: `visited[]` = squares already reached · `queue` = BFS frontier of square numbers · `moves` = dice rolls so far · `rc` = zigzag coordinate of a square **Pseudocode:**

BFS from square 1; each level = one dice move
for each square, try rolls 1..6 → candidate square
convert to (row,col) via zigzag; if snake/ladder, jump to its destination
if destination is n^2 , return moves; enqueue if unvisited

```

class Solution {
    public int snakesAndLadders(int[][] board) {
        int n = board.length;
        boolean[] visited = new boolean[n * n + 1];
        Queue<Integer> queue = new ArrayDeque<>();
        queue.offer(1);
        visited[1] = true;
        int moves = 0;
        while (!queue.isEmpty()) {
            int size = queue.size();
            for (int s = 0; s < size; s++) {
                int current = queue.poll();
                if (current == n * n) return moves;
                for (int k = 1; k <= 6 && current + k <= n * n; k++) {
                    int next = current + k;
                    int[] rc = toCoord(next, n); // ← VARIATION: number → zigzag coordinate
                    if (board[rc[0]][rc[1]] != -1) next = board[rc[0]][rc[1]]; // snake/ladder
                    if (!visited[next]) { visited[next] = true; queue.offer(next); }
                }
            }
            moves++;
        }
        return -1;
    }

    private int[] toCoord(int num, int n) {
        int row = (num - 1) / n, col = (num - 1) % n;
        if (row % 2 == 1) col = n - 1 - col; // ← VARIATION: reverse on odd rows
        return new int[]{n - 1 - row, col};
    }
}

```

Time $O(n^2)$ | **Space** $O(n^2)$

#1091 Shortest Path in Binary Matrix

Description: In an $n \times n$ binary grid, find the length of the shortest clear path (cells of 0) from top-left to bottom-right, moving in 8 directions. **Variation:** standard BFS but with 8-directional movement (includes diagonals).

Variables: `dr / dc` = 8-direction offsets (incl. diagonals) · `queue` = BFS frontier · `path` = cells on current shortest path

Pseudocode:

```

if start or end blocked, return -1
BFS from (0,0), path length starts at 1, marking visited by setting grid to 1
each level: pop cell, if it's bottom-right return path; push all clear 8-neighbors
increment path per level; return -1 if unreachable

```

```

class Solution {
    public int shortestPathBinaryMatrix(int[][] grid) {
        int n = grid.length;
        if (grid[0][0] == 1 || grid[n-1][n-1] == 1) return -1;
        int[] dr = {1,-1,0,0,1,1,-1,-1}, dc = {0,0,1,-1,1,-1,1,-1}; // ← VARIATION: 8 directions
        Queue<int[]> queue = new ArrayDeque<>();
        queue.offer(new int[]{0, 0});
        grid[0][0] = 1;
        int path = 1;
        while (!queue.isEmpty()) {
            int size = queue.size();
            for (int s = 0; s < size; s++) {
                int[] cell = queue.poll();
                if (cell[0] == n-1 && cell[1] == n-1) return path;
                for (int dir = 0; dir < 8; dir++) {
                    int ni = cell[0] + dr[dir], nj = cell[1] + dc[dir];
                    if (ni < 0 || ni >= n || nj < 0 || nj >= n || grid[ni][nj] != 0) continue;
                    grid[ni][nj] = 1;
                    queue.offer(new int[]{ni, nj});
                }
            }
            path++;
        }
        return -1;
    }
}

```

Time $O(m \cdot n)$ | **Space** $O(m \cdot n)$

Additional Reference Problems

#126 Word Ladder II

Description: Find all shortest transformation sequences from `beginWord` to `endWord`, changing one letter at a time, each intermediate word in `wordList`.

Intuition: BFS level-by-level builds a parent (predecessor) map of which words lead to which; once `endWord` is reached, DFS backtracks through parents to reconstruct every shortest path.

Algorithm: BFS recording all predecessors per word; stop expanding once `endWord` found at a level; then DFS from `endWord` back to `beginWord`.

Variables: `wordSet` = usable words · `parents` = word → predecessor words on shortest paths · `level / next` = current and next BFS frontier sets · `found` = `endWord` reached · `path` = path being reconstructed **Pseudocode:**

```

BFS level by level: remove this level's words from set, mutate each word position×26
    for each in-set candidate, record it as child with parent edge; if endWord, mark found
once found, DFS backtrack from endWord through parents to beginWord, collecting every path

```

```

class Solution {
    public List<List<String>> findLadders(String beginWord, String endWord, List<String> wordList) {
        List<List<String>> result = new ArrayList<>();
        Set<String> wordSet = new HashSet<>(wordList);
        if (!wordSet.contains(endWord)) return result;
        Map<String, List<String>> parents = new HashMap<>();
        Set<String> level = new HashSet<>();
        level.add(beginWord);
        boolean found = false;
        while (!level.isEmpty() && !found) {
            Set<String> next = new HashSet<>();
            wordSet.removeAll(level);
            for (String word : level) {
                char[] chars = word.toCharArray();
                for (int j = 0; j < chars.length; j++) {
                    char original = chars[j];
                    for (char c = 'a'; c <= 'z'; c++) {
                        chars[j] = c;
                        String candidate = new String(chars);
                        if (wordSet.contains(candidate)) {
                            if (candidate.equals(endWord)) found = true;
                            next.add(candidate);
                            parents.computeIfAbsent(candidate, x -> new ArrayList<>()).add(word);
                        }
                    }
                    chars[j] = original;
                }
            }
            level = next;
        }
        if (found) {
            LinkedList<String> path = new LinkedList<>();
            path.add(endWord);
            backtrack(endWord, beginWord, parents, path, result);
        }
        return result;
    }

    private void backtrack(String word, String beginWord, Map<String, List<String>> parents,
                           LinkedList<String> path, List<List<String>> result) {
        if (word.equals(beginWord)) {
            result.add(new ArrayList<>(path));
            return;
        }
        if (!parents.containsKey(word)) return;
        for (String parent : parents.get(word)) {
            path.addFirst(parent);
            backtrack(parent, beginWord, parents, path, result);
            path.removeFirst();
        }
    }
}

```

Time $O(N \cdot L \cdot 26)$ BFS + paths | **Space** $O(N \cdot L)$

#133 Clone Graph

Description: Deep-copy an undirected graph where each node has a value and a list of neighbors.

Intuition: Use a map from original node to its clone to avoid re-cloning and to wire neighbors correctly; BFS the graph, creating clones on first sight.

Algorithm: BFS with a `Map<Node, Node>` of original→clone; for each node, attach cloned neighbors.

Variables: clones = original node → its clone (doubles as visited) · queue = BFS frontier of originals **Pseudocode:**

```
if null return null; create clone of start, map it, enqueue start
BFS: pop original; for each neighbor
    if not yet cloned, create its clone, map it, enqueue
    wire current's clone to neighbor's clone
return clone of start
```

```
/*
// Definition for a Node.
class Node {
    public int val;
    public List<Node> neighbors;
    public Node() { val = 0; neighbors = new ArrayList<Node>(); }
    public Node(int _val) { val = _val; neighbors = new ArrayList<Node>(); }
    public Node(int _val, ArrayList<Node> _neighbors) { val = _val; neighbors = _neighbors; }
}
*/
class Solution {
    public Node cloneGraph(Node node) {
        if (node == null) return null;
        Map<Node, Node> clones = new HashMap<>();
        Queue<Node> queue = new ArrayDeque<>();
        queue.offer(node);
        clones.put(node, new Node(node.val));
        while (!queue.isEmpty()) {
            Node current = queue.poll();
            for (Node neighbor : current.neighbors) {
                if (!clones.containsKey(neighbor)) {
                    clones.put(neighbor, new Node(neighbor.val));
                    queue.offer(neighbor);
                }
                clones.get(current).neighbors.add(clones.get(neighbor));
            }
        }
        return clones.get(node);
    }
}
```

Time $O(V+E)$ | **Space** $O(V)$

#277 Find the Celebrity

Description: Among n people, find the celebrity: known by everyone, knows nobody. `knows(a, b)` is the API.

Intuition: A single linear scan narrows to one candidate (if `candidate` knows `i`, the candidate can't be the celebrity, so `i` becomes the new candidate); a second pass verifies.

Algorithm: Two passes — find candidate, then validate both directions.

Variables: `candidate` = current celebrity guess · `i` = person being compared **Pseudocode:**

```
pass 1: candidate=0; for each i, if candidate knows i then candidate=i (old one disqualified)
pass 2: verify candidate — must know nobody and be known by everyone; else return -1
return candidate
```

```

/* The knows API is defined in the parent class Relation.
   boolean knows(int a, int b); */
public class Solution extends Relation {
    public int findCelebrity(int n) {
        int candidate = 0;
        for (int i = 1; i < n; i++) {
            if (knows(candidate, i)) {
                candidate = i;
            }
        }
        for (int i = 0; i < n; i++) {
            if (i == candidate) continue;
            if (knows(candidate, i) || !knows(i, candidate)) return -1;
        }
        return candidate;
    }
}

```

Time $O(n)$ | **Space** $O(1)$

#296 Best Meeting Point

Description: Given a grid where `1` marks a home, find the minimum total Manhattan distance to a single meeting point.

Intuition: Manhattan distance separates into independent x and y components; the optimal coordinate on each axis is the median of the occupied coordinates.

Algorithm: Collect row and column indices (rows in sorted order, columns sorted), take the median on each axis, sum absolute distances.

Variables: `rowList` / `colList` = occupied row/col coordinates · `medianRow` / `medianCol` = median on each axis · `total` = summed Manhattan distance
Pseudocode:

```

collect home rows (outer loop → already sorted) and home cols
sort colList; pick median of each list (minimizes sum of |coord - p|)
sum |row - medianRow| over rows plus |col - medianCol| over cols

```

```

class Solution {
    public int minTotalDistance(int[][] grid) {
        int rows = grid.length, cols = grid[0].length;
        List<Integer> rowList = new ArrayList<>();
        List<Integer> colList = new ArrayList<>();
        for (int i = 0; i < rows; i++) // outer loop on i → rowList already sorted
            for (int j = 0; j < cols; j++)
                if (grid[i][j] == 1) { rowList.add(i); colList.add(j); }
        Collections.sort(colList); // colList built per-row, so sort it
        int total = 0;
        int medianRow = rowList.get(rowList.size() / 2); // median minimizes sum of |x - p|
        int medianCol = colList.get(colList.size() / 2);
        for (int r : rowList) {
            total += Math.abs(r - medianRow);
        }
        for (int c : colList) {
            total += Math.abs(c - medianCol);
        }
        return total;
    }
}

```

Time $O(m \cdot n)$ | **Space** $O(m \cdot n)$

#305 Number of Islands II

Description: Land cells are added one at a time to a water grid; after each addition return the current number of islands.

Variation: Online Union-Find — when a cell becomes land, union it with any already-land 4-neighbors; track component count.

Variables: `parent[]` = union-find (-1 = still water) · `rank[]` = balancing · `count` = current island count · `id / nid` = flattened cell indices · `result` = count after each addition **Pseudocode:**

```
parent all -1 (water); count=0
for each added position: if already land, record count and continue
    make it its own set, count++
    for each land 4-neighbor: if union merges, count--
append count to result
```

```
class Solution {
    int[] parent, rank;
    public List<Integer> numIslands2(int m, int n, int[][] positions) {
        parent = new int[m * n];
        rank = new int[m * n];
        Arrays.fill(parent, -1); // ← VARIATION: -1 marks water (not yet l
        int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
        List<Integer> result = new ArrayList<>();
        int count = 0;
        for (int[] p : positions) {
            int i = p[0], j = p[1], id = i * n + j;
            if (parent[id] != -1) { // already land
                result.add(count);
                continue;
            }
            parent[id] = id;
            count++;
            for (int dir = 0; dir < 4; dir++) {
                int ni = i + dr[dir], nj = j + dc[dir];
                if (ni < 0 || ni >= m || nj < 0 || nj >= n) continue;
                int nid = ni * n + nj;
                if (parent[nid] != -1 && union(id, nid)) count--;
            }
            result.add(count);
        }
        return result;
    }
    int find(int x) { return parent[x] == x ? x : (parent[x] = find(parent[x])); }
    boolean union(int x, int y) {
        int px = find(x), py = find(y);
        if (px == py) return false;
        if (rank[px] < rank[py]) { int t = px; px = py; py = t; }
        parent[py] = px;
        if (rank[px] == rank[py]) rank[px]++;
        return true;
    }
}
```

Time $O(k \cdot \alpha(m \cdot n))$ | **Space** $O(m \cdot n)$

#317 Shortest Distance from All Buildings

Description: Find the empty land cell 0 minimizing total walking distance to every building 1 (2 = obstacle).

Intuition: BFS from each building, accumulating distances into every reachable empty cell and counting how many buildings reach it; the answer is the minimum total among cells reachable by all buildings.

Algorithm: Multi-pass BFS — one BFS per building; track `total[][]` distance sum and `reach[][]` count.

Variables: `total[][]` = summed distance from all buildings to each empty cell · `reach[][]` = how many buildings reach a cell · `buildings` = building count · `queue / visited` = per-building BFS **Pseudocode:**

```
for each building: BFS level by level over empty cells
    add the level distance into total[cell], increment reach[cell]
after all buildings: among empty cells reachable by every building, return the smallest total
return -1 if none reachable by all
```

```
class Solution {
    public int shortestDistance(int[][] grid) {
        int rows = grid.length, cols = grid[0].length;
        int[][] total = new int[rows][cols];
        int[][] reach = new int[rows][cols];
        int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
        int buildings = 0;
        for (int i = 0; i < rows; i++) {
            for (int j = 0; j < cols; j++) {
                if (grid[i][j] != 1) continue;
                buildings++;
                Queue<int[]> queue = new ArrayDeque<>();
                queue.offer(new int[]{i, j});
                boolean[][] visited = new boolean[rows][cols];
                visited[i][j] = true;
                int dist = 0;
                while (!queue.isEmpty()) {
                    int size = queue.size();
                    dist++;
                    for (int s = 0; s < size; s++) {
                        int[] current = queue.poll();
                        for (int dir = 0; dir < 4; dir++) {
                            int ni = current[0] + dr[dir], nj = current[1] + dc[dir];
                            if (ni < 0 || ni >= rows || nj < 0 || nj >= cols) continue;
                            if (visited[ni][nj] || grid[ni][nj] != 0) continue;
                            visited[ni][nj] = true;
                            total[ni][nj] += dist;
                            reach[ni][nj]++;
                            queue.offer(new int[]{ni, nj});
                        }
                    }
                }
            }
        }
        int result = Integer.MAX_VALUE;
        for (int i = 0; i < rows; i++) {
            for (int j = 0; j < cols; j++) {
                if (grid[i][j] == 0 && reach[i][j] == buildings) {
                    result = Math.min(result, total[i][j]);
                }
            }
        }
        return result == Integer.MAX_VALUE ? -1 : result;
    }
}
```

Time $O(B \cdot m \cdot n)$ where B = buildings | **Space** $O(m \cdot n)$

#399 Evaluate Division

Description: Given equations $a/b = \text{value}$, answer queries c/d . Return -1.0 if undeterminable.

Intuition: Treat variables as nodes and ratios as weighted directed edges; the answer to a query is the product of edge weights along any path from numerator to denominator.

Algorithm: Build weighted graph, then DFS each query multiplying weights along the path.

Variables: `graph` = variable $\rightarrow$ (neighbor $\rightarrow$ ratio) · `visited` = DFS guard · `product` = accumulated ratio along path · `result[]` = answers per query **Pseudocode:**

```
build graph: a→b = value, b→a = 1/value
for each query (src,dst): if either var unknown, answer -1
    else DFS from src multiplying edge ratios; on reaching dst return product
DFS returns -1 if no path
```

```
class Solution {
    public double[] calcEquation(List<List<String>> equations, double[] values, List<List<String>> queries) {
        Map<String, Map<String, Double>> graph = new HashMap<>();
        for (int i = 0; i < equations.size(); i++) {
            String a = equations.get(i).get(0), b = equations.get(i).get(1);
            graph.computeIfAbsent(a, x -> new HashMap<>()).put(b, values[i]);
            graph.computeIfAbsent(b, x -> new HashMap<>()).put(a, 1.0 / values[i]);
        }
        double[] result = new double[queries.size()];
        for (int i = 0; i < queries.size(); i++) {
            String src = queries.get(i).get(0), dst = queries.get(i).get(1);
            if (!graph.containsKey(src) || !graph.containsKey(dst)) {
                result[i] = -1.0;
            } else {
                result[i] = dfs(graph, src, dst, 1.0, new HashSet<>());
            }
        }
        return result;
    }
    private double dfs(Map<String, Map<String, Double>> graph, String node, String target,
        double product, Set<String> visited) {
        if (node.equals(target)) return product;
        visited.add(node);
        for (Map.Entry<String, Double> nb : graph.get(node).entrySet()) {
            if (visited.contains(nb.getKey())) continue;
            double sub = dfs(graph, nb.getKey(), target, product * nb.getValue(), visited);
            if (sub != -1.0) return sub;
        }
        return -1.0;
    }
}
```

Time $O(Q \cdot (V+E))$ | **Space** $O(V+E)$

#407 Trapping Rain Water II

Description: Given a 2D height map, compute how much water it can trap after raining.

Variation: Dijkstra-style BFS from the border inward using a min-heap of boundary heights; water level at a cell is the highest of the minimum boundary it must pass — pop the lowest wall first.

Variables: `pq` = min-heap of boundary cells `{r,c,height}` · `visited[][]` = settled cells · `level` = current lowest wall
`height` · `water` = trapped total **Pseudocode:**

```
push all border cells (their own heights), mark visited
pop the lowest wall; its height is current water level
for each unvisited neighbor: if lower than level, trap (level - height) water
    push neighbor with max(level, its height) as its effective wall, mark visited
```

```
class Solution {
    public int trapRainWater(int[][] heightMap) {
        int rows = heightMap.length, cols = heightMap[0].length;
        if (rows < 3 || cols < 3) return 0;
        boolean[][] visited = new boolean[rows][cols];
        PriorityQueue<int[]> pq = new PriorityQueue<>((a, b) -> a[2] - b[2]); // ← VARIATION: heap on c
        for (int i = 0; i < rows; i++) {
            for (int j = 0; j < cols; j++) {
                if (i == 0 || i == rows - 1 || j == 0 || j == cols - 1) {
                    pq.offer(new int[]{i, j, heightMap[i][j]});
                    visited[i][j] = true;
                }
            }
        }
        int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
        int water = 0;
        while (!pq.isEmpty()) {
            int[] current = pq.poll();
            int level = current[2];
            for (int dir = 0; dir < 4; dir++) {
                int ni = current[0] + dr[dir], nj = current[1] + dc[dir];
                if (ni < 0 || ni >= rows || nj < 0 || nj >= cols || visited[ni][nj]) continue;
                visited[ni][nj] = true;
                if (heightMap[ni][nj] < level) water += level - heightMap[ni][nj];
                pq.offer(new int[]{ni, nj, Math.max(level, heightMap[ni][nj])});
            }
        }
        return water;
    }
}
```

Time $O(m \cdot n \cdot \log(m \cdot n))$ | **Space** $O(m \cdot n)$

#463 Island Perimeter

Description: Given a grid with exactly one island, return its perimeter.

Intuition: Each land cell contributes 4 sides, minus 2 for every shared edge with an adjacent land cell (counted once per pair).

Algorithm: Count land cells $\times 4$, subtract 2 for each adjacent land pair.

Variables: `perimeter` = running perimeter total **Pseudocode:**

```
for each land cell: add 4
    if its top neighbor is land, subtract 2 (shared edge, counts once per pair)
    if its left neighbor is land, subtract 2
return perimeter
```

```

class Solution {
    public int islandPerimeter(int[][] grid) {
        int rows = grid.length, cols = grid[0].length;
        int perimeter = 0;
        for (int i = 0; i < rows; i++) {
            for (int j = 0; j < cols; j++) {
                if (grid[i][j] == 1) {
                    perimeter += 4;
                    if (i > 0 && grid[i-1][j] == 1) perimeter -= 2;
                    if (j > 0 && grid[i][j-1] == 1) perimeter -= 2;
                }
            }
        }
        return perimeter;
    }
}

```

Time $O(m \cdot n)$ | **Space** $O(1)$

#529 Minesweeper

Description: Reveal a cell on a Minesweeper board. 'M' mine, 'E' unrevealed empty, 'B' revealed blank, digit = adjacent mine count.

Variation: BFS/DFS flood fill with 8 directions; if the clicked cell is a mine, mark 'X'; otherwise count adjacent mines, and only recurse when count is 0.

Variables: `cr / cc` = clicked cell · `dr / dc` = 8-direction offsets · `queue / visited` = flood fill · `mines` = adjacent mine count **Pseudocode:**

```

if clicked cell is a mine, mark 'X' and stop
BFS from click: for each cell count adjacent mines
    if mines > 0, label it with the digit (stop spreading)
    else mark 'B' and enqueue all unrevealed empty 8-neighbors

```

```

class Solution {
    public char[][] updateBoard(char[][] board, int[] click) {
        int rows = board.length, cols = board[0].length;
        int cr = click[0], cc = click[1];
        if (board[cr][cc] == 'M') {
            board[cr][cc] = 'X';
            return board;
        }
        int[] dr = {1,-1,0,0,1,1,-1,-1}, dc = {0,0,1,-1,1,-1,1,-1}; // ← VARIATION: 8 directions
        Queue<int[]> queue = new ArrayDeque<>();
        queue.offer(new int[]{cr, cc});
        boolean[][] visited = new boolean[rows][cols];
        visited[cr][cc] = true;
        while (!queue.isEmpty()) {
            int[] current = queue.poll();
            int r = current[0], c = current[1];
            int mines = 0;
            for (int dir = 0; dir < 8; dir++) {
                int nr = r + dr[dir], nc = c + dc[dir];
                if (nr >= 0 && nr < rows && nc >= 0 && nc < cols && board[nr][nc] == 'M') mines++;
            }
            if (mines > 0) {
                board[r][c] = (char) ('0' + mines);
            } else {
                board[r][c] = 'B';
                for (int dir = 0; dir < 8; dir++) {
                    int nr = r + dr[dir], nc = c + dc[dir];
                    if (nr < 0 || nr >= rows || nc < 0 || nc >= cols) continue;
                    if (!visited[nr][nc] && board[nr][nc] == 'E') {
                        visited[nr][nc] = true;
                        queue.offer(new int[]{nr, nc});
                    }
                }
            }
        }
        return board;
    }
}

```

Time $O(m \cdot n)$ | **Space** $O(m \cdot n)$

#694 Number of Distinct Islands

Description: Count islands that are distinct by shape (translations are the same, rotations are not).

Variation: DFS recording the path signature (the direction taken at each step plus a backtrack marker); two islands with identical signatures have the same shape.

Variables: `shapes` = set of distinct path signatures · `builder` = signature being built · `dir` = direction char entering a cell
Pseudocode:

```

for each unvisited land cell: DFS the island, sinking cells and appending the move direction
    append a backtrack marker 'b' after exploring (disambiguates otherwise-equal shapes)
add the signature string to a set
return number of distinct signatures

```

```

class Solution {
    public int numDistinctIslands(int[][] grid) {
        int rows = grid.length, cols = grid[0].length;
        Set<String> shapes = new HashSet<>();
        for (int i = 0; i < rows; i++) {
            for (int j = 0; j < cols; j++) {
                if (grid[i][j] == 1) {
                    StringBuilder builder = new StringBuilder();
                    dfs(grid, i, j, 'o', builder);           // ← VARIATION: record traversal path
                    shapes.add(builder.toString());
                }
            }
        }
        return shapes.size();
    }
    private void dfs(int[][] grid, int i, int j, char dir, StringBuilder builder) {
        if (i < 0 || i >= grid.length || j < 0 || j >= grid[0].length || grid[i][j] != 1) return;
        grid[i][j] = 0;
        builder.append(dir);
        dfs(grid, i + 1, j, 'd', builder);
        dfs(grid, i - 1, j, 'u', builder);
        dfs(grid, i, j + 1, 'r', builder);
        dfs(grid, i, j - 1, 'l', builder);
        builder.append('b');                               // ← VARIATION: backtrack marker disamb
    }
}

```

Time $O(m \cdot n)$ | **Space** $O(m \cdot n)$

#733 Flood Fill

Description: Starting at `(sr, sc)`, change all connected same-color pixels to `color`.

Algorithm: BFS/DFS flood fill from the start cell over 4 directions; guard against re-filling when the new color equals the original.

Variables: `original` = start cell's old color · `queue` = BFS frontier · `dr / dc` = 4-direction offsets **Pseudocode:**

```

record start color; if it already equals target, return unchanged (avoid infinite loop)
recolor start, enqueue it
BFS: pop cell, for each neighbor matching original color, recolor and enqueue

```

```

class Solution {
    public int[][] floodFill(int[][] image, int sr, int sc, int color) {
        int original = image[sr][sc];
        if (original == color) return image;
        int rows = image.length, cols = image[0].length;
        int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
        Queue<int[]> queue = new ArrayDeque<>();
        queue.offer(new int[]{sr, sc});
        image[sr][sc] = color;
        while (!queue.isEmpty()) {
            int[] current = queue.poll();
            for (int dir = 0; dir < 4; dir++) {
                int ni = current[0] + dr[dir], nj = current[1] + dc[dir];
                if (ni < 0 || ni >= rows || nj < 0 || nj >= cols) continue;
                if (image[ni][nj] == original) {
                    image[ni][nj] = color;
                    queue.offer(new int[]{ni, nj});
                }
            }
        }
        return image;
    }
}

```

Time $O(m \cdot n)$ | **Space** $O(m \cdot n)$

#752 Open the Lock

Description: A 4-wheel lock starts at "0000"; each move turns one wheel ± 1 . Find minimum moves to reach target, avoiding deadends.

Variation: BFS over the 4-digit state space; each state has 8 neighbors (each wheel up or down). Treat deadends as visited.

Variables: dead = deadend states (blocked) · visited = reached states · queue = BFS frontier of lock states · turns = moves so far

Pseudocode:

```

if "0000" is a deadend, return -1; if target is "0000", return 0
BFS from "0000": each level = one turn
for each state, for each of 4 wheels turn  $\pm 1 \rightarrow 8$  neighbors
    if neighbor == target return turns; else if not dead and unvisited, enqueue
return -1 if exhausted

```

```

class Solution {
    public int openLock(String[] deadends, String target) {
        Set<String> dead = new HashSet<>(Arrays.asList(deadends));
        if (dead.contains("0000")) return -1;
        if (target.equals("0000")) return 0;
        Set<String> visited = new HashSet<>();
        visited.add("0000");
        Queue<String> queue = new ArrayDeque<>();
        queue.offer("0000");
        int turns = 0;
        while (!queue.isEmpty()) {
            int size = queue.size();
            turns++;
            for (int s = 0; s < size; s++) {
                String current = queue.poll();
                for (int j = 0; j < 4; j++) {
                    char c = current.charAt(j);
                    for (int delta = -1; delta <= 1; delta += 2) {
                        char nc = (char) ('0' + (c - '0' + delta + 10) % 10);
                        String next = current.substring(0, j) + nc + current.substring(j + 1);
                        if (next.equals(target)) return turns;
                        if (!dead.contains(next) && visited.add(next)) queue.offer(next);
                    }
                }
            }
        }
        return -1;
    }
}

```

Time $O(10^4 \cdot 8)$ | **Space** $O(10^4)$

#778 Swim in Rising Water

Description: At time t you can stand on any cell with elevation $\leq t$. Find the least time to swim from $(0,0)$ to $(n-1, n-1)$.

Variation: Modified Dijkstra — minimize the maximum elevation along the path (not the sum). Min-heap ordered by current max elevation.

Variables: pq = min-heap on max-elevation-so-far $\{maxElev, r, c\}$ · $visited[][]$ = settled cells · $time$ = current path's max elevation **Pseudocode:**

```

push (grid[0][0], 0, 0), mark visited
pop cell with smallest max-elevation; if it's destination return that elevation
for each unvisited neighbor: push max(current, neighbor height) ← max, not sum
mark visited on push (Dijkstra settle)

```

```

class Solution {
    public int swimInWater(int[][] grid) {
        int n = grid.length;
        boolean[][] visited = new boolean[n][n];
        PriorityQueue<int[]> pq = new PriorityQueue<>((a, b) -> a[0] - b[0]); // [maxElev, r, c]
        pq.offer(new int[]{grid[0][0], 0, 0});
        visited[0][0] = true;
        int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
        while (!pq.isEmpty()) {
            int[] current = pq.poll();
            int time = current[0], r = current[1], c = current[2];
            if (r == n - 1 && c == n - 1) return time;
            for (int dir = 0; dir < 4; dir++) {
                int nr = r + dr[dir], nc = c + dc[dir];
                if (nr < 0 || nr >= n || nc < 0 || nc >= n || visited[nr][nc]) continue;
                visited[nr][nc] = true;
                pq.offer(new int[]{Math.max(time, grid[nr][nc]), nr, nc}); // ← VARIATION: max not sum
            }
        }
        return -1;
    }
}

```

Time $O(n^2 \cdot \log(n))$ | **Space** $O(n^2)$

#797 All Paths From Source to Target

Description: In a DAG given as adjacency list `graph`, return all paths from node `0` to node `n-1`.

Intuition: Since it is a DAG with no cycles, plain DFS backtracking enumerates every path; no visited set is needed.

Algorithm: DFS from `0`, appending nodes to a path, recording the path when reaching `n-1`.

Variables: `result` = all source-to-target paths · `path` = current path being extended **Pseudocode:**

```

start DFS at node 0 with path=[0]
if node == n-1, snapshot path into result
else for each neighbor: append, recurse, backtrack (remove last)
no visited set needed – it's a DAG

```

```

class Solution {
    public List<List<Integer>> allPathsSourceTarget(int[][] graph) {
        List<List<Integer>> result = new ArrayList<>();
        List<Integer> path = new ArrayList<>();
        path.add(0);
        dfs(graph, 0, path, result);
        return result;
    }
    private void dfs(int[][] graph, int node, List<Integer> path, List<List<Integer>> result) {
        if (node == graph.length - 1) {
            result.add(new ArrayList<>(path));
            return;
        }
        for (int neighbor : graph[node]) {
            path.add(neighbor);
            dfs(graph, neighbor, path, result);
            path.remove(path.size() - 1);
        }
    }
}

```

Time $O(2^V \cdot V)$ | **Space** $O(V)$

#802 Find Eventual Safe States

Description: A node is safe if every path from it eventually reaches a terminal node (no outgoing edges). Return all safe nodes sorted.

Variation: Topological sort on the reversed graph (Kahn's) — start from terminal nodes (out-degree 0); a node becomes safe once all its outgoing edges lead to safe nodes.

Variables: `reverse` = reversed adjacency · `outDegree[]` = remaining outgoing edges per node · `queue` = newly-safe nodes · `safe[]` = node safety flags **Pseudocode:**

```
build reversed graph; outDegree[i] = original out-degree
enqueue all terminal nodes (outDegree 0)
pop node, mark safe; for each predecessor, decrement its outDegree; enqueue when it hits 0
return sorted list of safe nodes
```

```
class Solution {
    public List<Integer> eventualSafeNodes(int[][] graph) {
        int n = graph.length;
        List<List<Integer>> reverse = new ArrayList<>();
        for (int i = 0; i < n; i++) reverse.add(new ArrayList<>());
        int[] outDegree = new int[n]; // ← VARIATION: track outgoing count
        for (int i = 0; i < n; i++) {
            outDegree[i] = graph[i].length;
            for (int neighbor : graph[i]) reverse.get(neighbor).add(i);
        }
        Queue<Integer> queue = new ArrayDeque<>();
        for (int i = 0; i < n; i++) if (outDegree[i] == 0) queue.offer(i);
        boolean[] safe = new boolean[n];
        while (!queue.isEmpty()) {
            int node = queue.poll();
            safe[node] = true;
            for (int prev : reverse.get(node)) {
                if (--outDegree[prev] == 0) queue.offer(prev);
            }
        }
        List<Integer> result = new ArrayList<>();
        for (int i = 0; i < n; i++) if (safe[i]) result.add(i);
        return result;
    }
}
```

Time $O(V+E)$ | **Space** $O(V+E)$

#815 Bus Routes

Description: `routes[i]` is the stops served by bus `i`. Find the minimum number of buses to travel from `source` to `target`.

Variation: BFS where the "nodes" are buses (routes); build stop→routes index, then BFS route-to-route through shared stops, counting buses taken.

Variables: `stopToRoutes` = stop → routes serving it · `queue` = stops to explore · `visitedStops` / `visitedRoutes[]` = dedup · `buses` = routes boarded so far **Pseudocode:**

```

if source==target return 0; index each stop to the routes serving it
BFS from source stop; each level = boarding one more bus
for each stop, for each unvisited route serving it: mark route used
    scan that route's stops; if target found return buses; enqueue new stops
return -1 if unreachable

```

```

class Solution {
    public int numBusesToDestination(int[][] routes, int source, int target) {
        if (source == target) return 0;
        Map<Integer, List<Integer>> stopToRoutes = new HashMap<>();
        for (int i = 0; i < routes.length; i++) {
            for (int stop : routes[i]) {
                stopToRoutes.computeIfAbsent(stop, x -> new ArrayList<>()).add(i);
            }
        }
        Queue<Integer> queue = new ArrayDeque<>();           // ← VARIATION: queue holds stops
        Set<Integer> visitedStops = new HashSet<>();
        boolean[] visitedRoutes = new boolean[routes.length];
        queue.offer(source);
        visitedStops.add(source);
        int buses = 0;
        while (!queue.isEmpty()) {
            int size = queue.size();
            buses++;
            for (int s = 0; s < size; s++) {
                int stop = queue.poll();
                for (int route : stopToRoutes.getOrDefault(stop, Collections.emptyList())) {
                    if (visitedRoutes[route]) continue;
                    visitedRoutes[route] = true;
                    for (int nextStop : routes[route]) {
                        if (nextStop == target) return buses;
                        if (visitedStops.add(nextStop)) queue.offer(nextStop);
                    }
                }
            }
        }
        return -1;
    }
}

```

Time $O(\text{sum of route lengths})$ | **Space** $O(\text{sum of route lengths})$

#847 Shortest Path Visiting All Nodes

Description: Find the length of the shortest path in an undirected graph that visits every node (may revisit nodes/edges).

Variation: BFS over states $(\text{node}, \text{visitedMask})$ where mask is a bitmask of visited nodes; the goal is any state with all bits set. Start BFS from every node simultaneously.

Variables: $\text{allVisited} = \text{full bitmask } (1 < n) - 1$ · $\text{queue} = \text{states } \{\text{node}, \text{mask}\}$ · $\text{visited}[\text{node}][\text{mask}] = \text{state seen}$ · $\text{steps} = \text{path length}$ **Pseudocode:**

```

seed queue with every node, its mask = bit for that node
BFS by level: for each state, if mask == all bits set return steps
    for each neighbor: nextMask = mask | bit(neighbor); enqueue if state unseen
increment steps each level

```

```

class Solution {
    public int shortestPathLength(int[][] graph) {
        int n = graph.length;
        int allVisited = (1 << n) - 1;
        Queue<int[]> queue = new ArrayDeque<>(); // [node, mask]
        boolean[][] visited = new boolean[n][1 << n];
        for (int i = 0; i < n; i++) { // ← VARIATION: seed all nodes
            queue.offer(new int[]{i, 1 << i});
            visited[i][1 << i] = true;
        }
        int steps = 0;
        while (!queue.isEmpty()) {
            int size = queue.size();
            for (int s = 0; s < size; s++) {
                int[] current = queue.poll();
                int node = current[0], mask = current[1];
                if (mask == allVisited) return steps;
                for (int neighbor : graph[node]) {
                    int nextMask = mask | (1 << neighbor);
                    if (!visited[neighbor][nextMask]) {
                        visited[neighbor][nextMask] = true;
                        queue.offer(new int[]{neighbor, nextMask});
                    }
                }
            }
            steps++;
        }
        return 0;
    }
}

```

Time $O(2^n \cdot n^2)$ | **Space** $O(2^n \cdot n)$

#851 Loud and Rich

Description: `richer[i] = [a, b]` means `a` is richer than `b`; `quiet[i]` is the quietness of person `i`. For each person find the quietest person among everyone at least as rich (themselves included).

Variation: Topological sort (Kahn's) on the richer→poorer graph; propagate the quietest-known answer from richer people down to poorer ones in topo order.

Variables: `graph` = richer → poorer edges · `inDegree[]` = richer-people count per node · `result[]` = quietest known person at least as rich · `queue` = ready nodes **Pseudocode:**

```

build richer→poorer edges; result[i]=i initially
enqueue richest people (inDegree 0)
topo-pop node; for each poorer neighbor, if node's answer is quieter, propagate it down
decrement neighbor inDegree, enqueue when 0

```

```

class Solution {
    public int[] loudAndRich(int[][] richer, int[] quiet) {
        int n = quiet.length;
        List<List<Integer>> graph = new ArrayList<>();
        for (int i = 0; i < n; i++) graph.add(new ArrayList<>());
        int[] inDegree = new int[n];
        for (int[] r : richer) {
            graph.get(r[0]).add(r[1]);
            inDegree[r[1]]++;
        }
        int[] result = new int[n];
        for (int i = 0; i < n; i++) result[i] = i;
        Queue<Integer> queue = new ArrayDeque<>();
        for (int i = 0; i < n; i++) if (inDegree[i] == 0) queue.offer(i);
        while (!queue.isEmpty()) {
            int node = queue.poll();
            for (int neighbor : graph.get(node)) {
                if (quiet[result[node]] < quiet[result[neighbor]]) {
                    result[neighbor] = result[node];
                    // ← VARIATION: propagate quietest down
                }
                if (--inDegree[neighbor] == 0) queue.offer(neighbor);
            }
        }
        return result;
    }
}

```

Time $O(V+E)$ | **Space** $O(V+E)$

#886 Possible Bipartition

Description: Given `dislikes` pairs, split `n` people into two groups so disliking people are never in the same group.

Algorithm: Bipartite 2-coloring via BFS over the dislike graph; a same-color conflict means impossible.

Variables: `graph` = dislike adjacency · `color[]` = -1/0/1 group · `queue` = BFS frontier · `start` = component seed (1..n) **Pseudocode:**

```

build undirected dislike graph
for each uncolored person: color 0, BFS
    paint each neighbor the opposite color; if a neighbor already shares this color, return false
return true if no conflicts

```

```

class Solution {
    public boolean possibleBipartition(int n, int[][] dislikes) {
        List<List<Integer>> graph = new ArrayList<>();
        for (int i = 0; i <= n; i++) graph.add(new ArrayList<>());
        for (int[] d : dislikes) {
            graph.get(d[0]).add(d[1]);
            graph.get(d[1]).add(d[0]);
        }
        int[] color = new int[n + 1];
        Arrays.fill(color, -1);
        Queue<Integer> queue = new ArrayDeque<>();
        for (int start = 1; start <= n; start++) {
            if (color[start] != -1) continue;
            color[start] = 0;
            queue.offer(start);
            while (!queue.isEmpty()) {
                int node = queue.poll();
                for (int neighbor : graph.get(node)) {
                    if (color[neighbor] == -1) {
                        color[neighbor] = 1 - color[node];
                        queue.offer(neighbor);
                    } else if (color[neighbor] == color[node]) {
                        return false;
                    }
                }
            }
        }
        return true;
    }
}

```

Time $O(V+E)$ | **Space** $O(V+E)$

#913 Cat and Mouse

Description: A mouse (start node 1) and cat (start node 2) move on a graph; mouse wins by reaching node 0, cat wins by catching the mouse, else draw. Return 0/1/2 with optimal play.

Variation: Game-theory BFS over states (mouse, cat, turn); start from known terminal states and propagate results backward (retrograde analysis) by counting undecided moves.

Variables: `result[m][c][turn]` = outcome (DRAW/MOUSE/CAT) of a state · `degree[m][c][turn]` = undecided moves left from a state · `queue` = decided states to propagate · `winner` = a state's resolved winner **Pseudocode:**

```

precompute each state's move count (cat cannot enter hole 0)
seed terminals: mouse at hole 0 → MOUSE wins; cat==mouse → CAT wins
BFS backward: for each parent of a decided state
    if mover can force its own win, mark and enqueue it
    else decrement parent's degree; when 0 (all moves lose), it takes opponent's winner
return result[1][2][0] (mouse start, cat start, mouse to move)

```

```

class Solution {
    public int catMouseGame(int[][] graph) {
        int n = graph.length;
        final int DRAW = 0, MOUSE = 1, CAT = 2;
        int[][][] result = new int[n][n][2]; // [mouse][cat][turn] : 0=mouse turn,1=c
        int[][][] degree = new int[n][n][2];
        Queue<int[]> queue = new ArrayDeque<>();
        for (int m = 0; m < n; m++) {
            for (int c = 0; c < n; c++) {
                degree[m][c][0] = graph[m].length;
                degree[m][c][1] = graph[c].length;
                for (int x : graph[c]) {
                    if (x == 0) { degree[m][c][1]--; break; } // cat cannot move into hole 0
                }
            }
        }
        for (int c = 0; c < n; c++) {
            for (int t = 0; t < 2; t++) {
                result[0][c][t] = MOUSE; // mouse at hole → mouse wins
                queue.offer(new int[]{0, c, t, MOUSE});
                if (c > 0) {
                    result[c][c][t] = CAT; // cat catches mouse
                    queue.offer(new int[]{c, c, t, CAT});
                }
            }
        }
        while (!queue.isEmpty()) {
            int[] state = queue.poll();
            int mouse = state[0], cat = state[1], turn = state[2], winner = state[3];
            for (int[] prev : parents(graph, mouse, cat, turn)) {
                int pm = prev[0], pc = prev[1], pt = prev[2];
                if (result[pm][pc][pt] != DRAW) continue;
                if ((pt == 0 && winner == MOUSE) || (pt == 1 && winner == CAT)) {
                    result[pm][pc][pt] = winner; // mover can force its own win
                    queue.offer(new int[]{pm, pc, pt, winner});
                } else if (--degree[pm][pc][pt] == 0) { // ← VARIATION: all moves lead to oppon
                    result[pm][pc][pt] = winner;
                    queue.offer(new int[]{pm, pc, pt, winner});
                }
            }
        }
        return result[1][2][0];
    }
    private List<int[]> parents(int[][] graph, int mouse, int cat, int turn) {
        List<int[]> result = new ArrayList<>();
        if (turn == 0) { // previous move was the cat's (turn 1)
            for (int pc : graph[cat]) {
                if (pc != 0) result.add(new int[]{mouse, pc, 1});
            }
        } else { // previous move was the mouse's (turn
            for (int pm : graph[mouse]) {
                result.add(new int[]{pm, cat, 0});
            }
        }
        return result;
    }
}

```

Time $O(V^3)$ | **Space** $O(V^2)$

#934 Shortest Bridge

Description: A grid has exactly two islands of 1's. Find the minimum number of 0's to flip to connect them.

Variation: DFS to mark the first island (seeding a BFS queue with its cells), then multi-source BFS expanding outward until reaching the second island; BFS levels = bridge length.

Variables: queue = first island's cells, then BFS frontier · found = first island located · steps = water cells flipped (bridge length) · dr / dc = 4-direction offsets **Pseudocode:**

```
find first '1', DFS-mark its whole island as 2, seeding queue with those cells
multi-source BFS outward, each level = one bridge step
    if a neighbor is '1' (second island) return steps
    if water '0', flip to 2 and enqueue
```

```
class Solution {
    public int shortestBridge(int[][] grid) {
        int n = grid.length;
        int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
        Queue<int[]> queue = new ArrayDeque<>();
        boolean found = false;
        for (int i = 0; i < n && !found; i++) {
            for (int j = 0; j < n && !found; j++) {
                if (grid[i][j] == 1) {
                    dfs(grid, i, j, queue);
                    found = true;
                }
            }
        }
        int steps = 0;
        while (!queue.isEmpty()) {
            int size = queue.size();
            for (int s = 0; s < size; s++) {
                int[] current = queue.poll();
                for (int dir = 0; dir < 4; dir++) {
                    int ni = current[0] + dr[dir], nj = current[1] + dc[dir];
                    if (ni < 0 || ni >= n || nj < 0 || nj >= n) continue;
                    if (grid[ni][nj] == 1) return steps;
                    if (grid[ni][nj] == 0) {
                        grid[ni][nj] = 2;
                        queue.offer(new int[]{ni, nj});
                    }
                }
            }
            steps++;
        }
        return -1;
    }
    private void dfs(int[][] grid, int i, int j, Queue<int[]> queue) {
        int n = grid.length;
        if (i < 0 || i >= n || j < 0 || j >= n || grid[i][j] != 1) return;
        grid[i][j] = 2;
        queue.offer(new int[]{i, j});
        int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
        for (int dir = 0; dir < 4; dir++) dfs(grid, i + dr[dir], j + dc[dir], queue);
    }
}
```

Time $O(n^2)$ | **Space** $O(n^2)$

#1034 Coloring A Border

Description: Color the border cells of the connected component containing (row, col) with color. A border cell touches the grid edge or a cell of a different original color.

Variation: BFS over same-color connected cells; mark a cell as a border when it has fewer than 4 same-component neighbors, recolor borders after traversal.

Variables: original = component's source color · visited[][] = BFS seen · borders = collected border cells · sameNeighbors = matching 4-neighbor count **Pseudocode:**

```
BFS the connected same-color component from (row,col)
for each cell, count same-color 4-neighbors; enqueue unvisited matching ones
if fewer than 4 same-color neighbors, it touches edge/different color → it's a border cell
after BFS, recolor every collected border cell
```

```
class Solution {
    public int[][] colorBorder(int[][] grid, int row, int col, int color) {
        int rows = grid.length, cols = grid[0].length;
        int original = grid[row][col];
        boolean[][] visited = new boolean[rows][cols];
        List<int[]> borders = new ArrayList<>();
        int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
        Queue<int[]> queue = new ArrayDeque<>();
        queue.offer(new int[]{row, col});
        visited[row][col] = true;
        while (!queue.isEmpty()) {
            int[] current = queue.poll();
            int r = current[0], c = current[1];
            int sameNeighbors = 0;
            for (int dir = 0; dir < 4; dir++) {
                int nr = r + dr[dir], nc = c + dc[dir];
                if (nr < 0 || nr >= rows || nc < 0 || nc >= cols) continue;
                if (grid[nr][nc] == original) sameNeighbors++;
                if (grid[nr][nc] == original && !visited[nr][nc]) {
                    visited[nr][nc] = true;
                    queue.offer(new int[]{nr, nc});
                }
            }
            if (sameNeighbors < 4) borders.add(new int[]{r, c}); // ← VARIATION: fewer than 4 component
        }
        for (int[] b : borders) grid[b[0]][b[1]] = color;
        return grid;
    }
}
```

Time $O(m \cdot n)$ | **Space** $O(m \cdot n)$

#1102 Path With Maximum Minimum Value

Description: Find a path from top-left to bottom-right maximizing the minimum cell value along the path (4-directional).

Variation: Modified Dijkstra with a max-heap — the path "score" is the minimum cell value seen; greedily expand the highest-scoring frontier first.

Variables: pq = max-heap on min-value-so-far {score,r,c} · visited[][] = settled cells · score = minimum cell value along the path **Pseudocode:**

```

push (grid[0][0],0,0), mark visited
pop cell with largest min-so-far; if it's destination return that score
for each unvisited neighbor: push min(score, neighbor value) ← min, not sum
mark visited on push

```

```

class Solution {
    public int maximumMinimumPath(int[][] grid) {
        int rows = grid.length, cols = grid[0].length;
        boolean[][] visited = new boolean[rows][cols];
        PriorityQueue<int[]> pq = new PriorityQueue<>((a, b) -> b[0] - a[0]); // ← VARIATION: max-heap
        pq.offer(new int[]{grid[0][0], 0, 0});
        visited[0][0] = true;
        int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
        while (!pq.isEmpty()) {
            int[] current = pq.poll();
            int score = current[0], r = current[1], c = current[2];
            if (r == rows - 1 && c == cols - 1) return score;
            for (int dir = 0; dir < 4; dir++) {
                int nr = r + dr[dir], nc = c + dc[dir];
                if (nr < 0 || nr >= rows || nc < 0 || nc >= cols || visited[nr][nc]) continue;
                visited[nr][nc] = true;
                pq.offer(new int[]{Math.min(score, grid[nr][nc]), nr, nc}); // ← VARIATION: min not sum
            }
        }
        return -1;
    }
}

```

Time $O(m \cdot n \cdot \log(m \cdot n))$ | **Space** $O(m \cdot n)$

#1136 Parallel Courses

Description: Courses 1..n with prerequisite relations; in each semester take all courses whose prerequisites are done. Return minimum semesters, or -1 if impossible.

Variation: Topological sort (Kahn's) processed level-by-level — each BFS level is one semester; if not all courses are processed, a cycle exists.

Variables: graph = prereq → dependent · inDegree[] = unmet prerequisites · queue = courses ready this semester · semesters / studied = counters **Pseudocode:**

```

build graph + inDegree; enqueue all inDegree=0 courses
while queue: one level = one semester, semesters++
    pop each course (studied++), relax neighbors, enqueue new zeros
return semesters if studied == n else -1 (cycle)

```

```

class Solution {
    public int minimumSemesters(int n, int[][] relations) {
        List<List<Integer>> graph = new ArrayList<>();
        for (int i = 0; i <= n; i++) graph.add(new ArrayList<>());
        int[] inDegree = new int[n + 1];
        for (int[] r : relations) {
            graph.get(r[0]).add(r[1]);
            inDegree[r[1]]++;
        }
        Queue<Integer> queue = new ArrayDeque<>();
        for (int i = 1; i <= n; i++) if (inDegree[i] == 0) queue.offer(i);
        int semesters = 0, studied = 0;
        while (!queue.isEmpty()) {
            int size = queue.size();
            semesters++; // ← VARIATION: each level = one semest
            for (int s = 0; s < size; s++) {
                int node = queue.poll();
                studied++;
                for (int neighbor : graph.get(node)) {
                    if (--inDegree[neighbor] == 0) queue.offer(neighbor);
                }
            }
        }
        return studied == n ? semesters : -1;
    }
}

```

Time $O(V+E)$ | **Space** $O(V+E)$

#1162 As Far from Land as Possible

Description: In a grid of `0` (water) and `1` (land), find the water cell whose distance to the nearest land is maximized; return that distance, or `-1`.

Variation: Multi-source BFS seeded with all land cells; the last BFS level expanded gives the maximum distance.

Variables: `queue` = land-rooted BFS frontier · `distance` = current BFS level · `dr / dc` = 4-direction offsets

Pseudocode:

```

enqueue all land cells; if all-land or all-water, return -1
BFS by level, distance++ each level
    expand into water cells, marking them as 1 (visited) and enqueueing
the last level reached gives the farthest water cell's distance

```

```

class Solution {
    public int maxDistance(int[][] grid) {
        int n = grid.length;
        Queue<int[]> queue = new ArrayDeque<>();
        for (int i = 0; i < n; i++) {
            for (int j = 0; j < n; j++) {
                if (grid[i][j] == 1) queue.offer(new int[]{i, j}); // ← VARIATION: seed ALL land cells
            }
        }
        if (queue.isEmpty() || queue.size() == n * n) return -1;
        int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
        int distance = -1;
        while (!queue.isEmpty()) {
            int size = queue.size();
            distance++;
            for (int s = 0; s < size; s++) {
                int[] current = queue.poll();
                for (int dir = 0; dir < 4; dir++) {
                    int ni = current[0] + dr[dir], nj = current[1] + dc[dir];
                    if (ni < 0 || ni >= n || nj < 0 || nj >= n || grid[ni][nj] != 0) continue;
                    grid[ni][nj] = 1;
                    queue.offer(new int[]{ni, nj});
                }
            }
        }
        return distance;
    }
}

```

Time $O(n^2)$ | **Space** $O(n^2)$

#1197 Minimum Knight Moves

Description: On an infinite chessboard, find the minimum knight moves from $(0,0)$ to (x, y) .

Variation: BFS over knight moves (8 jump offsets); exploit symmetry by working in the first quadrant to bound the visited set.

Variables: `dr / dc` = 8 knight-jump offsets · `queue` = BFS frontier · `visited` = "r,c" strings seen · `moves` = jumps so far

Pseudocode:

```

fold target to first quadrant via abs(x), abs(y) (symmetry)
BFS from (0,0); each level = one knight move
    if current cell is target return moves
    push each unvisited jump that stays near the first quadrant (>= -2)

```

```

class Solution {
    public int minKnightMoves(int x, int y) {
        x = Math.abs(x);
        y = Math.abs(y); // ← VARIATION: symmetry to first quadr
        int[] dr = {1,1,-1,-1,2,2,-2,-2}, dc = {2,-2,2,-2,1,-1,1,-1}; // knight offsets
        Queue<int[]> queue = new ArrayDeque<>();
        queue.offer(new int[]{0, 0});
        Set<String> visited = new HashSet<>();
        visited.add("0,0");
        int moves = 0;
        while (!queue.isEmpty()) {
            int size = queue.size();
            for (int s = 0; s < size; s++) {
                int[] current = queue.poll();
                if (current[0] == x && current[1] == y) return moves;
                for (int dir = 0; dir < 8; dir++) {
                    int ni = current[0] + dr[dir], nj = current[1] + dc[dir];
                    if (ni < -2 || nj < -2) continue; // stay near first quadrant
                    String key = ni + "," + nj;
                    if (visited.add(key)) queue.offer(new int[]{ni, nj});
                }
            }
            moves++;
        }
        return -1;
    }
}

```

Time $O(\max(x,y)^2)$ | **Space** $O(\max(x,y)^2)$

#1202 Smallest String With Swaps

Description: Given index `pairs` that may be swapped any number of times, return the lexicographically smallest string achievable.

Variation: Union-Find groups swappable indices into connected components; within each component, sort the characters and place them back in ascending index order.

Variables: `parent[] / rank[]` = union-find over indices · `groups` = root → indices in that component · `result` = output char array
Pseudocode:

```

union every swappable index pair
group indices by their root
per group: collect its chars, sort them, write back in ascending index order
return rebuilt string

```

```

class Solution {
    int[] parent, rank;
    public String smallestStringWithSwaps(String s, List<List<Integer>> pairs) {
        int n = s.length();
        parent = new int[n];
        rank = new int[n];
        for (int i = 0; i < n; i++) parent[i] = i;
        for (List<Integer> p : pairs) union(p.get(0), p.get(1)); // ← VARIATION: union swappable indices
        Map<Integer, List<Integer>> groups = new HashMap<>();
        for (int i = 0; i < n; i++) {
            groups.computeIfAbsent(find(i), x -> new ArrayList<>()).add(i);
        }
        char[] result = s.toCharArray();
        for (List<Integer> indices : groups.values()) {
            List<Character> chars = new ArrayList<>();
            for (int i : indices) chars.add(s.charAt(i));
            Collections.sort(chars);
            for (int k = 0; k < indices.size(); k++) result[indices.get(k)] = chars.get(k);
        }
        return new String(result);
    }
    int find(int x) { return parent[x] == x ? x : (parent[x] = find(parent[x])); }
    boolean union(int x, int y) {
        int px = find(x), py = find(y);
        if (px == py) return false;
        if (rank[px] < rank[py]) { int t = px; px = py; py = t; }
        parent[py] = px;
        if (rank[px] == rank[py]) rank[px]++;
        return true;
    }
}

```

Time $O(n \cdot \log(n) + E \cdot \alpha(n))$ | **Space** $O(n)$

#1245 Tree Diameter

Description: Given the edges of an undirected tree, return its diameter (the number of edges on the longest path between any two nodes).

Variation: Two BFS passes — BFS from any node finds the farthest node `u`; a second BFS from `u` gives the diameter as the maximum distance.

Variables: `graph` = tree adjacency · `first / second` = {farthest node, distance} from each BFS · `farthest / distance` = tracked during a BFS **Pseudocode:**

```

build adjacency (n = edges+1)
BFS from node 0 → farthest node u
BFS from u → its distance is the diameter

```

```

class Solution {
    public int treeDiameter(int[][] edges) {
        int n = edges.length + 1;
        List<List<Integer>> graph = new ArrayList<>();
        for (int i = 0; i < n; i++) graph.add(new ArrayList<>());
        for (int[] e : edges) {
            graph.get(e[0]).add(e[1]);
            graph.get(e[1]).add(e[0]);
        }
        int[] first = bfs(graph, 0, n); // ← VARIATION: farthest node from arbitrary
        int[] second = bfs(graph, first[0], n); // diameter from that farthest node
        return second[1];
    }
    private int[] bfs(List<List<Integer>> graph, int start, int n) {
        boolean[] visited = new boolean[n];
        Queue<Integer> queue = new ArrayDeque<>();
        queue.offer(start);
        visited[start] = true;
        int farthest = start, distance = -1;
        while (!queue.isEmpty()) {
            int size = queue.size();
            distance++;
            for (int s = 0; s < size; s++) {
                int node = queue.poll();
                farthest = node;
                for (int neighbor : graph.get(node)) {
                    if (!visited[neighbor]) {
                        visited[neighbor] = true;
                        queue.offer(neighbor);
                    }
                }
            }
        }
        return new int[]{farthest, distance};
    }
}

```

Time $O(V+E)$ | **Space** $O(V+E)$

#1293 Shortest Path in a Grid with Obstacles Elimination

Description: Find the shortest path from $(0,0)$ to $(m-1,n-1)$ in a grid where you may eliminate at most k obstacles ($1 \leq k \leq 10$).

Variation: BFS over states $(row, col, remainingK)$; the visited set tracks the best remaining eliminations per cell so a cell can be revisited with more budget.

Variables: $bestK[][]$ = best remaining eliminations seen at each cell · $queue$ = states $\{r,c,remainingK\}$ · $steps$ = path length · $nextRem$ = budget after stepping **Pseudocode:**

```

if k can cover a straight Manhattan path, return that length
BFS from  $(0,0,k)$ ,  $bestK[0][0]=k$ ; each level = one step
    if at destination return steps
    for each neighbor:  $nextRem = rem - cell(0/1)$ 
    only enqueue if  $nextRem$  beats  $bestK$  there (revisit with more budget)

```

```

class Solution {
    public int shortestPath(int[][] grid, int k) {
        int rows = grid.length, cols = grid[0].length;
        if (k >= rows + cols - 2) return rows + cols - 2; // enough to go straight
        int[][] bestK = new int[rows][cols];
        for (int[] row : bestK) Arrays.fill(row, -1);
        int[] dr = {1,-1,0,0}, dc = {0,0,1,-1};
        Queue<int[]> queue = new ArrayDeque<>(); // [r, c, remainingK]
        queue.offer(new int[]{0, 0, k});
        bestK[0][0] = k;
        int steps = 0;
        while (!queue.isEmpty()) {
            int size = queue.size();
            for (int s = 0; s < size; s++) {
                int[] current = queue.poll();
                int r = current[0], c = current[1], rem = current[2];
                if (r == rows - 1 && c == cols - 1) return steps;
                for (int dir = 0; dir < 4; dir++) {
                    int nr = r + dr[dir], nc = c + dc[dir];
                    if (nr < 0 || nr >= rows || nc < 0 || nc >= cols) continue;
                    int nextRem = rem - grid[nr][nc];
                    if (nextRem > bestK[nr][nc]) { // ← VARIATION: revisit if more budget
                        bestK[nr][nc] = nextRem;
                        queue.offer(new int[]{nr, nc, nextRem});
                    }
                }
            }
            steps++;
        }
        return -1;
    }
}

```

Time $O(m \cdot n \cdot k)$ | **Space** $O(m \cdot n)$

#1559 Detect Cycles in 2D Grid

Description: Return true if the grid contains a cycle of length ≥ 4 made of the same character.

Variation: Union-Find over grid cells — for each cell union it with its up and left same-character neighbors; if a union finds them already connected, a cycle exists.

Variables: `parent[] / rank[]` = union-find over flattened cells · `id` = current cell index **Pseudocode:**

```

init each cell its own set
scan cells: union with up neighbor and left neighbor when same character
    if either union finds them already connected → a cycle exists, return true
return false if no cycle

```

```

class Solution {
    int[] parent, rank;
    public boolean containsCycle(char[][] grid) {
        int rows = grid.length, cols = grid[0].length;
        parent = new int[rows * cols];
        rank = new int[rows * cols];
        for (int i = 0; i < rows * cols; i++) parent[i] = i;
        for (int i = 0; i < rows; i++) {
            for (int j = 0; j < cols; j++) {
                int id = i * cols + j;
                if (i > 0 && grid[i-1][j] == grid[i][j]) {
                    if (!union(id, (i-1) * cols + j)) return true; // ← VARIATION: already connected →
                }
                if (j > 0 && grid[i][j-1] == grid[i][j]) {
                    if (!union(id, i * cols + (j-1))) return true;
                }
            }
        }
        return false;
    }
    int find(int x) { return parent[x] == x ? x : (parent[x] = find(parent[x])); }
    boolean union(int x, int y) {
        int px = find(x), py = find(y);
        if (px == py) return false;
        if (rank[px] < rank[py]) { int t = px; px = py; py = t; }
        parent[py] = px;
        if (rank[px] == rank[py]) rank[px]++;
        return true;
    }
}

```

Time $O(m \cdot n \cdot \alpha(m \cdot n))$ | **Space** $O(m \cdot n)$

#1743 Restore the Array From Adjacent Pairs

Description: Given all adjacent pairs of an array (in any order), reconstruct the original array.

Variation: Build an adjacency graph; the two endpoints have a single neighbor. Start from an endpoint and walk the path, avoiding the previous node.

Variables: `graph` = value $\rightarrow$ its adjacent values · `start` = an endpoint (single neighbor) · `result[]` = reconstructed array
Pseudocode:

```

build adjacency from each pair (both directions)
find an endpoint: a value with exactly one neighbor → result[0]
result[1] = its only neighbor
walk forward: each next value is the neighbor that isn't the previous one

```

```

class Solution {
    public int[] restoreArray(int[][] adjacentPairs) {
        Map<Integer, List<Integer>> graph = new HashMap<>();
        for (int[] pair : adjacentPairs) {
            graph.computeIfAbsent(pair[0], x -> new ArrayList<>()).add(pair[1]);
            graph.computeIfAbsent(pair[1], x -> new ArrayList<>()).add(pair[0]);
        }
        int n = adjacentPairs.length + 1;
        int[] result = new int[n];
        int start = 0;
        for (Map.Entry<Integer, List<Integer>> entry : graph.entrySet()) {
            if (entry.getValue().size() == 1) { // ← VARIATION: endpoint has one neighb
                start = entry.getKey();
                break;
            }
        }
        result[0] = start;
        result[1] = graph.get(start).get(0);
        for (int i = 2; i < n; i++) {
            List<Integer> neighbors = graph.get(result[i-1]);
            result[i] = neighbors.get(0) == result[i-2] ? neighbors.get(1) : neighbors.get(0);
        }
        return result;
    }
}

```

Time $O(n)$ | **Space** $O(n)$