

Context-Free Grammars

Grammars were invented by Chomsky in the mid-1950s for describing natural languages. In the late 1950s, one of Chomsky's types of grammar (Type 2 or *context-free* grammar) was reinvented by Backus and proposed as a way to specify the syntax of the new language Algol.

Context-Free Grammars

Grammars were invented by Chomsky in the mid-1950s for describing natural languages. In the late 1950s, one of Chomsky's types of grammar (Type 2 or **context-free** grammar) was reinvented by Backus and proposed as a way to specify the syntax of the new language Algol.

This proposal was adopted in the **Algol 60 Report** (edited by Naur), an influential document considered to have done an excellent job of specifying Algol 60.

Context-Free Grammars

Grammars were invented by Chomsky in the mid-1950s for describing natural languages. In the late 1950s, one of Chomsky's types of grammar (Type 2 or **context-free** grammar) was reinvented by Backus and proposed as a way to specify the syntax of the new language Algol.

This proposal was adopted in the **Algol 60 Report** (edited by Naur), an influential document considered to have done an excellent job of specifying Algol 60.

The grammar notation used in the Algol 60 Report is now called "Backus Naur Form" or **BNF**.

Like many authors (but unlike Sethi) we use the term **BNF** more loosely, to simply mean "*a commonly used notation for writing context-free grammars*", and we refer to grammars written in such a notation as **BNF specifications**.

$$\begin{aligned}
 \langle expression \rangle &::= \langle expression \rangle + \langle term \rangle \\
 &\quad | \langle expression \rangle - \langle term \rangle \\
 &\quad | \langle term \rangle \\
 \langle term \rangle &::= \langle term \rangle * \langle factor \rangle \\
 &\quad | \langle term \rangle / \langle factor \rangle \\
 &\quad | \langle factor \rangle \\
 \langle factor \rangle &::= \text{number} \\
 &\quad | \text{name} \\
 &\quad | (\langle expression \rangle)
 \end{aligned}$$

A grammar written in BNF notation on p. 46 of Sethi (p. 47 in the course reader).

Figure 2.10 BNF syntactic rules for arithmetic expressions.

On p. 42, Sethi gives this equivalent grammar that is written in a similar notation. We will consider this notation to be BNF,

$$\begin{aligned}
 E &::= E + T \mid E - T \mid T \\
 T &::= T * F \mid T / F \mid F \\
 F &::= \text{number} \mid \text{name} \mid (E)
 \end{aligned}$$

Figure 2.6 A grammar for arithmetic expressions.

```

<expression> ::= <expression> + <term>
               | <expression> - <term>
               | <term>
<term> ::= <term> * <factor>
          | <term> / <factor>
          | <factor>
<factor> ::= number
           | name
           | ( <expression> )

```

A grammar written in BNF notation on p. 46 of Sethi (p. 47 in the course reader).

Figure 2.10 BNF syntactic rules for arithmetic expressions.

On p. 42, Sethi gives this equivalent grammar that is written in a similar notation. We will consider this notation to be BNF, even though it isn't exactly the same as the notation used in the Algol 60 Report and Sethi does not call it BNF.

```

E ::= E + T | E - T | T
T ::= T * F | T / F | F
F ::= number | name | ( E )

```

Figure 2.6 A grammar for arithmetic expressions.

We will use the term grammar to mean "context-free grammar"; we will not use other types of grammar.

-

-

-

-

We will use the term grammar to mean "context-free grammar"; we will not use other types of grammar.

- A grammar is a relatively concise way to precisely specify certain (possibly infinite) *sets of finite sequences of symbols*; those symbols are referred to as *terminals* of the grammar.

-

-

-

We will use the term **grammar** to mean "context-free grammar"; we will not use other types of grammar.

- A grammar is a relatively concise way to precisely specify certain (possibly infinite) *sets of finite sequences of symbols*; those symbols are referred to as ***terminals*** of the grammar.
- Each of the specified sets of finite sequences of terminals is denoted by a ***nonterminal*** of the grammar.
-

-

We will use the term **grammar** to mean "context-free grammar"; we will not use other types of grammar.

- A grammar is a relatively concise way to precisely specify certain (possibly infinite) *sets of finite sequences of symbols*; those symbols are referred to as ***terminals*** of the grammar.
- Each of the specified sets of finite sequences of terminals is denoted by a ***nonterminal*** of the grammar.
- One of the nonterminals is regarded as the “most important”: It is called the ***starting nonterminal*** (or *start symbol* or *sentence symbol*); the set of sequences of terminals it denotes is called the ***language generated by*** (or *language of*) the grammar.
-

We will use the term **grammar** to mean "context-free grammar"; we will not use other types of grammar.

- A grammar is a relatively concise way to precisely specify certain (possibly infinite) *sets of finite sequences of symbols*; those symbols are referred to as ***terminals*** of the grammar.
- Each of the specified sets of finite sequences of terminals is denoted by a ***nonterminal*** of the grammar.
- One of the nonterminals is regarded as the “most important”: It is called the ***starting nonterminal*** (or *start symbol* or *sentence symbol*); the set of sequences of terminals it denotes is called the ***language generated by*** (or *language of*) the grammar.
- We commonly think of the other nonterminals as being defined in order that they may be used in defining the starting nonterminal.

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

In the above grammar:

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

In the above grammar:

The following characters are the 11 *terminals*:

. 0 1 2 3 4 5 6 7 8 9

A *terminal* of a grammar is a constant symbol that is *not* defined by the grammar.

```

<real-number> ::= <integer-part> . <fraction>
<integer-part> ::= <digit> | <integer-part> <digit>
<fraction> ::= <digit> | <digit> <fraction>
<digit> ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

```

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

In the above grammar:

The following characters are the 11 *terminals*:

. 0 1 2 3 4 5 6 7 8 9

A *terminal* of a grammar is a constant symbol that is *not* defined by the grammar.

The following are the 4 *nonterminals*:

<real-number> <integer-part> <fraction> <digit>

A *nonterminal* of a grammar is a variable that denotes a set of finite sequences of terminals. For example,

```

<real-number> ::= <integer-part> . <fraction>
<integer-part> ::= <digit> | <integer-part> <digit>
<fraction> ::= <digit> | <digit> <fraction>
<digit> ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

```

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

In the above grammar:

The following characters are the 11 *terminals*:

. 0 1 2 3 4 5 6 7 8 9

A *terminal* of a grammar is a constant symbol that is *not* defined by the grammar.

The following are the 4 *nonterminals*:

<real-number> <integer-part> <fraction> <digit>

A *nonterminal* of a grammar is a variable that denotes a set of finite sequences of terminals. For example, <digit> denotes the set {0, 1, 2, 3, 4, 5, 6, 7, 8, 9}.

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

In the above grammar:

$$\begin{aligned}
\langle \text{real-number} \rangle &::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle \\
\langle \text{integer-part} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle \\
\langle \text{fraction} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle \\
\langle \text{digit} \rangle &::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9
\end{aligned}$$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

In the above grammar:

There are 15 rules called ***productions***. Each production:

- has a left side that is a *single nonterminal*, and
- has a right side that is a *sequence of 0 or more terminals and/or nonterminals*.

The “vertical bar” symbol \mid means:

*The left side of this production is the same as the left side of the **previous** production.*

Example: The 3rd production of the above grammar is


```

<real-number> ::= <integer-part> . <fraction>
<integer-part> ::= <digit> | <integer-part> <digit>
<fraction> ::= <digit> | <digit> <fraction>
<digit> ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

```

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

In the above grammar:

There are 15 rules called ***productions***. Each production:

- has a left side that is a *single nonterminal*, and
- has a right side that is a *sequence of 0 or more terminals and/or nonterminals*.

The “vertical bar” symbol | means:

*The left side of this production is the same as the left side of the **previous** production.*

Example: The 3rd production of the above grammar is

```
<integer-part> ::= <integer-part> <digit>
```

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

```

<real-number> ::= <integer-part> . <fraction>
<integer-part> ::= <digit> | <integer-part> <digit>
<fraction> ::= <digit> | <digit> <fraction>
<digit> ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

```

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

Grammar notation is “free format”: We can insert whitespace characters, *including newlines*, between symbols without changing the specified grammar!

For example, the 2nd and 3rd productions

`<integer-part> ::= <digit> | <integer-part> <digit>`

of the above grammar could be rewritten as:

```

<real-number> ::= <integer-part> . <fraction>
<integer-part> ::= <digit> | <integer-part> <digit>
<fraction> ::= <digit> | <digit> <fraction>
<digit> ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

```

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

Grammar notation is “free format”: We can insert whitespace characters, *including newlines*, between symbols without changing the specified grammar!

For example, the 2nd and 3rd productions

```

<integer-part> ::= <digit> | <integer-part> <digit>

```

of the above grammar could be rewritten as:

```

<integer-part> ::= <digit>
                  | <integer-part> <digit>

```

```

<real-number> ::= <integer-part> . <fraction>
<integer-part> ::= <digit> | <integer-part> <digit>
<fraction> ::= <digit> | <digit> <fraction>
<digit> ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

```

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

Grammar notation is “free format”: We can insert whitespace characters, *including newlines*, between symbols without changing the specified grammar!

For example, the 2nd and 3rd productions

```

<integer-part> ::= <digit> | <integer-part> <digit>

```

of the above grammar could be rewritten as:

```

<integer-part> ::= <digit>
                  | <integer-part> <digit>

```

Intuitively, a production $N ::= \dots$ means “any \dots is an N ”.

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

$$\begin{aligned}
\langle \text{real-number} \rangle &::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle \\
\langle \text{integer-part} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle \\
\langle \text{fraction} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle \\
\langle \text{digit} \rangle &::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9
\end{aligned}$$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

$\langle \text{real-number} \rangle$ is the *starting nonterminal* of the above grammar.

In this course, we use the convention that *unless otherwise indicated*, the starting nonterminal of a grammar is the nonterminal on the left side of the *first* production:

$$\begin{aligned}
\langle \text{real-number} \rangle &::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle \\
\langle \text{integer-part} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle \\
\langle \text{fraction} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle \\
\langle \text{digit} \rangle &::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9
\end{aligned}$$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

$\langle \text{real-number} \rangle$ is the *starting nonterminal* of the above grammar.

In this course, we use the convention that unless otherwise indicated, the starting nonterminal of a grammar is the nonterminal on the left side of the first production:

If you write a grammar and want *some other* nonterminal to be its starting nonterminal, you must explicitly indicate which nonterminal is the starting nonterminal!

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

A grammar given
by Sethi to
specify unsigned
floating point
literals in a
simple language.

Figure 2.3 BNF rules for real numbers.

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

$\langle \text{empty} \rangle$ denotes the empty string; other people write ϵ or λ to denote the empty string.

Example: Changing the 2nd production above from $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle$ to $\langle \text{integer-part} \rangle ::= \langle \text{empty} \rangle$ will allow a number with *no digits before the point* (e.g., .213) to belong to the language of the grammar.

Note that $\langle \text{empty} \rangle$ is neither a terminal nor a nonterminal!

Parse Trees

Q. Exactly which sequences of terminals belong to the set of sequences of terminals that is denoted by a given nonterminal N of a grammar?

Parse Trees

- Q. Exactly which sequences of terminals belong to the set of sequences of terminals that is denoted by a given nonterminal N of a grammar?
- A. A sequence of terminals $t_1 \dots t_k$ belongs to the set of sequences denoted by a nonterminal N *if and only if* there is a **parse tree with root N that generates $t_1 \dots t_k$.**

Parse Trees

Q. Exactly which sequences of terminals belong to the set of sequences of terminals that is denoted by a given nonterminal N of a grammar?

A. A sequence of terminals $t_1 \dots t_k$ belongs to the set of sequences denoted by a nonterminal N *if and only if* there is a **parse tree with root N that generates $t_1 \dots t_k$.**

Unless otherwise indicated, the term **parse tree** means **parse tree whose root is the starting nonterminal**.

So we can say that sequence of terminals $t_1 \dots t_k$ belongs to the language of a grammar *if and only if* there is a **parse tree that generates $t_1 \dots t_k$.**

Comment:

Parse Trees

Q. Exactly which sequences of terminals belong to the set of sequences of terminals that is denoted by a given nonterminal N of a grammar?

A. A sequence of terminals $t_1 \dots t_k$ belongs to the set of sequences denoted by a nonterminal N *if and only if* there is a **parse tree with root N that generates $t_1 \dots t_k$.**


Unless otherwise indicated, the term **parse tree** means parse tree whose root is the starting nonterminal.

So we can say that sequence of terminals $t_1 \dots t_k$ belongs to the language of a grammar *if and only if* there is a **parse tree that generates $t_1 \dots t_k$.**

Comment: Instead of using parse trees, we can also answer the above question using the concept of a **derivation** that is introduced on pp. 40 – 41 of Sethi.


Below is a parse tree, whose root is $\langle integer-part \rangle$, that shows **282** belongs to the set of sequences denoted by $\langle integer-part \rangle$ in the following grammar:

$\langle real-number \rangle ::= \langle integer-part \rangle . \langle fraction \rangle$
 $\langle integer-part \rangle ::= \langle empty \rangle \mid \langle integer-part \rangle \langle digit \rangle$
 $\langle fraction \rangle ::= \langle digit \rangle \mid \langle digit \rangle \langle fraction \rangle$
 $\langle digit \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$



Below is a parse tree that shows **282.83** belongs to the language of the same grammar:

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{empty} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$



Given a nonterminal N and a *parse tree with root N* is an ordered rooted tree with the following properties:

Given a nonterminal N and a *parse tree with root N* is an ordered rooted tree with the following properties:

1. The root is the nonterminal N .

Given a nonterminal N and a *parse tree with root N* is an ordered rooted tree with the following properties:

1. The root is the nonterminal N .
2. Each leaf either is a terminal or is $\langle \text{empty} \rangle$; moreover, a leaf that is $\langle \text{empty} \rangle$ has no sibling.

Given a nonterminal N and a *parse tree with root N* is an ordered rooted tree with the following properties:

1. The root is the nonterminal N .
2. Each leaf either is a terminal or is $\langle \text{empty} \rangle$; moreover, a leaf that is $\langle \text{empty} \rangle$ has no sibling.
3. Each internal node is a nonterminal.

Given a nonterminal N and a *parse tree with root N* is an ordered rooted tree with the following properties:

1. The root is the nonterminal N .
2. Each leaf either is a terminal or is *<empty>*; moreover, a leaf that is *<empty>* has no sibling.
3. Each internal node is a nonterminal.
4. The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M .

Given a nonterminal N and a *parse tree with root N* is an ordered rooted tree with the following properties:

1. The root is the nonterminal N .
2. Each leaf either is a terminal or is $\langle \text{empty} \rangle$; moreover, a leaf that is $\langle \text{empty} \rangle$ has no sibling.
3. Each internal node is a nonterminal.
4. The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M .

Unless otherwise indicated, the term *parse tree* means *parse tree whose root is the starting nonterminal*.

Given a nonterminal N and a **parse tree with root N** is an ordered rooted tree with the following properties:

1. The root is the nonterminal N .
2. Each leaf either is a terminal or is $\langle \text{empty} \rangle$; moreover, a leaf that is $\langle \text{empty} \rangle$ has no sibling.
3. Each internal node is a nonterminal.
4. The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M .

Unless otherwise indicated, the term **parse tree** means **parse tree whose root is the starting nonterminal**.

Given terminals t_1, \dots, t_k , a **parse tree with root N that generates $t_1 \dots t_k$** (or **parse tree with root N of $t_1 \dots t_k$**) is

Given a nonterminal N and a **parse tree with root N** is an ordered rooted tree with the following properties:

1. The root is the nonterminal N .
2. Each leaf either is a terminal or is $\langle \text{empty} \rangle$; moreover, a leaf that is $\langle \text{empty} \rangle$ has no sibling.
3. Each internal node is a nonterminal.
4. The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M .

Unless otherwise indicated, the term **parse tree** means **parse tree whose root is the starting nonterminal**.

Given terminals t_1, \dots, t_k , a **parse tree with root N that generates $t_1 \dots t_k$** (or **parse tree with root N of $t_1 \dots t_k$**) is a parse tree with root N for which the left-to-right sequence of leaves that are not $\langle \text{empty} \rangle$ is t_1, \dots, t_k .

RECALL:

Q. Exactly which sequences of terminals belong to the set of sequences of terminals that is denoted by a given nonterminal N of a grammar?

A. A sequence of terminals $t_1 \dots t_k$ belongs to the set of sequences denoted by a nonterminal N *if and only if* there is a **parse tree with root N that generates $t_1 \dots t_k$.**


Unless otherwise indicated, the term **parse tree** means parse tree whose root is the starting nonterminal.

So we can say that sequence of terminals $t_1 \dots t_k$ belongs to the language of a grammar *if and only if* there is a **parse tree that generates $t_1 \dots t_k$.**

Comment: Instead of using parse trees, we can also answer the above question using the concept of a **derivation** that is introduced on pp. 40 – 41 of Sethi.

Below is a parse tree that shows **282.83** belongs to the language of the same grammar:

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{empty} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$



Use of Grammars to Define *Syntactically* Valid Code

An important part of the work of a compiler or interpreter is lexical analysis or lexical scanning.

Lexical analysis decomposes the source program into **token instances** (i.e., instances of tokens).

Ten examples of tokens of a C-like language are:

; < -- -) { IDENTIFIER UNSIGNED-INT-LITERAL while if

Use of Grammars to Define *Syntactically* Valid Code

An important part of the work of a compiler or interpreter is lexical analysis or lexical scanning.

Lexical analysis decomposes the source program into **token instances** (i.e., instances of tokens).

Ten examples of tokens of a C-like language are:

; **<** **--** **-** **)** **{** **IDENTIFIER** **UNSIGNED-INT-LITERAL** **while** **if**

Each token T is a set of strings of characters; each member of that set is called an instance of T .

For Java:

3 instances of **IDENTIFIER** are: **x** **prevVal** **pi_2**

2 instances of **UNSIGNED-INT-LITERAL** are: **23** **0x1A1D**

Note:

Use of Grammars to Define *Syntactically* Valid Code

An important part of the work of a compiler or interpreter is lexical analysis or lexical scanning.

Lexical analysis decomposes the source program into **token instances** (i.e., instances of tokens).

Ten examples of tokens of a C-like language are:

; **<** **--** **-** **)** **{** **IDENTIFIER** **UNSIGNED-INT-LITERAL** **while** **if**

Each token T is a set of strings of characters; each member of that set is called an instance of T .

For Java:

3 instances of **IDENTIFIER** are: **x** **prevVal** **pi_2**

2 instances of **UNSIGNED-INT-LITERAL** are: **23** **0x1A1D**

Note: In sec. 2.3 of Sethi, the tokens **IDENTIFIER** and **UNSIGNED-INT-LITERAL** are called **name** and **number**, and a token instance is called a spelling.

If a piece of source code should be decomposed by a compiler into a sequence of token instances $t_1 \dots t_n$ in which each t_i is an instance of token T_i , we say $T_1 \dots T_n$ is the *sequence of tokens* of that source code.

Java Example: **IDENTIFIER = UNSIGNED-INT-LITERAL ;**
is the sequence of tokens of **x23 = 4;**

If a piece of source code should be decomposed by a compiler into a sequence of token instances $t_1 \dots t_n$ in which each t_i is an instance of token T_i , we say $T_1 \dots T_n$ is the sequence of tokens of that source code.

Java Example: **IDENTIFIER = UNSIGNED-INT-LITERAL ;**
is the sequence of tokens of **x23 = 4;**

For many programming languages L , we can construct a grammar G (whose terminals are L 's tokens) such that:

$T_1 \dots T_n$ belongs to the language generated by G
if (and, roughly speaking, only if) $T_1 \dots T_n$ is the
sequence of tokens of a possibly valid L source file.

- “possibly valid” means
- “roughly speaking” means

If a piece of source code should be decomposed by a compiler into a sequence of token instances $t_1 \dots t_n$ in which each t_i is an instance of token T_i , we say $T_1 \dots T_n$ is the sequence of tokens of that source code.

Java Example: **IDENTIFIER = UNSIGNED-INT-LITERAL ;**
is the sequence of tokens of **x23 = 4;**

For many programming languages L , we can construct a grammar G (whose terminals are L 's tokens) such that:

$T_1 \dots T_n$ belongs to the language generated by G
if (and, roughly speaking, only if) $T_1 \dots T_n$ is the
sequence of tokens of a possibly valid L source file.

- “possibly valid” means “can be successfully compiled under certain conditions” (e.g., if certain variables and functions are appropriately defined in other files).
- “roughly speaking” means

If a piece of source code should be decomposed by a compiler into a sequence of token instances $t_1 \dots t_n$ in which each t_i is an instance of token T_i , we say $T_1 \dots T_n$ is the sequence of tokens of that source code.

Java Example: **IDENTIFIER = UNSIGNED-INT-LITERAL ;**
is the sequence of tokens of **x23 = 4;**

For many programming languages L , we can construct a grammar G (whose terminals are L 's tokens) such that:

$T_1 \dots T_n$ belongs to the language generated by G
if (and, roughly speaking, only if) $T_1 \dots T_n$ is the
sequence of tokens of a possibly valid L source file.

- “possibly valid” means “can be successfully compiled under certain conditions” (e.g., if certain variables and functions are appropriately defined in other files).
- “roughly speaking” means some (but not too many) exceptions to the condition’s “only if” part are allowed.

For many programming languages L , we can construct a grammar G (whose terminals are L 's tokens) such that:

$T_1 \dots T_n$ belongs to the language generated by G
if (and, roughly speaking, only if) $T_1 \dots T_n$ is the
sequence of tokens of a possibly valid L source file.

- “possibly valid” means “can be successfully compiled under certain conditions” (e.g., if certain variables and functions are appropriately defined in other files).
- “roughly speaking” means some (but not too many) exceptions to the condition’s “only if” part are allowed.

For many programming languages L , we can construct a grammar G (whose terminals are L 's tokens) such that:

$T_1 \dots T_n$ belongs to the language generated by G
if (and, roughly speaking, only if) $T_1 \dots T_n$ is the
sequence of tokens of a possibly valid L source file.

- “possibly valid” means “can be successfully compiled under certain conditions” (e.g., if certain variables and functions are appropriately defined in other files).
- “roughly speaking” means some (but not too many) exceptions to the condition’s “only if” part are allowed.

For many programming languages L , we can construct a grammar G (whose terminals are L 's tokens) such that:

$T_1 \dots T_n$ belongs to the language generated by G
if (and, roughly speaking, only if) $T_1 \dots T_n$ is the
sequence of tokens of a possibly valid L source file.

- “possibly valid” means “can be successfully compiled under certain conditions” (e.g., if certain variables and functions are appropriately defined in other files).
- “roughly speaking” means some (but not too many) exceptions to the condition’s “only if” part are allowed.

We can then say a particular L source file is **syntactically valid** if its sequence of tokens belongs to the language generated by the grammar G .

Note: Replacing one identifier with another and replacing a literal constant with another of the same type (e.g., changing $9/x$ to $3/y$) will **not** affect the syntactic validity of a source file, as it won’t change its sequence of tokens!

EBNF: Extended BNF

EBNF notation supplements BNF notation with (...), [...], and { ... } to allow simpler specifications.

$(\gamma_1 \mid \dots \mid \gamma_k)$ means

$[\dots] =$

$\{ \dots \}$ means

EBNF: Extended BNF

EBNF notation supplements BNF notation with (\dots) , $[\dots]$, and $\{ \dots \}$ to allow simpler specifications.

$(\gamma_1 \mid \dots \mid \gamma_k)$ means “pick any one of $\gamma_1, \dots, \gamma_k$ ”.

$[\dots] =$

$\{ \dots \}$ means

EBNF: Extended BNF

EBNF notation supplements BNF notation with (\dots) , $[\dots]$, and $\{ \dots \}$ to allow simpler specifications.

$(\gamma_1 \mid \dots \mid \gamma_k)$ means “pick any one of $\gamma_1, \dots, \gamma_k$ ”.

$[\dots] = (\dots \mid \langle \text{empty} \rangle)$ means “... is optional”.

$\{ \dots \}$ means

EBNF: Extended BNF

EBNF notation supplements BNF notation with (...), [...], and { ... } to allow simpler specifications.

$(\gamma_1 \mid \dots \mid \gamma_k)$ means “pick any one of $\gamma_1, \dots, \gamma_k$ ”.

$[\dots] = (\dots \mid \langle \text{empty} \rangle)$ means “... is optional”.

$\{ \dots \}$ means “*zero or more* occurrences of ...”.

EBNF: Extended BNF

EBNF notation supplements BNF notation with (\dots) , $[\dots]$, and $\{ \dots \}$ to allow simpler specifications.

$(\gamma_1 \mid \dots \mid \gamma_k)$ means “pick any one of $\gamma_1, \dots, \gamma_k$ ”.

$[\dots] = (\dots \mid \langle \text{empty} \rangle)$ means “... is optional”.

$\{ \dots \}$ means “*zero or more* occurrences of ...”.

Examples

$\text{Expr} ::= \text{Term } (+ \mid -) \text{Term}$

is equivalent to the following 2 BNF productions:

EBNF: Extended BNF

EBNF notation supplements BNF notation with (\dots) , $[\dots]$, and $\{ \dots \}$ to allow simpler specifications.

$(\gamma_1 \mid \dots \mid \gamma_k)$ means “pick any one of $\gamma_1, \dots, \gamma_k$ ”.

$[\dots] = (\dots \mid \text{<empty>})$ means “... is optional”.

$\{ \dots \}$ means “*zero or more* occurrences of ...”.

Examples

$\text{Expr} ::= \text{Term } (+ \mid -) \text{Term}$

is equivalent to the following 2 BNF productions:

$$\begin{aligned} \text{Expr} ::= & \quad \text{Term} + \text{Term} \\ & \mid \text{Term} - \text{Term} \end{aligned}$$

EBNF: Extended BNF

EBNF notation supplements BNF notation with (\dots) , $[\dots]$, and $\{ \dots \}$ to allow simpler specifications.

$(\gamma_1 \mid \dots \mid \gamma_k)$ means “pick any one of $\gamma_1, \dots, \gamma_k$ ”.

$[\dots] = (\dots \mid \langle \text{empty} \rangle)$ means “... is optional”.

$\{ \dots \}$ means “zero or more occurrences of ...”.

Examples

$\text{Expr} ::= \text{Term } (+ \mid -) \text{Term}$

is equivalent to the following 2 BNF productions:

$$\begin{array}{l} \text{Expr} ::= \quad \text{Term } + \text{Term} \\ \quad \quad \mid \text{Term } - \text{Term} \end{array}$$

$\text{Expr} ::= [+ \mid -] \text{Term } (+ \mid -) \text{Term}$

is equivalent to

$\text{Expr} ::= (+ \mid - \mid \langle \text{empty} \rangle) \text{Term } (+ \mid -) \text{Term}$

which is equivalent to these 6 BNF productions:

EBNF: Extended BNF

EBNF notation supplements BNF notation with (\dots) , $[\dots]$, and $\{ \dots \}$ to allow simpler specifications.

$(\gamma_1 \mid \dots \mid \gamma_k)$ means “pick any one of $\gamma_1, \dots, \gamma_k$ ”.

$[\dots] = (\dots \mid \langle \text{empty} \rangle)$ means “... is optional”.

$\{ \dots \}$ means “zero or more occurrences of ...”.

Examples

$\text{Expr} ::= \text{Term } (+ \mid -) \text{Term}$

is equivalent to the following 2 BNF productions:

$$\begin{aligned} \text{Expr} ::= & \quad \text{Term} + \text{Term} \\ & \quad \mid \text{Term} - \text{Term} \end{aligned}$$

$\text{Expr} ::= [+ \mid -] \text{Term } (+ \mid -) \text{Term}$

is equivalent to

$\text{Expr} ::= (+ \mid - \mid \langle \text{empty} \rangle) \text{Term } (+ \mid -) \text{Term}$

which is equivalent to these 6 BNF productions:

$$\begin{aligned} \text{Expr} ::= & \quad + \text{Term} + \text{Term} \mid - \text{Term} + \text{Term} \mid \text{Term} + \text{Term} \\ & \quad \mid + \text{Term} - \text{Term} \mid - \text{Term} - \text{Term} \mid \text{Term} - \text{Term} \end{aligned}$$

$(\gamma_1 \mid \dots \mid \gamma_k)$ means “pick any one of $\gamma_1, \dots, \gamma_k$ ”.
 $[\dots] = (\dots \mid \langle \text{empty} \rangle)$ means “... is optional”.
 $\{ \dots \}$ means “zero or more occurrences of ...”.

Examples

$\text{Expr} ::= \text{Term } (+ \mid -) \text{Term}$

is equivalent to the following 2 BNF productions:

$\text{Expr} ::=$
 $\quad \text{Term} + \text{Term}$
 $\quad \mid \text{Term} - \text{Term}$

$\text{Expr} ::= [+ \mid -] \text{Term } (+ \mid -) \text{Term}$

is equivalent to

$\text{Expr} ::= (+ \mid - \mid \langle \text{empty} \rangle) \text{Term } (+ \mid -) \text{Term}$

which is equivalent to these 6 BNF productions:

$\text{Expr} ::=$
 $\quad + \text{Term} + \text{Term} \mid - \text{Term} + \text{Term} \mid \text{Term} + \text{Term}$
 $\quad \mid + \text{Term} - \text{Term} \mid - \text{Term} - \text{Term} \mid \text{Term} - \text{Term}$

$(\gamma_1 \mid \dots \mid \gamma_k)$ means “pick any one of $\gamma_1, \dots, \gamma_k$ ”.
 $[\dots] = (\dots \mid \langle \text{empty} \rangle)$ means “... is optional”.
 $\{ \dots \}$ means “zero or more occurrences of ...”.

Examples

$\text{Expr} ::= \text{Term } (+ \mid -) \text{Term}$

is equivalent to the following 2 BNF productions:

$\text{Expr} ::=$
 $\quad \text{Term} + \text{Term}$
 $\quad \mid \text{Term} - \text{Term}$

$\text{Expr} ::= [+ \mid -] \text{Term } (+ \mid -) \text{Term}$

is equivalent to

$\text{Expr} ::= (+ \mid - \mid \langle \text{empty} \rangle) \text{Term } (+ \mid -) \text{Term}$

which is equivalent to these 6 BNF productions:

$\text{Expr} ::=$
 $\quad + \text{Term} + \text{Term} \mid - \text{Term} + \text{Term} \mid \text{Term} + \text{Term}$
 $\quad \mid + \text{Term} - \text{Term} \mid - \text{Term} - \text{Term} \mid \text{Term} - \text{Term}$

$(\gamma_1 \mid \dots \mid \gamma_k)$ means “pick any one of $\gamma_1, \dots, \gamma_k$ ”.
 $[\dots] = (\dots \mid \langle \text{empty} \rangle)$ means “... is optional”.
 $\{ \dots \}$ means “zero or more occurrences of ...”.

Examples

$\text{Expr} ::= \text{Term } (+ \mid -) \text{Term}$

is equivalent to the following 2 BNF productions:

$\text{Expr} ::=$
 $\quad \text{Term} + \text{Term}$
 $\quad \mid \text{Term} - \text{Term}$

$\text{Expr} ::= [+ \mid -] \text{Term } (+ \mid -) \text{Term}$

is equivalent to

$\text{Expr} ::= (+ \mid - \mid \langle \text{empty} \rangle) \text{Term } (+ \mid -) \text{Term}$

which is equivalent to these 6 BNF productions:

$\text{Expr} ::=$
 $\quad + \text{Term} + \text{Term} \mid - \text{Term} + \text{Term} \mid \text{Term} + \text{Term}$
 $\quad \mid + \text{Term} - \text{Term} \mid - \text{Term} - \text{Term} \mid \text{Term} - \text{Term}$

$\text{Expr} ::= \text{Term } \{ (+ \mid -) \text{Term} \}$

is equivalent to an *infinite* collection of BNF productions, including productions such as

$\text{Expr} ::= \text{Term} + \text{Term} + \text{Term} - \text{Term} + \text{Term} - \text{Term} - \text{Term}$

A grammar can only have *finitely* many productions. However, any EBNF rule can be translated into an equivalent *finite* set of BNF productions as follows.

Working from the inside outwards, eliminate all occurrences of (...), [...], and { ... }:

-

-

-

A grammar can only have *finitely* many productions. However, any EBNF rule can be translated into an equivalent *finite* set of BNF productions as follows.

Working from the inside outwards, eliminate all occurrences of (...), [...], and { ... }:

- Replace each $(x_1 \mid \dots \mid x_k)$ with a new nonterminal (D , say) that is defined by these k productions:

$$D ::= x_1 \mid \dots \mid x_k$$

-

-

A grammar can only have *finitely* many productions. However, any EBNF rule can be translated into an equivalent *finite* set of BNF productions as follows.

Working from the inside outwards, eliminate all occurrences of (...), [...], and { ... }:

- Replace each $(x_1 \mid \dots \mid x_k)$ with a new nonterminal (D , say) that is defined by these k productions:
$$D ::= x_1 \mid \dots \mid x_k$$
- Replace each $[x_1 \mid \dots \mid x_k]$ with a new nonterminal (D , say) that is defined by these $k+1$ productions:
$$D ::= \langle \text{empty} \rangle \mid x_1 \mid \dots \mid x_k$$
-

A grammar can only have *finitely* many productions. However, any EBNF rule can be translated into an equivalent *finite* set of BNF productions as follows.

Working from the inside outwards, eliminate all occurrences of (...), [...], and { ... }:

- Replace each $(x_1 \mid \dots \mid x_k)$ with a new nonterminal (D , say) that is defined by these k productions:
$$D ::= x_1 \mid \dots \mid x_k$$
- Replace each $[x_1 \mid \dots \mid x_k]$ with a new nonterminal (D , say) that is defined by these $k+1$ productions:
$$D ::= \langle \text{empty} \rangle \mid x_1 \mid \dots \mid x_k$$
- Replace each $\{x_1 \mid \dots \mid x_k\}$ with a new nonterminal (D , say) that is defined by these $k+1$ productions:
$$D ::= \langle \text{empty} \rangle \mid Dx_1 \mid \dots \mid Dx_k$$

A grammar can only have *finitely* many productions. However, any EBNF rule can be translated into an equivalent *finite* set of BNF productions as follows.

Working from the inside outwards, eliminate all occurrences of (...), [...], and { ... }:

- Replace each $(x_1 \mid \dots \mid x_k)$ with a new nonterminal (D , say) that is defined by these k productions:
$$D ::= x_1 \mid \dots \mid x_k$$
- Replace each $[x_1 \mid \dots \mid x_k]$ with a new nonterminal (D , say) that is defined by these $k+1$ productions:
$$D ::= \langle \text{empty} \rangle \mid x_1 \mid \dots \mid x_k$$
- Replace each $\{x_1 \mid \dots \mid x_k\}$ with a new nonterminal (D , say) that is defined by these $k+1$ productions:
$$D ::= \langle \text{empty} \rangle \mid Dx_1 \mid \dots \mid Dx_k$$

Here k may be 1. Thus $\{ \textit{Digit} \}$ can be replaced with a new nonterminal ($\textit{DigitSeq}$, say) that is defined by:

$$\textit{DigitSeq} ::= \langle \text{empty} \rangle \mid \textit{DigitSeq} \textit{Digit}$$

Example: We now use the above method to translate

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$

(*)

into a finite set of BNF productions.

Example: We now use the above method to translate

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$ (*)

into a finite set of BNF productions.

1. First, replace $(+ \mid -)$ with a nonterminal Op
defined by: $\text{Op} ::= + \mid -$
(*) becomes:

Example: We now use the above method to translate

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$ (*)

into a finite set of BNF productions.

1. First, replace $(+ \mid -)$ with a nonterminal Op defined by: $\text{Op} ::= + \mid -$

(*) becomes: $\text{Expr} ::= [+ \mid -] \text{Term} \{ \text{Op} \text{Term} \}$ (**)

Example: We now use the above method to translate

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$ (*)

into a finite set of BNF productions.

1. First, replace $(+ \mid -)$ with a nonterminal Op defined by: $\text{Op} ::= + \mid -$

(*) becomes: $\text{Expr} ::= [+ \mid -] \text{Term} \{ \text{Op} \text{Term} \}$ (**)

2. Next, replace $\{ \text{Op} \text{Term} \}$ with a nonterminal Rest defined by: $\text{Rest} ::= \langle \text{empty} \rangle \mid \text{Rest} \text{Op} \text{Term}$
(**) becomes:

Example: We now use the above method to translate

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$ (*)

into a finite set of BNF productions.

1. First, replace $(+ \mid -)$ with a nonterminal Op defined by: $\text{Op} ::= + \mid -$

(*) becomes: $\text{Expr} ::= [+ \mid -] \text{Term} \{ \text{Op} \text{Term} \}$ (**)

2. Next, replace $\{ \text{Op} \text{Term} \}$ with a nonterminal Rest defined by: $\text{Rest} ::= \langle \text{empty} \rangle \mid \text{Rest} \text{Op} \text{Term}$

(**) becomes: $\text{Expr} ::= [+ \mid -] \text{Term} \text{Rest}$ (***)

Example: We now use the above method to translate

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$ (*)

into a finite set of BNF productions.

1. First, replace $(+ \mid -)$ with a nonterminal **Op** defined by:

$\text{Op} ::= + \mid -$

(*) becomes: $\text{Expr} ::= [+ \mid -] \text{Term} \{ \text{Op} \text{Term} \}$ (**)

2. Next, replace $\{ \text{Op} \text{Term} \}$ with a nonterminal **Rest** defined by:

$\text{Rest} ::= \langle \text{empty} \rangle \mid \text{Rest Op Term}$

(**) becomes: $\text{Expr} ::= [+ \mid -] \text{Term} \text{Rest}$ (***)

3. Finally, replace $[+ \mid -]$ with a nonterminal **OptSign** defined by

$\text{OptSign} ::= \langle \text{empty} \rangle \mid + \mid -$

(***) becomes:

Example: We now use the above method to translate

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$ (*)

into a finite set of BNF productions.

1. First, replace $(+ \mid -)$ with a nonterminal Op defined by:

$\text{Op} ::= + \mid -$

(*) becomes: $\text{Expr} ::= [+ \mid -] \text{Term} \{ \text{Op} \text{Term} \}$ (**)

2. Next, replace $\{ \text{Op} \text{Term} \}$ with a nonterminal Rest defined by:

$\text{Rest} ::= \langle \text{empty} \rangle \mid \text{Rest} \text{Op} \text{Term}$

(**) becomes: $\text{Expr} ::= [+ \mid -] \text{Term} \text{Rest}$ (***)

3. Finally, replace $[+ \mid -]$ with a nonterminal OptSign defined by

$\text{OptSign} ::= \langle \text{empty} \rangle \mid + \mid -$

(***) becomes: $\text{Expr} ::= \text{OptSign} \text{Term} \text{Rest}$

Example: We now use the above method to translate

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \} \quad (*)$

into a finite set of BNF productions.

1. First, replace $(+ \mid -)$ with a nonterminal **Op** defined by:

$\text{Op} ::= + \mid -$

$(*)$ becomes: $\text{Expr} ::= [+ \mid -] \text{Term} \{ \text{Op} \text{Term} \} \quad (**)$

2. Next, replace $\{ \text{Op} \text{Term} \}$ with a nonterminal **Rest** defined by:

$\text{Rest} ::= \langle \text{empty} \rangle \mid \text{Rest Op Term}$

$(**)$ becomes: $\text{Expr} ::= [+ \mid -] \text{Term} \text{Rest} \quad (***)$

3. Finally, replace $[+ \mid -]$ with a nonterminal **OptSign** defined by

$\text{OptSign} ::= \langle \text{empty} \rangle \mid + \mid -$

$(***)$ becomes: $\text{Expr} ::= \text{OptSign} \text{Term} \text{Rest}$

The result is the following set of 8 BNF productions:

$\text{Expr} ::= \text{OptSign} \text{Term} \text{Rest}$

$\text{OptSign} ::= \langle \text{empty} \rangle \mid + \mid -$

$\text{Rest} ::= \langle \text{empty} \rangle \mid \text{Rest Op Term}$

$\text{Op} ::= + \mid -$

While the above method is general, it will often **not** find a simplest BNF equivalent of the given EBNF rule. For example, here is a simpler BNF equivalent of the EBNF rule `Expr ::= [+ | -] Term {(+ | -) Term}` considered above:

While the above method is general, it will often **not** find a simplest BNF equivalent of the given EBNF rule.

For example, here is a simpler BNF equivalent of the EBNF rule `Expr ::= [+ | -] Term {(+ | -) Term}` considered above:

`Expr ::= Term | + Term | - Term | Expr + Term | Expr - Term`

While the above method is general, it will often not find a simplest BNF equivalent of the given EBNF rule.

For example, here is a simpler BNF equivalent of the EBNF rule `Expr ::= [+ | -] Term {(+ | -) Term}` considered above:
`Expr ::= Term | + Term | - Term | Expr + Term | Expr - Term`

EBNF can be used just like BNF to define what it means for a source code file to be “syntactically valid”:

For many programming languages L, we can construct ~~a grammar~~ **an EBNF specification** *G* (whose terminals are L’s tokens) such that:

$T_1 \dots T_n$ belongs to the language generated by *G*
if (and, roughly speaking, only if) $T_1 \dots T_n$ is the
sequence of tokens of a possibly valid L source file.

We can then say a particular L source file is syntactically valid if its sequence of tokens belongs to the language generated by the ~~grammar~~ **EBNF specification** *G*.

Note: Replacing one identifier with another and replacing a literal constant with another of the same type (e.g., changing 9/x to 3/y) will not affect the syntactic validity of a source file, as it won’t change its sequence of tokens!

A Rule to Follow When Writing EBNF Specifications

In EBNF, when any of the characters `| () [] { }` is a terminal, that terminal should be put in single quotes to make it clear that the character is not being used with its EBNF meaning!

Sethi says the following about this on p. 47 of his book (p. 48 of the course reader):

Symbols such as `{` and `}`, which have a special status in a language description, are called *metasymbols*.

EBNF has many more metasymbols than BNF. Furthermore, these same symbols can also appear in the syntax of a language—the index `i` in `A[i]` is not optional—so care is needed to distinguish tokens from metasymbols. Confusion between tokens and metasymbols will be avoided by enclosing tokens within single quotes if needed, as in `'('`.

An EBNF version of the grammar in Fig. 2.6 is

```
<expression> ::= <term> { (+|-) <term> }  
    <term> ::= <factor> { (*|/) <factor> }  
    <factor> ::= '(' <expression> ')' | name | number
```


Frequently Useful EBNF Equivalences

An *EBNF form* is “an expression that can be the right side of a valid EBNF rule”.

Frequently Useful EBNF Equivalences

An *EBNF form* is “an expression that can be the right side of a valid EBNF rule”. More precisely, γ is an *EBNF form* just if one of the following is true:

Frequently Useful EBNF Equivalences

An EBNF form is “an expression that can be the right side of a valid EBNF rule”. More precisely, γ is an EBNF form just if one of the following is true:

1. γ is a terminal, or a nonterminal, or $\langle \text{empty} \rangle$.
2. γ is (e) for some EBNF form e .
3. γ is $e_1 \dots e_n$ for some EBNF forms e_1, \dots, e_n .
4. γ is $e_1 \mid \dots \mid e_n$ for some EBNF forms e_1, \dots, e_n .
5. γ is $[e]$ for some EBNF form e .
6. γ is $\{e\}$ for some EBNF form e .

Frequently Useful EBNF Equivalences

An EBNF form is “an expression that can be the right side of a valid EBNF rule”. More precisely, γ is an EBNF form just if one of the following is true:

1. γ is a terminal, or a nonterminal, or $\langle \text{empty} \rangle$.
2. γ is (e) for some EBNF form e .
3. γ is $e_1 \dots e_n$ for some EBNF forms e_1, \dots, e_n .
4. γ is $e_1 \mid \dots \mid e_n$ for some EBNF forms e_1, \dots, e_n .
5. γ is $[e]$ for some EBNF form e .
6. γ is $\{e\}$ for some EBNF form e .

Now let α and β be any EBNF forms. Then:

-
-

Frequently Useful EBNF Equivalences

An EBNF form is “an expression that can be the right side of a valid EBNF rule”. More precisely, γ is an EBNF form just if one of the following is true:

1. γ is a terminal, or a nonterminal, or $\langle \text{empty} \rangle$.
2. γ is (e) for some EBNF form e .
3. γ is $e_1 \dots e_n$ for some EBNF forms e_1, \dots, e_n .
4. γ is $e_1 \mid \dots \mid e_n$ for some EBNF forms e_1, \dots, e_n .
5. γ is $[e]$ for some EBNF form e .
6. γ is $\{e\}$ for some EBNF form e .

Now let α and β be any EBNF forms. Then:

- $A ::= \begin{array}{c} A(\alpha) \\ \mid \\ \beta \end{array}$ is equivalent to
-

Frequently Useful EBNF Equivalences

An EBNF form is “an expression that can be the right side of a valid EBNF rule”. More precisely, γ is an EBNF form just if one of the following is true:

1. γ is a terminal, or a nonterminal, or $\langle \text{empty} \rangle$.
2. γ is (e) for some EBNF form e .
3. γ is $e_1 \dots e_n$ for some EBNF forms e_1, \dots, e_n .
4. γ is $e_1 \mid \dots \mid e_n$ for some EBNF forms e_1, \dots, e_n .
5. γ is $[e]$ for some EBNF form e .
6. γ is $\{e\}$ for some EBNF form e .

Now let α and β be any EBNF forms. Then:

- $A ::= \begin{matrix} A(\alpha) \\ \mid \\ \beta \end{matrix}$ is equivalent to $A ::= (\beta) \{\alpha\}$
-

Frequently Useful EBNF Equivalences

An EBNF form is “an expression that can be the right side of a valid EBNF rule”. More precisely, γ is an EBNF form just if one of the following is true:

1. γ is a terminal, or a nonterminal, or $\langle \text{empty} \rangle$.
2. γ is (e) for some EBNF form e .
3. γ is $e_1 \dots e_n$ for some EBNF forms e_1, \dots, e_n .
4. γ is $e_1 \mid \dots \mid e_n$ for some EBNF forms e_1, \dots, e_n .
5. γ is $[e]$ for some EBNF form e .
6. γ is $\{e\}$ for some EBNF form e .

Now let α and β be any EBNF forms. Then:

- $A ::= A(\alpha) \mid \beta$ is equivalent to $A ::= (\beta) \{ \alpha \}$
- $A ::= (\alpha) A \mid \beta$ is equivalent to

Frequently Useful EBNF Equivalences

An EBNF form is “an expression that can be the right side of a valid EBNF rule”. More precisely, γ is an EBNF form just if one of the following is true:

1. γ is a terminal, or a nonterminal, or $\langle \text{empty} \rangle$.
2. γ is (e) for some EBNF form e .
3. γ is $e_1 \dots e_n$ for some EBNF forms e_1, \dots, e_n .
4. γ is $e_1 \mid \dots \mid e_n$ for some EBNF forms e_1, \dots, e_n .
5. γ is $[e]$ for some EBNF form e .
6. γ is $\{e\}$ for some EBNF form e .

Now let α and β be any EBNF forms. Then:

- $A ::= \underset{\beta}{A(\alpha)}$ is equivalent to $A ::= (\beta) \{ \alpha \}$
- $A ::= \underset{\beta}{(\alpha) A}$ is equivalent to $A ::= \{ \alpha \} (\beta)$

Example: Translate $\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$
into BNF *without introducing new nonterminals*.

Solution:

Example: Translate $\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$
into BNF *without introducing new nonterminals*.

Solution:

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$

is equivalent to

$A ::= (\beta) \{ \alpha \}$

if A is Term , β is $[+ \mid -]$, and α is $(+ \mid -) \text{Term}$.

Example: Translate $\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$
into BNF *without introducing new nonterminals*.

Solution:

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$

is equivalent to

$A ::= (\beta) \{ \alpha \}$

if A is Expr , β is $+$ or $-$, and α is $(\text{Expr}) \{ \text{Expr} \}$.

Example: Translate $\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$
into BNF *without introducing new nonterminals*.

Solution:

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$

is equivalent to

$A ::= (\beta) \{ \alpha \}$

if A is Expr , β is $[+ \mid -] \text{Term}$, and α is .

Example: Translate $\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$
into BNF *without introducing new nonterminals*.

Solution:

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$

is equivalent to

$A ::= (\beta) \{ \alpha \}$

if A is Expr , β is $[+ \mid -] \text{Term}$, and α is $(+ \mid -) \text{Term}$.

Example: Translate $\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$
into BNF *without introducing new nonterminals*.

Solution:

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$

is equivalent to

$A ::= (\beta) \{ \alpha \}$

if A is Expr , β is $[+ \mid -] \text{Term}$, and α is $(+ \mid -) \text{Term}$.

So, since

$A ::= (\beta) \{ \alpha \}$ is equivalent to $A ::= A(\alpha)$
| β

we deduce that

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$

is equivalent to

$\text{Expr} ::= \text{Expr} \{ (+ \mid -) \text{Term} \}$
| $[+ \mid -] \text{Term}$

which can be expanded into these five BNF productions:

Example: Translate $\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$
into BNF *without introducing new nonterminals*.

Solution:

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$

is equivalent to

$A ::= (\beta) \{ \alpha \}$

if A is Expr , β is $[+ \mid -] \text{Term}$, and α is $(+ \mid -) \text{Term}$.

So, since

$A ::= (\beta) \{ \alpha \}$ is equivalent to $A ::= A(\alpha)$
| β

we deduce that

$\text{Expr} ::= [+ \mid -] \text{Term} \{ (+ \mid -) \text{Term} \}$

is equivalent to

$\text{Expr} ::= \text{Expr} \{ (+ \mid -) \text{Term} \}$
| $[+ \mid -] \text{Term}$

which can be expanded into these five BNF productions:

$\text{Expr} ::= \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Term}$

2nd Example: Translate the five BNF productions

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$
into a non-recursive EBNF rule.

Solution:

2nd Example: Translate the five BNF productions

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$
into a non-recursive EBNF rule.

Solution:

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$
can be rewritten in EBNF as

2nd Example: Translate the five BNF productions

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$
into a non-recursive EBNF rule.

Solution:

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$

can be rewritten in EBNF as

$\text{Expr} ::= \text{Expr} (+ \text{Term} \mid - \text{Term})$
 $\mid (\text{<empty>} \mid + \mid -) \text{Term}$

which can be simplified to

2nd Example: Translate the five BNF productions

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$
into a non-recursive EBNF rule.

Solution:

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$

can be rewritten in EBNF as

$\text{Expr} ::= \text{Expr} (+ \text{Term} \mid - \text{Term})$
 $\mid (<\text{empty}> \mid + \mid -) \text{Term}$

which can be simplified to

$\text{Expr} ::= \text{Expr} ((+ \mid -) \text{Term})$
 $\mid [+ \mid -] \text{Term} \quad (*)$

2nd Example: Translate the five BNF productions

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$
into a non-recursive EBNF rule.

Solution:

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$

can be rewritten in EBNF as

$\text{Expr} ::= \text{Expr} (+ \text{Term} \mid - \text{Term})$
 $\mid (\langle \text{empty} \rangle \mid + \mid -) \text{Term}$

which can be simplified to

$\text{Expr} ::= \text{Expr} ((+ \mid -) \text{Term})$
 $\mid [+ \mid -] \text{Term} \quad (*)$

This is of the form

$A ::= A(\alpha)$ if A is , α is ,
 $\mid \beta$ and β is .

2nd Example: Translate the five BNF productions

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$
into a non-recursive EBNF rule.

Solution:

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$

can be rewritten in EBNF as

$\text{Expr} ::= \text{Expr} (+ \text{Term} \mid - \text{Term})$
 $\quad \mid (\langle \text{empty} \rangle \mid + \mid -) \text{Term}$

which can be simplified to

$\text{Expr} ::= \text{Expr} ((+ \mid -) \text{Term})$
 $\quad \mid [+ \mid -] \text{Term} \quad (*)$

This is of the form

$A ::= A(\alpha)$ if A is Expr , α is ,
 $\quad \mid \beta$ and β is .

2nd Example: Translate the five BNF productions

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$
into a non-recursive EBNF rule.

Solution:

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$

can be rewritten in EBNF as

$\text{Expr} ::= \text{Expr} (+ \text{Term} \mid - \text{Term})$
 $\mid (\langle \text{empty} \rangle \mid + \mid -) \text{Term}$

which can be simplified to

$\text{Expr} ::= \text{Expr} ((+ \mid -) \text{Term})$
 $\mid [+ \mid -] \text{Term} \quad (*)$

This is of the form

$A ::= A(\alpha)$ if A is Expr , α is $(+ \mid -) \text{Term}$,
 $\mid \beta$ and β is .

2nd Example: Translate the five BNF productions

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$
into a non-recursive EBNF rule.

Solution:

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$

can be rewritten in EBNF as

$\text{Expr} ::= \text{Expr} (+ \text{Term} \mid - \text{Term})$
 $\mid (\langle \text{empty} \rangle \mid + \mid -) \text{Term}$

which can be simplified to

$\text{Expr} ::= \text{Expr} ((+ \mid -) \text{Term})$
 $\mid [+ \mid -] \text{Term} \quad (*)$

This is of the form

$A ::= A(\alpha)$ if A is Expr , α is $(+ \mid -) \text{Term}$,
 $\mid \beta$ and β is $[+ \mid -] \text{Term}$.

2nd Example: Translate the five BNF productions

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$
into a non-recursive EBNF rule.

Solution:

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$

can be rewritten in EBNF as

$$\begin{aligned} \text{Expr} ::= & \text{Expr} ((+ \mid -) \text{Term}) \\ & \mid [+ \mid -] \text{Term} \end{aligned} \quad (*)$$

This is of the form

$$\begin{aligned} A ::= & A(\alpha) && \text{if } A \text{ is } \text{Expr}, \alpha \text{ is } (+ \mid -) \text{Term}, \\ & \mid \beta && \text{and } \beta \text{ is } [+ \mid -] \text{Term}. \end{aligned}$$

2nd Example: Translate the five BNF productions

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$
into a non-recursive EBNF rule.

Solution:

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$

can be rewritten in EBNF as

$\text{Expr} ::= \text{Expr} ((+ \mid -) \text{Term})$
 $\quad \mid [+ \mid -] \text{Term} \quad (*)$

This is of the form

$A ::= A(\alpha)$ if A is Expr, α is $(+ \mid -) \text{Term}$,
 $\quad \mid \beta$ and β is $[+ \mid -] \text{Term}$.

So, since $A ::= A(\alpha)$ is equivalent to $A ::= (\beta) \{ \alpha \}$
 $\quad \mid \beta$
 $(*)$ is equivalent to:

2nd Example: Translate the five BNF productions

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$
into a non-recursive EBNF rule.

Solution:

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$

can be rewritten in EBNF as

$\text{Expr} ::= \text{Expr} ((+ \mid -) \text{Term})$
 $\quad \mid [+ \mid -] \text{Term} \quad (*)$

This is of the form

$A ::= A(\alpha)$ if A is Expr, α is $(+ \mid -) \text{Term}$,
 $\quad \mid \beta$ and β is $[+ \mid -] \text{Term}$.

So, since $A ::= A(\alpha)$ is equivalent to $A ::= (\beta) \{\alpha\}$
 $\quad \mid \beta$

(*) is equivalent to:

$\text{Expr} ::= ([+ \mid -] \text{Term}) \{(+ \mid -) \text{Term}\}$

This can be simplified to:

2nd Example: Translate the five BNF productions

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$
into a non-recursive EBNF rule.

Solution:

$\text{Expr} ::= \text{Term} \mid + \text{Term} \mid - \text{Term} \mid \text{Expr} + \text{Term} \mid \text{Expr} - \text{Term}$

can be rewritten in EBNF as

$$\begin{aligned} \text{Expr} ::= & \text{Expr} ((+ \mid -) \text{Term}) \\ & \mid [+ \mid -] \text{Term} \end{aligned} \quad (*)$$

This is of the form

$$\begin{aligned} A ::= & A(\alpha) && \text{if } A \text{ is Expr, } \alpha \text{ is } (+ \mid -) \text{Term,} \\ & \mid \beta && \text{and } \beta \text{ is } [+ \mid -] \text{Term.} \end{aligned}$$

So, since $A ::= A(\alpha) \mid \beta$ is equivalent to $A ::= (\beta) \{\alpha\}$

(*) is equivalent to:

$\text{Expr} ::= ([+ \mid -] \text{Term}) \{(+ \mid -) \text{Term}\}$

This can be simplified to:

$\text{Expr} ::= [+ \mid -] \text{Term} \{(+ \mid -) \text{Term}\}$