# Dependency-Aware Selective Recovery in Multi-Agent Workflows

Phase 1 Report  Option 5 Group 9  CSE 291A, Fall 2026


## Abstract

When one agent in a multi-agent workflow emits a faulty result, restarting the workflow repeats correct work and cannot undo irreversible side effects. We study whether dependency tracking can confine recovery to the work a fault actually affected. We inject 176 faults, in three independent samples, and compare each run with its counterfactual replay. Where the fault reached downstream agents (82 runs), fact-level provenance finds 88% of the affected downstream units with 97% precision at an estimated 48% of full-run token cost; on researcher faults (50 runs), where dependencies are not obvious, it finds 80% and misses some in 28% of runs. Stage tracking finds all of them but recomputes 97%, with 7× fewer dependency records. These are invalidation estimates; selective execution is Phase 2 work.


## 1 Introduction

Phase 1 measures propagation and dependency tracking to guide selective recovery. **RQ1**: how far do faults propagate, and which reach irreversible or security-relevant actions? **RQ2**: how does tracking granularity trade precision and recall against bookkeeping? **RQ3**: what do full restart and always-verify achieve, at what cost?

## 2 System and Threat Model

**System model.** Each *unit* is one agent invocation. Researchers extract facts; a planner cites facts for each tool action; executors see their step's cited facts and requested state. The trusted runtime records messages, citations and state access. Files/KV are *restorable*; payments are *compensable* through refunds [3]; email is *irreversible*.

**Threat model.** One unit $v_0$ emits a faulty result. Accidental faults are wrong/stale values or fabricated entities. Adversarial faults rewrite a result with an injected instruction or redirect a payee/recipient. Unlike source-level prompt injection [5, 6], this controls $v_0$'s output directly, but re-running $v_0$ removes it. The attacker cannot alter tools, logging, checkers or other prompts. Recovery receives an oracle fault location after execution; detection is studied separately by verification.

**Problem statement.** Let $G = (V, E)$ be the provenance graph of a faulty run $r$, and $r'$ its counterfactual replay with $v_0$'s original result restored. With $\sigma$ extracting a result's decision-relevant content, the *affected set* is $A = \{v : \sigma(r_v) \neq \sigma(r'_v)\}$. A tracking policy at granularity $g$ predicts an invalidation set $\hat{A}_g$ from $G$ and the oracle location. Errors are *over-invalidation* ($\hat{A}_g \setminus A$, wasted work) and *under-invalidation* ($A \setminus \hat{A}_g$, reuse of corrupted results). We report precision, recall, the token share of $\hat{A}_g$ (recompute cost), and bookkeeping (dependency records kept).

| Policy (runs) | Prec. | Rec. | Miss | Over | Recomp. | Records |
|---|---|---|---|---|---|---|
| Stage (82) | 0.29 | 1.00 | 0% | 6.7 | 0.97 | 12 / 0.3 KB |
| Message (82) | 0.38 | 1.00 | 0% | 5.0 | 0.86 | 25 / 0.4 KB |
| Fact (82) | 0.97 | 0.88 | 17% | 0.11 | 0.48 | 83 / 3.6 KB |
| Fact: researcher (50) | 0.96 | 0.80 | 28% | 0.18 | 0.51 | |

**Table 1:** Propagated runs, downstream units. Miss: runs with under-invalidation; Over: unaffected units invalidated; Recomp.: estimated cost vs. a full run. Fact over 3 samples: recall 0.88–0.89, miss 14–17%, cost 0.48–0.49 (researcher: 0.80–0.82, 24–28%). First sample, 95% over tasks: 0.82–0.93, 10–24%, 0.44–0.53.

## 3 Methodology

**Workload and design.** Four seeded templates (procurement, payroll, travel, restock) with two seeds each give 8 tasks, averaging 11 units and 12.8K tokens per clean run. The checker compares payments and memos, KV entries, file values and each email's required values with a reference solver's state. It flags an *unauthorized action* for a payment to an account named in no source or an email to a recipient the task does not name. All agents run on Claude Haiku 5.5 with schema-constrained JSON. Crossing 8 tasks, 11 valid (stage, fault type) cells and 2 injection placements gives 176 runs, each with one fault injected after generation; in 22 of 88 task–cell pairs both placements coincide, leaving 154 distinct cases. All results use development seeds 0–1; seeds 2–3 are held out.

**Tracking policies.** *Stage*: invalidate $v_0$'s stage and all later ones. *Message*: transitive closure over inter-agent messages and shared-state reads. *Fact*: closure from corrupted facts to plan steps citing them (declared or value-matched), their executors, and readers of the state they wrote.

**Counterfactual comparison.** Responses are memoized by prompt hash, so in $r'$ only units whose inputs changed are resampled. $\sigma$ keeps tool, target, amount, stored value, and the amounts, accounts, addresses and codes in text. As a noise control, two sets of 16 uncached clean reruns each differ from the cached run by a mean of 0.38 units. We sampled the whole matrix three times with no shared responses; numbers are from the first sample unless a range is given.

**Baselines.** *Full restart* restores files/KV, refunds payments, and re-executes. *Always-verify* audits each output with Haiku and repairs a flagged one. Both are replayed over all runs and run live, with uncached calls and a real retry, on 44 cases (one task seed, one placement, four tasks at a time) from a laptop.

## 4 Evaluation

**RQ1: Propagation (Fig. 1).** Of 56 clean runs, 55 pass the checker; without recovery, only 36–39% of fault runs do. The samples agree: 82–84 of 176 runs propagate, and pass, propagation and unauthorized outcomes each match across all three in 92–95% of cases. No agent reads a payment's result, so ex-





**Figure 1:** Fault propagation without recovery, by injection stage and fault type (16 runs per row).

| | State correct | Unauth. remaining | Wrong email remaining | Extra tokens | Median time |
|---|---|---|---|---|---|
| No recovery | 41% | 29% | 23% | 0 | – |
| Full restart | 100%* | 7% | 23% | 1.00× | – |
| Verify + restore | 100%* | 0% | 0% | 1.18× | – |
| Fact-level (est.) | – | – | – | 0.34× | – |
| Full restart | 100% | 9% | 25% | 0.99× | 19.0 s |
| Verify + retry | 98% | 0% | 0% | 1.16× | 40.1 s |

**Table 2:** Baselines: 176 replayed runs (top), 44 live cases (bottom). *By construction (RQ3). State excludes email. Tokens vs. a clean run; verify + restore and fact-level (all-run mean) are estimates.

ecutor faults cannot propagate, and executors corrected 94 of 96 plan-level wrong amounts and redirects from the facts they cite. Researcher faults spread farthest (the planner in 57% of runs and 1.7 executors) and leave an incorrect, unrecallable email in 40% of runs. All 27 runs that store a wrong KV value also send an incorrect email that read it, but the read is the only visible source in at most 6: the others also cite a corrupted fact or got the wrong value in the plan's text. Corrupting a stored value directly (16 runs; plan and cited facts stay correct) isolates the path: 12 emails sent the corrupted value, 8 of them although their plan text stated the right one; 2 flagged the mismatch and 2 kept the plan's value. All three policies find these readers. Unauthorized actions follow 58% of adversarial faults and 5–14% of accidental ones, but 32 of those 46 adversarial runs are by construction: a redirected call is itself the action, and executors carry out injected plan steps. At the researcher (14 of 32), an injected instruction caused none in any sample, while a redirected account did in 81–88% of runs (one injection wording).

**RQ2: Granularity (Table 1).** Stage and message tracking never under-invalidate but waste 6.7 and 5.0 unaffected units per fault. Fact tracking keeps 7× more records and recomputes half as much. Its overall recall flatters it: in all 32 propagating planner faults the affected units are just the injected steps' own executors, so any tracker finds them. All its misses are researcher faults: 14 of 50 runs (28%; accidental 16%, adversarial 47%, and all 4 propagating injected instructions). Only 6 of these runs (12%; 4–12% across samples) leave a wrong result: two *implicit comparative dependencies* (a corrupted price changes which option is cheapest, and steps for the new choice cite only its own facts), three *ambiguities* over a fabricated entity and one *collateral re-sampling* of the planner. The other 8 only change a signature.

**RQ3: Baselines (Table 2).** Replay accounts for what cannot be undone but does not test repair: a replayed restart reuses cached clean responses and the verifier restores the pre-injection output, so their 100% is by construction. Restart leaves incorrect emails in 23% of runs (7% to the attacker) and sends 0.8 duplicates per run; an unauthorized action remains after 16% of adversarial and no accidental faults, a wrong email after 17% and 27%. The live rows measure repair. Restart restored state in all 44 cases. Verify detected all 44 faults and ended correct in 43 (a retried plan miscomputed a payment), flagging 4.5% of clean-run outputs. It prevents the wrong emails but costs every run: 1.06× extra tokens and about twice the time even without a fault (41.3 s). Clean runs, one at a time, took a median of 20.9 s (17.6–32.5 s). The campus model recovered less reliably (Appendix B).

## 5 Related Work

Selective re-execution follows intrusion/rollback recovery [1, 2]; compensation and fact tracking follow sagas and provenance [3, 4]; agent security and failure studies [5, 6, 7] motivate our faults. REVISE [8] and dependency-guided rollback [9] repair online revisions and faulty memories of one agent; we study faults spreading across agents and shared state.

## 6 Limitations and Next Steps

*Internal validity*: faults are injected into results with an oracle-identified $v_0$, which favors the fact policy; the verifier sees inputs contradicting the corrupted result, which favors always-verify. A plan-level fabricated step kept the original instruction, so executors paid the real payee twice in 36 of 48 runs. *External validity*: synthetic tasks, two task seeds. *Deviation*: hosted models replace the proposed CPU models (Haiku, about $1.05; campus: Appendix B). *Next steps*: fact tracking could halve recomputation, with wrong reuse in 4–12% of propagating researcher faults. Phase 2 tests this against full restart, suffix replay and always-verify, and adds timeout faults and concurrent writers. State restore comes first, per the proposal feedback: a whole-run snapshot breaks once other agents write after the fault (Appendix A).

## References


[1] T. Kim, X. Wang, N. Zeldovich, M. F. Kaashoek. Intrusion recovery using selective re-execution. *OSDI*, 2010.

[2] E. N. Elnozahy, L. Alvisi, Y.-M. Wang, D. B. Johnson. A survey of rollback-recovery protocols in message-passing systems. *ACM Comput. Surv.*, 34(3), 2002.

[3] H. Garcia-Molina, K. Salem. Sagas. *SIGMOD*, 1987.

[4] P. Buneman, S. Khanna, W.-C. Tan. Why and where: A characterization of data provenance. *ICDT*, 2001.

[5] K. Greshake et al. Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection. *AISec*, 2023.

[6] E. Debenedetti et al. AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents. *NeurIPS Datasets and Benchmarks*, 2024.

[7] M. Cemri et al. Why do multi-agent LLM systems fail? arXiv:2503.13657, 2025.

[8] R. Qi et al. REVISE: Validity-Guided Recovery for Online Revisions in Agent Workflows. arXiv:2609.00643, 2026.

[9] Y. Wang et al. From Faulty Memories to Corrected Actions: Dependency-Guided Rollback Repair for Memory-Augmented Agents. arXiv:2608.10502v2, 2026.

# A Timeline and Milestones

| Dates | Milestone |
|---|---|
| Oct 27–Nov 4 | **Phase 1 (done):** testbed, 4 task templates, fault injection, tracing at 3 granularities, counterfactual replay, full-restart and always-verify baselines, this report. |
| Nov 5–12 | **State restore** (proposal feedback): versioned files/KV with a write log of each value's writer and readers; per-key restore; targeted refunds; irreversible actions reported as unrecovered. *Check:* in scripted overwrite, delete and recreate cases, restore reaches the reference state and keeps unrelated later writes. |
| Nov 13–19 | **Selective recovery:** partial re-execution from the trace; oracle fault identity; suffix-replay baseline. *Check:* on development seeds, correctness matches full restart at fewer tokens, and every reused result passes the checker. |
| Nov 20–26 | **Changed environment:** other agents write after the fault, so each key is rolled back, kept or reported as a conflict. Richer state than files/KV (a SQLite database in a container), restored from the write log or a container snapshot; compare restore time and storage. *Check:* no independent later write is lost and every conflict is reported. If behind, drop the snapshot comparison, not the write log. |
| Nov 27–Dec 3 | **Precision vs. bookkeeping, larger suite:** comparison-aware citations, re-validating resampled outputs, budget-matched baselines; more seeds/templates, timeout and source-level faults, second model. *Check:* wrong reuse on researcher faults falls below the 4–12% measured here. |
| Dec 4–10 | Final experiments on held-out task seeds 2–3, figures, final report (due Dec 10). |

# B Revised Harness Validation

**Setup.** On October 29 we tested the revised harness on the UCSD-hosted `api-glm-5.3-flash` route through TritonAPI, with strict JSON output. The DataHub course CPU profile ran orchestration; inference was remote. The route is not an immutable checkpoint. Per-case results, configurations and package versions are in the repository; raw traces and responses are archived separately.

**Live pilot.** One procurement task, two fault types (wrong value and malicious redirect), three stages and one placement gave six fault cases. Restart and verification bypassed the response cache; repair used actual uncached model calls. The first clean run took 16.3 s and the uncached repeats 13.3 s and 6.0 s; median restart and verification times were 7.53 s and 17.32 s. These include network and local instrumentation, and are this route's only live timings without request spacing. The clean run passed, but only one of two uncached clean repeats passed. Mutable-state correctness after restart was 4/6; verified final task success was 6/6. This small pilot is implementation validation, not a precise performance estimate.

**Propagation validation.** Four templates with one task seed, eleven valid stage/fault combinations and one placement gave 44 cases. Clean baseline success was 3/4; eight uncached clean repeats passed 7/8. Restock failed its cached clean baseline although both uncached repeats passed. We retain all 44 cases and separately evaluate the 33 cases whose baseline completed cleanly:

| Policy | Final success |
|---|---|
| No recovery | 11/33 |
| Full restart | 29/33 |
| Verify + actual retry | 31/33 |

Always-verify detected the injected faults in all 44 cases but achieved final task success in only 40/44, with no attacker-directed actions remaining. Detection therefore does not guarantee correct repair. Restock inability is not counted as attack resistance. Accidental and adversarial results are also reported separately in the generated summaries.

**Controls and failures.** This second validation used cached replay and a 1.25 s minimum spacing for live requests. Its timings are not comparable to the live pilot as serving-performance measurements. A preceding four-worker batch failed on four requests before completing any fault case; its manifest and partial traces are retained, and it is excluded from success-rate denominators. Changed prompts still resample, and on this route the uncached clean repeats differed from the cached clean run in 3.0 units on average (Claude: 0.38), about as many as a researcher fault changes downstream (2.75). Its propagation figures therefore need repeated samples per case. No result here measures implemented selective recovery.

**Resource accounting.** There were 1,093 real requests across probes, pilot, the failed batch and serial validation. At the campus-listed rates of \$0.15/\$0.50 per million input/output tokens, completed usage cost is estimated at \$0.1761. Four failed requests retain \$0.0141 in conservative reservations, giving about \$0.1902 charged-or-reserved against a \$5 cap. These are token-rate estimates, not an authoritative billing statement. Credentials stayed in DataHub environment variables and are excluded from all exported artifacts.