Dependency-Aware Selective Recovery in Multi-Agent Workflows

Phase 1 Report: Fault Propagation, Dependency Tracking, and Baselines

Option 5 Group 9 CSE 291A, Fall 2026

Abstract

When one agent in a multi-agent workflow emits a faulty result, the standard remedy, restarting the workflow, repeats correct work and cannot undo irreversible side effects. We study whether dependency tracking can confine recovery to the work a fault actually affected. We inject 176 faults and compare each run with its counterfactual replay. In the 82 runs where the fault reached downstream agents, fact-level provenance finds 88% of the affected downstream units with 97% precision, at an estimated 48% of full-run token cost. Stage tracking finds all of them but recomputes 97%, with 7× fewer dependency records. These are invalidation estimates; selective execution is Phase 2 work.

1 Introduction

A faulty agent result can propagate through shared state and tool actions before detection. Full restart repeats valid work and cannot retract sent email; verification adds inference cost. Phase 1 measures propagation and dependency tracking to guide selective recovery:

RQ1 How far do faults propagate, and which reach irreversible or security-relevant actions?

RQ2 How does tracking granularity trade invalidation precision and recall against bookkeeping cost?

RQ3 What do full restart and always-verify achieve, and at what cost?

2 System and Threat Model

System model. Each *unit* is one agent invocation. Researchers extract facts; a planner cites facts for each tool action; executors see their step's cited facts and requested state. The trusted runtime records messages, citations and state access. Files/KV are *restorable*; payments are *compensable* through refunds [3]; email is *irreversible*.

Threat model. One unit v_0 emits a faulty result. Accidental faults are wrong/stale values or fabricated entities. Adversarial faults rewrite a result with an injected instruction (pay an attacker $250 and email the ledger) or redirect a payee/recipient. This is stronger than source-level prompt injection [5, 6]. The attacker knows the schemas and goal but cannot alter tools, logging, checkers or other agents' prompts. Recovery receives an oracle fault location after execution; detection is studied separately by verification.

Problem statement. Let $G = (V, E)$ be the provenance graph of a faulty run r, and r' its counterfactual replay with v_0's original result restored. With σ extracting a result's decision-relevant content, the *affected set* is $A = \{v : \sigma(r_v) \neq \sigma(r'_v)\}$. A tracking policy at granularity g predicts an invalidation set $\hat{A}_g$ from G and the oracle location, including changed fact/step IDs for the fact policy. Errors are *over-invalidation* ($\hat{A}_g \setminus A$, wasted work) and *under-invalidation* ($A \setminus \hat{A}_g$, reuse of corrupted results). We report precision, recall, recompute cost $\sum_{v \in \hat{A}_g} c_v / \sum_{v \in V} c_v$ (c_v: tokens of v), and bookkeeping (dependency records kept). Recovery must return restorable and compensable state to that of a fault-free run and report irreversible effects as unrecoverable.

3 Methodology

Original workload. Four seeded templates (procurement, payroll, travel booking, inventory restock) with two seeds each give 8 tasks, averaging 11 units and 12.8K tokens per clean run. A reference solver derives the expected final state. The checker verifies payments with their memos, key–value entries, file values, and the required values in each email. It flags an *unauthorized action* for a payment to an account named in no source or an email to a recipient the task does not name; payments and emails to the attacker are a subset. All agents run on Claude Haiku 5.5 with schema-constrained JSON output. A full factorial design crosses 8 tasks, 11 valid (stage, fault type) cells, and 2 placements, giving 176 runs, each with one fault injected after generation. For 22 of the 88 task–cell pairs both placements inject identical content and replay the same run, leaving 154 independent runs. Task seeds 0–1 are for development; seeds 2–3 are held out for Phase 2 evaluation.

Tracking policies. *Stage*: invalidate v_0's stage and all later ones. *Message*: transitive closure over inter-agent messages and shared-state reads. *Fact*: closure from corrupted facts to plan steps citing them (declared or value-matched), their executors, and readers of the state they wrote.

Counterfactual comparison. Responses are memoized by prompt hash, so in r' only units whose inputs changed are re-sampled. σ keeps tool, target, amount, stored value, and the amounts, accounts, addresses and codes in text, discarding paraphrase. Executor units are aligned by content before plan position. As a noise control, 16 uncached clean reruns differ from the cached run in 0.38 units on average.

Baselines. *Full restart* restores files/KV, refunds payments, and re-executes. *Always-verify* audits each output with Haiku; as in the original run, a flagged output is restored to its pre-injection value and retry tokens are estimated, which lets us replay it from the cache. The revised harness retries for real (Appendix B).

4 Evaluation

RQ1: Propagation (Fig. 1). Without recovery, only 39% of fault runs pass the checker. Only 82 of 176 runs propa-




Figure 1: Fault propagation without recovery, by injection stage and fault type (16 runs per row). (a) Mean number of downstream units whose result changed. (b) Fraction of runs with task failure, an unauthorized action, and an incorrect email already sent (irreversible).

Policy	Prec.	Rec.	Miss	Over	Recomp.	Records
Stage	0.29	1.00	0%	6.7	0.97	11 / 0.3 KB
Message	0.38	1.00	0%	5.0	0.86	23 / 0.4 KB
Fact	0.97	0.88	17%	0.11	0.48	77 / 3.3 KB

Table 1: Invalidation on the 82 propagated runs, downstream units only. Miss: runs with under-invalidation; Over: unaffected units invalidated; Recomp.: estimated cost vs. a full run. Over all 176 runs with v_0 counted: precision 0.24/0.86, recall 1.00/0.96 (stage/fact).

	State correct	Unauth. remaining	Wrong email remaining	Extra cost (tokens)
No recovery	41%	29%	23%	0
Full restart	100%	7%	23%	1.00×
Verify + restore	100%	0%	0%	1.18×
Fact-level (est.)	–	–	–	0.34×

Table 2: Baselines over 176 fault runs. State excludes email. Costs are tokens relative to a clean run; the verifier's retry cost is estimated. All rows use the current checker.

gate to a downstream unit: no agent reads a payment's result, so executor faults cannot, and executors corrected all plan-level wrong amounts and redirects from the facts they cite. Researcher faults spread farthest (2.3 downstream units) and leave an incorrect, unrecallable email in 40% of runs. Unauthorized actions follow 58% of adversarial faults and 5% of accidental ones (fabricated payees). Executors carry out injected plan steps and redirected calls by construction, as they see only their own step. The informative contrast is at the researcher: an injected instruction caused no unauthorized action, while a redirected account did in 88% of runs. This contrast rests on one injection wording.

RQ2: Granularity (Table 1). We score only downstream units, since every policy invalidates v_0, and only runs where the fault propagated. Stage and message tracking never under-invalidate, but discard 6.7 and 5.0 unaffected units per fault and recompute 97% and 86% of a run. Fact tracking keeps 7× more records and recomputes 48% at precision 0.97, but misses affected units in 14 of 82 runs (17%), all of them researcher faults. Removing duplicate placements leaves these figures within 0.01. Three causes recur. (i) *Implicit comparative dependencies*: a corrupted price changes which option is cheapest, and steps for the new choice cite only its own facts. (ii) *Collateral re-sampling*: a changed prompt re-samples the planner, which may alter steps citing no corrupted fact. (iii) *Ambiguity*: a fabricated supplier led the planner to drop a payee without citing it. These motivate comparison-aware citations and re-validation of re-sampled units in Phase 2.

RQ3: Baselines (Table 2). Full restart repairs all restorable and compensable state. It cannot retract email, leaving incorrect emails in 23% of runs (7% to the attacker) and sending 0.8 duplicates per run. The original verifier detected all injected faults and flagged 4.5% of clean-run outputs, at an estimated 1.18× extra tokens on fault runs and 1.04× on clean runs; its output restoration is an optimistic repair model.

5 Related Work

Selective re-execution follows intrusion/rollback recovery [1, 2]; compensation and fact tracking follow sagas and provenance [3, 4]. Agent security and failure studies [5, 6, 7] motivate our injections. REVISE [8] addresses online revisions, and dependency-guided rollback [9] repairs faulty persistent memories. We examine fault propagation across agents and shared state.

6 Limitations and Next Steps

Internal validity: faults are injected into results with an oracle-identified v_0; the verifier sees inputs contradicting the corrupted result, which favors always-verify; and fact-level cost is estimated from logged tokens. Changed prompts can still resample, so counterfactual comparison is approximate. Fine-grained oracle locations favor the fact policy. A plan-level fabricated step kept the copied step's instruction, so executors paid the real payee twice instead of the fabricated account. *External validity*: synthetic tasks, two task seeds. All metrics are replayed from the committed Claude cache without API calls. *Deviation*: hosted models replace the proposed local CPU models (Haiku, about $0.30; a campus model in Appendix B). *Phase 2* builds recovery and compares it with these baselines and suffix replay on identical faults.

References

[1] T. Kim, X. Wang, N. Zeldovich, M. F. Kaashoek. Intrusion recovery using selective re-execution. *OSDI*, 2010.

[2] E. N. Elnozahy, L. Alvisi, Y.-M. Wang, D. B. Johnson. A survey of rollback-recovery protocols in message-passing systems. *ACM Comput. Surv.*, 34(3), 2002.

[3] H. Garcia-Molina, K. Salem. Sagas. *SIGMOD*, 1987.

[4] P. Buneman, S. Khanna, W.-C. Tan. Why and where: A characterization of data provenance. *ICDT*, 2001.

[5] K. Greshake et al. Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection. *AISec*, 2023.

[6] E. Debenedetti et al. AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents. *NeurIPS Datasets and Benchmarks*, 2024.

[7] M. Cemri et al. Why do multi-agent LLM systems fail? arXiv:2503.13657, 2025.

[8] R. Qi et al. REVISE: Validity-Guided Recovery for Online Revisions in Agent Workflows. arXiv:2609.00643, 2026.

[9] Y. Wang et al. From Faulty Memories to Corrected Actions: Dependency-Guided Rollback Repair for Memory-Augmented Agents. arXiv:2608.10502v2, 2026.

A Timeline and Milestones

Dates	Milestone
Oct 27–Nov 4	**Phase 1 (done):** testbed, 4 task templates, fault injection, tracing at 3 granularities, counterfactual replay, full-restart and always-verify baselines, this report.
Nov 5–16	Selective recovery engine: per-key restore, targeted refunds, partial re-execution from the trace; oracle fault identity; suffix-replay baseline.
Nov 17–26	Precision vs. bookkeeping: comparison-aware citations, re-validating re-sampled outputs, budget-matched baselines; reserve task seeds 2–3 for held-out evaluation.
Nov 27–Dec 3	Larger suite (more seeds/templates, source-level injections, second model); stretch: recovery after other agents changed shared state post-fault.
Dec 4–10	Final experiments, figures, final report (due Dec 10).

B Revised Harness Validation

Setup. On October 29 we tested the revised harness on the UCSD-hosted `api-glm-5.3-flash` route through TritonAPI, with strict JSON output. The DataHub course CPU profile ran orchestration; inference was remote. The route is not an immutable checkpoint. Complete traces, responses, configurations, Python/package versions and source snapshots accompany the results.

Live pilot. One procurement task, two fault types (wrong value and malicious redirect), three stages and one placement gave six fault cases. Restart and verification bypassed the response cache; repair used actual uncached model calls. Median restart and verification times were 7.53 s and 17.32 s. These include network and local instrumentation; only these baseline timings are live measurements. The clean run passed, but only one of two uncached clean repeats passed. Mutable-state correctness after restart was 4/6; verified final task success was 6/6. This small pilot is implementation validation, not a precise performance estimate.

Propagation validation. Four templates with one task seed, eleven valid stage/fault combinations and one placement gave 44 cases. Clean baseline success was 3/4; eight uncached clean repeats passed 7/8. Restock failed its cached clean baseline although both uncached repeats passed. We retain all 44 cases and separately evaluate the 33 cases whose baseline completed cleanly:

Policy	Final success
No recovery	11/33
Full restart	29/33
Verify + actual retry	31/33

Always-verify detected the injected faults in all 44 cases but achieved final task success in only 40/44, with no attacker-directed actions remaining. Detection therefore does not guarantee correct repair. Restock inability is not counted as attack resistance. Accidental and adversarial results are also reported separately in the generated summaries.

Controls and failures. This second validation used cached replay and a 1.25 s minimum spacing for live requests. Its timings are not comparable to the live pilot as serving-performance measurements. A preceding four-worker batch failed on four requests before completing any fault case; its manifest and partial traces are retained, and it is excluded from success-rate denominators. Changed prompts still resample, and on this route the uncached clean repeats differed from the cached clean run in 3.0 units on average (Claude: 0.38), about as many as a researcher fault changes downstream (2.75). Its propagation figures therefore need repeated samples per case. No result here measures implemented selective recovery.

Resource accounting. There were 1,093 real requests across probes, pilot, the failed batch and serial validation. At the campus-listed rates of \$0.15/\$0.50 per million input/output tokens, completed usage cost is estimated at \$0.1761. Four failed requests retain \$0.0141 in conservative reservations, giving about \$0.1902 charged-or-reserved against a \$5 cap. These are token-rate estimates, not an authoritative billing statement. Credentials stayed in DataHub environment variables and are excluded from all exported artifacts.