1 Trajectory Sampling

Coding Trajectory Sources

400+ trajectories

DeepSWE | Terminal-Bench | SWE-Marathon

Diverse Source Models

11 models

GPT · Claude · MiniMax · GLM · Kimi · DeepSeek

Source Artifacts

Code files | Terminal | Test reports

Locate Candidate Misjudgments

overturn the previous conclusion

Available observations → Initial judgment → Further execution → Revised judgment

Evidence + candidate claim
Verify against prior evidence

Construction / verification only
Excluded from model input

2 Judgment Construction

Pre-judgment Evidence

Task context | Tool output

Label Check

Claim supported?

Judgment item

Task context
Task goal + relevant state

Evidence
Code, commands + tool outputs

Question
Is this factual claim supported by the evidence?
The reference answer is withheld from the model.

TRUE / FALSE
346 items

MULTIPLE CHOICE
179 items · 3–5 options

Fixed Input Boundary

Included
Task context · prior evidence · question + options

Excluded
Reference answer · rationale · later events

Reference
Scoring only

Same questions →

3 System I Evaluation

Diverse System One Models

14 Systems · 13 open implementations

TypeSafe Jev | Open-Jev | Simple-Jev

+10 additional System 1 systems

Model comparison

	Overall	T/F	MC	F2R	T2A
Simple-JEV 27B	64.3	66.5	60.1	55.3	79.7
TypeSafe	61.5	63.9	57.0	58.0	70.9
Winnow	56.2	61.0	46.9	47.3	77.2
OpenJEV-RB	55.0	59.5	46.4	58.5	60.8
Claude Opus 4.8	74.6	76.4	70.9	83.8	67.7

Accuracy (%) 0 50 100

Top 4 System 1 systems + best answer-only LM
5 evaluation views

14 systems span 37.0–64.3% overall accuracy

Measures rejection of prior misjudgments and acceptance of corrections