

WHAT'S NEW

Week 24 · June 8–12, 2026

Move a session to a new directory with `/cd`, let subagents spawn their own subagents, and troubleshoot a broken configuration with safe mode.

Releases **v2.1.166** → **v2.1.176**

3 features · June 8–12

Move a session with `/cd` v2.1.169

The new `/cd` command moves the current session to a different working directory without rebuilding the prompt cache: the new directory's `CLAUDE.md` is appended as a message instead of replacing the system prompt. The session relocates to the new directory's project storage, so `--resume` and `--continue` find it there. Claude prompts you to trust the directory if you haven't worked in it before.

Move the session into another project without restarting:

Claude Code

```
> /cd ../other-project
```

[Commands reference](#) →

Subagents can spawn subagents v2.1.172

Subagents can now spawn their own subagents. The subagent panel below the prompt shows the full tree: each row carries a count of its descendants and a path back to `main`. Subagent chains are capped at five levels deep to prevent runaway concurrent

trees.

Open the agents view to watch the nested tree as work fans out:

Claude Code

> /agents

[Spawn nested subagents →](#)

Troubleshoot with safe mode v2.1.169

Start Claude Code with `--safe-mode`, or set `CLAUDE_CODE_SAFE_MODE`, to launch with all customizations disabled: `CLAUDE.md`, skills, plugins, hooks, MCP servers, and custom commands and agents do not load. Authentication, model selection, built-in tools, and permissions still work. If a problem disappears in safe mode, one of those surfaces is the cause.

Launch a clean session to isolate a broken configuration:

terminal

```
claude --safe-mode
```

[Test against a clean configuration →](#)

Other wins

- + `fallbackModel` configures up to three fallback models tried in order when the primary is overloaded or unavailable, and `--fallback-model` now applies to interactive sessions too
- + Session titles are now generated in the language of your conversation; pin a specific one with the `language` setting
- + `claude agents --json` adds `--all` to include completed sessions plus new `id` and `state` fields, and no longer omits blocked or newly dispatched sessions
- + Browsing a marketplace's plugins in `/plugin` now has a search bar

- | | |
|--|--|
| <ul style="list-style-type: none">+ New <code>disableBundledSkills</code> setting and <code>CLAUDE_CODE_DISABLE_BUNDLED_SKILLS</code> hide bundled skills, workflows, and built-in commands from the model <hr/> | <ul style="list-style-type: none">+ Deny rules accept a glob in the tool-name position, so <code>"*"</code> denies all tools, and unknown tool names in deny rules now warn at startup <hr/> |
| <ul style="list-style-type: none">+ Cross-session messaging is hardened: messages relayed via <code>SendMessage</code> from other sessions no longer carry user authority, and auto mode blocks them <hr/> | <ul style="list-style-type: none">+ Amazon Bedrock reads the AWS region from <code>~/.aws</code> config files when <code>AWS_REGION</code> is unset, and <code>/status</code> shows where the region came from <hr/> |
| <ul style="list-style-type: none">+ New <code>enforceAvailableModels</code> managed setting makes the <code>availableModels</code> allowlist also constrain the Default model <hr/> | <ul style="list-style-type: none">+ Claude in Chrome browser tools now load in a single batched call instead of one per tool <hr/> |
| <ul style="list-style-type: none">+ <code>claude update</code> announces the target version before downloading instead of going silent | <ul style="list-style-type: none">+ New <code>footerLinksRegexes</code> setting adds regex-matched link badges to the footer row |

[Full changelog for v2.1.166-v2.1.176 →](#)