

WHAT'S NEW

Week 25 · June 15–19, 2026

Publish a live, shareable page from your session with Artifacts, match tool parameters in deny and ask rules, and set any setting from the prompt with /config.

Releases [v2.1.178](#) → [v2.1.183](#)

3 features · June 15–19

Artifacts

An artifact is a live, interactive page that Claude Code publishes from your session to a private URL on claude.ai, and it updates in place as the session keeps working. Ask for one when terminal text is the wrong medium, such as a PR walkthrough with the diff annotated inline or a dashboard built from session data. Artifacts are in beta on Team and Enterprise plans.

```

● 4 Explore agents finished (ctrl+o to expand)
  | funnel math · 14 tool uses · 38.1k tokens
  | L Done
  | cohort cuts · 11 tool uses · 24.6k tokens
  | L Done
  | session replays · 12 tool uses · 31.2k tokens
  | L Done
  | voice of user · 9 tool uses · 18.4k tokens
  | L Done

● Read(telemetry/exports.sql)
  | Export completed 27.8% · Pro cohort drops hardest at the
  | sheet
  * Cerebrating...

> Try "refactor <filepath>"

-- auto mode on (shift+fah to cycle) · 6 for agents
  
```

Ask Claude for a page, then approve the publish prompt:

> Make an artifact that walks through this PR with the diff annotated inline.

[Create an artifact →](#)

Match by input parameter v2.1.178

Deny and ask permission rules can now match a tool's input parameters with the `Tool(param:value)` syntax. For example, `Agent(model:opus)` matches subagent spawns that request the Opus model tier. The value accepts `*` as a wildcard, so `Agent(isolation:*)` matches any explicit isolation value.

Add a parameter rule to the deny list in `settings.json` :

`.claude/settings.json`

```
{
  "permissions": {
    "deny": ["Agent(model:opus)"]
  }
}
```

[Match by input parameter →](#)

Set any setting from the prompt v2.1.181

Pass `key=value` to `/config` to change a setting directly without opening the Settings interface. The syntax also works in non-interactive mode with the `-p` flag and from Remote Control.

Set the `thinking` setting from the prompt:

```
> /config thinking=false
```

[Commands reference →](#)

Other wins

- + Auto mode now blocks destructive git commands (`git reset --hard`, `git clean -fd`, `git stash drop`) when you didn't ask to discard local work, and blocks `terraform destroy` unless you asked for the specific stack
- + In the `/config` interface, Enter and Space both change the selected setting, and Esc now saves and closes instead of reverting
- + Point `CLAUDE_CLIENT_PRESENCE_FILE` at a marker file to suppress mobile push notifications while you're at the machine
- + API connection drops mid-thinking now retry automatically instead of showing "Connection closed while thinking"
- + Skills in nested `.claude/skills` directories load when working on files there; on a name clash the nested skill appears as `<dir>: <name>` so both stay available
- + Fixed Write and Edit producing zero-byte or truncated files on network drives and cloud-synced folders
- + Set the new `attribution.sessionUrl` setting to `false` to omit the claude.ai session link from commits and PRs in web and Remote Control sessions
- + New `sandbox.allowAppleEvents` opt-in setting lets sandboxed commands send Apple Events on macOS
- + Long paragraphs now stream line by line instead of waiting for the first line break
- + With `CLAUDE_CODE_EXPERIMENTAL_AGENT_TEAMS=1` set, every session has one implicit team, so you spawn teammates directly with the Agent tool's `name` parameter
- + Fixed prompt caching not reading on a custom `ANTHROPIC_BASE_URL` and on Foundry

[Full changelog for v2.1.178-v2.1.183 →](#)