




Max-Planck-Institut
für Meteorologie



The Coupling Library YAC

Moritz Hanke (DKRZ), René Redler (MPI-M), and Nils-Arne Dreier (DKRZ)



YAC-Team

- Main developer:
 - Moritz Hanke (DKRZ)
- With contributions from:
 - René Redler (MPI-M)
 - Nils-Arne Dreier (DKRZ)
 - Teresa Holfeld (MPI-M, student assistant)
 - Maxim Yastremsky (MPI-M, student assistant)
 - Thomas Jahns (DKRZ)
 - Uwe Schulzweida (MPI-M)
 - Hendryk Bockelmann (DKRZ)
 - Jörg Behrens (DKRZ)
 - Sergey Kosukhin (MPI-M)


Introduction

- What does a coupler do?
 - exchange of data between independent components (e.g. atmosphere and ocean) at predefined time intervals
 - components can use different grids
 - coupler takes care of regridding between both grids
 - components can have different decompositions
 - coupler takes care of data redistribution
 - components can have different exchange periods
 - coupler takes care of matching of the exchanges and data aggregation if necessary

Introduction

- Library linked to components
 - Written in C
 - Unit tests cover 99.5% of the code
 - C-, Fortran-, and Python-Interface
- Supports all common grid types
- Provides various 2D-interpolation schemes
 - All computation on the unit sphere using cartesian coordinates
- Parallel online weight computation
- Licenced under BSD 3-Clause License
- Used in official ICON-release (but developed independently)
- runs on Piz Daint¹, JUWELS², Levante³, LUMI⁴, MAC OS, and Linux systems with little to no porting effort



Supported grids



Interpolations

- 2D inter- and extrapolation
 - Various methods with different properties
 - All grid combinations are supported
- Fields can be defined on cells, vertices, or edges

Interpolation Stack




(https://dkrz-sw.gitlab-pages.dkrz.de/yac/db/dbc/interp_stack.html)


Interpolation Quality

- Benchmark on regridding quality by CERFACS in the frame of ISENES-Project
 - “This benchmark leads us to conclude that YAC, ESMF, and XIOS can all three be considered as high-quality regridding libraries [...]”
 - Valcke, S.; Piacentini, A.; Jonville, G. Benchmarking Regridding Libraries Used in Earth System Modelling. Math. Comput. Appl. 2022, 27, 31. <https://doi.org/10.3390/mca27020031>

Supported coupling configurations



Usage



Fortran example

```
USE yac
```

```
CALL yac_finit()
```

```
CALL yac_fdef_calendar(&  
    YAC_PROLEPTIC_GREGORIAN)
```

Fortran example

```
CALL yac_fread_config_yaml( &  
    "coupling.yaml")
```

Fortran example

```
INTEGER :: comp_id  
INTEGER :: comp_comm  
  
CALL yac_fdef_comp( &  
    "atmosphere", comp_id)  
CALL yac_fget_comp_comm( &  
    comp_id, comp_comm)
```

Fortran example

```
INTEGER, PARAMETER :: nbr_vertices = ...
INTEGER, PARAMETER :: nbr_cells = ...
INTEGER, PARAMETER :: nbr_vertices_per_cell = ...
REAL, ALLOCATABLE :: vertex_lon(nbr_vertices)
REAL, ALLOCATABLE :: vertex_lat(nbr_vertices)
INTEGER, ALLOCATABLE :: &
    cell_to_vertex(nbr_vertices_per_cell,nbr_cells)

INTEGER :: grid_id

CALL yac_fdef_grid( &
    "atmosphere_grid", nbr_vertices, nbr_cells, &
    nbr_vertices_per_cell, vertex_lon, vertex_lat, &
    cell_to_vertex, grid_id)
```

Fortran example

```
REAL, ALLOCATABLE :: cell_lon(nbr_cells)
REAL, ALLOCATABLE :: cell_lat(nbr_cells)

INTEGER :: cell_point_id

CALL yac_fdef_points( &
    grid_id, nbr_cells, &
    YAC_LOCATION_CELL, &
    cell_lon, cell_lat, &
    cell_point_id)
```

Fortran example

```
INTEGER, PARAMETER :: collection_size = ...
```

```
INTEGER :: taux_field_id
```

```
CALL yac_fdef_field( &  
    "TAUX", comp_id, &  
    (/cell_point_id/), 1, &  
    collection_size, "600", &  
    YAC_TIME_UNIT_SECOND, &  
    taux_field_id)
```


Fortran example

```
CALL yac_fenddef( )
```

Fortran example

```
REAL :: taux_buffer(nbr_cells, &  
                    collection_size)  
INTEGER :: info, error  
  
DO t = 1, ntimes  
  ...  
  CALL yac_fput( &  
    taux_field_id, nbr_cells, &  
    collection_size, taux_buffer, &  
    info, error)  
  ...  
END DO
```

Fortran example

```
REAL :: taux_buffer(nbr_cells, &  
                    collection_size)  
INTEGER :: info, error  
  
DO t = 1, ntimes  
  ...  
  CALL yac_fget( &  
    taux_field_id, nbr_cells, &  
    collection_size, taux_buffer, &  
    info, error)  
  ...  
END DO
```

Fortran example

```
CALL yac_fffinalize()
```

End

- Questions?
- Download: <https://gitlab.dkrz.de/dkrz-sw/yac>
- Documentation: <https://dkrz-sw.gitlab-pages.dkrz.de/yac/>
- References
 - M. Hanke, R. Redler, T. Holfeld und M. Yastremsky, 2016: YAC 1.2.0: new aspects for coupling software in Earth system modelling. Geoscientific Model Development, 9, 2755-2769, <https://doi.org/10.5194/gmd-9-2755-2016>
 - M. Hanke und R. Redler, 2019: New features with YAC 1.5.0. Reports on ICON, No 3. https://doi.org/10.5676/DWD_pub/nwv/icon_003
 - E. Kritsikis, M. Aechtner, Y. Meurdesoif, and T. Dubos: Conservative interpolation between general spherical meshes, Geosci. Model Dev., 10, 425–431, <https://doi.org/10.5194/gmd-10-425-2017>, 2017
 - Xiaoyu Liu, Larry L. Schumaker, Hybrid Bézier patches on sphere-like surfaces, Journal of Computational and Applied Mathematics, Volume 73, Issues 1–2, 1996, Pages 157-172, ISSN 0377-0427, [https://doi.org/10.1016/0377-0427\(96\)00041-6](https://doi.org/10.1016/0377-0427(96)00041-6)